# **SOTON Capacryl Haftprimer**



Version	Revision Date:	SDS Number:	Date of last issue: 03.03.2023
4.0	10.04.2024	6005273	Date of first issue: 30.10.2019

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

<b>1.1 Product identifier</b> Trade name	:	SOTON Capacryl Haftprimer
1.2 Relevant identified uses of the	he s	substance or mixture and uses advised against
Use of the Sub- stance/Mixture	:	Water-borne coatings
Recommended restrictions on use	:	within adequate application - none
1.3 Details of the supplier of the	saf	ety data sheet
Company	:	Caparol Farben Lacke GmbH Roßdörfer Straße 50 64372 Ober-Ramstadt
Telephone	:	+496154710
Telefax		+4961547170222
Website E-mail address Responsi- ble/issuing person	:	msds@dr-rmi.com
1 4 Emergeney telephone		

#### 1.4 Emergency telephone

Emergency telephone 1	: +49613284463 GBK GmbH
-----------------------	-------------------------

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

#### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

#### **Additional Labeling**

- EUH208 Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2Hisothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.
- EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not

# **SOTON Capacryl Haftprimer**



Version	Revision Date:	SDS Number:
4.0	10.04.2024	6005273

Date of last issue: 03.03.2023 Date of first issue: 30.10.2019

breathe spray or mist.

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Chemical nature	:	Dispersion-based primer, aqueous
-----------------	---	----------------------------------

#### Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.	Classification	(% w/w)
	Index-No.		(//////////////////////////////////////
	Registration number		
titanium dioxide; [in powder form	13463-67-7	Carc. 2; H351	>= 10 - < 20
containing 1 % or more of parti-	236-675-5		
cles with aerodynamic diameter ≤	022-006-00-2		
10 µm]	01-2119489379-17		
2-(2-butoxyethoxy)ethanol	112-34-5	Eye Irrit. 2; H319	>= 1 - < 10
	203-961-6		
	603-096-00-8		
	01-2119475104-44		
1,2-benzisothiazol-3(2H)-one	2634-33-5	Acute Tox. 4; H302	>= 0,0025 - <
	220-120-9	Skin Irrit. 2; H315	0,025
	613-088-00-6	Eye Dam. 1; H318	
	01-2120761540-60	Skin Sens. 1; H317	
		Aquatic Acute 1;	
		H400	
		Aquatic Chronic 2;	
		H411	
		Acute Tox. 2; H330	
		M-Factor (Acute	
		aquatic toxicity): 1	
		M-Factor (Chronic	
		aquatic toxicity): 1	

### SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

DE / EN

# **SOTON Capacryl Haftprimer**



rsion	Revision Date: 10.04.2024	SDS Numb 6005273		of last issue: 03.03.2023 of first issue: 30.10.2019	
reacti	on mass of 5-chloro-2	- 5596	5-84-9	specific concentration limit Skin Sens. 1; H317 >= 0,05 %	>= 0,0002 - <
methy	/l-2H-isothiazol-3-one /l-2H-isothiazol-3-one	and 2- (3:1) 613-1	67-00-5 20764691-48	Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071  M-Factor (Acute	0,0015
				aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100 	
				>= 0,6 % Skin Irrit. 2; H315 0,06 - < 0,6 % Eye Irrit. 2; H319 0,06 - < 0,6 % Skin Sens. 1A; H317 >= 0,0015 % Eye Dam. 1; H318 >= 0,6 %	
	ances with a workplac			1	
Talc (	Mg3H2(SiO3)4)	238-8	7-96-6 77-9 20140278-58		>= 10 - < 20

For explanation of abbreviations see section 16.

:

### **SECTION 4: First aid measures**

#### 4.1 Description of first-aid measures

General advice

Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

DE / EN

# **SOTON Capacryl Haftprimer**



Version 4.0	Revision Date: 10.04.2024	SDS Number: 6005273	Date of last issue: 03.03.2023 Date of first issue: 30.10.2019
			dangerous area. eeds to protect himself.
lf inh	aled	: Move to fres	h air.
In case of skin contact			solvents or thinners. Intact, immediately flush skin with soap and plenty
In ca	se of eye contact	IF IN EYES:	on persists: Get medical advice/ attention. Rinse cautiously with water for several minutes. tact lenses, if present and easy to do. Continue
lf swa	allowed		al advice. a with water and drink afterwards plenty of water. , DO NOT induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment

: No information available.

### **SECTION 5: Firefighting measures**

5.1	Extinguishing media		
	Suitable extinguishing media	:	Use water spray, alcohol-resistant foam, dry chemical or car- bon dioxide. Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment. Do not use a solid water stream as it may scatter and spread fire.
	Unsuitable extinguishing media	:	None known.
5.2	Special hazards arising from	the	substance or mixture
	Specific hazards during fire fighting	:	In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocar- bons (smoke).
5.3	Advice for firefighters Special protective equipment		Wear self-contained breathing apparatus for firefighting if nec-
	for fire-fighters	•	essary.

# **SOTON Capacryl Haftprimer**



Version	Revision Date: 10.04.2024	SDS Number:	Date of last issue: 03.03.2023
4.0		6005273	Date of first issue: 30.10.2019
Furth	er information	Standard proc	ay to cool unopened containers. edure for chemical fires. self does not burn.

### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Use protective shoes or boots with rough rubber sole. Material can create slippery conditions. Do not get in eyes, on skin, or on clothing.	
6.2 Environmental precautions		Prevent further leakage or spillage if safe to do so	

Environmental precautions	Prevent further leakage or spillage if safe to do so.
	If the product contaminates rivers and lakes or drains inform respective authorities.
	Do not flush into surface water or sanitary sewer system.

#### 6.3 Methods and material for containment and cleaning up

uitable, closed containers for disposal. with inert absorbent material (e.g. sand, silica gel, er, universal binder, sawdust).
/

#### 6.4 Reference to other sections

For further information see Section 7 of the safety data sheet. , For personal protection see section 8., For disposal considerations see section 13.

### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Advice on safe handling	:	Use only with adequate ventilation. For personal protection see section 8. No special technical protective measures required.
		In addition, the current technical information for this product and its application on www.caparol.com must be observed.
Hygiene measures	:	Wash hands before eating, drinking, or smoking. Do not eat, drink or smoke when using this product. Remove contaminat- ed clothing and protective equipment before entering eating areas.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage	:	Perishable if frozen. To maintain product quality, do not store		
areas and containers		in heat or direct sunlight. Store at room temperature in the		
		original container. Containers which are opened must be care-		
		fully resealed and kept upright to prevent leakage.		

# **SOTON Capacryl Haftprimer**



Version 4.0	Revision Date: 10.04.2024	SDS Number: 6005273	Date of last issue: 03.03.2023 Date of first issue: 30.10.2019
Advic	e on common storage	: Keep away f materials.	rom oxidizing agents and strongly acid or alkaline
Storage class (TRGS 510)		: 12	
7.3 Specific end use(s) Specific use(s)		: This information	tion is not available.

### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis	
titanium dioxide; [in powder form con- taining 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	MAK (measured as the alveolate fraction)	0,3 mg/m3	DE DFG MAK	
			nat cause cancer in humans		
			enic for humans and for whi		
			mbryo or foetus is unlikely wl	nen the MAK	
	value or the B	AT value is observe			
		AGW (Inhalable	10 mg/m3	DE TRGS	
		fraction)	(Titanium dioxide)	900	
	Peak-limit cat				
			s compliance with the OEL ar	nd biological	
	tolerance valu		of harming the unborn child	-	
		AGW (Alveolate	1,25 mg/m3	DE TRGS	
		fraction)	(Titanium dioxide)	900	
	Peak-limit cat				
			s compliance with the OEL a	nd biological	
	tolerance valu		of harming the unborn child		
		BM (Alveolar	0,5 mg/m3	DE TRGS	
		dust fraction)		527	
Talc	14807-96-6	AGW (Inhalable	10 mg/m3	DE TRGS	
(Mg3H2(SiO3)4)		fraction)		900	
	Peak-limit cat				
			s compliance with the OEL a	nd biological	
	tolerance valu	ies, there is no risk c	of harming the unborn child		
		AGW (Alveolate	1,25 mg/m3	DE TRGS	
		fraction)		900	
	Peak-limit cat				
			s compliance with the OEL a	nd biological	
	tolerance valu	lerance values, there is no risk of harming the unborn child			
2-(2-	112-34-5	TWA	10 ppm	2006/15/EC	
butoxyeth-			67,5 mg/m3		

### SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

DE / EN

# **SOTON Capacryl Haftprimer**



Ver 4.0	sion Revisi 10.04.		SDS Number: 6005273	Date of last issue: 03 Date of first issue: 30	
oxy)ethanol					
		Further in	nformation: Indicati	ive	
			STEL	15 ppm	2006/15/EC
				101,2 mg/m3	
		Further in	nformation: Indicati	ive	
			AGW (Vapo	ur 10 ppm	DE TRGS
			and aerosols	s) 67 mg/m3	900
		Peak-lim	it category: 1.5;(I)		
Further information: When there is compli			there is compliance with the	he OEL and biological	
		tolerance	values, there is no	o risk of harming the unbo	orn child
			MAK	10 ppm	DE DFG MAK
				67 mg/m3	

Further information: Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of expo- sure	Potential health ef- fects	Value
titanium dioxide; [in powder form contain- ing 1 % or more of particles with aerody- namic diameter $\leq$ 10 µm]	Consumers	Ingestion	Long-term systemic effects	700,00 mg/kg bw/day
	Workers	Inhalation	Long-term local ef- fects	10,00 mg/m3
propane-1,2-diol	Consumers	Inhalation	Long-term systemic effects	50,00 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	10,00 mg/m3
	Workers	Inhalation	Long-term systemic effects	168,00 mg/m3
	Workers	Inhalation	Long-term systemic effects	168,00 mg/m3
	Workers	Inhalation	Long-term local ef- fects	10,00 mg/m3
	Workers	Inhalation	Long-term local ef- fects	10,00 mg/m3
	Consumers	Inhalation	Long-term systemic effects	50,00 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	10,00 mg/m3
2-(2- butoxyethoxy)ethanol	Consumers	Inhalation	Acute local effects	60,70 mg/m3
	Consumers	Ingestion	Long-term systemic effects	5,00 mg/kg bw/day
	Consumers	Inhalation	Long-term local ef- fects	40,50 mg/m3
	Consumers	Skin contact	Long-term systemic effects	50,00 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic	40,50 mg/m3

### SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

DE / EN

# **SOTON Capacryl Haftprimer**



Version 4.0	Revision Date: 10.04.2024	SDS Nu 6005273		Date of last issue: 03.03.2023 Date of first issue: 30.10.2019	
				effects	
		Workers	Inhalatio	on Acute local effects	101,20 mg/m3
		Workers	Inhalatio	on Long-term systemic effects	67,50 mg/m3
		Workers	Inhalatio	on Long-term local ef- fects	67,50 mg/m3
		Workers	Skin co	ntact Long-term systemic effects	83,00 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
titanium dioxide; [in powder form containing 1 % or more of parti- cles with aerodynamic diameter ≤ 10 µm]	Sewage treatment plant	100 mg/l
	Fresh water	0,184 mg/l
	Soil	100 mg/kg dry weight (d.w.)
	Sea water	0,0184 mg/l
	Fresh water sediment	1000 mg/kg dry weight (d.w.)
	Sea sediment	100 mg/kg dry weight (d.w.)
	Intermittent use/release	0,193 mg/l
propane-1,2-diol	Sea sediment	57,2 mg/kg dry weight (d.w.)
	Soil	50 mg/kg dry weight (d.w.)
	Sea water	26 mg/l
	Fresh water sediment	572 mg/kg dry weight (d.w.)
	Fresh water	260 mg/l
	Intermittent use/release	183 mg/l
	Sewage treatment plant	20000 mg/l
2-(2-butoxyethoxy)ethanol	Fresh water	1,1 mg/l
	Fresh water sediment	4,4 mg/kg dry weight (d.w.)
	Intermittent use/release	11 mg/l
	Sea water	0,11 mg/l
	Sea sediment	0,44 mg/kg dry weight (d.w.)
	Sewage treatment plant	200 mg/l
	Soil	0,32 mg/kg dry weight (d.w.)
	Secondary Poisoning	56 mg/kg food

#### 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection

: DGUV Regulation 112-192 - Use of eye and face protection

Goggles

# **SOTON Capacryl Haftprimer**



Version 4.0	Revision Date: 10.04.2024	SDS Number: 6005273	Date of last issue: 03.03.2023 Date of first issue: 30.10.2019
M G	l protection aterial love thickness rotective index	: Nitrile rubber : 0,2 mm : Class 3	
R	Remarks :		ing gloves clean them with soap and water. gloves tested to EN374. ation 112-195 - Use of protective gloves
Skin	and body protection	: Long sleeved	clothing
			protection according to the amount and con- he dangerous substance at the work place.
		Skin should b	e washed after contact.
		Safety shoes	
Resp	iratory protection	: No personal r quired.	espiratory protective equipment normally re-
		• • •	application: Do not breathe spray dust. Use nation filter for paint spraying.
		DGUV Regula	ation 112-190 - Use of breathing equipment

### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Color	:	white
Odor	:	characteristic
Melting point/freezing point	:	ca. 0 °C
Boiling point/boiling range	:	ca. 100 °C
Upper explosion limit / Upper flammability limit	:	not determined

Lower explosion limit / Lower : not determined

# **SOTON Capacryl Haftprimer**



Vers 4.0	ion	Revision Date: 10.04.2024		S Number: 5273	Date of last issue: 03.03.2023 Date of first issue: 30.10.2019
	flamma	bility limit			
	Flash p	oint	:	Not applicable	
	Autoign	ition temperature	:	not determined	
	Decom	position temperature	:	Not applicable	
	рН		:	8,5 (20 °C) Concentration: 10 Method: DIN EN	00 % ISO 19396-1:2020-05
	Viscosit Visc	ty osity, dynamic	:	350 mPa.s (20 °C Method: ISO 321	
	Visc	osity, kinematic	:	not determined	
	Flow tin	ne	:	not determined	
	Solubili Wat	ty(ies) er solubility	:	completely miscil	ble
	Partition octanol	n coefficient: n- /water	:	not determined	
	Vapor p	pressure	:	ca. 23,4 hPa (20	°C)
	Relative	e density	:	not determined	
	Density		:	1,5 g/cm3 (20 °C Method: DIN EN	) ISO 2811-1
	Bulk de	nsity	:	Not applicable	
	Relative	e vapor density	:	not determined	

### 9.2 Other information

# **SOTON Capacryl Haftprimer**



Version 4.0	Revision Date: 10.04.2024		DS Number: 05273	Date of last issue: 03.03.2023 Date of first issue: 30.10.2019
Explo	sives	:	Not applicable	
Oxidizing properties		:	Not applicable	
Flammability (liquids)		:	The product is n	ot flammable.

### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No decomposition if stored and applied as directed.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions	:	No decomposition if stored and applied as directed.
10.4 Conditions to avoid		

### Conditions to avoid : Protect from frost, heat and sunlight.

#### 10.5 Incompatible materials

Materials to avoid

: Incompatible with acids and bases. Incompatible with oxidizing agents.

#### **10.6 Hazardous decomposition products**

No decomposition if stored and applied as directed.

### **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity		
Not classified based on availa	able	information.
<u>Components:</u>		
2-(2-butoxyethoxy)ethanol:		
Acute oral toxicity	:	LD50 (Mouse): 2.410 mg/kg
Acute dermal toxicity	:	LD50 (Rabbit): 2.764 mg/kg
1,2-benzisothiazol-3(2H)-on	e:	
Acute oral toxicity	:	LD50 (Rat): 532 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 0,4 mg/l

# **SOTON Capacryl Haftprimer**



ersion .0	Revision Date: 10.04.2024	SDS Number: 6005273	Date of last issue: 03.03.2023 Date of first issue: 30.10.2019			
		Exposure t Test atmos	me: 4 h phere: dust/mist			
Acute	e dermal toxicity	: LD50 (Rat)	: > 2.000 mg/kg			
react (3:1):		o-2-methyl-2H-iso	thiazol-3-one and 2-methyl-2H-isothiazol-3-one			
Acute	oral toxicity	: LD50 (Rat) Method: O	: 66 mg/kg ECD Test Guideline 401			
Acute	inhalation toxicity	Exposure t Test atmos	<ul> <li>LC50 (Rat): 0,17 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403</li> </ul>			
Acute	e dermal toxicity	: LD50 (Rat) Method: O	: > 141 mg/kg ECD Test Guideline 402			
Resp	lassified based on ava iratory or skin sensi sensitization					
-	-	tization				
	lassified based on ava	ailable information				
	iratory sensitization					
-	lassified based on ava					
	cell mutagenicity					
	lassified based on ava	ailable information.				
	nogenicity					
Not c	lassified based on ava	ailable information.				
Repr	oductive toxicity					
Not c	lassified based on ava	ailable information.				
STO	-single exposure					
Not c	lassified based on ava	ailable information.				
STO	-repeated exposure					
Not c	lassified based on ava	ailable information.				
Aspir	ation toxicity					
	anon toxiony					

# **SOTON Capacryl Haftprimer**



Version	Revision Date:	SDS Number:	Date of last issue: 03.03.2023
4.0	10.04.2024	6005273	Date of first issue: 30.10.2019

#### 11.2 Information on other hazards

Endocrine disrupting properties

Not classified based on available information.

#### Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

#### Components:

1,2-benzisothiazol-3(2H)-one:	
Toxicity to fish :	LC50 (Oncorhynchus mykiss (rainbow trout)): 2,2 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other : aquatic invertebrates	EC50 (Daphnia): 3,27 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic : plants	EC50 (Selenastrum capricornutum (green algae)): 0,11 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
M-Factor (Acute aquatic tox- : icity)	1
M-Factor (Chronic aquatic : toxicity)	1
reaction mass of 5-chloro-2-m (3:1):	ethyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one
M-Factor (Acute aquatic tox- : icity)	100
M-Factor (Chronic aquatic : toxicity)	100
2 Parsistance and degradability	

#### 12.2 Persistence and degradability

No data available

## **SOTON Capacryl Haftprimer**



Version	Revision Date:	SDS Number:	Date of last issue: 03.03.2023
4.0	10.04.2024	6005273	Date of first issue: 30.10.2019

#### 12.3 Bioaccumulative potential

#### Components:

#### 2-(2-butoxyethoxy)ethanol:

Partition coefficient: n- : log Pow: 0,56 octanol/water

#### 1,2-benzisothiazol-3(2H)-one:

Partition coefficient: noctanol/water : log Pow: 0,63 - 0,76 pH: 7

# reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

Partition coefficient: n-	:	log Pow: <= 0,75
octanol/water		Method: OECD Test Guideline 117

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

#### 12.6 Endocrine disrupting properties

Ρ	ra	bd	u	C	<u>t:</u>	

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

#### 12.7 Other adverse effects

#### Product:

Additional ecological infor-	:	An environmental hazard cannot be excluded in the event of
mation		unprofessional handling or disposal.

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : .

# **SOTON Capacryl Haftprimer**



Version 4.0	Revision Date: 10.04.2024	SDS Number: 6005273	Date of last issue: 03.03.2023 Date of first issue: 30.10.2019	
		Waste should	not be disposed of via wastewater.	
Contaminated packaging		: Only completely emptied containers should be given for recy- cling.		
Waste Code		: used product 080112, waste in 08 01 11*	e paint and varnish other than those mentioned	

### **SECTION 14: Transport information**

#### 14.1 UN number or ID number

	ADN	:	Not regulated as a dangerous good
	ADR	:	Not regulated as a dangerous good
	RID	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	ΙΑΤΑ	:	Not regulated as a dangerous good
14.	2 UN proper shipping name		
	ADN	:	Not regulated as a dangerous good
	ADR	:	Not regulated as a dangerous good
	RID	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	ΙΑΤΑ	:	Not regulated as a dangerous good
14.:	3 Transport hazard class(es)		
	ADN	:	Not regulated as a dangerous good
	ADR	:	Not regulated as a dangerous good
	RID	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	ΙΑΤΑ	:	Not regulated as a dangerous good
14.	4 Packing group		
	ADN	:	Not regulated as a dangerous good
	ADR	:	Not regulated as a dangerous good
	RID	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	IATA (Cargo)	:	Not regulated as a dangerous good
	IATA (Passenger)	:	Not regulated as a dangerous good

# **SOTON Capacryl Haftprimer**



Version	Revision Date:	SDS Number:	Date of last issue: 03.03.2023
4.0	10.04.2024	6005273	Date of first issue: 30.10.2019

#### 14.5 Environmental hazards

Remarks

Not regulated as a dangerous good

14.6 Special precautions for user

Not classified as dangerous in the meaning of transport regulations.

#### 14.7 Maritime transport in bulk according to IMO instruments

:

Not applicable for product as supplied.

### **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)			:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 75 If you intend to use this product as tattoo ink, please contact your ven- dor.
REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59).			:	None
Regulation (EC) No 1005/2009 on substances that de- plete the ozone layer			:	Not applicable
Regulation (EU) 2019/1021 on persistent organic pollu- tants (recast)			:	Not applicable
REACH - List of substances subject to authorisation (Annex XIV)			:	None
Seveso III: Directive 2012/18/EU of the Euro- pean Parliament and of the Council on the control of major-accident hazards involving dangerous substances.				
Water hazard class (Germa- : WGK 1 slightly water endangering ny) Classification according to AwSV, Annex 1 (5.2)				
Product paints /	code for laquers and Giscode	: M-LW01 Water-based varnishes		
•		: BSW30 Coating mate	rials,	, water-based, containing solvents
Volatile	organic compounds			4 November 2010 on industrial ution prevention and control)
		16/10		

# **SOTON Capacryl Haftprimer**



Version 4.0	Revision Date: 10.04.2024	SDS Number: 6005273	Date of last issue: 03.03.2023 Date of first issue: 30.10.2019	
		Volatile organic o	compounds (VOC) content: 3,19 %	
Volatile organic compounds		: Directive 2004/42/EC < 6 % < 80 g/l		

### **15.2 Chemical Safety Assessment**

A Chemical Safety Assessment is not required for this mixture.

### **SECTION 16: Other information**

Full text of H-Statements		
H301	:	Toxic if swallowed.
H302	:	Harmful if swallowed.
H310	:	Fatal in contact with skin.
H314	:	Causes severe skin burns and eye damage.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H319	:	Causes serious eye irritation.
H330	:	Fatal if inhaled.
H351	:	Suspected of causing cancer if inhaled.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H411	:	Toxic to aquatic life with long lasting effects.
EUH071	:	Corrosive to the respiratory tract.
Full text of other abbreviation	าร	
Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Carc.	:	Carcinogenicity
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Skin Corr.	:	Skin corrosion
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitization
2006/15/EC	:	Europe. Indicative occupational exposure limit values
DE DFG MAK	:	Germany. MAK BAT Annex IIa
DE TRGS 527	:	Germany. TRGS 527 - Activities with nanomaterials
DE TRGS 900	:	Germany. TRGS 900 - Occupational exposure limit values.
2006/15/EC / TWA	:	Limit Value - eight hours
2006/15/EC / STEL	:	Short term exposure limit
DE DFG MAK / MAK	:	MAK value
DE TRGS 527 / BM	:	Assessment scale
DE TRGS 900 / AGW	:	Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the

#### SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

DE / EN

# **SOTON Capacryl Haftprimer**



Version	Revision Date:	SDS Number:	Date of last issue: 03.03.2023
4.0	10.04.2024	6005273	Date of first issue: 30.10.2019

German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration, ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Miritime Organization; IECSC - Inventry and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; DS0 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; no.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Substances of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; T

#### Further information

Other information	:	No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC. Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.
Sources of key data used to compile the Material Safety Data Sheet	:	ECHA WebSite ACGIH (American Conference of Government Industrial Hy- gienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH NIOSH - Registry of toxic effects of chemical substances ECDIN - Environmental Chemicals Data and Information Net- work - Joint Research Centre, Commission of the European Communities SAX'S - Dangerous properties of industrial materials GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the Ger- man Social Accident Insurance) Toxnet - Toxicology Data Network

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

# **SOTON Capacryl Haftprimer**



Version	Revision Date:	SDS Number:	Date of last issue: 03.03.2023
4.0	10.04.2024	6005273	Date of first issue: 30.10.2019

#### **REACH Information**

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN