

# CD DecoGrund 2,5 LT



## technical data

Specific use(s)	Coating material
Density	1,67 g/cm <sup>3</sup>
consumption	150 - 200 ml/m <sup>2</sup>

## Components

product code/GISCODE	M-GP01
declaration of ingredients	Dispersion-based primer, aqueous
preservatives	contained
VOC content in accordance with Directive 2004/42/EC	0 %
VOC-indhold LEED [less water]	< 1 g/l
solvent and plasticiser-free in accordance with VdL- RL 01	yes
water-dilutable in accordance with 2004/42/EC (Decopaint)	yes
lead, cadmium, chromium VI * (* not contained in the formulation)	not contained

## environmental labels

building certifications

suitability for DGNB criteria ENV 1.2 (2012) "Risks for the Local Environment"

No.	application site	Product Type	QS 1	QS 2	QS 3	QS 4
2	Liquid coatings on primarily mineral undercoats, such as concrete, masonry, mortar, filler, plaster, wallpaper, fleece or plasterboard. Floor space and thoroughfares such as underground car parks, access roads, etc are not taken into account.	Decorative paints, decorative fillers, dust-binding coatings, floor coverings without special resistance requirements, concrete protection coatings	yes	yes	yes	yes
27	Factory-coated components, e.g. façade elements, doors, radiators, etc. Galvanising is not considered coating under this criterion.	primer and top coating (e.g. paints, varnishes)	yes	yes	yes	yes

Suitability for use in accordance with LEED	category (IEQ4.2 - 2009)	primer, sealer or undercoat
	VOC limit below limit	100 g/l yes
recycling share	not contained	
production location	DAW SE Roßdörfer Straße 50 DE-64372 Ober-Ramstadt	