

Capalac Aqua Metallschutz weiß



Technical data

Specific use(s)	Coating material
Density	1,29 g/cm ³
Corrosion protection class	C3 (DIN EN ISO 12944-5)

Components

Product Code/GISCODE	M-LW01
Declaration of ingredients preservatives	Polyacrylate-based lacquer, aqueous contained
VOC content in accordance with Directive 2004/42/EC	< 3 % < 30 g/l
VOC content LEED [less water]	< 60 g/l
Water-dilutable in accordance with 2004/42/EC (Decopaint)	yes
Lead, cadmium, chromium VI * (* not contained in the formulation)	not contained

Environmental labels

Complies with the VOC requirements in accordance with	RAL-UZ 12a
---	------------

Building certifications

Suitability for DGNB criteria ENV 1.2 (2012) "Risks for the Local Environment"

No.	Application site	Product type	QS 1	QS 2	QS 3	QS 4
1	Liquid coatings on non-mineral undercoats: metals, wood, plastics	Varnishes/Glazes	yes	yes	yes	yes
14a	Non-load-bearing metal components such as banisters, metal substructures, frames, steel doors, façade elements, etc.	Corrosion protection coatings	yes	yes	yes	yes
14b	Non-load-bearing metal components such as banisters, metal substructures, frames, steel doors, façade elements, etc. (metallic effect varnishes)	Effect coatings (e.g. metallic effect varnishes)	yes	yes	yes	yes
26	Components made of aluminium and stainless steel on the façade: cladding	Products for surface coating of metal	yes	yes	yes	yes
27	Factory-coated components, e.g. façade elements, doors, radiators, etc. Galvanising is not considered coating under this criterion.	Primer and top coating (e.g. paints, varnishes)	yes	yes	yes	yes

Suitability for use in accordance with LEED	Category (IEQ4.2 - 2009)	anti-corrosive coating
	VOC limit	250 g/l
	Limit fulfilled	yes
Recycling share	not contained	
Production site	DAW SE Roßdörfer Straße 50 DE-64372 Ober-Ramstadt	