

# ThermoSan NQG



## technical data

Specific use(s)	Water-borne coatings
Density	1,48 g/cm <sup>3</sup>
consumption	150 - 250 ml/m <sup>2</sup>
gloss level	matt (in accordance with DIN EN 13300)

## Components

product code/GISCODE	M-SF01F
preservatives	contained
VOC content in accordance with Directive 2004/42/EC	< 2 % < 30 g/l
VOC-indhold LEED [less water]	< 50 g/l
water-dilutable in accordance with 2004/42/EC (Decopaint)	yes
lead, cadmium, chromium VI * (* not contained in the formulation)	not contained

## environmental labels

building certifications

suitability for DGNB criteria ENV 1.2 (2012) "Risks for the Local Environment"

No.	application site	product type	QS 1	QS 2	QS 3	QS 4
3	liquid coating materials for outdoor mineral surfaces. E.g. concrete, masonry, mineral mortar and filler, plaster, ETICS	decorative paints	yes	yes	yes	yes
27	Factory-coated components, e.g. façade elements, doors, radiators, etc. Galvanising is not considered coating under this criterion.	primer and top coating (e.g. paints, varnishes)	yes	yes	yes	yes

Suitability for use in accordance with LEED

category (IEQ4.2 - 2009)

flat topcoat

VOC limit  
below limit

50 g/l  
yes

category (IEQ4.2 - 2009)

flat topcoat with colorant added at the point-of-sale  
VOC limit  
below limit  
100 g/l  
yes

recycling share

not contained

production location

DAW SE  
Roßdörfer Straße 50  
DE-64372 Ober-Ramstadt