

Reibeputz R 30



Technical data

Specific use(s)	Coating material
Density	1,80 g/cm ³
Consumption	3,6 - 4,0 kg/m ²
Gloss level	Matt (in accordance with DIN EN 13300)

Components

Product Code/GISCODE	M-DF01
Declaration of ingredients	Synthetic resin plaster, solvent-free
preservatives	not contained
VOC content in accordance with Directive 2004/42/EC	< 0.1 %
VOC content LEED [less water]	< 1 g/l
Solvent and plasticiser-free in accordance with VdL- RL 01	< 1 g/l
Water-dilutable in accordance with 2004/42/EC (Decopaint)	yes
Lead, cadmium, chromium VI *	yes
(* not contained in the formulation)	not contained

Environmental labels

Building certifications

Suitability for DGNB criteria ENV 1.2 (2012) "Risks for the Local Environment"

No.	Application site	Product type	QS 1	QS 2	QS 3	QS 4
2	Liquid coatings on primarily mineral undercoats, such as concrete, masonry, mortar, filler, plaster, wallpaper, fleece or plasterboard. Floor space and thoroughfares such as underground car parks, access roads, etc are not taken into account.	Decorative paints, decorative fillers, dust-binding coatings, floor coverings without special resistance requirements, concrete protection coatings	yes	yes	yes	yes

Suitability for use in accordance with LEED	Category (IEQ4.2 - 2009)	flat topcoat
	VOC limit	50 g/l
	Limit fulfilled	yes
Recycling share	not contained	
Production site	DAW SE Roßdörfer Straße 50 DE-64372 Ober-Ramstadt	