

EffektGrund Halbtransparent



Technical data

Specific use(s)	Priming
Density	1,33 g/cm ³
Consumption	200 ml/m ²
Gloss level	Matt (in accordance with DIN EN 13300)

Components

Product Code/GISCODE	M-GP01
Declaration of ingredients	Mixture
preservatives	contained
VOC content in accordance with	< 2 %
Directive 2004/42/EC	< 30 g/l
VOC content LEED [less water]	< 50 g/l
Water-dilutable in accordance with	yes
2004/42/EC (Decopaint)	
Lead, cadmium, chromium VI *	not contained
(* not contained in the formulation)	

Environmental labels

Building certifications

Suitability for DGNB criteria ENV 1.2 (2012) "Risks for the Local Environment"

No.	Application site	Product type	QS 1	QS 2	QS 3	QS 4
3	Liquid coating materials for outdoor mineral surfaces. E.g. concrete, masonry, mineral mortar and filler, plaster, ETICS	Decorative paints	yes	yes	yes	yes
27	Factory-coated components, e.g. façade elements, doors, radiators, etc. Galvanising is not considered coating under this criterion.	Primer and top coating (e.g. paints, varnishes)	yes	yes	yes	yes

Suitability for use in accordance with LEED

Category (IEQ4.2 - 2009)

primer, sealer or undercoat

VOC limit

100 g/l

Limit fulfilled

yes

Category (IEQ4.2 - 2009)

primer or undercoat with colourant added at the point of sale

VOC limit

250 g/l

Limit fulfilled

yes

Recycling share

not contained

Production site

DAW SE
Roßdörfer Straße 50
DE-64372 Ober-Ramstadt