

Capacryl Haftprimer NAST BasisW



Technical data

| | |
|-----------------|--|
| Specific use(s) | Water-borne coatings |
| Density | 1,33 g/cm ³ |
| Consumption | 120 - 160 ml/m ² |
| Gloss level | Matt (in accordance with DIN EN 13300) |

Components

| | |
|--------------------------------------|--|
| Product Code/GISCODE | M-LW01 |
| Declaration of ingredients | Polyurethane/polyacrylate-based lacquer, aqueous |
| preservatives | contained |
| VOC content in accordance with | < 10 % |
| Directive 2004/42/EC | < 130 g/l |
| VOC content LEED [less water] | < 250 g/l |
| Lead, cadmium, chromium VI * | not contained |
| (* not contained in the formulation) | |

Environmental labels

| | |
|------------------------------------|------------|
| Blue Angel (environmental label) | RAL-UZ 12a |
| Complies with the VOC requirements | RAL-UZ 12a |
| in accordance with | |

Building certifications

Suitability for DGNB criteria ENV 1.2 (2012) "Risks for the Local Environment"

| No. | Application site | Product type | QS 1 | QS 2 | QS 3 | QS 4 |
|-----|---|---|------|------|------|------|
| 1 | Liquid coatings on non-mineral undercoats: metals, wood, plastics | Varnishes/Glazes | yes | no | yes | yes |
| 26 | Components made of aluminium and stainless steel on the façade: cladding | Products for surface coating of metal | yes | yes | yes | yes |
| 27 | Factory-coated components, e.g. façade elements, doors, radiators, etc. Galvanising is not considered coating under this criterion. | Primer and top coating (e.g. paints, varnishes) | yes | yes | yes | yes |

| | | |
|---|---|-------------------|
| Suitability for use in accordance with LEED | Category (IEQ4.2 - 2009) | pigmented lacquer |
| | VOC limit | 550 g/l |
| | Limit fulfilled | yes |
| Recycling share | not contained | |
| Production site | DAW SE Roßdörfer Straße 50 DE-64372 Ober-Ramstadt | |