

Capacryl PU-Matt NAST BasisW



Technical data

Specific use(s)	Water-borne coatings
Density	1,33 g/cm ³
Consumption	120 - 160 ml/m ²
Gloss level	Matt (in accordance with DIN EN 13300)

Components

Product Code/GISCODE	M-LW01
Declaration of ingredients	Polyurethane/polyacrylate-based lacquer, aqueous
preservatives	contained
VOC content in accordance with	< 10 %
Directive 2004/42/EC	< 130 g/l
VOC content LEED [less water]	< 250 g/l
Lead, cadmium, chromium VI *	not contained
(* not contained in the formulation)	

Environmental labels

Blue Angel (environmental label)	RAL-UZ 12a
Complies with the VOC requirements	RAL-UZ 12a
in accordance with	

Building certifications

Suitability for DGNB criteria ENV 1.2 (2012) "Risks for the Local Environment"

No.	Application site	Product type	QS 1	QS 2	QS 3	QS 4
1	Liquid coatings on non-mineral undercoats: metals, wood, plastics	Varnishes/Glazes	yes	no	yes	yes
26	Components made of aluminium and stainless steel on the façade: cladding	Products for surface coating of metal	yes	yes	yes	yes
27	Factory-coated components, e.g. façade elements, doors, radiators, etc. Galvanising is not considered coating under this criterion.	Primer and top coating (e.g. paints, varnishes)	yes	yes	yes	yes

Suitability for use in accordance with LEED	Category (IEQ4.2 - 2009)	pigmented lacquer
	VOC limit	550 g/l
	Limit fulfilled	yes
Recycling share	not contained	
Production site	DAW SE Roßdörfer Straße 50 DE-64372 Ober-Ramstadt	