

VarioColl



Technical data

Specific use(s)	Water-borne coatings
Density	1,27 g/cm ³
Consumption	280 - 350 ml/m ²

Components

Product Code/GISCODE	M-GP01
Declaration of ingredients	Mixture
preservatives	contained
VOC content in accordance with	< 0.1 %
Directive 2004/42/EC	< 1 g/l
VOC content LEED [less water]	< 1 g/l
Solvent and plasticiser-free in	yes
accordance with VdL- RL 01	
Water-dilutable in accordance with	yes
2004/42/EC (Decopaint)	
Lead, cadmium, chromium VI *	not contained
(* not contained in the formulation)	

Environmental labels

AgBB approval	passed
---------------	--------

Building certifications

Suitability for DGNB criteria ENV 1.2 (2012) "Risks for the Local Environment"

No.	Application site	Product type	QS 1	QS 2	QS 3	QS 4
9	Wall and ceiling cladding	Wallpaper glue	yes	yes	yes	yes

Suitability for use in accordance with LEED	Category (IEQ4.2 - 2009)	cannot be classified
	VOC limit	
	Limit fulfilled	
Recycling share	not contained	
Production site	DAW SE Roßdörfer Straße 50 DE-64372 Ober-Ramstadt	

Sustainability Data Sheet Update: 05.12.2017

This data sheet has been compiled based on state-of-the-art technology and our experience. However, in light of the wide range of requirements regarding buildings certifications, the buyer/user remains personally responsible for checking that our assessment is suitable for the intended certification system and its respective requirements. This data sheet is only valid in its latest version and in combination with the current Technical Information and the Material Safety Data Sheet. Please refer to our website to check the up-to-dateness of this version, if necessary.