

Capatect-SockelFlex



Technical data

Specific use(s)	Water-borne coatings
Density	1,10 g/cm ³
Consumption	2,6 kg/m ²

Components

Product Code/GISCODE	M-DF01
Preservation agents	contained
VOC content in accordance with Directive 2004/42/EC	< 1 %
VOC content LEED [less water]	< 10 g/l
Water-dilutable in accordance with 2004/42/EC (Decopaint)	yes
Lead, cadmium, chromium VI * (* not contained in the formulation)	not contained

Environmental labels

Building certifications

Suitability for DGNB criteria ENV 1.2 (2012) "Risks for the Local Environment"

No.	Application site	Product Type	QS 1	QS 2	QS 3	QS 4
3	Liquid coating materials for outdoor mineral surfaces. E.g. concrete, masonry, mineral mortar and filler, plaster, ETICS	Decorative paints	yes	yes	yes	yes

Suitability for use in accordance with LEED	Category (IEQ4.2 - 2009)	primer, sealer or undercoat
	VOC limit	100 g/l
	Limit fulfilled	yes
Recycling share	not contained	
Production site	DAW SE Roßdörfer Straße 50 DE-64372 Ober-Ramstadt	

Sustainability Data Sheet Update: 29.05.2018

This data sheet has been compiled based on state-of-the-art technology and our experience. However, in light of the wide range of requirements regarding buildings certifications, the buyer/user remains personally responsible for checking that our assessment is suitable for the intended certification system and its respective requirements. This data sheet is only valid in its latest version and in combination with the current Technical Information and the Material Safety Data Sheet. Please refer to our website to check the up-to-dateness of this version, if necessary.