

Akkordspachtel KF



Technical data

Specific use(s)	Water-borne coatings
Density	1,68 g/cm ³
Consumption	1,7 kg/m ²

Components

Product Code/GISCODE	M-DF01; BSW20
Preservation agents	contained
VOC content in accordance with Directive 2004/42/EC	< 0.1 %
VOC content LEED [less water]	< 1 g/l
Solvent and plasticiser-free in accordance with VdL- RL 01	yes
Water-dilutable in accordance with 2004/42/EC (Decopaint)	yes
Lead, cadmium, chromium VI * (* not contained in the formulation)	not contained

Environmental labels

Building certifications - DGNB

Suitable according to DGNB criteria ENV1.2 (System version 2018 and 2015)

No.	Application site	Product Type	Considered substances / aspects	QS 1	QS 2	QS 3	QS 4
2	Coatings on predominantly mineral interior surfaces as well as on wallpaper, non-woven materials, plasterboard, etc. Floor areas with special resistance requirements (such as OS (surface protection) systems) and traffic routes such as underground garages and access roads are not taken into account	This refers to decorative paints, primers, decorative fillers (incl. Q-filler) and deep primer, floor coatings with no special resistance requirements, concrete glazes	VOC / SVOC	Ja	Ja	Ja	Ja

Building certifications - LEED

LEED v.4 (EQ CREDIT: Low emitting materials)	not fulfilled
LEED 2009 (IEQ4.1/ IEQ4.2/ IEQ4.3)	fulfilled
Product category	flat topcoat
VOC limit	50 g/l
Limit fulfilled	yes
Recycling share	not contained
Production site	DAW SE Roßdörfer Straße 50 DE-64372 Ober-Ramstadt

Building certifications - Assessment System NaWoh

Assessment System Sustainable Housing Constructions (NaWoh) v3.1	suitable
--	----------