

Cool Protect



Technical data

Specific use(s)	Water-borne coatings
Density	1,47 g/cm ³
Consumption	200 ml/m ²

Components

Product Code/GISCODE	M-SF01F; BSW50
Declaration of ingredients	Silicone resin paint, aqueous , with film protection
VOC content in accordance with Directive 2004/42/EC	< 3 %
VOC content LEED [less water]	< 40 g/l
Water-dilutable in accordance with 2004/42/EC (Decopaint)	< 80 g/l
Film protection	yes
Lead, cadmium, chromium VI *	contained (agent corresponds to 528/2012/EG)
(* not contained in the formulation)	not contained

Environmental labels

Building certifications - DGNB

Suitable according to DGNB criteria ENV1.2 (System version 2018 and 2015)

No.	Application site	Product Type	Considered substances / aspects	QS 1	QS 2	QS 3	QS 4
5	Coating materials for exterior mineral surfaces such as concrete, masonry, mineral mortar and filler, plaster, ETICS, wallpaper (façade wallpaper), plasterboard, etc.	Currently, just decorative paints and dispersion insulation adhesives are taken into account	VOC	Ja	Ja	Ja	Ja
31	Products with film preservation and good treated with biocides	Exterior plasters, façade coatings, floor coverings made of wool/natural fibres, wood glazes with film preservation	Biocides (product type 7 and 9 in accordance with 528/2012/EC: Preservatives for construction materials) e.g. algicides, fungicides, moth repellents	Ja	Ja	Ja	

Building certifications - LEED

LEED v.4 (EQ CREDIT: Low emitting materials)	fulfilled
LEED 2009 (IEQ4.1/ IEQ4.2/ IEQ4.3)	fulfilled
Product category	cannot be classified
VOC limit	
Limit fulfilled	
Recycling share	not contained
Production site	DAW SE Roßdörfer Straße 50 DE-64372 Ober-Ramstadt

Building certifications - Assessment System NaWoh

Assessment System Sustainable Housing Constructions (NaWoh) v3.1	suitable
--	----------