

GUP FaserFix 210



Technical data

Specific use(s)	Cement
Density	1,40 g/cm ³
Consumption	8 - 20 kg/m ²

Components

Product Code/GISCODE	ZP1; ZP1
Declaration of ingredients	Cement mortar with hydrated lime
Preservation agents	not contained
VOC content in accordance with Directive 2004/42/EC	< 0.1 %
VOC content LEED [less water]	< 1 g/l
Water-dilutable in accordance with 2004/42/EC (Decopaint)	< 1 g/l
Lead, cadmium, chromium VI * (* not contained in the formulation)	yes
	not contained

Environmental labels

Building certifications - DGNB

Suitable according to DGNB criteria ENV1.2 (System version 2018 and 2015)

No.	Application site	Product Type	Considered substances / aspects	QS 1	QS 2	QS 3	QS 4
5	Coating materials for exterior mineral surfaces such as concrete, masonry, mineral mortar and filler, plaster, ETICS, wallpaper (façade wallpaper), plasterboard, etc.	Currently, just decorative paints and dispersion insulation adhesives are taken into account	VOC	Ja	Ja	Ja	Ja

Building certifications - LEED

Product category	cannot be classified
VOC limit	
Limit fulfilled	
Recycling share	not contained
Production site	DAW SE Roßdörfer Straße 50 DE-64372 Ober-Ramstadt

Building certifications - Assessment System NaWoh

Assessment System Sustainable Housing Constructions (NaWoh) v3.1	not suitable
--	--------------