

# Capatect CarboNit Flüssigkomponente



## Technical data

Specific use(s)	Water-borne coatings
Density	1,46 g/cm <sup>3</sup>

## Components

Product Code/GISCODE	M-DF01; BSW20
Preservation agents	contained
VOC content in accordance with Directive 2004/42/EC	< 0.1 %
VOC content LEED [less water]	< 1 g/l
Solvent and plasticiser-free in accordance with VdL- RL 01	yes
Water-dilutable in accordance with 2004/42/EC (Decopaint)	yes
Lead, cadmium, chromium VI *	not contained
SVHC >0,1% - Substances of Very High Concern	not contained
(* not contained in the formulation)	

## Environmental labels

## Building certifications - DGNB

Suitable according to DGNB criteria ENV1.2 (System version 2018 and 2015)

No.	Application site	Product Type	Considered substances / aspects	QS 1	QS 2	QS 3	QS 4
5	Coating materials forexterior mineral surfacessuch asconcrete, masonry,mineral mortar and filler,plaster, ETICS, wallpaper(façade wallpaper),plasterboard, etc.	Currently, just decorative paints and dispersioninsulation adhesiveare taken into account	VOC	Ja	Ja	Ja	Ja

## Building certifications - LEED

LEED v.4 (EQ CREDIT: Low emitting materials)	fulfilled
LEED 2009 (IEQ4.1/ IEQ4.2/ IEQ4.3)	fulfilled
Product category	flat topcoat
VOC limit	50 g/l
Limit fulfilled	yes
Recycling share	not contained
Production site	DAW SE Roßdörfer Straße 50 DE-64372 Ober-Ramstadt

## Building certifications - Assessment System NaWoh

Assessment System Sustainable Housing Constructions (NaWoh) v3.1	suitable
--	----------