

DisboCRET 505



Technical data

Specific use(s)	Cement
Density	3,00 g/cm ³
Consumption	2 kg/m ²

Components

Product Code/GISCODE	ZP1; ZP1
Preservation agents	not contained
VOC content in accordance with Directive 2004/42/EC	< 0.1 %
VOC content LEED [less water]	< 1 g/l
Solvent and plasticiser-free in accordance with VdL- RL 01	yes
Water-dilutable in accordance with 2004/42/EC (Decopaint)	yes
Lead, cadmium, chromium VI *	not contained
SVHC >0,1% - Substances of Very High Concern (* not contained in the formulation)	not contained

Environmental labels

Sustainability Data Sheet Print Date: 09.02.2024 Revision Date: 03.11.2023

This data sheet has been compiled based on state-of-the-art technology and our experience. However, in light of the wide range of requirements regarding buildings certifications, the buyer/user remains personally responsible for checking that our assessment is suitable for the intended certification system and its respective requirements. This data sheet is only valid in its latest version and in combination with the current Technical Information and the Material Safety Data Sheet. Please refer to our website to check the up-to-dateness of this version, if necessary.

Building certifications - DGNB

Suitable according to DGNB criteria ENV1.2 (System version 2018 and 2015)

No.	Application site	Product Type	Considered substances / aspects	QS 1	QS 2	QS 3	QS 4
2	Coatings on predominantly mineral interior subsurfaces as well as on wallpaper, non-woven materials, plasterboard, etc. Floor areas with special resistance requirements (such as OS (surface protection) systems) and traffic routes such as underground garages and access roads are not taken into account	This refers to decorative paints, primers, decorative fillers (incl. Q-filler) and deep primer, floor coatings with no special resistance requirements, concrete glazes	VOC / SVOC	Ja	Ja	Ja	Ja
5	Coating materials for exterior mineral surfaces such as concrete, masonry, mineral mortar and filler, plaster, ETICS, wallpaper (façade wallpaper), plasterboard, etc.	Currently, just decorative paints and dispersion insulation adhesive are taken into account	VOC	Ja	Ja	Ja	Ja

Building certifications - LEED

LEED v.4 (EQ CREDIT: Low emitting materials)	not fulfilled
LEED 2009 (IEQ4.1/ IEQ4.2/ IEQ4.3)	fulfilled
Product category	flat topcoat
VOC limit	50 g/l
Limit fulfilled	yes
Recycling share	not contained
Production site	DAW SE Roßdörfer Straße 50 DE-64372 Ober-Ramstadt

Building certifications - Assessment System NaWoh

Sustainability Data Sheet Print Date: 09.02.2024 Revision Date: 03.11.2023

This data sheet has been compiled based on state-of-the-art technology and our experience. However, in light of the wide range of requirements regarding buildings certifications, the buyer/user remains personally responsible for checking that our assessment is suitable for the intended certification system and its respective requirements. This data sheet is only valid in its latest version and in combination with the current Technical Information and the Material Safety Data Sheet. Please refer to our website to check the up-to-dateness of this version, if necessary.