according to Regulation (EC) No. 1907/2006



DE / EN

# **Cap-elast Phase 2-W**

Version Revision Date: SDS Number: Date of last issue: 17.12.2021 4.0 09.01.2023 6003134 Date of first issue: 01.12.2019

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Cap-elast Phase 2-W

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-: Water-borne coatings

stance/Mixture

Recommended restrictions

on use

: within adequate application - none

1.3 Details of the supplier of the safety data sheet

Company : Caparol Farben Lacke GmbH

Roßdörfer Straße 50 64372 Ober-Ramstadt

Telephone : +496154710 Telefax : +4961547170222

E-mail address Responsi-

ble/issuing person

: msds@dr-rmi.com

1.4 Emergency telephone

Emergency telephone 1 : +49613284463 GBK GmbH

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

# Classification (REGULATION (EC) No 1272/2008)

Skin sensitization, Category 1 H317: May cause an allergic skin reaction.

Long-term (chronic) aquatic hazard, Cat-

egory 3

H412: Harmful to aquatic life with long lasting ef-

fects.

#### 2.2 Label elements

#### Labeling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006

DE / EN



# **Cap-elast Phase 2-W**

Version Revision Date: SDS Number: Date of last issue: 17.12.2021 4.0 09.01.2023 6003134 Date of first issue: 01.12.2019

Hazard pictograms

Signal Word Warning

**Hazard Statements** H317 May cause an allergic skin reaction.

> H412 Harmful to aquatic life with long lasting effects.

P101 If medical advice is needed, have product container or **Precautionary Statements** 

label at hand.

P102 Keep out of reach of children.

Prevention:

P262 Do not get in eyes, on skin, or on clothing.

P273 Avoid release to the environment. P280 Wear protective gloves/ eye protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and

water.

## Hazardous ingredients which must be listed on the label:

1,2-benzisothiazol-3(2H)-one octhilinone (ISO)

2-methylisothiazol-3(2H)-one

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

#### **Additional Labeling**

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not

breathe spray or mist.

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006



DE / EN

# **Cap-elast Phase 2-W**

Version Revision Date: SDS Number: Date of last issue: 17.12.2021 4.0 09.01.2023 6003134 Date of first issue: 01.12.2019

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Chemical nature : Emulsion paint, aqueous

## Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7 236-675-5 022-006-00-2 01-2119489379-17	Carc. 2; H351	>= 10 - < 20
2-methylpentane-2,4-diol	107-41-5 203-489-0 603-053-00-3 01-2119539582-35	Skin Irrit. 2; H315 Eye Irrit. 2; H319	>= 1 - < 10
1,2-benzisothiazol-3(2H)-one	2634-33-5 220-120-9 613-088-00-6 01-2120761540-60	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 Acute Tox. 2; H330  M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1  specific concentration limit Skin Sens. 1; H317 >= 0,05 %	>= 0,0025 - < 0,025
octhilinone (ISO)	26530-20-1 247-761-7 613-112-00-5 01-2120768921-45	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 3; H311 Skin Corr. 1; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1;	>= 0,0025 - < 0,025

according to Regulation (EC) No. 1907/2006



DE / EN

# **Cap-elast Phase 2-W**

Version	Revision Date:	SDS Number:	Date of last issue: 17.12.2021
4.0	09.01.2023	6003134	Date of first issue: 01.12.2019

09.01.2023	0005154	Date of 1113t 133de. 01.12.2013	
		H410 EUH071	
		M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100	
		specific concentration limit Skin Sens. 1A; H317 >= 0,0015 %	
		Acute toxicity esti- mate	
		Acute oral toxicity: 125 mg/kg Acute inhalation toxicity (dust/mist): 0,27 mg/l Acute dermal toxicity: 311 mg/kg	
terbutryn	886-50-0 212-950-5	Acute Tox. 4; H302 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Skin Sens. 1; H317	>= 0,0025 - < 0,025
		M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100	
		specific concentration limit Skin Sens. 1; H317 >= 3 %	
2-methylisothiazol-3(2H)-on	e 2682-20-4 220-239-6 613-326-00-9 01-2120764690	Acute Tox. 2; H330 Acute Tox. 3; H311 Acute Tox. 3; H301 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317	>= 0,0025 - < 0,025

according to Regulation (EC) No. 1907/2006



DE / EN

Cap-elast Phase 2-W	

Version	Revision Date:	SDS Number:	Date of last issue: 17.12.2021
4.0	09.01.2023	6003134	Date of first issue: 01.12.2019

U	09.01.2023 600	)3134	Date of first issue: 01.12.2019	<u>'</u>
			Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071  M-Factor (Acute aquatic toxicity): 10	
			M-Factor (Chronic aquatic toxicity): 1  specific concentration limit Skin Sens. 1A; H317 >= 0,0015 %	
	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9 613-167-00-5 01-212076469	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071  M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100  specific concentration limit Skin Corr. 1C; H314 >= 0,6 % Skin Irrit. 2; H315 0,06 - < 0,6 % Eye Irrit. 2; H319 0,06 - < 0,6 % Skin Sens. 1A; H317 >= 0,0015 % Eye Dam. 1; H318 >= 0,6 %	>= 0,0002 - < 0,0015

according to Regulation (EC) No. 1907/2006



DE / EN

# **Cap-elast Phase 2-W**

Version Revision Date: SDS Number: Date of last issue: 17.12.2021 4.0 09.01.2023 6003134 Date of first issue: 01.12.2019

Substances with a workplace exposure limit :			
Kieselguhr, soda ash flux-calcined	68855-54-9		>= 1 - < 10
	272-489-0		
	21-2119488518-22		

For explanation of abbreviations see section 16.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first-aid measures

General advice Never give anything by mouth to an unconscious person.

If you feel unwell, seek medical advice (show the label where

possible).

Move out of dangerous area. First aider needs to protect himself.

If inhaled Move to fresh air.

In case of skin contact Take off all contaminated clothing immediately.

Do NOT use solvents or thinners.

In case of contact, immediately flush skin with soap and plenty

of water.

If eye irritation persists: Get medical advice/ attention. In case of eye contact

> IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

If swallowed Seek medical advice.

Clean mouth with water and drink afterwards plenty of water.

If swallowed, DO NOT induce vomiting.

## 4.2 Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction. Risks

#### 4.3 Indication of any immediate medical attention and special treatment needed

**Treatment** : No information available.

### **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or car-

bon dioxide.

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

according to Regulation (EC) No. 1907/2006

DE / EN



**Cap-elast Phase 2-W** 

Version Revision Date: SDS Number: Date of last issue: 17.12.2021 4.0 09.01.2023 6003134 Date of first issue: 01.12.2019

Do not use a solid water stream as it may scatter and spread

fire.

Unsuitable extinguishing

media

None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire

fighting

In case of fire hazardous decomposition products may be

produced such as:

Carbon monoxide, carbon dioxide and unburned hydrocar-

bons (smoke).

5.3 Advice for firefighters

Special protective equipment :

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

Further information : Use water spray to cool unopened containers.

Standard procedure for chemical fires. The product itself does not burn.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use protective shoes or boots with rough rubber sole.

Material can create slippery conditions. Do not get in eyes, on skin, or on clothing.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Do not flush into surface water or sanitary sewer system.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

#### 6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.

, For personal protection see section 8., For disposal considerations see section 13.

according to Regulation (EC) No. 1907/2006



DE / EN

# **Cap-elast Phase 2-W**

Version Revision Date: SDS Number: Date of last issue: 17.12.2021 4.0 09.01.2023 6003134 Date of first issue: 01.12.2019

## **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Advice on safe handling Use only with adequate ventilation.

For personal protection see section 8.

No special technical protective measures required.

No interior use.

In addition, the current technical information for this product and its application on www.caparol.com must be observed.

Hygiene measures Wash hands before eating, drinking, or smoking. Do not eat,

> drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering eating

areas.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage

areas and containers

: Perishable if frozen. To maintain product quality, do not store in heat or direct sunlight. Store at room temperature in the original container. Containers which are opened must be care-

fully resealed and kept upright to prevent leakage.

Keep away from oxidizing agents and strongly acid or alkaline Advice on common storage

materials.

Storage class (TRGS 510) : 12

7.3 Specific end use(s)

Specific use(s) This information is not available.

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form	Control parameters	Basis
		of exposure)		
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	AGW (Inhalable fraction)	10 mg/m3 (Titanium dioxide)	DE TRGS 900
, -	Peak-limit cat	egory: 2;(II)		

according to Regulation (EC) No. 1907/2006



DE / EN

# **Cap-elast Phase 2-W**

Version Revision Date: SDS Number: Date of last issue: 17.12.2021 4.0 09.01.2023 6003134 Date of first issue: 01.12.2019

1	Further information: When there is compliance with the OEL and biological				
	tolerance valu	ies, there is no risk c	of harming the unborn child	· ·	
		AGW (Alveolate	1,25 mg/m3	DE TRGS	
		fraction)	(Titanium dioxide)	900	
	Peak-limit cat	egory: 2;(II)			
			compliance with the OEL ar	nd biological	
	tolerance valu	es, there is no risk o	f harming the unborn child		
		BM (Alveolar 0,5 mg/m3 DE TRG			
		dust fraction)		527	
Kieselguhr, soda	68855-54-9	AGW (Alveolate	0,3 mg/m3	DE TRGS	
ash flux-calcined	fraction) 900				
			compliance with the OEL ar	nd biological	
	tolerance valu	ies, there is no risk c	of harming the unborn child		
octhilinone (ISO)	26530-20-1	AGW (Inhalable	0,05 mg/m3	DE TRGS	
		fraction)		900	
	Peak-limit category: 2;(I)				
	Further information: Skin absorption, When there is compliance with the OEL				
	and biological tolerance values, there is no risk of harming the unborn child				

# Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of expo- sure	Potential health effects	Value
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm]	Consumers	Ingestion	Long-term systemic effects	700,00 mg/kg bw/day
	Workers	Inhalation	Long-term local ef- fects	10,00 mg/m3
Kieselguhr, soda ash flux-calcined	Consumers	Ingestion	Long-term systemic effects	18,70 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,05 mg/m3
	Workers	Inhalation	Long-term systemic effects	0,05 mg/m3
Kaolin, calcined	Workers	Inhalation	Acute systemic effects	3,00 mg/m3
	Workers	Inhalation	Acute local effects	3,00 mg/m3
	Workers	Inhalation	Long-term systemic effects	3,00 mg/m3
	Workers	Inhalation	Long-term local ef- fects	3,00 mg/m3
1-(2-butoxy-1- methylethoxy)propan- 2-ol	Consumers	Inhalation	Long-term systemic effects	1,20 mg/m3
	Consumers	Ingestion	Long-term systemic effects	7,50 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic	1,10 mg/kg

according to Regulation (EC) No. 1907/2006



DE / EN

# **Cap-elast Phase 2-W**

Version Revision Date: SDS Number: Date of last issue: 17.12.2021 4.0 09.01.2023 6003134 Date of first issue: 01.12.2019

			effects	bw/day
	Workers	Inhalation	Long-term systemic effects	10,00 mg/m3
	Workers	Skin contact	Long-term systemic effects	3,00 mg/kg bw/day
2-methylpentane-2,4- diol	Consumers	Inhalation	Long-term local ef- fects	25,00 mg/m3
	Consumers	Inhalation	Long-term systemic effects	3,50 mg/m3
	Consumers	Ingestion	Long-term systemic effects	1,00 mg/kg bw/day
	Consumers	Inhalation	Acute local effects	49,00 mg/m3
	Consumers	Skin contact	Long-term systemic effects	1,00 mg/kg bw/day
	Workers	Inhalation	Acute local effects	98,00 mg/m3
	Workers	Inhalation	Long-term systemic effects	14,00 mg/m3
	Workers	Inhalation	Long-term local ef- fects	49,00 mg/m3
	Workers	Skin contact	Long-term systemic effects	2,00 mg/kg bw/day

# Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm]	Sewage treatment plant	100 mg/l
	Fresh water	0,184 mg/l
	Soil	100 mg/kg dry weight (d.w.)
	Sea water	0,0184 mg/l
	Fresh water sediment	1000 mg/kg dry weight (d.w.)
	Sea sediment	100 mg/kg dry weight (d.w.)
	Intermittent use/release	0,193 mg/l
Kieselguhr, soda ash flux- calcined	Sewage treatment plant	100 mg/l
Kaolin, calcined	Intermittent use/release	25 mg/l
	Fresh water	4,1 mg/l
	Sea water	0,41 mg/l
	Sewage treatment plant	1400 mg/l
1-(2-butoxy-1- methylethoxy)propan-2-ol	Sewage treatment plant	100 mg/l
	Fresh water	0,519 mg/l
	Soil	0,287 mg/kg dry weight (d.w.)
	Intermittent use/release	5,19 mg/l

according to Regulation (EC) No. 1907/2006

CAPAROL

DE / EN

# **Cap-elast Phase 2-W**

Version Revision Date: SDS Number: Date of last issue: 17.12.2021 4.0 09.01.2023 6003134 Date of first issue: 01.12.2019

	Fresh water sediment	2,96 mg/kg dry weight (d.w.)
	Sea water	0,0519 mg/l
	Sea sediment	0,296 mg/kg dry weight (d.w.)
2-methylpentane-2,4-diol	Soil	0,11 mg/kg dry weight (d.w.)
	Intermittent use/release	4,29 mg/l
	Secondary Poisoning	100 mg/kg food
	Fresh water sediment	1,79 mg/kg dry weight (d.w.)
	Sea water	0,0429 mg/l
	Sewage treatment plant	20 mg/l
	Sea sediment	0,179 mg/kg dry weight (d.w.)
	Fresh water	0,429 mg/l

#### 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection : DGUV Regulation 112-192 - Use of eye and face protection

Goggles

Hand protection

Material : Nitrile rubber Glove thickness : 0,2 mm Protective index : Class 3

Remarks : Before removing gloves clean them with soap and water.

Wear suitable gloves tested to EN374.

DGUV Regulation 112-195 - Use of protective gloves

Skin and body protection : Safety shoes

Long sleeved clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

Remove and wash contaminated clothing before re-use.

During spray application: impervious clothing

Respiratory protection : No personal respiratory protective equipment normally re-

quired.

DGUV Regulation 112-190 - Use of breathing equipment

according to Regulation (EC) No. 1907/2006

DE / EN



# **Cap-elast Phase 2-W**

Version Revision Date: SDS Number: Date of last issue: 17.12.2021 4.0 09.01.2023 6003134 Date of first issue: 01.12.2019

During spray application: Do not breathe spray dust. Use A2/P2 combination filter for paint spraying.

# **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

Physical state : liquid

Color : No data available

Odor : No data available

Melting point/freezing point : ca. 0 °C

Boiling point/boiling range : ca. 100 °C

Upper explosion limit / Upper

flammability limit

not determined

Lower explosion limit / Lower

flammability limit

not determined

Flash point : Not applicable

Autoignition temperature : not determined

Decomposition temperature : Not applicable

pH : 8-9

Concentration: 100 %

Viscosity

Viscosity, dynamic : No data available

Solubility(ies)

Water solubility : completely miscible

Partition coefficient: n-

octanol/water

not determined

Vapor pressure : ca. 23,4 hPa (20 °C)

Density : 1,2500 g/cm3

Relative vapor density : not determined

#### 9.2 Other information

according to Regulation (EC) No. 1907/2006

according to Regulation (EC) No. 1907/



DE / EN

# **Cap-elast Phase 2-W**

Version Revision Date: SDS Number: Date of last issue: 17.12.2021 4.0 09.01.2023 6003134 Date of first issue: 01.12.2019

Explosives : Not applicable

Oxidizing properties : Not applicable

Flammability (liquids) : The product is not flammable.

Evaporation rate : Not applicable

### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No decomposition if stored and applied as directed.

# 10.2 Chemical stability

No decomposition if stored and applied as directed.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

10.5 Incompatible materials

Materials to avoid : Incompatible with acids and bases.

Incompatible with oxidizing agents.

# 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

# **SECTION 11: Toxicological information**

# 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Acute toxicity**

Not classified based on available information.

### **Components:**

# 1,2-benzisothiazol-3(2H)-one:

Acute oral toxicity : LD50 (Rat): 532 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0,4 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

according to Regulation (EC) No. 1907/2006



DE / EN

**Cap-elast Phase 2-W** 

Version Revision Date: SDS Number: Date of last issue: 17.12.2021 4.0 09.01.2023 6003134 Date of first issue: 01.12.2019

octhilinone (ISO):

Acute oral toxicity : Acute toxicity estimate: 125 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

Acute inhalation toxicity : Acute toxicity estimate: 0,27 mg/l

Test atmosphere: dust/mist

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

Acute dermal toxicity : Acute toxicity estimate: 311 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

terbutryn:

Acute oral toxicity : LD50 Oral (Rat): > 300 mg/kg

Acute dermal toxicity : LD50 Dermal (Rat): > 2.000 mg/kg

2-methylisothiazol-3(2H)-one:

Acute oral toxicity : LD50 (Rat): 120 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0,145 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one

(3:1):

Acute oral toxicity : LD50 (Rat): 66 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 0,17 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 141 mg/kg

Method: OECD Test Guideline 402

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

according to Regulation (EC) No. 1907/2006

DE / EN



# **Cap-elast Phase 2-W**

Version Revision Date: SDS Number: Date of last issue: 17.12.2021 4.0 09.01.2023 6003134 Date of first issue: 01.12.2019

#### Respiratory or skin sensitization

#### Skin sensitization

May cause an allergic skin reaction.

#### Respiratory sensitization

Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

#### Reproductive toxicity

Not classified based on available information.

#### STOT-single exposure

Not classified based on available information.

#### STOT-repeated exposure

Not classified based on available information.

#### **Aspiration toxicity**

Not classified based on available information.

## 11.2 Information on other hazards

#### **Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

#### **Product:**

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna Straus (Water flea)): > 10 mg/l

End point: Immobilization Exposure time: 48 h

Test Type: static test

Method: OECD Test Guideline 202

GLP: no

Toxicity to algae/aquatic

plants

: ErC50 (Pseudokirchneriella subcapitata (green algae)): > 10

mg/l

according to Regulation (EC) No. 1907/2006

DE / EN



**Cap-elast Phase 2-W** 

Version Revision Date: SDS Number: Date of last issue: 17.12.2021 4.0 09.01.2023 6003134 Date of first issue: 01.12.2019

End point: Growth inhibition

Exposure time: 72 h

Test Type: Cell multiplication inhibition test

Method: OECD Test Guideline 201

GLP: no

**Ecotoxicology Assessment** 

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

**Components:** 

1,2-benzisothiazol-3(2H)-one:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2,2 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia): 3,27 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Selenastrum capricornutum (green algae)): 0,11 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

M-Factor (Acute aquatic tox-

icity)

: 1

M-Factor (Chronic aquatic

toxicity)

1

octhilinone (ISO):

M-Factor (Acute aquatic tox-

100

icity)

M-Factor (Chronic aquatic

toxicity)

100

terbutryn:

M-Factor (Acute aquatic tox-

icity)

100

M-Factor (Chronic aquatic

toxicity)

100

2-methylisothiazol-3(2H)-one:

M-Factor (Acute aquatic tox- : 10

according to Regulation (EC) No. 1907/2006



DE / EN

**Cap-elast Phase 2-W** 

Version Revision Date: SDS Number: Date of last issue: 17.12.2021 4.0 09.01.2023 6003134 Date of first issue: 01.12.2019

icity)

M-Factor (Chronic aquatic

toxicity)

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one

(3:1):

M-Factor (Acute aquatic tox- : 100

icity)

M-Factor (Chronic aquatic

toxicity)

100

: 1

## 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

#### **Components:**

octhilinone (ISO):

Partition coefficient: n- : log Pow: 2,92

octanol/water Method: OECD Test Guideline 117

terbutryn:

Partition coefficient: n-

octanol/water

log Pow: 3,66

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one

(3:1):

Partition coefficient: n- : log Pow: <= 0,71

octanol/water Method: OECD Test Guideline 117

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

#### **Product:**

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

#### 12.6 Endocrine disrupting properties

#### **Product:**

according to Regulation (EC) No. 1907/2006

DE / EN



**Cap-elast Phase 2-W** 

Version Revision Date: SDS Number: Date of last issue: 17.12.2021 4.0 09.01.2023 6003134 Date of first issue: 01.12.2019

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

#### 12.7 Other adverse effects

**Product:** 

Additional ecological infor-

mation

Harmful to aquatic organisms, may cause long-term adverse

effects in the aquatic environment.

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product :

Waste should not be disposed of via wastewater.

Contaminated packaging : Only completely emptied containers should be given for recy-

cling.

Waste Code : used product

080112, waste paint and varnish other than those mentioned

in 08 01 11\*

# **SECTION 14: Transport information**

#### 14.1 UN number or ID number

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

according to Regulation (EC) No. 1907/2006

DE / EN



# **Cap-elast Phase 2-W**

Version Revision Date: SDS Number: Date of last issue: 17.12.2021 4.0 09.01.2023 6003134 Date of first issue: 01.12.2019

#### 14.3 Transport hazard class(es)

**ADN** Not regulated as a dangerous good **ADR** Not regulated as a dangerous good RID Not regulated as a dangerous good **IMDG** Not regulated as a dangerous good **IATA** Not regulated as a dangerous good

14.4 Packing group

**ADN** Not regulated as a dangerous good **ADR** Not regulated as a dangerous good RID Not regulated as a dangerous good **IMDG** Not regulated as a dangerous good IATA (Cargo) Not regulated as a dangerous good IATA (Passenger) Not regulated as a dangerous good

#### 14.5 Environmental hazards

Not regulated as a dangerous good

#### 14.6 Special precautions for user

Remarks Not classified as dangerous in the meaning of transport regu-

lations.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

#### **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered: Number on list 3

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59).

This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be gener-

ated.

Regulation (EC) No 1005/2009 on substances that de-Not applicable

according to Regulation (EC) No. 1907/2006



DE / EN

# **Cap-elast Phase 2-W**

Version Revision Date: SDS Number: Date of last issue: 17.12.2021 4.0 09.01.2023 6003134 Date of first issue: 01.12.2019

plete the ozone layer

Regulation (EU) 2019/1021 on persistent organic pollu-Not applicable

tants (recast)

REACH - List of substances subject to authorisation None

(Annex XIV)

Seveso III: Directive 2012/18/EU of the Eurobean Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

ny)

Water hazard class (Germa: WGK 1 slightly water endangering

Classification according to AwSV, Annex 1 (5.2)

paints / Giscode

Product code for laquers and : M-DF02F Water-based paints, active agents

: BSW50 Coating materials, water-based, containing solvents,

film-protected

: Directive 2004/42/EC Volatile organic compounds

> < 3 % < 40 g/l

#### Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

## 15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

#### **SECTION 16: Other information**

#### **Full text of H-Statements**

H301 Toxic if swallowed. H302 Harmful if swallowed. Fatal in contact with skin. H310 Toxic in contact with skin. H311

H314 : Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage. Causes serious eye irritation. H319

Fatal if inhaled. H330

according to Regulation (EC) No. 1907/2006

DE / EN



# **Cap-elast Phase 2-W**

Version Revision Date: SDS Number: Date of last issue: 17.12.2021 4.0 09.01.2023 6003134 Date of first issue: 01.12.2019

H351 : Suspected of causing cancer if inhaled.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.H411 : Toxic to aquatic life with long lasting effects.

EUH071 : Corrosive to the respiratory tract.

#### Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard

Carc. : Carcinogenicity
Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation
Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitization

DE TRGS 527 : Germany. TRGS 527 - Activities with nanomaterials

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

DE TRGS 527 / BM : Assessment scale
DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AlIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELX - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Covid Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - Lethal Dose to 50% of a test population; Chorae Existing Chemicals Inventory; LC50 - Lethal Concentration to 50% of a test population; LD50 - Lethal Dose to 50% of a test population; Chorae Existing Chemicals Inventory; LC50 - Lethal Concentration to 50% of a test population; Chorae Existing Chemicals Inventory; LC50 - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Loading Rate; NIC10C - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumula

#### **Further information**

#### Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

## Sources of key data used to compile the Material Safety Data Sheet:

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH NIOSH - Registry of toxic effects of chemical substances

according to Regulation (EC) No. 1907/2006

DE / EN



# **Cap-elast Phase 2-W**

Version Revision Date: SDS Number: Date of last issue: 17.12.2021 4.0 09.01.2023 6003134 Date of first issue: 01.12.2019

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

## Classification of the mixture: Classification procedure:

Skin Sens. 1 H317 Calculation method

Aquatic Chronic 3 H412 Based on product data or assessment

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

# **REACH Information**

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN