

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect Fassadenputz R30 Sonderton

Version	Revision Date:	Print Date	Date of last issue: 04.10.2019
2.0	17.11.2020	19.11.2020	Date of first issue: 04.10.2019

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Capatect Fassadenputz R30 Sonderton

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Water-borne coatings

Recommended restrictions : within adequate application - none on use

#### 1.3 Details of the supplier of the safety data sheet

Company : Caparol Farben Lacke GmbH  
Roßdörfer Straße 50  
64372 Ober-Ramstadt

Telephone : +496154710  
Telefax : +4961547170222  
E-mail address Responsible/issuing person : msds@dr-rmi.com

#### 1.4 Emergency telephone number

Emergency telephone number 1 : +49613284463 GBK GmbH

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect Fassadenputz R30 Sonderton

Version	Revision Date:	Print Date	Date of last issue: 04.10.2019
2.0	17.11.2020	19.11.2020	Date of first issue: 04.10.2019

Precautionary statements : P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

### Prevention:

P262 Do not get in eyes, on skin, or on clothing.

P280 Wear protective gloves/ eye protection.

### Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

### Hazardous components which must be listed on the label:

1,2-benzisothiazol-3(2H)-one

2-methylisothiazol-3(2H)-one

### Additional Labelling

**EUH211** Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Synthetic resin plaster, aqueous

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
titanium dioxide	13463-67-7 236-675-5 022-006-00-2 01-2119489379-17	Carc. 2; H351	>= 1 - < 10
1,2-benzisothiazol-3(2H)-one	2634-33-5 220-120-9 613-088-00-6 01-2120761540-60	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2;	>= 0,0025 - < 0,025

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect Fassadenputz R30 Sonderton

Version 2.0      Revision Date: 17.11.2020      Print Date 19.11.2020      Date of last issue: 04.10.2019  
Date of first issue: 04.10.2019

		H411 Acute Tox. 2; H330  M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	
2-methylisothiazol-3(2H)-one	2682-20-4 220-239-6 613-326-00-9 01-2120764690-50	Acute Tox. 2; H330 Acute Tox. 3; H311 Acute Tox. 3; H301 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410  M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1	$\geq 0,0025 - < 0,025$
pyrithione zinc	13463-41-7 236-671-3 01-2119511196-46	Acute Tox. 3; H301 Acute Tox. 2; H330 Eye Dam. 1; H318 Aquatic Acute 1; H400 Aquatic Chronic 1; H410  M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 10	$\geq 0,0002 - < 0,0025$
Substances with a workplace exposure limit :			
aluminium hydroxide	21645-51-2 244-492-7 01-2119529246-39		$\geq 1 - < 10$

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

General advice : Never give anything by mouth to an unconscious person.  
If you feel unwell, seek medical advice (show the label where possible).

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect Fassadenputz R30 Sonderton

Version	Revision Date:	Print Date	Date of last issue: 04.10.2019
2.0	17.11.2020	19.11.2020	Date of first issue: 04.10.2019

- Move out of dangerous area.  
First aider needs to protect himself.
- If inhaled : Move to fresh air.
- In case of skin contact : Do NOT use solvents or thinners.  
In case of contact, immediately flush skin with soap and plenty of water.
- In case of eye contact : If eye irritation persists: Get medical advice/ attention.  
IF IN EYES: Rinse cautiously with water for several minutes.  
Remove contact lenses, if present and easy to do. Continue rinsing.
- If swallowed : Seek medical advice.  
Clean mouth with water and drink afterwards plenty of water.  
If swallowed, DO NOT induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

None known.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media : None known.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : In case of fire hazardous decomposition products may be produced such as:  
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Standard procedure for chemical fires.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect Fassadenputz R30 Sonderton

Version	Revision Date:	Print Date	Date of last issue: 04.10.2019
2.0	17.11.2020	19.11.2020	Date of first issue: 04.10.2019

The product itself does not burn.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use protective shoes or boots with rough rubber sole.  
Material can create slippery conditions.  
Do not get in eyes, on skin, or on clothing.

#### 6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.  
Do not flush into surface water or sanitary sewer system.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

#### 6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.

,For personal protection see section 8.,For disposal considerations see section 13.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.  
No special technical protective measures required.

In addition, the current technical information for this product and its application on [www.caparol.com](http://www.caparol.com) must be observed.

Hygiene measures : Wash hands before eating, drinking, or smoking. Do not eat, drink or smoke when using this product.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Perishable if frozen. To maintain product quality, do not store in heat or direct sunlight. Store at room temperature in the original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline materials.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect Fassadenputz R30 Sonderton

Version	Revision Date:	Print Date	Date of last issue: 04.10.2019
2.0	17.11.2020	19.11.2020	Date of first issue: 04.10.2019

Storage class (TRGS 510) : 12, Non Combustible Liquids

### 7.3 Specific end use(s)

Specific use(s) : This information is not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
aluminium hydroxide	21645-51-2	AGW (Inhalable fraction)	10 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., Commission for dangerous substances, General dust value. For this substance no specific occupational exposure limit value is established, since the AGS does not yet have information regarding unspecific action on the respiratory organs in excess of the normal values.			
		AGW (Alveolate fraction)	1,25 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., Commission for dangerous substances, General dust value. For this substance no specific occupational exposure limit value is established, since the AGS does not yet have information regarding unspecific action on the respiratory organs in excess of the normal values.			
titanium dioxide	13463-67-7	AGW (Inhalable fraction)	10 mg/m <sup>3</sup> (Titanium dioxide)	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(II)			
		AGW (Alveolate fraction)	1,25 mg/m <sup>3</sup> (Titanium dioxide)	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(II)			

#### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
aluminium hydroxide	Consumers	Ingestion	Long-term systemic effects	4,74 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	10,76 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	10,76 mg/m <sup>3</sup>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect Fassadenputz R30 Sonderton

Version 2.0      Revision Date: 17.11.2020      Print Date 19.11.2020      Date of last issue: 04.10.2019  
Date of first issue: 04.10.2019

titanium dioxide	Consumers	Ingestion	Long-term systemic effects	700,00 mg/kg bw/day
	Workers	Inhalation	Long-term local effects	10,00 mg/m <sup>3</sup>
pyrithione zinc	Workers	Skin contact	Long-term systemic effects	0,01 mg/kg bw/day

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
titanium dioxide	Sewage treatment plant	100 mg/l
	Fresh water	0,184 mg/l
	Soil	100 mg/kg dry weight (d.w.)
	Marine water	0,0184 mg/l
	Fresh water sediment	1000 mg/kg dry weight (d.w.)
	Marine sediment	100 mg/kg dry weight (d.w.)
pyrithione zinc	Intermittent use/release	0,193 mg/l
	Marine sediment	0,0095 mg/kg dry weight (d.w.)
	Fresh water sediment	0,0095 mg/kg dry weight (d.w.)
	Soil	1,02 mg/kg dry weight (d.w.)
	Sewage treatment plant	0,01 mg/l

## 8.2 Exposure controls

### Personal protective equipment

Eye protection : German trade association rules - BGR 192 Eye protection  
Goggles

### Hand protection

Material : Nitrile rubber  
Glove thickness : 0,2 mm  
Protective index : Class 3

Remarks : Before removing gloves clean them with soap and water.  
Wear suitable gloves tested to EN374.  
German trade association leaflet: Carry gloves (ZH 1/706)

Skin and body protection : Safety shoes  
Long sleeved clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect Fassadenputz R30 Sonderton

Version	Revision Date:	Print Date	Date of last issue: 04.10.2019
2.0	17.11.2020	19.11.2020	Date of first issue: 04.10.2019

Skin should be washed after contact.

Remove and wash contaminated clothing before re-use.  
During spray application: impervious clothing

Respiratory protection : No personal respiratory protective equipment normally required.

German trade association rules - BGR 190 Breathing protection

During spray application: Do not breathe spray dust. Use A2/P2 combination filter for paint spraying.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: No data available
Odour	: No data available
Odour Threshold	: Not relevant
pH	: 8 - 9 Concentration: 100 %
Melting point/freezing point	: not determined
Boiling point/boiling range	: not determined
Flash point	: Not applicable
Evaporation rate	: Not applicable
Upper explosion limit / Upper flammability limit	: not determined
Lower explosion limit / Lower flammability limit	: not determined
Vapour pressure	: not determined
Relative vapour density	: not determined
Relative density	: not determined



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect Fassadenputz R30 Sonderton

Version	Revision Date:	Print Date	Date of last issue: 04.10.2019
2.0	17.11.2020	19.11.2020	Date of first issue: 04.10.2019

Density : 1,8 g/cm<sup>3</sup>

Solubility(ies)  
Water solubility : completely miscible

Partition coefficient: n-  
octanol/water : not determined

Auto-ignition temperature : not determined

Decomposition temperature : Not applicable

Viscosity  
Viscosity, dynamic : No data available

Explosive properties : Not applicable

Oxidizing properties : Not applicable

### 9.2 Other information

Flammability (liquids) : The product is not flammable.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

### 10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

### 10.5 Incompatible materials

Materials to avoid : Incompatible with acids and bases.  
Incompatible with oxidizing agents.

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect Fassadenputz R30 Sonderton

Version	Revision Date:	Print Date	Date of last issue: 04.10.2019
2.0	17.11.2020	19.11.2020	Date of first issue: 04.10.2019

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

##### Acute toxicity

###### Product:

- Acute oral toxicity : Remarks: Based on available data, the classification criteria are not met.
- Acute inhalation toxicity : Remarks: Based on available data, the classification criteria are not met.
- Acute dermal toxicity : Remarks: Based on available data, the classification criteria are not met.

###### Components:

###### **1,2-benzisothiazol-3(2H)-one:**

- Acute oral toxicity : LD50 (Rat): 532 mg/kg
- Acute inhalation toxicity : LC50 (Rat): 0,4 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist
- Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

###### **2-methylisothiazol-3(2H)-one:**

- Acute oral toxicity : LD50 (Rat): 120 mg/kg
- Acute inhalation toxicity : LC50 (Rat): 0,145 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

###### **pyrithione zinc:**

- Acute oral toxicity : LD50 (Rat): 200 mg/kg  
Method: OECD Test Guideline 401
- Acute inhalation toxicity : LC50: 0,5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist
- Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect Fassadenputz R30 Sonderton

Version	Revision Date:	Print Date	Date of last issue: 04.10.2019
2.0	17.11.2020	19.11.2020	Date of first issue: 04.10.2019

### Skin corrosion/irritation

**Product:**

Remarks : According to the classification criteria of the European Union, the product is not considered as being a skin irritant.

### Serious eye damage/eye irritation

**Product:**

Remarks : According to the classification criteria of the European Union, the product is not considered as being an eye irritant.

**Components:**

**pyrithione zinc:**

Assessment : Risk of serious damage to eyes.

### Respiratory or skin sensitisation

**Product:**

Remarks : Causes sensitisation.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

**Product:**

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

**Components:**

**1,2-benzisothiazol-3(2H)-one:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2,2 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 3,27 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 0,11 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect Fassadenputz R30 Sonderton

Version	Revision Date:	Print Date	Date of last issue: 04.10.2019
2.0	17.11.2020	19.11.2020	Date of first issue: 04.10.2019

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

### **2-methylisothiazol-3(2H)-one:**

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 1

### **pyrithione zinc:**

M-Factor (Acute aquatic toxicity) : 100

M-Factor (Chronic aquatic toxicity) : 10

## 12.2 Persistence and degradability

No data available

## 12.3 Bioaccumulative potential

No data available

## 12.4 Mobility in soil

No data available

## 12.5 Results of PBT and vPvB assessment

### **Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

## 12.6 Other adverse effects

### **Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect Fassadenputz R30 Sonderton

Version	Revision Date:	Print Date	Date of last issue: 04.10.2019
2.0	17.11.2020	19.11.2020	Date of first issue: 04.10.2019

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Product : .  
Waste should not be disposed of via wastewater.

Contaminated packaging : Only completely emptied containers should be given for recycling.

Waste Code : used product  
080112, waste paint and varnish other than those mentioned  
in 08 01 11\*

### SECTION 14: Transport information

#### 14.1 UN number

Not regulated as a dangerous good

#### 14.2 UN proper shipping name

Not regulated as a dangerous good

#### 14.3 Transport hazard class(es)

Not regulated as a dangerous good

#### 14.4 Packing group

Not regulated as a dangerous good

#### 14.5 Environmental hazards

Not regulated as a dangerous good

#### 14.6 Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport regulations.

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 3

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect Fassadenputz R30 Sonderton

Version	Revision Date:	Print Date	Date of last issue: 04.10.2019
2.0	17.11.2020	19.11.2020	Date of first issue: 04.10.2019

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be generated.

REACH - List of substances subject to authorisation (Annex XIV) : None

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.  
Not applicable

Water contaminating class (Germany) : 1 slightly water endangering  
Classification according to AwSV, Annex 1 (5.2)

Product code for laquers and paints / Giscode : M-DF02 Water-based paints

. : BSW20 Coating materials, water-based

Volatile organic compounds : Directive 2004/42/EC  
< 2 %  
< 20 g/l

### Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

### 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

## SECTION 16: Other information

### Full text of H-Statements

H301 : Toxic if swallowed.  
H302 : Harmful if swallowed.  
H311 : Toxic in contact with skin.  
H314 : Causes severe skin burns and eye damage.  
H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H318 : Causes serious eye damage.  
H330 : Fatal if inhaled.  
H351 : Suspected of causing cancer if inhaled.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect Fassadenputz R30 Sonderton

Version	Revision Date:	Print Date	Date of last issue: 04.10.2019
2.0	17.11.2020	19.11.2020	Date of first issue: 04.10.2019

H400 : Very toxic to aquatic life.  
H410 : Very toxic to aquatic life with long lasting effects.  
H411 : Toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Acute : Short-term (acute) aquatic hazard  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Carc. : Carcinogenicity  
Eye Dam. : Serious eye damage  
Skin Corr. : Skin corrosion  
Skin Irrit. : Skin irritation  
Skin Sens. : Skin sensitisation  
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.  
DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

#### Sources of key data used to compile the Safety Data Sheet:

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs.

Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect Fassadenputz R30 Sonderton

Version	Revision Date:	Print Date	Date of last issue: 04.10.2019
2.0	17.11.2020	19.11.2020	Date of first issue: 04.10.2019

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

### Classification of the mixture:

Skin Sens. 1

H317

### Classification procedure:

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

### REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN