

Capatect Fassadenputz K15

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
3.1	10.05.2023	6000620	Date of first issue: 10.05.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier	
Trade name	: Capatect Fassadenputz K15
1.2 Relevant identified uses of t	he substance or mixture and uses advised against
Use of the Sub- stance/Mixture	: Water-borne coatings
Recommended restrictions on use	: within adequate application - none
1.3 Details of the supplier of the	safety data sheet
Company	: Caparol Farben Lacke GmbH Roßdörfer Straße 50 64372 Ober-Ramstadt
Telephone	: +496154710
Telefax	: +4961547170222
Website	:
E-mail address Responsi- ble/issuing person	: msds@dr-rmi.com
1.4 Emergency telephone	
Emergency telephone 1	: +49613284463 GBK GmbH
SECTION 2: Hazards identified	ation

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)				
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.			

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms



2

Signal Word

Warning



Capatect Fassadenputz K15

Version 3.1	Revision Date: 10.05.2023	-	DS Num 000620	er: Date of last issue Date of first issue	
Hazar	d Statements	:	H317	May cause an allergic skin re	eaction.
Precautionary Statements		:	P101 label at P102	f medical advice is needed, nand. Keep out of reach of children	
			Prever P262 P280	i on: Do not get in eyes, on skin, c Near protective gloves/ eye	
			Respo	se:	
			P302 + water. P362 + before	P364 Take off contaminate	vith plenty of soap and ed clothing and wash it

Hazardous ingredients which must be listed on the label:

1,2-benzisothiazol-3(2H)-one 2-methylisothiazol-3(2H)-one reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature

: Synthetic resin plaster, aqueous

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
	Registration number		



Capatect Fassadenputz K15

$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	ersion 1	Revision Date: 10.05.2023	SDS 6000			of last issue: 02.02.2023 of first issue: 10.05.2023	
1,2-benzisothiazol-3(2H)-one 2634-33-5 220-120-9 613-088-00-6 01-2120761540-60 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 Acute Tox. 2; H330 >= 0,0025 - < 0,025 2.methylisothiazol-3(2H)-one 2682-20-4 220-239-6 613-326-00-9 01-2120764690-50 Acute Tox. 2; H330 Acute Tox. 2; H330 Acute Tox. 2; H330 Acute Tox. 3; H311 Skin Sens. 1; H317 >= 0,0025 - < 0,025 2-methylisothiazol-3(2H)-one 2682-20-4 220-239-6 613-326-00-9 01-2120764690-50 Acute Tox. 2; H330 Acute Tox. 3; H311 Acute Tox. 3; H314 Eye Dam. 1; H318 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Chronic 1; H440 >= 0,0025 - < 0,025 M-Factor (Acute aquatic toxicity): 1	contair cles w	ning 1 % or more of par ith aerodynamic diamet	ti- er ≤	236-675-5 022-006-00-2	17	Carc. 2; H351	>= 0,1 - < 1
220-239-6 Acute Tox. 3; H311 0,025 613-326-00-9 01-2120764690-50 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1 specific concentration limit Skin Sens. 1A; H317 Skin Sens. 1A; H317				2634-33-5 220-120-9 613-088-00-6		Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 Acute Tox. 2; H330 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1 specific concentration limit Skin Sens. 1; H317	>= 0,0025 - < 0,025
	2-meth	nylisothiazol-3(2H)-one		220-239-6 613-326-00-9	50	Acute Tox. 3; H311 Acute Tox. 3; H301 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1 specific concentration limit Skin Sens. 1A; H317	>= 0,0025 - < 0,025





Capatect Fassadenputz K15

sion		SDS Number: 6000620	Date of last issue: 02.02.2023 Date of first issue: 10.05.2023
	yl-2H-isothiazol-3-one and yl-2H-isothiazol-3-one (3:		-48 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100 Specific concentration limit Skin Corr. 1C; H314 >= 0,6 % Skin Irrit. 2; H315 0,06 - < 0,6 % Eye Irrit. 2; H319 0,06 - < 0,6 % Skin Sens. 1A; H317 >= 0,0015 %
			Eye Dam. 1; H318 >= 0,6 %
	tances with a workplace e		
Kiese	lguhr, soda ash flux-calci	ned 68855-54-9 272-489-0	>= 1 - < 10
		21-2119488518	-22

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice	 Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Move out of dangerous area. First aider needs to protect himself.
If inhaled	: Move to fresh air.



Capatect Fassadenputz K15

Version 3.1	Revision Date: 10.05.2023	SDS Numb 6000620	Der: Date of last issue: 02.02.2023 Date of first issue: 10.05.2023
In cas	e of skin contact		T use solvents or thinners. of contact, immediately flush skin with soap and plenty er.
In cas	e of eye contact	IF IN E	rritation persists: Get medical advice/ attention. YES: Rinse cautiously with water for several minutes. re contact lenses, if present and easy to do. Continue
lf swa	llowed	Clean	nedical advice. mouth with water and drink afterwards plenty of water. owed, DO NOT induce vomiting.
4.2 Most i	mportant symptoms a	Ind effects,	both acute and delayed
Risks		: May ca	use an allergic skin reaction.
4.3 Indicat	tion of any immediate	medical att	ention and special treatment needed
Treatr	-		rmation available.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media	:	Use water spray, alcohol-resistant foam, dry chemical or car- bon dioxide. Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment. Do not use a solid water stream as it may scatter and spread fire.
Unsuitable extinguishing media	:	None known.
5.2 Special hazards arising from	the	e substance or mixture
Specific hazards during fire fighting	:	In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocar- bons (smoke).
5.3 Advice for firefighters		
Special protective equipment for fire-fighters	:	Wear self-contained breathing apparatus for firefighting if nec- essary.
Further information	:	Standard procedure for chemical fires. The product itself does not burn.



Capatect Fassadenputz K15

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
3.1	10.05.2023	6000620	Date of first issue: 10.05.2023

SECTION 6: Accidental release measures

6.1 Personal precautions, protectiv	e equipment and emergency procedures			
Personal precautions :	Use protective shoes or boots with rough rubber sole. Material can create slippery conditions. Do not get in eyes, on skin, or on clothing.			
6.2 Environmental precautions				
Environmental precautions :	Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities. Do not flush into surface water or sanitary sewer system.			
6.3 Methods and material for containment and cleaning up				

Methods for cleaning up	:	Keep in suitable, closed containers for disposal. Soak up with inert absorbent material (e.g. sand, silica gel,
		acid binder, universal binder, sawdust).

6.4 Reference to other sections

For further information see Section 7 of the safety data sheet. , For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling	
Advice on safe handling :	For personal protection see section 8. No special technical protective measures required.
	In addition, the current technical information for this product and its application on www.caparol.com must be observed.
Hygiene measures :	Wash hands before eating, drinking, or smoking. Do not eat, drink or smoke when using this product. Remove contaminat- ed clothing and protective equipment before entering eating areas.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers	:	Perishable if frozen. To maintain product quality, do not store in heat or direct sunlight. Store at room temperature in the original container. Containers which are opened must be care- fully resealed and kept upright to prevent leakage.
Advice on common storage	:	Keep away from oxidizing agents and strongly acid or alkaline



Capatect Fassadenputz K15

Version 3.1	Revision Date: 10.05.2023		DS Number: 000620	Date of last issue: 02.02.2023 Date of first issue: 10.05.2023
			materials.	
Storag	e class (TRGS 510)	:	12	
•	c end use(s) ic use(s)	:	This information i	s not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis			
Kieselguhr, soda ash flux-calcined	68855-54-9	AGW (Alveolate fraction)	0,3 mg/m3	DE TRGS 900			
			compliance with the OEL ar	nd biological			
	tolerance valu	ies, there is no risk c	of harming the unborn child				
titanium dioxide; [in powder form con- taining 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	AGW (Inhalable fraction)	10 mg/m3 (Titanium dioxide)	DE TRGS 900			
	Peak-limit category: 2;(II)						
	Further information: When there is compliance with the OEL and biological						
	tolerance valu	tolerance values, there is no risk of harming the unborn child					
		AGW (Alveolate fraction)	1,25 mg/m3 (Titanium dioxide)	DE TRGS 900			
	Peak-limit category: 2;(II)						
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child						
		BM (Alveolar dust fraction)	0,5 mg/m3	DE TRGS 527			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of expo- sure	Potential health ef- fects	Value
Kieselguhr, soda ash flux-calcined	Consumers	Ingestion	Long-term systemic effects	18,70 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,05 mg/m3
	Workers	Inhalation	Long-term systemic effects	0,05 mg/m3
zinc sulphide	Consumers	Skin contact	Long-term systemic effects	83,00 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic	2,50 mg/m3



Capatect Fassadenputz K15

Version 3.1	Revision Date: 10.05.2023	SDS Number: 6000620	Date of last issue: 02.02.2023 Date of first issue: 10.05.2023	
	I	I		

			effects	
	Consumers	Ingestion	Long-term systemic effects	0,83 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	5,00 mg/m3
	Workers	Skin contact	Long-term systemic effects	83,00 mg/kg bw/day
titanium dioxide; [in powder form contain- ing 1 % or more of particles with aerody- namic diameter ≤ 10 µm]	Consumers	Ingestion	Long-term systemic effects	700,00 mg/kg bw/day
	Workers	Inhalation	Long-term local ef- fects	10,00 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Kieselguhr, soda ash flux- calcined	Sewage treatment plant	100 mg/l
zinc sulphide	Fresh water	20,6 µg/l
	Fresh water sediment	117,8 mg/kg dry weight (d.w.)
	Soil	35,6 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 µg/l
	Sea sediment	56,5 mg/kg dry weight (d.w.)
	Sea water	6,1 µg/l
titanium dioxide; [in powder form containing 1 % or more of parti- cles with aerodynamic diameter ≤ 10 µm]	Sewage treatment plant	100 mg/l
	Fresh water	0,184 mg/l
	Soil	100 mg/kg dry weight (d.w.)
	Sea water	0,0184 mg/l
	Fresh water sediment	1000 mg/kg dry weight (d.w.)
	Sea sediment	100 mg/kg dry weight (d.w.)
	Intermittent use/release	0,193 mg/l

8.2 Exposure controls

Personal protective equipment

Eye/face protection

: DGUV Regulation 112-192 - Use of eye and face protection

Goggles



Capatect Fassadenputz K15

Version 3.1	Revision Date: 10.05.2023		DS Number: 000620	Date of last issue: 02.02.2023 Date of first issue: 10.05.2023		
Hand protection Material : Glove thickness : Protective index :		:	Nitrile rubber 0,2 mm Class 3			
Remarks :		Before removing gloves clean them with soap and water. Wear suitable gloves tested to EN374. DGUV Regulation 112-195 - Use of protective gloves				
Skin and body protection		:	Safety shoes Long sleeved clothing			
				tection according to the amount and con- dangerous substance at the work place.		
			Skin should be w	ashed after contact.		
				th contaminated clothing before re-use.		
Respiratory protection		:	No personal resp quired.	iratory protective equipment normally re-		
			DGUV Regulation	n 112-190 - Use of breathing equipment		
				lication: Do not breathe spray dust. Use on filter for paint spraying.		

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Color	:	white
Odor	:	No data available
Melting point/freezing point	:	ca. 0 °C
Boiling point/boiling range	:	ca. 100 °C
Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower flammability limit	:	not determined



Capatect Fassadenputz K15

Ver 3.1	sion	Revision Date: 10.05.2023		S Number: 00620	Date of last issue: 02.02.2023 Date of first issue: 10.05.2023
	Flash p	point	:	Not applicable	
	Autoig	nition temperature	:	not determined	
	Decom	position temperature	:	Not applicable	
	рН		:	8 - 9 Concentration: 1	00 %
	Viscos Viso	ity cosity, dynamic	:	No data available	e
	Solubil Wa	ity(ies) ter solubility	:	completely misci	ble
	Partitic octano	n coefficient: n- I/water	:	Not applicable	
	Vapor	pressure	:	ca. 23,4 hPa (20	°C)
	Relativ	e density	:	not determined	
	Density	y	:	1,8000 g/cm3	
	Relativ	e vapor density	:	Not applicable	
9.2	Other iı	nformation			
	Explos	ives	:	Not applicable	
	Oxidizi	ng properties	:	Not applicable	
	Flamm	ability (liquids)	:	The product is n	ot flammable.

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions :	No decomposition if stored and applied as directed.
-----------------------	---

10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.



Capatect Fassadenputz K15

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
3.1	10.05.2023	6000620	Date of first issue: 10.05.2023

10.5 Incompatible materials

Materials to avoid

: Incompatible with acids and bases. Incompatible with oxidizing agents.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

1,2-benzisothiazol-3(2H)-one:

Acute oral toxicity	:	LD50 (Rat): 532 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 0,4 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	:	LD50 (Rat): > 2.000 mg/kg
2-methylisothiazol-3(2H)-one	: :	
Acute oral toxicity	:	LD50 (Rat): 120 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 0,145 mg/l Exposure time: 4 h Test atmosphere: dust/mist

 reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

 Acute oral toxicity
 :
 LD50 (Rat): 66 mg/kg Method: OECD Test Guideline 401

Acute inhalation toxicity	:	LC50 (Rat): 0,17 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403
Acute dermal toxicity	:	LD50 (Rat): > 141 mg/kg Method: OECD Test Guideline 402



Capatect Fassadenputz K15

VersionRevision Date:SDS Number:3.110.05.20236000620

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

2

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Date of last issue: 02.02.2023

Date of first issue: 10.05.2023

SECTION 12: Ecological information

12.1 Toxicity

Components:

1,2-benzisothiazol-3(2H)-one:

Toxicity to fish

: LC50 (Oncorhynchus mykiss (rainbow trout)): 2,2 mg/l



Capatect Fassadenputz K15

		00	00620	Date of first issue: 10.05.2023			
			Exposure time: 9 Method: OECD T	6 h Test Guideline 203			
	Toxicity to daphnia and other aquatic invertebrates		: EC50 (Daphnia): 3,27 mg/l Exposure time: 48 h Method: OECD Test Guideline 202				
	xicity to algae/aquatic nts	:	EC50 (Selenastrum capricornutum (green algae)): 0,11 Exposure time: 72 h Method: OECD Test Guideline 201				
M- icit	Factor (Acute aquatic tox- y)	:	1				
	Factor (Chronic aquatic icity)	:	1				
2-r	nethylisothiazol-3(2H)-on	e:					
	Factor (Acute aquatic tox-		10				
	Factor (Chronic aquatic icity)	:	: 1				
rea (3:		-me	thyl-2H-isothiazo	I-3-one and 2-methyl-2H-isothiazol-3-one			
•	Factor (Acute aquatic tox-	:	100				
	Factor (Chronic aquatic icity)	:	100				
	rsistence and degradabi data available	lity					
12.3 Bi	oaccumulative potential						
<u>Co</u>	mponents:						
rea (3:		-me	thyl-2H-isothiazo	I-3-one and 2-methyl-2H-isothiazol-3-one			
	rtition coefficient: n- anol/water	:		est Guideline 117			
12.4 Mc	obility in soil						
	data available						



Capatect Fassadenputz K15

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
3.1	10.05.2023	6000620	Date of first issue: 10.05.2023

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

: The substance/mixture does not contain components consid- ered to have endocrine disrupting properties according to
REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-	:	An environmental hazard cannot be excluded in the event of
mation		unprofessional handling or disposal.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

J. I	waste ireatinent methods		
	Product	:	
			Waste should not be disposed of via wastewater.
	Contaminated packaging	:	Only completely emptied containers should be given for recy- cling.
	Waste Code	:	used product 080112, waste paint and varnish other than those mentioned in 08 01 11*

SECTION 14: Transport information

14.1 UN number or ID number

ADN	:	Not regulated as a dangerous good
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good



Capatect Fassadenputz K15

Version 3.1	Revision Date: 10.05.2023		DS Number: 00620	Date of last issue: 02.02.2023 Date of first issue: 10.05.2023
IMDG		:	Not regulated a	s a dangerous good
ΙΑΤΑ		:	Not regulated a	s a dangerous good
14.2 UN pr	oper shipping name			
ADN		:	Not regulated a	s a dangerous good
ADR		:	Ū	s a dangerous good
RID		:	-	s a dangerous good
IMDG		:	-	s a dangerous good
ΙΑΤΑ		:	-	s a dangerous good
14.3 Trans	port hazard class(es	;)	-	
ADN		:	Not regulated a	s a dangerous good
ADR		:	-	s a dangerous good
RID		:	-	s a dangerous good
IMDG		:	Ū	s a dangerous good
ΙΑΤΑ		:	-	s a dangerous good
14.4 Packi	ng group		C C	
ADN			Not regulated a	s a dangerous good
ADR		:	-	s a dangerous good
RID		:	-	s a dangerous good
IMDG		:	-	s a dangerous good
ΙΑΤΑ	(Cargo)	:	-	s a dangerous good
ΙΑΤΑ	(Passenger)	:	Not regulated a	s a dangerous good
	onmental hazards gulated as a dangerou	us go	od	
	al precautions for us			
Rema	•	:	Not classified as lations.	s dangerous in the meaning of transport regu-

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture



Capatect Fassadenputz K15

Version 3.1	Revision Date: 10.05.2023	SDS Number: 6000620		f last issue: 02.02.2023 f first issue: 10.05.2023
the	ACH - Restrictions on the market and use of certain tures and articles (Annex	dangerous substanc		Conditions of restriction for the fol- lowing entries should be considered: Number on list 3
				N,N-dimethylformamide (Number on list 76, 72, 30) formaldehyde (Number on list 72, 28)
	ACH - Candidate List of S cern for Authorization (Ar		gh :	This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be gener- ated.
	ulation (EC) No 1005/200 e the ozone layer	09 on substances that	de- :	Not applicable
	ulation (EU) 2019/1021 o s (recast)	on persistent organic p	ollu- :	Not applicable
	ACH - List of substances s nex XIV)	subject to authorisatic	on :	None
pea con	eso III: Directive 2012/18 n Parliament and of the C trol of major-accident haz gerous substances.	Council on the	Not	t applicable
Wat ny)	er hazard class (Germa-	: WGK 1 slightly Classification ad		angering 9 AwSV, Annex 1 (5.2)
	duct code for laquers and its / Giscode	: M-DF02 Water-	based pair	nts
		: BSW20 Coating	materials	, water-based
Vola	atile organic compounds	: Directive 2004/4 < 2 % < 20 g/l	12/EC	

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national



Capatect Fassadenputz K15

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
3.1	10.05.2023	6000620	Date of first issue: 10.05.2023

regulations, where applicable.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

SECTION 16: Other information

H315: Causes skin irritation.H317: May cause an allergic skin reaction.H318: Causes serious eye damage.H330: Fatal if inhaled.H351: Suspected of causing cancer if inhaled.H400: Very toxic to aquatic life.H410: Very toxic to aquatic life with long lasting effects.H411: Toxic to aquatic life with long lasting effects.EUH071: Corrosive to the respiratory tract.
--

Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Carc.	:	Carcinogenicity
Eye Dam.	:	Serious eye damage
Skin Corr.	:	Skin corrosion
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitization
DE TRGS 527	:	Germany. TRGS 527 - Activities with nanomaterials
DE TRGS 900	:	Germany. TRGS 900 - Occupational exposure limit values.
DE TRGS 527 / BM	:	Assessment scale
DE TRGS 900 / AGW	:	Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELX - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Coil Aviation Organization; IELCS - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Convention for the Prevention of 5% of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; no.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Loading Rate; NZIOC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Of fice of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Phillippines Inventory of Chemicals and Chemi cal Substances; (Q)XAR - (Quantitative) Structure Activity Rel



Capatect Fassadenputz K15

Version	Revision Date:	SDS Number:	Date of last issue: 02.02.2023
3.1	10.05.2023	6000620	Date of first issue: 10.05.2023

stance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

Sources of key data used to compile the Material Safety Data Sheet:

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

Classification of the mixture:

Skin Sens. 1 H317

Classification procedure:

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.



Capatect Fassadenputz K15

VersionRevision Date:SDS Number:Date of last issue: 02.02.20233.110.05.20236000620Date of first issue: 10.05.2023	
---	--

DE / EN