

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect AmphiSilan Fassadenputz R30 Son

|         |                |            |                                 |
|---------|----------------|------------|---------------------------------|
| Version | Revision Date: | Print Date | Date of last issue: 06.04.2022  |
| 4.0     | 13.04.2022     | 15.04.2022 | Date of first issue: 30.10.2019 |

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Capatect AmphiSilan Fassadenputz R30 Son

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Water-borne coatings

Recommended restrictions : within adequate application - none on use

#### 1.3 Details of the supplier of the safety data sheet

Company : Caparol Farben Lacke GmbH  
Roßdörfer Straße 50  
64372 Ober-Ramstadt

Telephone : +496154710  
Telefax : +4961547170222  
E-mail address Responsible/issuing person : msds@dr-rmi.com

#### 1.4 Emergency telephone

Emergency telephone 1 : +49613284463 GBK GmbH

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Long-term (chronic) aquatic hazard, Category 3 : H412: Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labeling (REGULATION (EC) No 1272/2008)

Hazard Statements : H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements : P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.

##### Prevention:

P273 Avoid release to the environment.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect AmphiSilan Fassadenputz R30 Son

|         |                |            |                                 |
|---------|----------------|------------|---------------------------------|
| Version | Revision Date: | Print Date | Date of last issue: 06.04.2022  |
| 4.0     | 13.04.2022     | 15.04.2022 | Date of first issue: 30.10.2019 |

### Additional Labeling

**EUH211** Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

**EUH208** Contains 1,2-benzisothiazol-3(2H)-one, octhlinone (ISO), reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1).  
**May produce an allergic reaction.**

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Silicone resin plaster, aqueous , with film protection

#### Components

| Chemical name  | CAS-No.<br>EC-No.<br>Index-No.<br>Registration number       | Classification  | Concentration<br>(% w/w) |
|--|---|---|--------------------------|
| titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq$ 10 $\mu$ m] | 13463-67-7<br>236-675-5<br>022-006-00-2<br>01-2119489379-17 | Carc. 2; H351   | $\geq$ 1 - < 10          |
| 1,2-benzisothiazol-3(2H)-one   | 2634-33-5<br>220-120-9<br>613-088-00-6<br>01-2120761540-60  | Acute Tox. 4; H302<br>Skin Irrit. 2; H315<br>Eye Dam. 1; H318<br>Skin Sens. 1; H317<br>Aquatic Acute 1;<br>H400<br>Aquatic Chronic 2;<br>H411<br>Acute Tox. 2; H330 | $\geq$ 0,025 - < 0,05    |
|  |   | M-Factor (Acute   |                          |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect AmphiSilan Fassadenputz R30 Son

Version 4.0      Revision Date: 13.04.2022      Print Date 15.04.2022      Date of last issue: 06.04.2022  
Date of first issue: 30.10.2019

|                                       |   |   |                        |
|---------------------------------------|---|---|------------------------|
|                                       |   | aquatic toxicity): 1<br>M-Factor (Chronic aquatic toxicity): 1  |                        |
|                                       |   | specific concentration limit<br>Skin Sens. 1; H317<br>>= 0,05 %   |                        |
| pyridine-2-thiol 1-oxide, sodium salt | 3811-73-2<br>223-296-5<br>01-2119493385-28                  | Acute Tox. 4; H302<br>Acute Tox. 4; H332<br>Eye Dam. 1; H318<br>Aquatic Acute 1;<br>H400<br>Aquatic Chronic 2;<br>H411  | >= 0,0025 - <<br>0,025 |
|                                       |   | M-Factor (Acute aquatic toxicity): 100<br>M-Factor (Chronic aquatic toxicity): 1  |                        |
| octhilinone (ISO)                     | 26530-20-1<br>247-761-7<br>613-112-00-5<br>01-2120768921-45 | Acute Tox. 3; H301<br>Acute Tox. 2; H330<br>Acute Tox. 3; H311<br>Skin Corr. 1; H314<br>Eye Dam. 1; H318<br>Skin Sens. 1A; H317<br>Aquatic Acute 1;<br>H400<br>Aquatic Chronic 1;<br>H410<br>EUH071 | >= 0,0025 - <<br>0,025 |
|                                       |   | M-Factor (Acute aquatic toxicity): 100<br>M-Factor (Chronic aquatic toxicity): 100  |                        |
|                                       |   | specific concentration limit<br>Skin Sens. 1A; H317<br>>= 0,0015 %  |                        |
|                                       |   | Acute toxicity estimate   |                        |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect AmphiSilan Fassadenputz R30 Son

Version 4.0      Revision Date: 13.04.2022      Print Date 15.04.2022      Date of last issue: 06.04.2022  
Date of first issue: 30.10.2019

|   |  |  |             |
|---|--|--|-------------|
|   |  | Acute oral toxicity:<br>125 mg/kg<br>Acute inhalation toxicity (dust/mist): 0,27 mg/l<br><br>Acute dermal toxicity:<br>311 mg/kg   |             |
| reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) | 55965-84-9<br>613-167-00-5<br>01-2120764691-48 | Acute Tox. 3; H301<br>Acute Tox. 2; H330<br>Acute Tox. 2; H310<br>Skin Corr. 1C; H314<br>Eye Dam. 1; H318<br>Skin Sens. 1A; H317<br>Aquatic Acute 1;<br>H400<br>Aquatic Chronic 1;<br>H410<br>EUH071<br><br>M-Factor (Acute aquatic toxicity): 100<br>M-Factor (Chronic aquatic toxicity): 100<br><br>specific concentration limit<br>Skin Corr. 1C; H314<br>>= 0,6 %<br>Skin Irrit. 2; H315<br>0,06 - < 0,6 %<br>Eye Irrit. 2; H319<br>0,06 - < 0,6 %<br>Skin Sens. 1A; H317<br>>= 0,0015 %<br>Eye Dam. 1; H318<br>>= 0,6 % | <= 0,0002   |
| Substances with a workplace exposure limit :  |  |  |             |
| Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )                       | 14807-96-6<br>238-877-9<br>01-2120140278-58    |  | >= 1 - < 10 |

For explanation of abbreviations see section 16.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect AmphiSilan Fassadenputz R30 Son

|         |                |            |                                 |
|---------|----------------|------------|---------------------------------|
| Version | Revision Date: | Print Date | Date of last issue: 06.04.2022  |
| 4.0     | 13.04.2022     | 15.04.2022 | Date of first issue: 30.10.2019 |

### SECTION 4: First aid measures

#### 4.1 Description of first-aid measures

- General advice : Never give anything by mouth to an unconscious person.  
If you feel unwell, seek medical advice (show the label where possible).  
Move out of dangerous area.  
First aider needs to protect himself.
- If inhaled : Move to fresh air.
- In case of skin contact : Take off all contaminated clothing immediately.  
Do NOT use solvents or thinners.  
In case of contact, immediately flush skin with soap and plenty of water.
- In case of eye contact : If eye irritation persists: Get medical advice/ attention.  
IF IN EYES: Rinse cautiously with water for several minutes.  
Remove contact lenses, if present and easy to do. Continue rinsing.
- If swallowed : Seek medical advice.  
Clean mouth with water and drink afterwards plenty of water.  
If swallowed, DO NOT induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed

None known.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Do not use a solid water stream as it may scatter and spread fire.
- Unsuitable extinguishing media : None known.

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire : In case of fire hazardous decomposition products may be

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect AmphiSilan Fassadenputz R30 Son

|         |                |            |                                 |
|---------|----------------|------------|---------------------------------|
| Version | Revision Date: | Print Date | Date of last issue: 06.04.2022  |
| 4.0     | 13.04.2022     | 15.04.2022 | Date of first issue: 30.10.2019 |

fighting produced such as:  
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

### 5.3 Advice for firefighters

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Use water spray to cool unopened containers. Standard procedure for chemical fires. The product itself does not burn.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use protective shoes or boots with rough rubber sole. Material can create slippery conditions. Do not get in eyes, on skin, or on clothing.

### 6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities. Do not flush into surface water or sanitary sewer system.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

### 6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.

,For personal protection see section 8.,For disposal considerations see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Use only with adequate ventilation. For personal protection see section 8. No special technical protective measures required.

In addition, the current technical information for this product and its application on [www.caparol.com](http://www.caparol.com) must be observed.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect AmphiSilan Fassadenputz R30 Son

|         |                |            |                                 |
|---------|----------------|------------|---------------------------------|
| Version | Revision Date: | Print Date | Date of last issue: 06.04.2022  |
| 4.0     | 13.04.2022     | 15.04.2022 | Date of first issue: 30.10.2019 |

Hygiene measures : Wash hands before eating, drinking, or smoking. Do not eat, drink or smoke when using this product.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Perishable if frozen. To maintain product quality, do not store in heat or direct sunlight. Store at room temperature in the original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline materials.

Storage class (TRGS 510) : 12, Non Combustible Liquids

### 7.3 Specific end use(s)

Specific use(s) : This information is not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

| Components   | CAS-No.    | Value type (Form of exposure)  | Control parameters                         | Basis       |
|--|------------|--|--|-------------|
| Talc<br>(Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> ) | 14807-96-6 | AGW (Inhalable fraction)   | 10 mg/m <sup>3</sup>                       | DE TRGS 900 |
|  |            | Peak-limit category: 2;(II)  |  |             |
|  |            | Further information: Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., Commission for dangerous substances, General dust value. For this substance no specific occupational exposure limit value is established, since the AGS does not yet have information regarding unspecific action on the respiratory organs in excess of the normal values. |  |             |
|  |            | AGW (Alveolate fraction)   | 1,25 mg/m <sup>3</sup>                     | DE TRGS 900 |
|  |            | Peak-limit category: 2;(II)  |  |             |
|  |            | Further information: Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., Commission for dangerous substances, General dust value. For this substance no specific occupational exposure limit value is established, since the AGS does not yet have information regarding unspecific action on the respiratory organs in excess of the normal values. |  |             |
| titanium dioxide; [in powder form containing 1 % or more of particles      | 13463-67-7 | AGW (Inhalable fraction)   | 10 mg/m <sup>3</sup><br>(Titanium dioxide) | DE TRGS 900 |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect AmphiSilan Fassadenputz R30 Son

Version 4.0      Revision Date: 13.04.2022      Print Date: 15.04.2022      Date of last issue: 06.04.2022  
Date of first issue: 30.10.2019

|   |   |                          |  |                |
|---|---|--------------------------|--|----------------|
| with aerodynamic diameter $\leq 10 \mu\text{m}$ ] |   |                          |  |                |
|   | Peak-limit category: 2;(II)   |                          |  |                |
|   |   | AGW (Alveolate fraction) | 1,25 mg/m <sup>3</sup><br>(Titanium dioxide) | DE TRGS<br>900 |
|   | Peak-limit category: 2;(II)   |                          |  |                |
| pyridine-2-thiol 1-oxide, sodium salt             | 3811-73-2   | AGW (Inhalable fraction) | 1 mg/m <sup>3</sup>                          | DE TRGS<br>900 |
|   | Peak-limit category: 2;(II)   |                          |  |                |
|   | Further information: When there is compliance with the OEL and biological tolerance values, harm to the unborn child can not be excluded, Skin absorption, Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission). |                          |  |                |
| octhilonone (ISO)                                 | 26530-20-1  | AGW (Inhalable fraction) | 0,05 mg/m <sup>3</sup>                       | DE TRGS<br>900 |
|   | Peak-limit category: 2;(I)  |                          |  |                |
|   | Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child   |                          |  |                |

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name  | End Use   | Routes of exposure | Potential health effects   | Value                   |
|---|-----------|--------------------|----------------------------|-------------------------|
| titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ] | Consumers | Ingestion          | Long-term systemic effects | 700,00 mg/kg bw/day     |
|   | Workers   | Inhalation         | Long-term local effects    | 10,00 mg/m <sup>3</sup> |

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

| Substance name  | Environmental Compartment | Value                        |
|---|---------------------------|------------------------------|
| titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ] | Sewage treatment plant    | 100 mg/l                     |
|   | Fresh water               | 0,184 mg/l                   |
|   | Soil                      | 100 mg/kg dry weight (d.w.)  |
|   | Sea water                 | 0,0184 mg/l                  |
|   | Fresh water sediment      | 1000 mg/kg dry weight (d.w.) |
|   | Sea sediment              | 100 mg/kg dry weight (d.w.)  |
|   | Intermittent use/release  | 0,193 mg/l                   |
| glass, oxide, chemicals   | Fresh water sediment      | 174 mg/kg dry weight (d.w.)  |
|   | Secondary Poisoning       | 10,9 mg/kg food              |



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect AmphiSilan Fassadenputz R30 Son

Version 4.0      Revision Date: 13.04.2022      Print Date 15.04.2022      Date of last issue: 06.04.2022  
Date of first issue: 30.10.2019

|  |                        |                             |
|--|------------------------|-----------------------------|
|  | Sea water              | 3,4 µg/l                    |
|  | Sewage treatment plant | 100 µg/l                    |
|  | Sea sediment           | 164 mg/kg dry weight (d.w.) |
|  | Soil                   | 147 mg/kg dry weight (d.w.) |
|  | Fresh water            | 6,5 µg/l                    |

### 8.2 Exposure controls

#### Personal protective equipment

Eye protection : German trade association rules - BGR 192 Eye protection

Goggles

Hand protection

Material : Nitrile rubber

Glove thickness : 0,2 mm

Protective index : Class 3

Remarks : Before removing gloves clean them with soap and water.  
Wear suitable gloves tested to EN374.

Skin and body protection : Safety shoes  
Long sleeved clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

During spray application: impervious clothing

Respiratory protection : No personal respiratory protective equipment normally required.

German trade association rules - BGR 190 Breathing protection

During spray application: Do not breathe spray dust. Use A2/P2 combination filter for paint spraying.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state : liquid

Color : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect AmphiSilan Fassadenputz R30 Son

|         |                |            |                                 |
|---------|----------------|------------|---------------------------------|
| Version | Revision Date: | Print Date | Date of last issue: 06.04.2022  |
| 4.0     | 13.04.2022     | 15.04.2022 | Date of first issue: 30.10.2019 |

Odor : No data available

Melting point/freezing point : ca. 0 °C

Boiling point/boiling range : ca. 100 °C

Upper explosion limit / Upper flammability limit : not determined

Lower explosion limit / Lower flammability limit : not determined

Flash point : Not applicable

Autoignition temperature : not determined

Decomposition temperature : Not applicable

pH : 8 - 9  
Concentration: 100 %

Viscosity  
Viscosity, dynamic : No data available

Solubility(ies)  
Water solubility : completely miscible

Partition coefficient: n-octanol/water : not determined

Vapor pressure : not determined

Relative density : not determined

Density : 1,8 g/cm<sup>3</sup>

Relative vapor density : not determined

### 9.2 Other information

Explosives : Not applicable

Oxidizing properties : Not applicable

Flammability (liquids) : The product is not flammable.

Evaporation rate : Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect AmphiSilan Fassadenputz R30 Son

|         |                |            |                                 |
|---------|----------------|------------|---------------------------------|
| Version | Revision Date: | Print Date | Date of last issue: 06.04.2022  |
| 4.0     | 13.04.2022     | 15.04.2022 | Date of first issue: 30.10.2019 |

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

No decomposition if stored and applied as directed.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

#### 10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

#### 10.5 Incompatible materials

Materials to avoid : Incompatible with acids and bases.  
Incompatible with oxidizing agents.

#### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

Not classified based on available information.

##### Components:

##### **1,2-benzisothiazol-3(2H)-one:**

Acute oral toxicity : LD50 (Rat): 532 mg/kg  
Acute inhalation toxicity : LC50 (Rat): 0,4 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

##### **pyridine-2-thiol 1-oxide, sodium salt:**

Acute oral toxicity : LD50 (Rat, female): 1.208 mg/kg  
Acute inhalation toxicity : LC50 (Rat): 1,08 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect AmphiSilan Fassadenputz R30 Son

|         |                |            |                                 |
|---------|----------------|------------|---------------------------------|
| Version | Revision Date: | Print Date | Date of last issue: 06.04.2022  |
| 4.0     | 13.04.2022     | 15.04.2022 | Date of first issue: 30.10.2019 |

### octhilinone (ISO):

- Acute oral toxicity : Acute toxicity estimate: 125 mg/kg  
Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008
- Acute inhalation toxicity : Acute toxicity estimate: 0,27 mg/l  
Test atmosphere: dust/mist  
Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008
- Acute dermal toxicity : Acute toxicity estimate: 311 mg/kg  
Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008

### reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

- Acute oral toxicity : LD50 (Rat): 66 mg/kg  
Method: OECD Test Guideline 401
- Acute inhalation toxicity : LC50 (Rat): 0,17 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403
- Acute dermal toxicity : LD50 (Rat): > 141 mg/kg  
Method: OECD Test Guideline 402

### Skin corrosion/irritation

Not classified based on available information.

### Serious eye damage/eye irritation

Not classified based on available information.

### Respiratory or skin sensitization

#### Skin sensitization

Not classified based on available information.

#### Respiratory sensitization

Not classified based on available information.

### Product:

- Remarks : Not skin sensitising on the basis of the results of similar tested mixtures, applying bridging principles in accordance with CLP Regulation Article 9(4). Result of studies: Sensitization OECD 429 (LLNA) (mouse) not sensitizing

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect AmphiSilan Fassadenputz R30 Son

|         |                |            |                                 |
|---------|----------------|------------|---------------------------------|
| Version | Revision Date: | Print Date | Date of last issue: 06.04.2022  |
| 4.0     | 13.04.2022     | 15.04.2022 | Date of first issue: 30.10.2019 |

### **Germ cell mutagenicity**

Not classified based on available information.

### **Carcinogenicity**

Not classified based on available information.

### **Reproductive toxicity**

Not classified based on available information.

### **STOT-single exposure**

Not classified based on available information.

### **STOT-repeated exposure**

Not classified based on available information.

### **Aspiration toxicity**

Not classified based on available information.

## 11.2 Information on other hazards

### **Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### **Product:**

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

#### **Components:**

##### **1,2-benzisothiazol-3(2H)-one:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2,2 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia): 3,27 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect AmphiSilan Fassadenputz R30 Son

|         |                |            |                                 |
|---------|----------------|------------|---------------------------------|
| Version | Revision Date: | Print Date | Date of last issue: 06.04.2022  |
| 4.0     | 13.04.2022     | 15.04.2022 | Date of first issue: 30.10.2019 |

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 0,11 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

### **pyridine-2-thiol 1-oxide, sodium salt:**

M-Factor (Acute aquatic toxicity) : 100

M-Factor (Chronic aquatic toxicity) : 1

### **octhilinone (ISO):**

M-Factor (Acute aquatic toxicity) : 100

M-Factor (Chronic aquatic toxicity) : 100

### **reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):**

M-Factor (Acute aquatic toxicity) : 100

M-Factor (Chronic aquatic toxicity) : 100

## 12.2 Persistence and degradability

No data available

## 12.3 Bioaccumulative potential

### **Components:**

#### **pyridine-2-thiol 1-oxide, sodium salt:**

Partition coefficient: n-octanol/water : Pow: 0,002 (20 °C)

#### **octhilinone (ISO):**

Partition coefficient: n-octanol/water : log Pow: 2,92  
Method: OECD Test Guideline 117

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect AmphiSilan Fassadenputz R30 Son

|         |                |            |                                 |
|---------|----------------|------------|---------------------------------|
| Version | Revision Date: | Print Date | Date of last issue: 06.04.2022  |
| 4.0     | 13.04.2022     | 15.04.2022 | Date of first issue: 30.10.2019 |

### reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

Partition coefficient: n-octanol/water : log Pow: <= 0,71  
Method: OECD Test Guideline 117

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

#### Product:

Additional ecological information : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : .  
Waste should not be disposed of via wastewater.

Contaminated packaging : Only completely emptied containers should be given for recycling.

Waste Code : used product  
080112, waste paint and varnish other than those mentioned in 08 01 11\*

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect AmphiSilan Fassadenputz R30 Son

|         |                |            |                                 |
|---------|----------------|------------|---------------------------------|
| Version | Revision Date: | Print Date | Date of last issue: 06.04.2022  |
| 4.0     | 13.04.2022     | 15.04.2022 | Date of first issue: 30.10.2019 |

### SECTION 14: Transport information

#### 14.1 UN number or ID number

Not regulated as a dangerous good

#### 14.2 UN proper shipping name

Not regulated as a dangerous good

#### 14.3 Transport hazard class(es)

Not regulated as a dangerous good

#### 14.4 Packing group

Not regulated as a dangerous good

#### 14.5 Environmental hazards

Not regulated as a dangerous good

#### 14.6 Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport regulations.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59). : This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be generated.

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : None



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect AmphiSilan Fassadenputz R30 Son

|         |                |            |                                 |
|---------|----------------|------------|---------------------------------|
| Version | Revision Date: | Print Date | Date of last issue: 06.04.2022  |
| 4.0     | 13.04.2022     | 15.04.2022 | Date of first issue: 30.10.2019 |

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Water hazard class (Germany) : 2 significantly water endangering  
Classification according to AwSV, Annex 1 (5.2)

Product code for laquers and paints / Giscode : M-SF01F Water-based, silicone resin paints, active agents

. : BSW50 Coating materials, water-based, containing solvents, film-protected

Volatile organic compounds : Directive 2004/42/EC  
< 1 %  
< 10 g/l

### Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

### 15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

## SECTION 16: Other information

### Full text of H-Statements

|        |   |
|--------|---|
| H301   | : Toxic if swallowed.                                   |
| H302   | : Harmful if swallowed.                                 |
| H310   | : Fatal in contact with skin.                           |
| H311   | : Toxic in contact with skin.                           |
| H314   | : Causes severe skin burns and eye damage.              |
| H315   | : Causes skin irritation.                               |
| H317   | : May cause an allergic skin reaction.                  |
| H318   | : Causes serious eye damage.                            |
| H330   | : Fatal if inhaled.                                     |
| H332   | : Harmful if inhaled.                                   |
| H351   | : Suspected of causing cancer if inhaled.               |
| H400   | : Very toxic to aquatic life.                           |
| H410   | : Very toxic to aquatic life with long lasting effects. |
| H411   | : Toxic to aquatic life with long lasting effects.      |
| EUH071 | : Corrosive to the respiratory tract.                   |

### Full text of other abbreviations

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect AmphiSilan Fassadenputz R30 Son

|         |                |            |                                 |
|---------|----------------|------------|---------------------------------|
| Version | Revision Date: | Print Date | Date of last issue: 06.04.2022  |
| 4.0     | 13.04.2022     | 15.04.2022 | Date of first issue: 30.10.2019 |

|                   |   |   |
|-------------------|---|---|
| Acute Tox.        | : | Acute toxicity  |
| Aquatic Acute     | : | Short-term (acute) aquatic hazard                       |
| Aquatic Chronic   | : | Long-term (chronic) aquatic hazard                      |
| Carc.             | : | Carcinogenicity   |
| Eye Dam.          | : | Serious eye damage                                      |
| Skin Corr.        | : | Skin corrosion  |
| Skin Irrit.       | : | Skin irritation   |
| Skin Sens.        | : | Skin sensitization                                      |
| DE TRGS 900       | : | Germany. TRGS 900 - Occupational exposure limit values. |
| DE TRGS 900 / AGW | : | Time Weighted Average                                   |

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### **Other information:**

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

#### **Sources of key data used to compile the Material Safety Data Sheet:**

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs.

Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capatect AmphiSilan Fassadenputz R30 Son

|         |                |            |                                 |
|---------|----------------|------------|---------------------------------|
| Version | Revision Date: | Print Date | Date of last issue: 06.04.2022  |
| 4.0     | 13.04.2022     | 15.04.2022 | Date of first issue: 30.10.2019 |

### Classification of the mixture:

Aquatic Chronic 3

H412

### Classification procedure:

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

### REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN