

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Capacryl Haftprimer NAST Basis T

Version	Revision Date:	Print Date	Date of last issue: 25.02.2019
2.0	23.05.2019	24.05.2019	Date of first issue: 25.02.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Capacryl Haftprimer NAST Basis T

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Water-borne coatings

Recommended restrictions : within adequate application - none on use

1.3 Details of the supplier of the safety data sheet

Company : Caparol Farben Lacke GmbH
Roßdörfer Straße 50
64372 Ober-Ramstadt

Telephone : +496154710
Telefax : +49615471222
E-mail address Responsible/issuing person : msds@dr-rmi.com

1.4 Emergency telephone number

Emergency telephone number 1 : +49615471202

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : **Warning**

Hazard statements : **H317** May cause an allergic skin reaction.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Capacryl Haftprimer NAST Basis T

Version 2.0 Revision Date: 23.05.2019 Print Date 24.05.2019 Date of last issue: 25.02.2019
Date of first issue: 25.02.2019

Precautionary statements : P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.

Prevention:
P262 Do not get in eyes, on skin, or on clothing.
P280 Wear protective gloves/ eye protection.

Response:
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

Hazardous components which must be listed on the label:

2-methyl-2H-isothiazol-3-one
1,2-benzisothiazol-3(2H)-one
mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1) < 15 ppm

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Dispersion-based primer, aqueous

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2-(2-butoxyethoxy)ethanol	112-34-5 203-961-6 603-096-00-8 01-2119475104-44	Eye Irrit. 2; H319	>= 1 - < 10
2-methyl-2H-isothiazol-3-one	2682-20-4 220-239-6 01-2120764690-50	Acute Tox. 2; H330 Acute Tox. 3; H311 Acute Tox. 3; H301 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute): 10 M-Factor (Chronic): 1	>= 0,0025 - < 0,025
1,2-benzisothiazol-3(2H)-one	2634-33-5	Acute Tox. 4; H302	>= 0,0025 - <

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Capacryl Haftprimer NAST Basis T

Version 2.0 Revision Date: 23.05.2019 Print Date 24.05.2019 Date of last issue: 25.02.2019
Date of first issue: 25.02.2019

	220-120-9 613-088-00-6 01-2120761540-60	Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 Acute Tox. 2; H330 M-Factor (Acute): 1 M-Factor (Chronic): 1	0,025
mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9 613-167-00-5 01-2120764691-48	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1B; H314 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute): 100 M-Factor (Chronic): 10	>= 0,0002 - < 0,0015
Substances with a workplace exposure limit :			
Talc (Mg ₃ H ₂ (SiO ₃) ₄)	14807-96-6 238-877-9 01-2120140278-58		>= 10 - < 20

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : First aider needs to protect himself.
Move out of dangerous area.
If you feel unwell, seek medical advice (show the label where possible).
Never give anything by mouth to an unconscious person.
- If inhaled : Move to fresh air.
- In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
Do NOT use solvents or thinners.
- In case of eye contact : IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/ attention.
- If swallowed : If swallowed, DO NOT induce vomiting.
Clean mouth with water and drink afterwards plenty of water.
Seek medical advice.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Capacryl Haftprimer NAST Basis T

Version	Revision Date:	Print Date	Date of last issue: 25.02.2019
2.0	23.05.2019	24.05.2019	Date of first issue: 25.02.2019

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : In case of fire hazardous decomposition products may be produced such as:
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : The product itself does not burn.
Standard procedure for chemical fires.
Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Do not get in eyes, on skin, or on clothing.
Material can create slippery conditions.
Use protective shoes or boots with rough rubber sole.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.
Prevent further leakage or spillage if safe to do so.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Capacryl Haftprimer NAST Basis T

Version	Revision Date:	Print Date	Date of last issue: 25.02.2019
2.0	23.05.2019	24.05.2019	Date of first issue: 25.02.2019

6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8., For further information see Section 7 of the safety data sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : No special technical protective measures required.
For personal protection see section 8.
Use only with adequate ventilation.
- Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands before eating, drinking, or smoking.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store at room temperature in the original container. To maintain product quality, do not store in heat or direct sunlight. Perishable if frozen.
- Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline materials.
- Storage class (TRGS 510) : 12, Non Combustible Liquids

7.3 Specific end use(s)

- Specific use(s) : Please follow the technical information.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Talc (Mg ₃ H ₂ (SiO ₃) ₄)	14807-96-6	AGW (Inhalable fraction)	10 mg/m ³	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)			
Further information	General dust value. For this substance no specific occupational exposure limit value is established, since the AGS does not yet have information regarding unspecific action on the respiratory organs in excess of the normal values., Commission for dangerous substances, Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
		AGW (Alveolate fraction)	1,25 mg/m ³	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Capacryl Haftprimer NAST Basis T

Version 2.0 Revision Date: 23.05.2019 Print Date 24.05.2019 Date of last issue: 25.02.2019
Date of first issue: 25.02.2019

Further information	General dust value. For this substance no specific occupational exposure limit value is established, since the AGS does not yet have information regarding unspecific action on the respiratory organs in excess of the normal values., Commission for dangerous substances, Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
2-(2-butoxyethoxy)ethanol	112-34-5	STEL	15 ppm 101,2 mg/m ³	2006/15/EC
Further information	Indicative			
		TWA	10 ppm 67,5 mg/m ³	2006/15/EC
Further information	Indicative			
		AGW (Vapour and aerosols)	10 ppm 67 mg/m ³	DE TRGS 900
Peak-limit: excursion factor (category)	1.5;(I)			
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., European Union (The EU has established a limit value: deviations in value and peak limit are possible), Sum of vapor and aerosols., When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
propane-1,2-diol	Consumers	Inhalation	Long-term systemic effects	50,00 mg/m ³
	Consumers	Inhalation	Long-term local effects	10,00 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	250,00 mg/m ³
2-(2-butoxyethoxy)ethanol	Consumers	Inhalation	Acute local effects	60,70 mg/m ³
	Consumers	Ingestion	Long-term systemic effects	200,00 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	5,00 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	2000,00 mg/kg bw/day
	Consumers	Inhalation	Long-term local effects	40,50 mg/m ³
Consumers	Skin contact	Long-term systemic effects	50,00 mg/kg bw/day	
Consumers	Inhalation	Long-term systemic effects	40,50 mg/m ³	

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
propane-1,2-diol	Marine sediment	57,2 mg/kg dry weight (d.w.)
	Soil	50 mg/kg dry weight (d.w.)
	Marine water	26 mg/l
	Fresh water sediment	572 mg/kg dry

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Capacryl Haftprimer NAST Basis T

Version 2.0 Revision Date: 23.05.2019 Print Date 24.05.2019 Date of last issue: 25.02.2019
Date of first issue: 25.02.2019

		weight (d.w.)
	Fresh water	260 mg/l
	Intermittent use/release	183 mg/l
	Sewage treatment plant	20000 mg/l
2-(2-butoxyethoxy)ethanol	Fresh water	1,1 mg/l
	Fresh water sediment	4,4 mg/kg dry weight (d.w.)
	Intermittent use/release	11 mg/l
	Marine water	0,11 mg/l
	Marine sediment	0,44 mg/kg dry weight (d.w.)
	Sewage treatment plant	200 mg/l
	Soil	0,32 mg/kg dry weight (d.w.)
	Secondary Poisoning	56 mg/kg food

8.2 Exposure controls

Personal protective equipment

Eye protection : German trade association rules - BGR 192 Eye protection

Safety glasses

Hand protection

Material : Nitrile rubber
Glove thickness : 0,2 mm
Protective index : Class 3

Remarks : Wear suitable gloves tested to EN374. Before removing gloves clean them with soap and water.

Skin and body protection : Long sleeved clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

Safety shoes

Remove and wash contaminated clothing before re-use.
During spray application: impervious clothing

Respiratory protection : No personal respiratory protective equipment normally required.

German trade association rules - BGR 190 Breathing protection

During spray application: Do not breathe spray dust. Use A2/P2 combination filter for paint spraying.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Capacryl Haftprimer NAST Basis T

Version 2.0	Revision Date: 23.05.2019	Print Date 24.05.2019	Date of last issue: 25.02.2019 Date of first issue: 25.02.2019
----------------	------------------------------	--------------------------	---

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: No data available
Odour	: No data available
Odour Threshold	: Not relevant
pH	: not determined
Melting point/freezing point	: not determined
Boiling point/boiling range	: not determined
Flash point	: Not applicable
Evaporation rate	: Not applicable
Flammability (solid, gas)	: The product is not flammable.
Upper explosion limit / Upper flammability limit	: not determined
Lower explosion limit / Lower flammability limit	: not determined
Vapour pressure	: not determined
Relative vapour density	: not determined
Relative density	: not determined
Density	: 1,3700 g/cm ³
Solubility(ies) Water solubility	: completely miscible
Partition coefficient: n-octanol/water	: not determined
Auto-ignition temperature	: not determined
Decomposition temperature	: Not applicable
Viscosity Viscosity, dynamic	: No data available
Explosive properties	: Not applicable
Oxidizing properties	: Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Capacryl Haftprimer NAST Basis T

Version 2.0	Revision Date: 23.05.2019	Print Date 24.05.2019	Date of last issue: 25.02.2019 Date of first issue: 25.02.2019
----------------	------------------------------	--------------------------	---

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

10.5 Incompatible materials

Materials to avoid : Incompatible with oxidizing agents.
Incompatible with acids and bases.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:

Acute oral toxicity : Remarks: Based on available data, the classification criteria are not met.

Acute inhalation toxicity : Remarks: Based on available data, the classification criteria are not met.

Acute dermal toxicity : Remarks: Based on available data, the classification criteria are not met.

Components:

2-(2-butoxyethoxy)ethanol:

Acute oral toxicity : LD50 (Mouse): 2.410 mg/kg

LD50 (Rat): 3.305 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 2.764 mg/kg

2-methyl-2H-isothiazol-3-one:

Acute oral toxicity : LD50 (Rat): 120 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Capacryl Haftprimer NAST Basis T

Version 2.0	Revision Date: 23.05.2019	Print Date 24.05.2019	Date of last issue: 25.02.2019 Date of first issue: 25.02.2019
----------------	------------------------------	--------------------------	---

Acute inhalation toxicity : LC50 (Rat): 0,145 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Remarks: see user defined free text

1,2-benzisothiazol-3(2H)-one:

Acute oral toxicity : LD50 (Rat): 532 mg/kg
Acute inhalation toxicity : LC50 (Rat): 0,4 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):

Acute oral toxicity : LD50 (Rat): 66 mg/kg
Method: OECD Test Guideline 401
Acute inhalation toxicity : LC50 (Rat): 0,17 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Acute dermal toxicity : LD50 (Rat): > 141 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation

Product:

Remarks : According to the classification criteria of the European Union, the product is not considered as being a skin irritant.

Serious eye damage/eye irritation

Product:

Remarks : According to the classification criteria of the European Union, the product is not considered as being an eye irritant.

Respiratory or skin sensitisation

Product:

Remarks : Causes sensitisation.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Capacryl Haftprimer NAST Basis T

Version	Revision Date:	Print Date	Date of last issue: 25.02.2019
2.0	23.05.2019	24.05.2019	Date of first issue: 25.02.2019

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Components:

2-methyl-2H-isothiazol-3-one:

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 1

1,2-benzisothiazol-3(2H)-one:

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):

M-Factor (Acute aquatic toxicity) : 100

M-Factor (Chronic aquatic toxicity) : 10

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):

Partition coefficient: n-octanol/water : log Pow: <= 0,71
Method: OECD Test Guideline 117

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Capacryl Haftprimer NAST Basis T

Version 2.0	Revision Date: 23.05.2019	Print Date 24.05.2019	Date of last issue: 25.02.2019 Date of first issue: 25.02.2019
----------------	------------------------------	--------------------------	---

12.6 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : .
Waste should not be disposed of via wastewater.

Contaminated packaging : Only completely emptied containers should be given for recycling.

Waste Code : used product
080112, waste paint and varnish other than those mentioned in 08 01 11*

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport regulations.
see sections 6-8

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Capacryl Haftprimer NAST Basis T

Version	Revision Date:	Print Date	Date of last issue: 25.02.2019
2.0	23.05.2019	24.05.2019	Date of first issue: 25.02.2019

0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be generated.

REACH - List of substances subject to authorisation (Annex XIV) : None

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

Water contaminating class (Germany) : 1 slightly water endangering
Classification according to AwSV, Annex 1 (5.2)

Product code for laquers and paints / Giscode : M-LW01 Water-based varnishes

. : BSW30 Coating materials, water-based, containing solvents

Volatile organic compounds : Directive 2004/42/EC
< 6 %
< 80 g/l

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

H301 : Toxic if swallowed.
H302 : Harmful if swallowed.
H310 : Fatal in contact with skin.
H311 : Toxic in contact with skin.
H314 : Causes severe skin burns and eye damage.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.
H330 : Fatal if inhaled.
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.
H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Capacryl Haftprimer NAST Basis T

Version	Revision Date:	Print Date	Date of last issue: 25.02.2019
2.0	23.05.2019	24.05.2019	Date of first issue: 25.02.2019

Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Skin Corr.	:	Skin corrosion
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
2006/15/EC	:	Europe. Indicative occupational exposure limit values
DE TRGS 900	:	Germany. TRGS 900 - Occupational exposure limit values.
2006/15/EC / TWA	:	Limit Value - eight hours
2006/15/EC / STEL	:	Short term exposure limit
DE TRGS 900 / AGW	:	Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECS - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Skin Sens. 1

H317

Classification procedure:

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly. This will be put into practice depending on the register-deadline of the substances involved during the transition period from December 1, 2010 till May 31, 2018.

DE / EN