

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

DE / EN



## Capadur ClassicLasur Eiche

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 10.04.2024  |
| 5.0     | 21.10.2025     | 6005025     | Date of first issue: 04.06.2019 |

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Capadur ClassicLasur Eiche

Unique Formula Identifier (UFI) : SR0K-6Q6P-Q01W-587G

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Solvent-borne coatings

Recommended restrictions on use : within adequate application - none

#### 1.3 Details of the supplier of the safety data sheet

Company : Caparol Farben Lacke GmbH  
Roßdörfer Straße 50  
64372 Ober-Ramstadt

Telephone : +496154710  
Telefax : +4961547170222

Website :  
E-mail address Responsible/issuing person : msds@dr-rmi.com

#### 1.4 Emergency telephone

Emergency telephone 1 : +49613284463 GBK GmbH

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Skin sensitization, Category 1 H317: May cause an allergic skin reaction.

Long-term (chronic) aquatic hazard, Category 3 H412: Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

DE / EN



## Capadur ClassicLasur Eiche

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 10.04.2024  |
| 5.0     | 21.10.2025     | 6005025     | Date of first issue: 04.06.2019 |

|                                |   |   |
|--------------------------------|---|---|
| Hazard pictograms              | : |   |
| Signal Word                    | : | Warning   |
| Hazard Statements              | : | H317 May cause an allergic skin reaction.<br>H412 Harmful to aquatic life with long lasting effects.  |
| Supplemental Hazard Statements | : | EUH066 Repeated exposure may cause skin dryness or cracking.  |
| Precautionary Statements       | : | P101 If medical advice is needed, have product container or label at hand.<br>P102 Keep out of reach of children.<br><b>Prevention:</b><br>P261 Avoid breathing mist or vapors.<br>P273 Avoid release to the environment.<br>P280 Wear protective gloves.<br><b>Disposal:</b><br>P501 Dispose of contents/ container to an approved waste disposal plant. |

### Hazardous ingredients which must be listed on the label:

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate  
3-iodo-2-propynyl butylcarbamate  
Fatty acids, C18-unsatd., dimers, compds. with coco alkylamines  
4,5-dichloro-2-octyl-2H-isothiazol-3-one  
octhilinone (ISO)

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Hotline for allergy inquiries: 0800/1895000 (free of charge from the German landline).

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

DE / EN



## Capadur ClassicLasur Eiche

Version 5.0      Revision Date: 21.10.2025      SDS Number: 6005025      Date of last issue: 10.04.2024  
Date of first issue: 04.06.2019

Chemical nature : Alkyd-resin-based wood varnish, solvent-containing, with film protection

### Components

| Chemical name  | CAS-No.<br>EC-No.<br>Index-No.<br>Registration number   | Classification   | Concentration<br>(% w/w) |
|--|---|--|--------------------------|
| Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha                                    | 64742-48-9<br>265-150-3<br>649-327-00-6<br>01-2119457273-39,<br>01-2119463258-33,<br>01-2119486659-16 | Asp. Tox. 1; H304<br>EUH066  | >= 30 - < 50             |
| Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate | 1065336-91-5<br>915-687-0<br>01-2119491304-40   | Skin Sens. 1A; H317<br>Aquatic Acute 1;<br>H400<br>Aquatic Chronic 1;<br>H410<br>Repr. 2; H361f  | >= 0,25 - < 1            |
| 3-iodo-2-propynyl butylcarbamate   | 55406-53-6<br>259-627-5<br>616-212-00-7<br>01-2120762115-60   | Acute Tox. 4; H302<br>Acute Tox. 3; H331<br>Eye Dam. 1; H318<br>Skin Sens. 1; H317<br>STOT RE 1; H372<br>(larynx)<br>Aquatic Acute 1;<br>H400<br>Aquatic Chronic 1;<br>H410<br><br>M-Factor (Acute aquatic toxicity): 10<br>M-Factor (Chronic aquatic toxicity): 1 | >= 0,1 - < 0,25          |
| Fatty acids, C18-unsatd., dimers, compds. with coco alkylamines  | 68647-95-0<br><br>01-2120099181-55  | Skin Irrit. 2; H315<br>Skin Sens. 1B; H317<br>STOT RE 2; H373<br>Aquatic Acute 1;<br>H400<br>Aquatic Chronic 1;<br>H410  | >= 0,1 - < 0,25          |
| 4,5-dichloro-2-octyl-2H-isothiazol-3-one   | 64359-81-5<br>264-843-8<br>613-335-00-8   | Acute Tox. 4; H302<br>Acute Tox. 2; H330<br>Skin Corr. 1; H314<br>Eye Dam. 1; H318<br>Skin Sens. 1A; H317<br>Aquatic Acute 1;<br>H400<br>Aquatic Chronic 1;<br>H410  | >= 0,0025 - < 0,025      |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

DE / EN



**CAPAROL**

## Capadur ClassicLasur Eiche

Version  
5.0

Revision Date:  
21.10.2025

SDS Number:  
6005025

Date of last issue: 10.04.2024  
Date of first issue: 04.06.2019

|                   |   |  |                     |
|-------------------|---|--|---------------------|
|                   |   | <p>EUH071</p> <hr/> <p>M-Factor (Acute aquatic toxicity): 100<br/>M-Factor (Chronic aquatic toxicity): 100</p> <hr/> <p>specific concentration limit<br/>Skin Irrit. 2; H315<br/>0,025 - &lt; 5 %<br/>Eye Irrit. 2; H319<br/>0,025 - &lt; 3 %<br/>Skin Sens. 1A; H317<br/>&gt;= 0,0015 %</p> <hr/> <p>Acute toxicity estimate</p> <p>Acute oral toxicity:<br/>567 mg/kg<br/>Acute inhalation toxicity (dust/mist): 0,16 mg/l</p> |                     |
| octhilinone (ISO) | 26530-20-1<br>247-761-7<br>613-112-00-5<br>01-2120768921-45 | <p>Acute Tox. 3; H301<br/>Acute Tox. 2; H330<br/>Acute Tox. 3; H311<br/>Skin Corr. 1; H314<br/>Eye Dam. 1; H318<br/>Skin Sens. 1A; H317<br/>Aquatic Acute 1;<br/>H400<br/>Aquatic Chronic 1;<br/>H410<br/>EUH071</p> <hr/> <p>M-Factor (Acute aquatic toxicity): 100<br/>M-Factor (Chronic aquatic toxicity): 100</p> <hr/> <p>specific concentration limit<br/>Skin Sens. 1A; H317<br/>&gt;= 0,0015 %</p>                       | >= 0,0025 - < 0,025 |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

DE / EN



**CAPAROL**

## Capadur ClassicLasur Eiche

Version 5.0      Revision Date: 21.10.2025      SDS Number: 6005025      Date of last issue: 10.04.2024  
Date of first issue: 04.06.2019

|  |   |  |             |
|--|---|--|-------------|
|  |   | Acute toxicity estimate  |             |
|  |   | Acute oral toxicity:<br>125 mg/kg<br>Acute inhalation toxicity (dust/mist): 0,27 mg/l<br>Acute dermal toxicity:<br>311 mg/kg |             |
| Substances with a workplace exposure limit : |   |  |             |
| Silica gel, pptd., cryst.-free               | 112926-00-8<br>231-545-4<br>01-2119379499-16,<br>01-2120105300-82 |  | >= 1 - < 10 |

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first-aid measures

- General advice : Never give anything by mouth to an unconscious person.  
If you feel unwell, seek medical advice (show the label where possible).  
Move out of dangerous area.  
First aider needs to protect himself.
- If inhaled : Call a physician.  
If breathing is irregular or stopped, administer artificial respiration.  
If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.  
Move to fresh air.
- In case of skin contact : Do NOT use solvents or thinners.  
In case of contact, immediately flush skin with soap and plenty of water.  
Take off all contaminated clothing immediately.
- In case of eye contact : If eye irritation persists: Get medical advice/ attention.  
IF IN EYES: Rinse cautiously with water for several minutes.  
Remove contact lenses, if present and easy to do. Continue rinsing.
- If swallowed : Seek medical advice.  
Clean mouth with water and drink afterwards plenty of water.  
If swallowed, DO NOT induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

DE / EN



## Capadur ClassicLasur Eiche

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 10.04.2024  |
| 5.0     | 21.10.2025     | 6005025     | Date of first issue: 04.06.2019 |

Risks : May cause an allergic skin reaction.  
Repeated exposure may cause skin dryness or cracking.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.  
Do not use a solid water stream as it may scatter and spread fire.

Unsuitable extinguishing media : None known.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Cool closed containers exposed to fire with water spray.  
In case of fire hazardous decomposition products may be produced such as:  
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

### 5.3 Advice for firefighters

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.  
In the event of fire and/or explosion do not breathe fumes.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Do not get in eyes, on skin, or on clothing.  
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.  
Ensure adequate ventilation.  
Remove all sources of ignition.

### 6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

DE / EN



**CAPAROL**

## Capadur ClassicLasur Eiche

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 10.04.2024  |
| 5.0     | 21.10.2025     | 6005025     | Date of first issue: 04.06.2019 |

Do not flush into surface water or sanitary sewer system.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

### 6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.

, For personal protection see section 8., For disposal considerations see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Non-sparking tools should be used.  
For personal protection see section 8.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Provide sufficient air exchange and/or exhaust in work rooms.

Advice on protection against fire and explosion : Vapors may form explosive mixtures with air. Vapors are heavier than air and may spread along floors. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hygiene measures : Avoid contact with the skin and the eyes. Wash hands before eating, drinking, or smoking. Do not eat, drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering eating areas.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Store between 41 and 77 °F in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510) : 10

### 7.3 Specific end use(s)

Specific use(s) : This information is not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

| Components | CAS-No. | Value type (Form | Control parameters | Basis |
|------------|---------|------------------|--------------------|-------|
|------------|---------|------------------|--------------------|-------|

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

DE / EN

## Capadur ClassicLasur Eiche



Version 5.0      Revision Date: 21.10.2025      SDS Number: 6005025      Date of last issue: 10.04.2024  
Date of first issue: 04.06.2019

|  |             |  |                                      |             |
|--|-------------|--|--------------------------------------|-------------|
|  |             | of exposure)                             |                                      |             |
| Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha  | 64742-48-9  | MAK                                      | 50 ppm<br>300 mg/m <sup>3</sup>      | DE DFG MAK  |
| Peak-limit category: 2; II   |             |  |                                      |             |
| Further information: Either there are no data for an assessment of damage to the embryo or foetus, including developmental neurotoxicity, or the currently available data are not sufficient for classification in one of the groups A - C |             |  |                                      |             |
|  |             | AGW                                      | 300 mg/m <sup>3</sup>                | DE TRGS 900 |
| Peak-limit category: 2;(II)  |             |  |                                      |             |
| Further information: Group exposure limit for hydrocarbon solvent mixtures   |             |  |                                      |             |
| Silica gel, pptd., cryst.-free   | 112926-00-8 | AGW (Inhalable fraction)                 | 1 mg/m <sup>3</sup><br>(Silica)      | DE TRGS 900 |
| Peak-limit category: 8;(II)  |             |  |                                      |             |
| Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child   |             |  |                                      |             |
|  |             | MAK (measured as the alveolate fraction) | 0,02 mg/m <sup>3</sup>               | DE DFG MAK  |
| Peak-limit category: 8; II   |             |  |                                      |             |
| Further information: Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed  |             |  |                                      |             |
| 3-iodo-2-propynyl butylcarbamate   | 55406-53-6  | MAK                                      | 0,005 ppm<br>0,058 mg/m <sup>3</sup> | DE DFG MAK  |
| Peak-limit category: 2; I  |             |  |                                      |             |
| Further information: Danger of sensitization of the skin, Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed   |             |  |                                      |             |
|  |             | AGW (Vapour and aerosols)                | 0,005 ppm<br>0,058 mg/m <sup>3</sup> | DE TRGS 900 |
| Peak-limit category: 2;(I)   |             |  |                                      |             |
| Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child, Substance sensitizing through the skin   |             |  |                                      |             |
| octhlinone (ISO)   | 26530-20-1  | MAK (inhalable fraction)                 | 0,05 mg/m <sup>3</sup>               | DE DFG MAK  |
| Peak-limit category: 2; I  |             |  |                                      |             |
| Further information: Danger of sensitization of the skin, Danger of absorption through the skin, Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed  |             |  |                                      |             |
|  |             | AGW (Inhalable fraction)                 | 0,05 mg/m <sup>3</sup>               | DE TRGS 900 |
| Peak-limit category: 2;(I)   |             |  |                                      |             |
| Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child  |             |  |                                      |             |

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name | End Use | Routes of exposure | Potential health effects | Value |
|----------------|---------|--------------------|--------------------------|-------|
|----------------|---------|--------------------|--------------------------|-------|

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

DE / EN



## Capadur ClassicLasur Eiche

Version 5.0      Revision Date: 21.10.2025      SDS Number: 6005025      Date of last issue: 10.04.2024  
Date of first issue: 04.06.2019

|  |           |              |                            |                         |
|--|-----------|--------------|----------------------------|-------------------------|
| isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol  | Consumers | Inhalation   | Long-term systemic effects | 14,50 mg/m <sup>3</sup> |
|  | Consumers | Ingestion    | Long-term systemic effects | 8,33 mg/kg bw/day       |
|  | Consumers | Skin contact | Long-term systemic effects | 8,33 mg/kg bw/day       |
|  | Workers   | Inhalation   | Long-term systemic effects | 49,00 mg/m <sup>3</sup> |
|  | Workers   | Skin contact | Long-term systemic effects | 13,90 mg/kg bw/day      |
| Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate | Consumers | Inhalation   | Acute local effects        | 0,58 mg/m <sup>3</sup>  |
|  | Consumers | Ingestion    | Long-term systemic effects | 1,25 mg/kg bw/day       |
|  | Consumers | Inhalation   | Long-term systemic effects | 0,58 mg/m <sup>3</sup>  |
|  | Consumers | Inhalation   | Acute systemic effects     | 0,58 mg/m <sup>3</sup>  |
|  | Consumers | Skin contact | Long-term systemic effects | 1,25 mg/kg bw/day       |
|  | Consumers | Skin contact | Acute systemic effects     | 1,25 mg/kg bw/day       |
|  | Consumers | Ingestion    | Acute systemic effects     | 1,25 mg/kg bw/day       |
|  | Workers   | Inhalation   | Acute systemic effects     | 2,35 mg/m <sup>3</sup>  |
|  | Workers   | Inhalation   | Acute local effects        | 2,35 mg/m <sup>3</sup>  |
|  | Workers   | Inhalation   | Long-term systemic effects | 2,35 mg/m <sup>3</sup>  |
|  | Workers   | Skin contact | Acute systemic effects     | 2,50 mg/kg bw/day       |
|  | Workers   | Skin contact | Long-term systemic effects | 2,50 mg/kg bw/day       |

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

| Substance name  | Environmental Compartment | Value                         |
|---|---------------------------|-------------------------------|
| isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol | Fresh water sediment      | 0,78 mg/kg dry weight (d.w.)  |
|   | Sea water                 | 0,0015 mg/l                   |
|   | Sea sediment              | 0,078 mg/kg dry weight (d.w.) |
|   | Soil                      | 0,147 mg/kg dry weight (d.w.) |
|   | Sewage treatment plant    | 7,5 mg/l                      |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

DE / EN



## Capadur ClassicLasur Eiche

Version 5.0      Revision Date: 21.10.2025      SDS Number: 6005025      Date of last issue: 10.04.2024  
Date of first issue: 04.06.2019

|  |                          |                              |
|--|--------------------------|------------------------------|
|  | Secondary Poisoning      | 66,7 mg/kg food              |
|  | Intermittent use/release | 0,15 mg/l                    |
|  | Fresh water              | 0,015 mg/l                   |
| Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate | Sea water                | 0,00022 mg/l                 |
|  | Soil                     | 0,21 mg/kg dry weight (d.w.) |
|  | Fresh water              | 0,0022 mg/l                  |
|  | Sewage treatment plant   | 1 mg/l                       |
|  | Fresh water sediment     | 1,05 mg/kg dry weight (d.w.) |
|  | Intermittent use/release | 0,009 mg/l                   |
|  | Sea sediment             | 0,11 mg/kg dry weight (d.w.) |

### 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection : DGVU Regulation 112-192 - Use of eye and face protection  
Goggles

#### Hand protection

Material : Nitrile rubber  
Glove thickness : 0,2 mm  
Protective index : Class 3

Remarks : Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Before removing gloves clean them with soap and water. Wear suitable gloves tested to EN374.  
DGVU Regulation 112-195 - Use of protective gloves

#### Skin and body protection

: Safety shoes  
Long sleeved clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

Remove and wash contaminated clothing before re-use.  
During spray application: impervious clothing

#### Respiratory protection

: Roller application or brushing: This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



DE / EN

## Capadur ClassicLasur Eiche

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 10.04.2024  |
| 5.0     | 21.10.2025     | 6005025     | Date of first issue: 04.06.2019 |

During spray application: Do not breathe spray dust. Use  
A2/P2 combination filter for paint spraying.

DGUV Regulation 112-190 - Use of breathing equipment

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

|  |   |                                   |
|--|---|-----------------------------------|
| Physical state                                   | : | liquid                            |
| Color  | : | brown                             |
| Odor   | : | No data available                 |
| Odor Threshold                                   | : | Not relevant                      |
| Melting point/freezing point                     | : | not determined                    |
| Boiling point/boiling range                      | : | not determined                    |
| Upper explosion limit / Upper flammability limit | : | not determined                    |
| Lower explosion limit / Lower flammability limit | : | not determined                    |
| Flash point                                      | : | 64 °C                             |
| Autoignition temperature                         | : | not determined                    |
| Decomposition temperature                        | : | Not applicable                    |
| pH   | : | 6,95<br>Concentration: 10 %       |
| Viscosity  | : |                                   |
| Viscosity, dynamic                               | : | No data available                 |
| Viscosity, kinematic                             | : | > 20,5 mm <sup>2</sup> /s (40 °C) |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

DE / EN



## Capadur ClassicLasur Eiche

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 10.04.2024  |
| 5.0     | 21.10.2025     | 6005025     | Date of first issue: 04.06.2019 |

---

Solubility(ies)  
Water solubility : partly miscible

Partition coefficient: n-  
octanol/water : not determined

Vapor pressure : not determined

Relative density : not determined

Density : 0,9300 g/cm<sup>3</sup>

Relative vapor density : Heavier than air.

### 9.2 Other information

Explosives : Not applicable

Oxidizing properties : Not applicable

Flammability (liquids) : Sustains combustion

Evaporation rate : Not applicable

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Vapors may form explosive mixture with air.  
Hazardous decomposition products formed under fire conditions.

### 10.4 Conditions to avoid

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

DE / EN



## Capadur ClassicLasur Eiche

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 10.04.2024  |
| 5.0     | 21.10.2025     | 6005025     | Date of first issue: 04.06.2019 |

Conditions to avoid : Protect from frost, heat and sunlight.

### 10.5 Incompatible materials

Materials to avoid : Incompatible with acids and bases.  
Incompatible with oxidizing agents.

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute inhalation toxicity : Acute toxicity estimate: > 5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Calculation method

#### Components:

##### **3-iodo-2-propynyl butylcarbamate:**

Acute oral toxicity : LD50 (Rat, female): 1.056 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 0,763 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

##### **4,5-dichloro-2-octyl-2H-isothiazol-3-one:**

Acute oral toxicity : Acute toxicity estimate: 567 mg/kg  
Method: Acute toxicity estimate according to Regulation (EC)  
No. 1272/2008

Acute inhalation toxicity : Acute toxicity estimate: 0,16 mg/l  
Test atmosphere: dust/mist  
Method: Acute toxicity estimate according to Regulation (EC)  
No. 1272/2008

##### **octhilinone (ISO):**

Acute oral toxicity : Acute toxicity estimate: 125 mg/kg  
Method: Acute toxicity estimate according to Regulation (EC)  
No. 1272/2008

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

DE / EN



## Capadur ClassicLasur Eiche

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 10.04.2024  |
| 5.0     | 21.10.2025     | 6005025     | Date of first issue: 04.06.2019 |

Acute inhalation toxicity : Acute toxicity estimate: 0,27 mg/l  
Test atmosphere: dust/mist  
Method: Acute toxicity estimate according to Regulation (EC)  
No. 1272/2008

Acute dermal toxicity : Acute toxicity estimate: 311 mg/kg  
Method: Acute toxicity estimate according to Regulation (EC)  
No. 1272/2008

### **Silica gel, pptd., cryst.-free:**

Acute oral toxicity : LD50 Oral (Rat): > 10.000 mg/kg

Acute dermal toxicity : LD50 (Rat): > 5.000 mg/kg

### **Skin corrosion/irritation**

Repeated exposure may cause skin dryness or cracking.

### **Serious eye damage/eye irritation**

Not classified based on available information.

### **Respiratory or skin sensitization**

#### **Skin sensitization**

May cause an allergic skin reaction.

#### **Respiratory sensitization**

Not classified based on available information.

#### **Germ cell mutagenicity**

Not classified based on available information.

#### **Carcinogenicity**

Not classified based on available information.

#### **Reproductive toxicity**

Not classified based on available information.

#### **STOT-single exposure**

Not classified based on available information.

#### **STOT-repeated exposure**

Not classified based on available information.

#### **Aspiration toxicity**

Not classified based on available information.

## **11.2 Information on other hazards**

### **Endocrine disrupting properties**

Not classified based on available information.

### **Product:**

Assessment : The substance/mixture does not contain components consid-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

DE / EN



## Capadur ClassicLasur Eiche

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 10.04.2024  |
| 5.0     | 21.10.2025     | 6005025     | Date of first issue: 04.06.2019 |

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

##### **3-iodo-2-propynyl butylcarbamate:**

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 1

##### **4,5-dichloro-2-octyl-2H-isothiazol-3-one:**

M-Factor (Acute aquatic toxicity) : 100

M-Factor (Chronic aquatic toxicity) : 100

##### **octhilinone (ISO):**

M-Factor (Acute aquatic toxicity) : 100

M-Factor (Chronic aquatic toxicity) : 100

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

#### Components:

##### **Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha:**

Partition coefficient: n-octanol/water : log Pow: 1,99 - 18,02 (20 °C)  
pH: 7

##### **Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:**

Partition coefficient: n-octanol/water : log Pow: 2,37 - 2,77 (25 °C)  
pH: 7,0

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

DE / EN



## Capadur ClassicLasur Eiche

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 10.04.2024  |
| 5.0     | 21.10.2025     | 6005025     | Date of first issue: 04.06.2019 |

### **3-iodo-2-propynyl butylcarbamate:**

Partition coefficient: n-octanol/water : log Pow: 2,81 (25 °C)

### **octhilinone (ISO):**

Partition coefficient: n-octanol/water : log Pow: 2,61 (25 °C)  
pH: 7

### **12.4 Mobility in soil**

No data available

### **12.5 Results of PBT and vPvB assessment**

#### **Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### **12.6 Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### **12.7 Other adverse effects**

#### **Product:**

Additional ecological information : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

---

## **SECTION 13: Disposal considerations**

### **13.1 Waste treatment methods**

Product : Materials and all related packaging must be disposed of in a safe way in accordance with the full requirements of the local, regional, national and international authorities.

Must not reach sewage system or environment.

Contaminated packaging : Only completely emptied containers should be given for recycling.

Waste Code : used product  
080112, waste paint and varnish other than those mentioned

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

DE / EN



## Capadur ClassicLasur Eiche

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 10.04.2024  |
| 5.0     | 21.10.2025     | 6005025     | Date of first issue: 04.06.2019 |

in 08 01 11\*

### SECTION 14: Transport information

#### 14.1 UN number or ID number

ADN : Not regulated as a dangerous good  
ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

#### 14.2 UN proper shipping name

ADN : Not regulated as a dangerous good  
ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

#### 14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good  
ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

#### 14.4 Packing group

ADN : Not regulated as a dangerous good  
ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA (Cargo) : Not regulated as a dangerous good  
IATA (Passenger) : Not regulated as a dangerous good

#### 14.5 Environmental hazards

Not regulated as a dangerous good

#### 14.6 Special precautions for user

Not applicable

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

DE / EN



## Capadur ClassicLasur Eiche

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 10.04.2024  |
| 5.0     | 21.10.2025     | 6005025     | Date of first issue: 04.06.2019 |

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 75, 3

If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59) (SVHC) : None

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : None

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. 34 Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Water hazard class (Germany) : **WGK 3 highly water endangering**  
**Classification according to AwSV, Annex 1 (5.2)**

Product code for laquers and paints / Giscode : M-KH02F Solvent-based varnishes / wood glaze, aromatics removed, active agents

. : BSL40: Coating materials, strongly solvent-based, aromatic-free, classified

Labeling according to Regulation (EU) 528/2012 : Treated article, contains a biocidal product. Film preservative: IPBC, DCOIT, OIT.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

DE / EN



## Capadur ClassicLasur Eiche

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 10.04.2024  |
| 5.0     | 21.10.2025     | 6005025     | Date of first issue: 04.06.2019 |

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 40,02 %

Volatile organic compounds : Directive 2004/42/EC  
< 41 %  
< 380 g/l

### Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

### 15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

## SECTION 16: Other information

### Full text of H-Statements

H301 : Toxic if swallowed.  
H302 : Harmful if swallowed.  
H304 : May be fatal if swallowed and enters airways.  
H311 : Toxic in contact with skin.  
H314 : Causes severe skin burns and eye damage.  
H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H318 : Causes serious eye damage.  
H330 : Fatal if inhaled.  
H331 : Toxic if inhaled.  
H361f : Suspected of damaging fertility.  
H372 : Causes damage to organs through prolonged or repeated exposure if inhaled.  
H373 : May cause damage to organs through prolonged or repeated exposure if swallowed.  
H400 : Very toxic to aquatic life.  
H410 : Very toxic to aquatic life with long lasting effects.  
EUH066 : Repeated exposure may cause skin dryness or cracking.  
EUH071 : Corrosive to the respiratory tract.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Acute : Short-term (acute) aquatic hazard  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Asp. Tox. : Aspiration hazard

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

DE / EN



## Capadur ClassicLasur Eiche

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 10.04.2024  |
| 5.0     | 21.10.2025     | 6005025     | Date of first issue: 04.06.2019 |

|                   |   |
|-------------------|---|
| Eye Dam.          | : Serious eye damage                                      |
| Repr.             | : Reproductive toxicity                                   |
| Skin Corr.        | : Skin corrosion  |
| Skin Irrit.       | : Skin irritation   |
| Skin Sens.        | : Skin sensitization                                      |
| STOT RE           | : Specific target organ toxicity - repeated exposure      |
| DE DFG MAK        | : Germany. MAK BAT Annex IIa                              |
| DE TRGS 900       | : Germany. TRGS 900 - Occupational exposure limit values. |
| DE DFG MAK / MAK  | : MAK value   |
| DE TRGS 900 / AGW | : Time Weighted Average                                   |

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Other information : No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC. Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

Sources of key data used to compile the Material Safety Data Sheet : ECHA WebSite  
ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation.  
2014 ACGIH, Cincinnati OH  
NIOSH - Registry of toxic effects of chemical substances  
ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities  
SAX'S - Dangerous properties of industrial materials  
GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)  
Toxnet - Toxicology Data Network

**Classification of the mixture:**

**Classification procedure:**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

DE / EN

## Capadur ClassicLasur Eiche



|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 10.04.2024  |
| 5.0     | 21.10.2025     | 6005025     | Date of first issue: 04.06.2019 |

|                   |      |                    |
|-------------------|------|--------------------|
| Skin Sens. 1      | H317 | Calculation method |
| Aquatic Chronic 3 | H412 | Calculation method |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

### REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN