

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



Capacryl PU-Vorlack Weiß

Version	Revision Date:	SDS Number:	Date of last issue: 25.01.2023
4.1	12.06.2024	6005237	Date of first issue: 19.09.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Capacryl PU-Vorlack Weiß

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Water-borne coatings

Recommended restrictions : within adequate application - none
on use

1.3 Details of the supplier of the safety data sheet

Company : Caparol Farben Lacke GmbH
Roßdörfer Straße 50
64372 Ober-Ramstadt

Telephone : +496154710
Telefax : +4961547170222

Website :
E-mail address Responsible/issuing person : msds@dr-rmi.com

1.4 Emergency telephone

Emergency telephone 1 : +49613284463 GBK GmbH

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required.

Additional Labeling

EUH208 Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



CAPAROL

DE / EN

Capacryl PU-Vorlack Weiß

Version	Revision Date:	SDS Number:	Date of last issue: 25.01.2023
4.1	12.06.2024	6005237	Date of first issue: 19.09.2019

breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Keep out of reach of children. For spraying work, use combination filter A2/P2 and protective goggles. Use dust filter P2 for grinding work. Ensure thorough ventilation during application and drying. Avoid eating, drinking and smoking while using the paint. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, waterways or soil. Clean tools immediately after use with soap and water. For further technical information and advice for allergy sufferers, please call

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Polyurethane-based lacquer, aqueous

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10 μm]	13463-67-7 236-675-5 022-006-00-2 01-2119489379-17	Carc. 2; H351	\geq 20 - < 30
1,2-benzisothiazol-3(2H)-one	2634-33-5 220-120-9 613-088-00-6 01-2120761540-60	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 Acute Tox. 2; H330	\geq 0,025 - < 0,05
		M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN

Capacryl PU-Vorlack Weiß



Version 4.1 Revision Date: 12.06.2024 SDS Number: 6005237 Date of last issue: 25.01.2023
Date of first issue: 19.09.2019

		specific concentration limit Skin Sens. 1; H317 >= 0,05 %	
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9 613-167-00-5 01-2120764691-48	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100 specific concentration limit Skin Corr. 1C; H314 >= 0,6 % Skin Irrit. 2; H315 0,06 - < 0,6 % Eye Irrit. 2; H319 0,06 - < 0,6 % Skin Sens. 1A; H317 >= 0,0015 % Eye Dam. 1; H318 >= 0,6 %	>= 0,0002 - < 0,0015
Substances with a workplace exposure limit :			
Talc (Mg ₃ H ₂ (SiO ₃) ₄)	14807-96-6 238-877-9 01-2120140278-58		>= 1 - < 10
kaolin	1332-58-7 310-194-1		>= 1 - < 10
(2-methoxymethylethoxy)propanol	34590-94-8 252-104-2 01-2119450011-60		>= 1 - < 10

For explanation of abbreviations see section 16.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



Capacryl PU-Vorlack Weiß

Version	Revision Date:	SDS Number:	Date of last issue: 25.01.2023
4.1	12.06.2024	6005237	Date of first issue: 19.09.2019

SECTION 4: First aid measures

4.1 Description of first-aid measures

- General advice : Never give anything by mouth to an unconscious person.
If you feel unwell, seek medical advice (show the label where possible).
Move out of dangerous area.
First aider needs to protect himself.
- If inhaled : Move to fresh air.
- In case of skin contact : Do NOT use solvents or thinners.
In case of contact, immediately flush skin with soap and plenty of water.
- In case of eye contact : If eye irritation persists: Get medical advice/ attention.
IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.
- If swallowed : Seek medical advice.
Clean mouth with water and drink afterwards plenty of water.
If swallowed, DO NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Do not use a solid water stream as it may scatter and spread fire.
- Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire fighting : In case of fire hazardous decomposition products may be produced such as:
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



Capacryl PU-Vorlack Weiß

Version	Revision Date:	SDS Number:	Date of last issue: 25.01.2023
4.1	12.06.2024	6005237	Date of first issue: 19.09.2019

5.3 Advice for firefighters

- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
- Further information : Use water spray to cool unopened containers. Standard procedure for chemical fires. The product itself does not burn.
-

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Use protective shoes or boots with rough rubber sole. Material can create slippery conditions. Do not get in eyes, on skin, or on clothing.

6.2 Environmental precautions

- Environmental precautions : Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities. Do not flush into surface water or sanitary sewer system.

6.3 Methods and material for containment and cleaning up

- Methods for cleaning up : Keep in suitable, closed containers for disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.
, For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Use only with adequate ventilation. For personal protection see section 8. No special technical protective measures required.

In addition, the current technical information for this product and its application on www.caparol.com must be observed.

- Hygiene measures : Wash hands before eating, drinking, or smoking. Do not eat, drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering eating areas.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



Capacryl PU-Vorlack Weiß

Version 4.1 Revision Date: 12.06.2024 SDS Number: 6005237 Date of last issue: 25.01.2023
Date of first issue: 19.09.2019

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Perishable if frozen. To maintain product quality, do not store in heat or direct sunlight. Store at room temperature in the original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline materials.

Storage class (TRGS 510) : 12

7.3 Specific end use(s)

Specific use(s) : This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]	13463-67-7	MAK (measured as the alveolate fraction)	0,3 mg/m ³	DE DFG MAK
	Further information: Substances that cause cancer in humans or animals or that are considered to be carcinogenic for humans and for which a MAK value can be derived., Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			
		AGW (Inhalable fraction)	10 mg/m ³ (Titanium dioxide)	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		AGW (Alveolate fraction)	1,25 mg/m ³ (Titanium dioxide)	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		BM (Alveolar dust fraction)	0,5 mg/m ³	DE TRGS 527
Talc (Mg ₃ H ₂ (SiO ₃) ₄)	14807-96-6	AGW (Inhalable fraction)	10 mg/m ³	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		AGW (Alveolate)	1,25 mg/m ³	DE TRGS

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN

Capacryl PU-Vorlack Weiß



Version 4.1 Revision Date: 12.06.2024 SDS Number: 6005237 Date of last issue: 25.01.2023
Date of first issue: 19.09.2019

		fraction)		900
	Peak-limit category: 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
kaolin	1332-58-7	TWA (Respirable dust)	0,1 mg/m ³	2004/37/EC
	Further information: Carcinogens or mutagens			
(2-methoxymethylethoxy)propanol	34590-94-8	TWA	50 ppm 308 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		MAK	50 ppm 310 mg/m ³	DE DFG MAK
	Further information: Either there are no data for an assessment of damage to the embryo or foetus, including developmental neurotoxicity, or the currently available data are not sufficient for classification in one of the groups A - C			
		AGW (Vapour and aerosols)	50 ppm 310 mg/m ³	DE TRGS 900
	Peak-limit category: 1;(I)			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of exposure	Potential health effects	Value
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	Consumers	Ingestion	Long-term systemic effects	700,00 mg/kg bw/day
	Workers	Inhalation	Long-term local effects	10,00 mg/m ³
Kaolin, calcined	Workers	Inhalation	Acute systemic effects	3,00 mg/m ³
	Workers	Inhalation	Acute local effects	3,00 mg/m ³
	Workers	Inhalation	Long-term systemic effects	3,00 mg/m ³
	Workers	Inhalation	Long-term local effects	3,00 mg/m ³
1-(2-butoxy-1-methylethoxy)propan-2-ol	Consumers	Inhalation	Long-term systemic effects	1,20 mg/m ³
	Consumers	Ingestion	Long-term systemic effects	7,50 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	1,10 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	10,00 mg/m ³
	Workers	Skin contact	Long-term systemic effects	3,00 mg/kg bw/day
(2-	Consumers	Ingestion	Long-term systemic	0,33 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN

Capacryl PU-Vorlack Weiß



Version 4.1 Revision Date: 12.06.2024 SDS Number: 6005237 Date of last issue: 25.01.2023
Date of first issue: 19.09.2019

methoxymethylethoxy)propanol			effects	bw/day
	Consumers	Skin contact	Long-term systemic effects	475,00 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	202,00 mg/m3
	Consumers	Ingestion	Long-term systemic effects	36,00 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	121,00 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	37,20 mg/m3
	Workers	Inhalation	Long-term systemic effects	308,00 mg/m3
	Workers	Inhalation	Long-term systemic effects	404,00 mg/m3
	Workers	Skin contact	Long-term systemic effects	283,00 mg/kg bw/day
	Workers	Skin contact	Long-term systemic effects	950,00 mg/kg bw/day
propane-1,2-diol	Consumers	Inhalation	Long-term systemic effects	50,00 mg/m3
	Consumers	Inhalation	Long-term local effects	10,00 mg/m3
	Workers	Inhalation	Long-term systemic effects	168,00 mg/m3
	Workers	Inhalation	Long-term systemic effects	168,00 mg/m3
	Workers	Inhalation	Long-term local effects	10,00 mg/m3
	Workers	Inhalation	Long-term local effects	10,00 mg/m3
	Consumers	Inhalation	Long-term systemic effects	50,00 mg/m3
	Consumers	Inhalation	Long-term local effects	10,00 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]	Sewage treatment plant	100 mg/l
	Fresh water	0,184 mg/l
	Soil	100 mg/kg dry weight (d.w.)
	Sea water	0,0184 mg/l
	Fresh water sediment	1000 mg/kg dry weight (d.w.)
	Sea sediment	100 mg/kg dry weight (d.w.)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



Capacryl PU-Vorlack Weiß

Version 4.1 Revision Date: 12.06.2024 SDS Number: 6005237 Date of last issue: 25.01.2023
Date of first issue: 19.09.2019

	Intermittent use/release	0,193 mg/l
Kaolin, calcined	Intermittent use/release	25 mg/l
	Fresh water	4,1 mg/l
	Sea water	0,41 mg/l
	Sewage treatment plant	1400 mg/l
1-(2-butoxy-1-methylethoxy)propan-2-ol	Sewage treatment plant	100 mg/l
	Fresh water	0,519 mg/l
	Soil	0,287 mg/kg dry weight (d.w.)
	Intermittent use/release	5,19 mg/l
	Fresh water sediment	2,96 mg/kg dry weight (d.w.)
	Sea water	0,0519 mg/l
	Sea sediment	0,296 mg/kg dry weight (d.w.)
	Soil	2,2 mg/kg dry weight (d.w.)
(2-methoxymethylethoxy)propanol	Intermittent use/release	192 mg/l
	Fresh water	19,2 mg/l
	Sewage treatment plant	4168 mg/l
	Sea water	1,92 mg/l
	Intermittent use/release	190 mg/l
	Fresh water sediment	70,2 mg/kg dry weight (d.w.)
	Sea water	1,9 mg/l
	Soil	2,74 mg/kg dry weight (d.w.)
	Sea sediment	7,02 mg/kg dry weight (d.w.)
	Fresh water	19 mg/l
	Sea sediment	57,2 mg/kg dry weight (d.w.)
	Soil	50 mg/kg dry weight (d.w.)
propane-1,2-diol	Sea water	26 mg/l
	Fresh water sediment	572 mg/kg dry weight (d.w.)
	Fresh water	260 mg/l
	Intermittent use/release	183 mg/l
	Sewage treatment plant	20000 mg/l

8.2 Exposure controls

Personal protective equipment

Eye/face protection : DGUV Regulation 112-192 - Use of eye and face protection

Goggles

Hand protection

Material : Nitrile rubber

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



Capacryl PU-Vorlack Weiß

Version	Revision Date:	SDS Number:	Date of last issue: 25.01.2023
4.1	12.06.2024	6005237	Date of first issue: 19.09.2019

Glove thickness : 0,2 mm
Protective index : Class 3

Remarks : Before removing gloves clean them with soap and water.
Wear suitable gloves tested to EN374.
DGUV Regulation 112-195 - Use of protective gloves

Skin and body protection : Long sleeved clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

Safety shoes

Respiratory protection : No personal respiratory protective equipment normally required.

During spray application: Do not breathe spray dust. Use A2/P2 combination filter for paint spraying.

DGUV Regulation 112-190 - Use of breathing equipment

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Color : white

Odor : characteristic

Melting point/freezing point : ca. 0 °C

Boiling point/boiling range : ca. 100 °C

Upper explosion limit / Upper flammability limit : not determined

Lower explosion limit / Lower flammability limit : not determined

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



Capacryl PU-Vorlack Weiß

Version	Revision Date:	SDS Number:	Date of last issue: 25.01.2023
4.1	12.06.2024	6005237	Date of first issue: 19.09.2019

Flash point	:	Not applicable
Autoignition temperature	:	not determined
Decomposition temperature	:	Not applicable
pH	:	8 - 9 (20 °C) Concentration: 100 % Method: DIN EN ISO 19396-1:2020-05
Viscosity		
Viscosity, dynamic	:	not determined
Viscosity, kinematic	:	not determined
Flow time	:	not determined
Solubility(ies)		
Water solubility	:	completely miscible
Partition coefficient: n-octanol/water	:	not determined
Vapor pressure	:	ca. 23,4 hPa (20 °C)
Relative density	:	not determined
Density	:	1,41 g/cm ³ (20 °C) Method: DIN EN ISO 2811-1
Bulk density	:	Not applicable
Relative vapor density	:	not determined

9.2 Other information

Explosives	:	Not applicable
------------	---	----------------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



Capacryl PU-Vorlack Weiß

Version	Revision Date:	SDS Number:	Date of last issue: 25.01.2023
4.1	12.06.2024	6005237	Date of first issue: 19.09.2019

Oxidizing properties : Not applicable

Flammability (liquids) : The product is not flammable.

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

10.5 Incompatible materials

Materials to avoid : Incompatible with acids and bases.
Incompatible with oxidizing agents.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

1,2-benzisothiazol-3(2H)-one:

Acute oral toxicity : LD50 (Rat): 532 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0,4 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

Acute oral toxicity : LD50 (Rat): 66 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



Capacryl PU-Vorlack Weiß

Version	Revision Date:	SDS Number:	Date of last issue: 25.01.2023
4.1	12.06.2024	6005237	Date of first issue: 19.09.2019

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 0,17 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 141 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Not classified based on available information.

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN

Capacryl PU-Vorlack Weiß



Version	Revision Date:	SDS Number:	Date of last issue: 25.01.2023
4.1	12.06.2024	6005237	Date of first issue: 19.09.2019

SECTION 12: Ecological information

12.1 Toxicity

Components:

1,2-benzisothiazol-3(2H)-one:

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2,2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia): 3,27 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 0,11 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- M-Factor (Acute aquatic toxicity) : 1
- M-Factor (Chronic aquatic toxicity) : 1

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

- M-Factor (Acute aquatic toxicity) : 100
- M-Factor (Chronic aquatic toxicity) : 100

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

1,2-benzisothiazol-3(2H)-one:

- Partition coefficient: n-octanol/water : log Pow: 0,63 - 0,76
pH: 7

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

- Partition coefficient: n-octanol/water : log Pow: <= 0,75
Method: OECD Test Guideline 117

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



Capacryl PU-Vorlack Weiß

Version	Revision Date:	SDS Number:	Date of last issue: 25.01.2023
4.1	12.06.2024	6005237	Date of first issue: 19.09.2019

(2-methoxymethylethoxy)propanol:

Partition coefficient: n- : Pow: 1,01 (25 °C)
octanol/water

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of liquid material residues at the collection point for old paints/varnishes, dispose of dried material residues as construction and demolition waste or as municipal waste or household waste.

Waste should not be disposed of via wastewater.

Contaminated packaging : Only completely emptied containers should be given for recycling.

Waste Code : used product
080112, waste paint and varnish other than those mentioned in 08 01 11*

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



Capacryl PU-Vorlack Weiß

Version	Revision Date:	SDS Number:	Date of last issue: 25.01.2023
4.1	12.06.2024	6005237	Date of first issue: 19.09.2019

SECTION 14: Transport information

14.1 UN number or ID number

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.4 Packing group

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN

Capacryl PU-Vorlack Weiß



Version	Revision Date:	SDS Number:	Date of last issue: 25.01.2023
4.1	12.06.2024	6005237	Date of first issue: 19.09.2019

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 75
If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59). : None

Regulation (EC) on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : None

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. : Not applicable

Water hazard class (Germany) : WGK 1 slightly water endangering
Classification according to AwSV, Annex 1 (5.2)

Product code for laquers and paints / Giscode : M-LW01 Water-based varnishes

. : BSW30 Coating materials, water-based, containing solvents

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 2,62 %

Volatile organic compounds : Directive 2004/42/EC
< 6 %
< 80 g/l

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN

Capacryl PU-Vorlack Weiß



Version	Revision Date:	SDS Number:	Date of last issue: 25.01.2023
4.1	12.06.2024	6005237	Date of first issue: 19.09.2019

15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

SECTION 16: Other information

Full text of H-Statements

H301	: Toxic if swallowed.
H302	: Harmful if swallowed.
H310	: Fatal in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H330	: Fatal if inhaled.
H351	: Suspected of causing cancer if inhaled.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.
EUH071	: Corrosive to the respiratory tract.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Carc.	: Carcinogenicity
Eye Dam.	: Serious eye damage
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitization
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2004/37/EC	: Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work
DE DFG MAK	: Germany. MAK BAT Annex IIa
DE TRGS 527	: Germany. TRGS 527 - Activities with nanomaterials
DE TRGS 900	: Germany. TRGS 900 - Occupational exposure limit values.
2000/39/EC / TWA	: Limit Value - eight hours
2004/37/EC / TWA	: Long term exposure limit
DE DFG MAK / MAK	: MAK value
DE TRGS 527 / BM	: Assessment scale
DE TRGS 900 / AGW	: Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inven-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



Capacryl PU-Vorlack Weiß

Version	Revision Date:	SDS Number:	Date of last issue: 25.01.2023
4.1	12.06.2024	6005237	Date of first issue: 19.09.2019

tory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC. Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

Sources of key data used to compile the Material Safety Data Sheet : ECHA WebSite
ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH
NIOSH - Registry of toxic effects of chemical substances
ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities
SAX'S - Dangerous properties of industrial materials
GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)
Toxnet - Toxicology Data Network

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN

Capacryl PU-Vorlack Weiß



Version	Revision Date:	SDS Number:	Date of last issue: 25.01.2023
4.1	12.06.2024	6005237	Date of first issue: 19.09.2019

DE / EN