

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capacryl PU-Satin Basis W

Version	Revision Date:	SDS Number:	Date of last issue: 10.03.2022
4.0	11.01.2023	6004684	Date of first issue: 10.11.2019

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Capacryl PU-Satin Basis W

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Water-borne coatings

Recommended restrictions : within adequate application - none  
on use

#### 1.3 Details of the supplier of the safety data sheet

Company : Caparol Farben Lacke GmbH  
Roßdörfer Straße 50  
64372 Ober-Ramstadt

Telephone : +496154710  
Telefax : +4961547170222

E-mail address Responsible/issuing person : msds@dr-rmi.com

#### 1.4 Emergency telephone

Emergency telephone 1 : +49613284463 GBK GmbH

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

#### 2.2 Label elements

##### Labeling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

Precautionary Statements : P101 If medical advice is needed, have product container or  
label at hand.  
P102 Keep out of reach of children.

#### Additional Labeling

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capacryl PU-Satin Basis W

Version	Revision Date:	SDS Number:	Date of last issue: 10.03.2022
4.0	11.01.2023	6004684	Date of first issue: 10.11.2019

**EUH208** Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

**EUH211** Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Ensure good ventilation during use and drying. Do not eat, drink or smoke while using the product. In case of contact with eyes or skin, immediately and thoroughly rinse with water. Do not allow product to enter drains, waterways or soil. Clean utensils immediately after use with soap and water.

Use P2 dust filter for grinding.

Do not breathe spray dust. Use A2/P2 combination filter and goggles for paint spraying.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Polyurethane/polyacrylate-based lacquer, aqueous

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq$ 10 $\mu$ m]	13463-67-7 236-675-5 022-006-00-2 01-2119489379-17	Carc. 2; H351	$\geq$ 20 - < 30
2-(2-butoxyethoxy)ethanol	112-34-5 203-961-6 603-096-00-8 01-2119475104-44	Eye Irrit. 2; H319	$\geq$ 1 - < 10
propylidynetrimethanol	77-99-6	Repr. 2; H361fd	$\geq$ 0,1 - < 1

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capacryl PU-Satin Basis W

Version 4.0      Revision Date: 11.01.2023      SDS Number: 6004684      Date of last issue: 10.03.2022  
Date of first issue: 10.11.2019

	201-074-9 01-2119486799-10		
1,2-benzisothiazol-3(2H)-one	2634-33-5 220-120-9 613-088-00-6 01-2120761540-60	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 Acute Tox. 2; H330  M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1  specific concentration limit Skin Sens. 1; H317 >= 0,05 %	>= 0,0025 - < 0,025
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9 613-167-00-5 01-2120764691-48	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071  M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100  specific concentration limit Skin Corr. 1C; H314 >= 0,6 % Skin Irrit. 2; H315 0,06 - < 0,6 % Eye Irrit. 2; H319 0,06 - < 0,6 %	>= 0,0002 - < 0,0015

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capacryl PU-Satin Basis W

Version	Revision Date:	SDS Number:	Date of last issue: 10.03.2022
4.0	11.01.2023	6004684	Date of first issue: 10.11.2019

		Skin Sens. 1A; H317 >= 0,0015 % Eye Dam. 1; H318 >= 0,6 %	
--	--	--	--

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first-aid measures

- General advice : Never give anything by mouth to an unconscious person.  
If you feel unwell, seek medical advice (show the label where possible).  
Move out of dangerous area.  
First aider needs to protect himself.
- If inhaled : Move to fresh air.
- In case of skin contact : Do NOT use solvents or thinners.  
In case of contact, immediately flush skin with soap and plenty of water.
- In case of eye contact : If eye irritation persists: Get medical advice/ attention.  
IF IN EYES: Rinse cautiously with water for several minutes.  
Remove contact lenses, if present and easy to do. Continue rinsing.
- If swallowed : Seek medical advice.  
Clean mouth with water and drink afterwards plenty of water.  
If swallowed, DO NOT induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed

None known.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Do not use a solid water stream as it may scatter and spread

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capacryl PU-Satin Basis W

Version	Revision Date:	SDS Number:	Date of last issue: 10.03.2022
4.0	11.01.2023	6004684	Date of first issue: 10.11.2019

fire.

Unsuitable extinguishing media : None known.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : In case of fire hazardous decomposition products may be produced such as:  
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

### 5.3 Advice for firefighters

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Use water spray to cool unopened containers.  
Standard procedure for chemical fires.  
The product itself does not burn.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use protective shoes or boots with rough rubber sole.  
Material can create slippery conditions.  
Do not get in eyes, on skin, or on clothing.

### 6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.  
Do not flush into surface water or sanitary sewer system.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

### 6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.  
, For personal protection see section 8., For disposal considerations see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capacryl PU-Satin Basis W

Version 4.0      Revision Date: 11.01.2023      SDS Number: 6004684      Date of last issue: 10.03.2022  
Date of first issue: 10.11.2019

Advice on safe handling : Use only with adequate ventilation.  
For personal protection see section 8.  
No special technical protective measures required.

In addition, the current technical information for this product and its application on [www.caparol.com](http://www.caparol.com) must be observed.

Hygiene measures : Wash hands before eating, drinking, or smoking. Do not eat, drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering eating areas.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Perishable if frozen. To maintain product quality, do not store in heat or direct sunlight. Store at room temperature in the original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline materials.

Storage class (TRGS 510) : 12

### 7.3 Specific end use(s)

Specific use(s) : This information is not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ]	13463-67-7	AGW (Inhalable fraction)	10 mg/m <sup>3</sup> (Titanium dioxide)	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		AGW (Alveolate fraction)	1,25 mg/m <sup>3</sup> (Titanium dioxide)	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: When there is compliance with the OEL and biological			

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capacryl PU-Satin Basis W

Version 4.0      Revision Date: 11.01.2023      SDS Number: 6004684      Date of last issue: 10.03.2022  
Date of first issue: 10.11.2019

		tolerance values, there is no risk of harming the unborn child		
		BM (Alveolar dust fraction)	0,5 mg/m <sup>3</sup>	DE TRGS 527
2-(2-butoxyethoxy)ethanol	112-34-5	TWA	10 ppm 67,5 mg/m <sup>3</sup>	2006/15/EC
	Further information: Indicative			
		STEL	15 ppm 101,2 mg/m <sup>3</sup>	2006/15/EC
	Further information: Indicative			
		AGW (Vapour and aerosols)	10 ppm 67 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 1.5;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of exposure	Potential health effects	Value
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	Consumers	Ingestion	Long-term systemic effects	700,00 mg/kg bw/day
	Workers	Inhalation	Long-term local effects	10,00 mg/m <sup>3</sup>
propane-1,2-diol	Consumers	Inhalation	Long-term systemic effects	50,00 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	10,00 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	168,00 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	168,00 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	10,00 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	10,00 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	50,00 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	10,00 mg/m <sup>3</sup>
Silicic acid, aluminum sodium salt	Workers	Inhalation	Long-term local effects	4,00 mg/m <sup>3</sup>
2-(2-butoxyethoxy)ethanol	Consumers	Inhalation	Acute local effects	60,70 mg/m <sup>3</sup>
	Consumers	Ingestion	Long-term systemic effects	5,00 mg/kg bw/day

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capacryl PU-Satin Basis W

Version 4.0      Revision Date: 11.01.2023      SDS Number: 6004684      Date of last issue: 10.03.2022  
Date of first issue: 10.11.2019

	Consumers	Inhalation	Long-term local effects	40,50 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	50,00 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	40,50 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	101,20 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	67,50 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	67,50 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	83,00 mg/kg bw/day
propylidynetrimethanol	Consumers	Skin contact	Acute systemic effects	83,30 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	1,68 mg/kg bw/day
	Consumers	Inhalation	Acute systemic effects	925,00 mg/m <sup>3</sup>
	Consumers	Ingestion	Acute systemic effects	50,00 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	5,03 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	1,68 mg/kg bw/day
	Workers	Inhalation	Acute systemic effects	3037,30 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	19,54 mg/m <sup>3</sup>
	Workers	Skin contact	Acute systemic effects	138,80 mg/kg bw/day
	Workers	Skin contact	Long-term systemic effects	2,79 mg/kg bw/day

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq$ 10 $\mu$ m]	Sewage treatment plant	100 mg/l
	Fresh water	0,184 mg/l
	Soil	100 mg/kg dry weight (d.w.)
	Sea water	0,0184 mg/l
	Fresh water sediment	1000 mg/kg dry weight (d.w.)
	Sea sediment	100 mg/kg dry weight (d.w.)
	Intermittent use/release	0,193 mg/l



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capacryl PU-Satin Basis W

Version 4.0      Revision Date: 11.01.2023      SDS Number: 6004684      Date of last issue: 10.03.2022  
Date of first issue: 10.11.2019

propane-1,2-diol	Sea sediment	57,2 mg/kg dry weight (d.w.)
	Soil	50 mg/kg dry weight (d.w.)
	Sea water	26 mg/l
	Fresh water sediment	572 mg/kg dry weight (d.w.)
	Fresh water	260 mg/l
	Intermittent use/release	183 mg/l
	Sewage treatment plant	20000 mg/l
2-(2-butoxyethoxy)ethanol	Fresh water	1,1 mg/l
	Fresh water sediment	4,4 mg/kg dry weight (d.w.)
	Intermittent use/release	11 mg/l
	Sea water	0,11 mg/l
	Sea sediment	0,44 mg/kg dry weight (d.w.)
	Sewage treatment plant	200 mg/l
	Soil	0,32 mg/kg dry weight (d.w.)
	Secondary Poisoning	56 mg/kg food
propylidynetrimethanol	Fresh water	1 mg/l
	Sewage treatment plant	100 mg/l
	Sea sediment	0,351 mg/kg dry weight (d.w.)
	Sea water	0,1 mg/l
	Soil	0,241 mg/kg dry weight (d.w.)
	Fresh water sediment	3,505 mg/kg dry weight (d.w.)
	Intermittent use/release	10 mg/l

### 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection : DGUV Regulation 112-192 - Use of eye and face protection

Goggles

Hand protection

Material : Nitrile rubber  
Glove thickness : 0,2 mm  
Protective index : Class 3

Remarks : Before removing gloves clean them with soap and water.  
Wear suitable gloves tested to EN374.  
DGUV Regulation 112-195 - Use of protective gloves

Skin and body protection : Long sleeved clothing

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capacryl PU-Satin Basis W

Version	Revision Date:	SDS Number:	Date of last issue: 10.03.2022
4.0	11.01.2023	6004684	Date of first issue: 10.11.2019

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

Safety shoes

Respiratory protection : No personal respiratory protective equipment normally required.

DGUV Regulation 112-190 - Use of breathing equipment

During spray application: Do not breathe spray dust. Use A2/P2 combination filter for paint spraying.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Color	:	No data available
Odor	:	No data available
Melting point/freezing point	:	ca. 0 °C
Boiling point/boiling range	:	ca. 100 °C
Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower flammability limit	:	not determined
Flash point	:	Not applicable
Autoignition temperature	:	not determined
Decomposition temperature	:	Not applicable
pH	:	8 - 9 Concentration: 100 %
Viscosity	:	
Viscosity, dynamic	:	No data available
Solubility(ies)	:	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capacryl PU-Satin Basis W

Version	Revision Date:	SDS Number:	Date of last issue: 10.03.2022
4.0	11.01.2023	6004684	Date of first issue: 10.11.2019

Water solubility : completely miscible

Partition coefficient: n-octanol/water : not determined

Vapor pressure : ca. 23,4 hPa (20 °C)

Relative density : not determined

Density : 1,2800 g/cm<sup>3</sup>

Relative vapor density : not determined

### 9.2 Other information

Explosives : Not applicable

Oxidizing properties : Not applicable

Flammability (liquids) : The product is not flammable.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

### 10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

### 10.5 Incompatible materials

Materials to avoid : Incompatible with acids and bases.  
Incompatible with oxidizing agents.

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capacryl PU-Satin Basis W

Version	Revision Date:	SDS Number:	Date of last issue: 10.03.2022
4.0	11.01.2023	6004684	Date of first issue: 10.11.2019

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

Not classified based on available information.

##### Components:

##### **2-(2-butoxyethoxy)ethanol:**

Acute oral toxicity : LD50 (Mouse): 2.410 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 2.764 mg/kg

##### **1,2-benzisothiazol-3(2H)-one:**

Acute oral toxicity : LD50 (Rat): 532 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0,4 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

##### **reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):**

Acute oral toxicity : LD50 (Rat): 66 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 0,17 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 141 mg/kg  
Method: OECD Test Guideline 402

##### **Skin corrosion/irritation**

Not classified based on available information.

##### **Serious eye damage/eye irritation**

Not classified based on available information.

##### **Respiratory or skin sensitization**

##### **Skin sensitization**

Not classified based on available information.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capacryl PU-Satin Basis W

Version	Revision Date:	SDS Number:	Date of last issue: 10.03.2022
4.0	11.01.2023	6004684	Date of first issue: 10.11.2019

### Respiratory sensitization

Not classified based on available information.

### Germ cell mutagenicity

Not classified based on available information.

### Carcinogenicity

Not classified based on available information.

### Reproductive toxicity

Not classified based on available information.

### STOT-single exposure

Not classified based on available information.

### STOT-repeated exposure

Not classified based on available information.

### Aspiration toxicity

Not classified based on available information.

## 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

#### **1,2-benzisothiazol-3(2H)-one:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2,2 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia): 3,27 mg/l  
aquatic invertebrates : Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : EC50 (Selenastrum capricornutum (green algae)): 0,11 mg/l  
plants : Exposure time: 72 h  
Method: OECD Test Guideline 201

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capacryl PU-Satin Basis W

Version	Revision Date:	SDS Number:	Date of last issue: 10.03.2022
4.0	11.01.2023	6004684	Date of first issue: 10.11.2019

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

### reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

M-Factor (Acute aquatic toxicity) : 100

M-Factor (Chronic aquatic toxicity) : 100

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

#### Components:

#### **2-(2-butoxyethoxy)ethanol:**

Partition coefficient: n-octanol/water : log Pow: 0,56

### reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

Partition coefficient: n-octanol/water : log Pow: <= 0,71  
Method: OECD Test Guideline 117

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capacryl PU-Satin Basis W

Version	Revision Date:	SDS Number:	Date of last issue: 10.03.2022
4.0	11.01.2023	6004684	Date of first issue: 10.11.2019

REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : .  
Waste should not be disposed of via wastewater.

Contaminated packaging : Only completely emptied containers should be given for recycling.

Waste Code : used product  
080112, waste paint and varnish other than those mentioned in 08 01 11\*

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADN : Not regulated as a dangerous good  
ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

### 14.2 UN proper shipping name

ADN : Not regulated as a dangerous good  
ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

### 14.3 Transport hazard class(es)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capacryl PU-Satin Basis W

Version	Revision Date:	SDS Number:	Date of last issue: 10.03.2022
4.0	11.01.2023	6004684	Date of first issue: 10.11.2019

**ADN** : Not regulated as a dangerous good  
**ADR** : Not regulated as a dangerous good  
**RID** : Not regulated as a dangerous good  
**IMDG** : Not regulated as a dangerous good  
**IATA** : Not regulated as a dangerous good

### 14.4 Packing group

**ADN** : Not regulated as a dangerous good  
**ADR** : Not regulated as a dangerous good  
**RID** : Not regulated as a dangerous good  
**IMDG** : Not regulated as a dangerous good  
**IATA (Cargo)** : Not regulated as a dangerous good  
**IATA (Passenger)** : Not regulated as a dangerous good

### 14.5 Environmental hazards

Not regulated as a dangerous good

### 14.6 Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59). : This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be generated.

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capacryl PU-Satin Basis W

Version	Revision Date:	SDS Number:	Date of last issue: 10.03.2022
4.0	11.01.2023	6004684	Date of first issue: 10.11.2019

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : None

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. Not applicable

Water hazard class (Germany) : WGK 1 slightly water endangering  
Classification according to AwSV, Annex 1 (5.2)

Product code for laquers and paints / Giscode : M-LW01 Water-based varnishes

. : BSW30 Coating materials, water-based, containing solvents

Volatile organic compounds : Directive 2004/42/EC  
< 9 %  
< 110 g/l

### Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

## 15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

## SECTION 16: Other information

### Full text of H-Statements

H301	: Toxic if swallowed.
H302	: Harmful if swallowed.
H310	: Fatal in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H330	: Fatal if inhaled.
H351	: Suspected of causing cancer if inhaled.
H361fd	: Suspected of damaging fertility. Suspected of damaging the unborn child.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capacryl PU-Satin Basis W

Version	Revision Date:	SDS Number:	Date of last issue: 10.03.2022
4.0	11.01.2023	6004684	Date of first issue: 10.11.2019

H400 : Very toxic to aquatic life.  
H410 : Very toxic to aquatic life with long lasting effects.  
H411 : Toxic to aquatic life with long lasting effects.  
EUH071 : Corrosive to the respiratory tract.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Acute : Short-term (acute) aquatic hazard  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Carc. : Carcinogenicity  
Eye Dam. : Serious eye damage  
Eye Irrit. : Eye irritation  
Repr. : Reproductive toxicity  
Skin Corr. : Skin corrosion  
Skin Irrit. : Skin irritation  
Skin Sens. : Skin sensitization  
2006/15/EC : Europe. Indicative occupational exposure limit values  
DE TRGS 527 : Germany. TRGS 527 - Activities with nanomaterials  
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.  
2006/15/EC / TWA : Limit Value - eight hours  
2006/15/EC / STEL : Short term exposure limit  
DE TRGS 527 / BM : Assessment scale  
DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

### Sources of key data used to compile the Material Safety Data Sheet:

ECHA WebSite

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capacryl PU-Satin Basis W

Version	Revision Date:	SDS Number:	Date of last issue: 10.03.2022
4.0	11.01.2023	6004684	Date of first issue: 10.11.2019

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH  
NIOSH - Registry of toxic effects of chemical substances  
ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities  
SAX'S - Dangerous properties of industrial materials  
GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)  
Toxnet - Toxicology Data Network

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

### REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.  
Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN