

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capacryl PU-Satin Basis R

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 17.12.2020  |
| 3.0     | 26.01.2023     | 6004801     | Date of first issue: 01.12.2019 |

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Capacryl PU-Satin Basis R

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Water-borne coatings

Recommended restrictions on use : within adequate application - none

#### 1.3 Details of the supplier of the safety data sheet

Company : Caparol Farben Lacke GmbH  
Roßdörfer Straße 50  
64372 Ober-Ramstadt

Telephone : +496154710  
Telefax : +4961547170222

E-mail address Responsible/issuing person : msds@dr-rmi.com

#### 1.4 Emergency telephone

Emergency telephone 1 : +49613284463 GBK GmbH

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

#### 2.2 Label elements

##### Labeling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

Precautionary Statements : P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.

#### Additional Labeling

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capacryl PU-Satin Basis R

Version 3.0      Revision Date: 26.01.2023      SDS Number: 6004801      Date of last issue: 17.12.2020  
Date of first issue: 01.12.2019

EUH208      Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: **The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.**

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature      :      Polyurethane/polyacrylate-based lacquer, aqueous

#### Components

| Chemical name  | CAS-No.<br>EC-No.<br>Index-No.<br>Registration number       | Classification  | Concentration<br>(% w/w) |
|--|---|---|--------------------------|
| 2-methylpentane-2,4-diol   | 107-41-5<br>203-489-0<br>603-053-00-3<br>01-2119539582-35   | Skin Irrit. 2; H315<br>Eye Irrit. 2; H319   | >= 1 - < 10              |
| 2-(2-butoxyethoxy)ethanol  | 112-34-5<br>203-961-6<br>603-096-00-8<br>01-2119475104-44   | Eye Irrit. 2; H319  | >= 1 - < 10              |
| titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] | 13463-67-7<br>236-675-5<br>022-006-00-2<br>01-2119489379-17 | Carc. 2; H351   | >= 0,1 - < 1             |
| 1,2-benzisothiazol-3(2H)-one   | 2634-33-5<br>220-120-9<br>613-088-00-6<br>01-2120761540-60  | Acute Tox. 4; H302<br>Skin Irrit. 2; H315<br>Eye Dam. 1; H318<br>Skin Sens. 1; H317<br>Aquatic Acute 1;<br>H400 | >= 0,0025 - < 0,025      |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capacryl PU-Satin Basis R

Version 3.0      Revision Date: 26.01.2023      SDS Number: 6004801      Date of last issue: 17.12.2020  
Date of first issue: 01.12.2019

|   |  |   |                         |
|---|--|---|-------------------------|
|   |  | Aquatic Chronic 2;<br>H411<br>Acute Tox. 2; H330<br><br>M-Factor (Acute<br>aquatic toxicity): 1<br>M-Factor (Chronic<br>aquatic toxicity): 1<br><br>specific concentration<br>limit<br>Skin Sens. 1; H317<br>>= 0,05 %  |                         |
| reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) | 55965-84-9<br>613-167-00-5<br>01-2120764691-48 | Acute Tox. 3; H301<br>Acute Tox. 2; H330<br>Acute Tox. 2; H310<br>Skin Corr. 1C; H314<br>Eye Dam. 1; H318<br>Skin Sens. 1A; H317<br>Aquatic Acute 1;<br>H400<br>Aquatic Chronic 1;<br>H410<br>EUH071<br><br>M-Factor (Acute<br>aquatic toxicity): 100<br>M-Factor (Chronic<br>aquatic toxicity): 100<br><br>specific concentration<br>limit<br>Skin Corr. 1C; H314<br>>= 0,6 %<br>Skin Irrit. 2; H315<br>0,06 - < 0,6 %<br>Eye Irrit. 2; H319<br>0,06 - < 0,6 %<br>Skin Sens. 1A; H317<br>>= 0,0015 %<br>Eye Dam. 1; H318<br>>= 0,6 % | >= 0,0002 - <<br>0,0015 |

For explanation of abbreviations see section 16.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capacryl PU-Satin Basis R

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 17.12.2020  |
| 3.0     | 26.01.2023     | 6004801     | Date of first issue: 01.12.2019 |

### SECTION 4: First aid measures

#### 4.1 Description of first-aid measures

- General advice : Never give anything by mouth to an unconscious person.  
If you feel unwell, seek medical advice (show the label where possible).  
Move out of dangerous area.  
First aider needs to protect himself.
- If inhaled : Move to fresh air.
- In case of skin contact : Do NOT use solvents or thinners.  
In case of contact, immediately flush skin with soap and plenty of water.
- In case of eye contact : If eye irritation persists: Get medical advice/ attention.  
IF IN EYES: Rinse cautiously with water for several minutes.  
Remove contact lenses, if present and easy to do. Continue rinsing.
- If swallowed : Seek medical advice.  
Clean mouth with water and drink afterwards plenty of water.  
If swallowed, DO NOT induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed

None known.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Do not use a solid water stream as it may scatter and spread fire.
- Unsuitable extinguishing media : None known.

#### 5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire fighting : In case of fire hazardous decomposition products may be produced such as:

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capacryl PU-Satin Basis R

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 17.12.2020  |
| 3.0     | 26.01.2023     | 6004801     | Date of first issue: 01.12.2019 |

Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

### 5.3 Advice for firefighters

- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
- Further information : Use water spray to cool unopened containers. Standard procedure for chemical fires. The product itself does not burn.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Use protective shoes or boots with rough rubber sole. Material can create slippery conditions. Do not get in eyes, on skin, or on clothing.

### 6.2 Environmental precautions

- Environmental precautions : Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities. Do not flush into surface water or sanitary sewer system.

### 6.3 Methods and material for containment and cleaning up

- Methods for cleaning up : Keep in suitable, closed containers for disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

### 6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.  
, For personal protection see section 8., For disposal considerations see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- Advice on safe handling : Use only with adequate ventilation. For personal protection see section 8. No special technical protective measures required.

In addition, the current technical information for this product and its application on [www.caparol.com](http://www.caparol.com) must be observed.

- Hygiene measures : Wash hands before eating, drinking, or smoking. Do not eat,

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capacryl PU-Satin Basis R

Version 3.0      Revision Date: 26.01.2023      SDS Number: 6004801      Date of last issue: 17.12.2020  
Date of first issue: 01.12.2019

drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering eating areas.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Perishable if frozen. To maintain product quality, do not store in heat or direct sunlight. Store at room temperature in the original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline materials.

Storage class (TRGS 510) : 12

### 7.3 Specific end use(s)

Specific use(s) : This information is not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

| Components   | CAS-No.  | Value type (Form of exposure) | Control parameters                         | Basis       |
|--|--|-------------------------------|--|-------------|
| 2-(2-butoxyethoxy)ethanol  | 112-34-5   | TWA                           | 10 ppm<br>67,5 mg/m <sup>3</sup>           | 2006/15/EC  |
|  | Further information: Indicative  |                               |  |             |
|  |  | STEL                          | 15 ppm<br>101,2 mg/m <sup>3</sup>          | 2006/15/EC  |
|  | Further information: Indicative  |                               |  |             |
|  |  | AGW (Vapour and aerosols)     | 10 ppm<br>67 mg/m <sup>3</sup>             | DE TRGS 900 |
|  | Peak-limit category: 1.5;(I)   |                               |  |             |
|  | Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child |                               |  |             |
| titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] | 13463-67-7   | AGW (Inhalable fraction)      | 10 mg/m <sup>3</sup><br>(Titanium dioxide) | DE TRGS 900 |
|  | Peak-limit category: 2;(II)  |                               |  |             |
|  | Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child |                               |  |             |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capacryl PU-Satin Basis R

Version 3.0      Revision Date: 26.01.2023      SDS Number: 6004801      Date of last issue: 17.12.2020  
Date of first issue: 01.12.2019

|  |  |                             |  |                |
|--|--|-----------------------------|--|----------------|
|  |  | AGW (Alveolate fraction)    | 1,25 mg/m <sup>3</sup><br>(Titanium dioxide) | DE TRGS<br>900 |
|  | Peak-limit category: 2;(II)  |                             |  |                |
|  | Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child |                             |  |                |
|  |  | BM (Alveolar dust fraction) | 0,5 mg/m <sup>3</sup>                        | DE TRGS<br>527 |

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name  | End Use                   | Routes of exposure | Potential health effects   | Value                   |
|---|---------------------------|--------------------|----------------------------|-------------------------|
| 3,6-Bis(4-chlorophenyl)pyrrolo[3,4-c]pyrrole-1,4(2H,5H)-dione | Consumers                 | Skin contact       | Long-term systemic effects | 1,66 mg/kg bw/day       |
|   | Consumers                 | Inhalation         | Long-term systemic effects | 2,90 mg/m <sup>3</sup>  |
|   | Consumers                 | Ingestion          | Long-term systemic effects | 1,66 mg/kg bw/day       |
|   | Workers                   | Skin contact       | Long-term systemic effects | 3,33 mg/kg bw/day       |
|   | Workers                   | Inhalation         | Long-term systemic effects | 11,75 mg/m <sup>3</sup> |
| Silicic acid, aluminum sodium salt                            | Workers                   | Inhalation         | Long-term local effects    | 4,00 mg/m <sup>3</sup>  |
| 2-methylpentane-2,4-diol                                      | Consumers                 | Inhalation         | Long-term local effects    | 25,00 mg/m <sup>3</sup> |
|   | Consumers                 | Inhalation         | Long-term systemic effects | 3,50 mg/m <sup>3</sup>  |
|   | Consumers                 | Ingestion          | Long-term systemic effects | 1,00 mg/kg bw/day       |
|   | Consumers                 | Inhalation         | Acute local effects        | 49,00 mg/m <sup>3</sup> |
|   | Consumers                 | Skin contact       | Long-term systemic effects | 1,00 mg/kg bw/day       |
|   | Workers                   | Inhalation         | Acute local effects        | 98,00 mg/m <sup>3</sup> |
|   | Workers                   | Inhalation         | Long-term systemic effects | 14,00 mg/m <sup>3</sup> |
|   | Workers                   | Inhalation         | Long-term local effects    | 49,00 mg/m <sup>3</sup> |
|   | Workers                   | Skin contact       | Long-term systemic effects | 2,00 mg/kg bw/day       |
|   | 2-(2-butoxyethoxy)ethanol | Consumers          | Inhalation                 | Acute local effects     |
| Consumers   |                           | Ingestion          | Long-term systemic effects | 5,00 mg/kg bw/day       |
| Consumers   |                           | Inhalation         | Long-term local effects    | 40,50 mg/m <sup>3</sup> |
| Consumers   |                           | Skin contact       | Long-term systemic         | 50,00 mg/kg             |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capacryl PU-Satin Basis R

Version 3.0      Revision Date: 26.01.2023      SDS Number: 6004801      Date of last issue: 17.12.2020  
Date of first issue: 01.12.2019

|  |           |              | effects                    | bw/day                   |
|--|-----------|--------------|----------------------------|--------------------------|
|  | Consumers | Inhalation   | Long-term systemic effects | 40,50 mg/m <sup>3</sup>  |
|  | Workers   | Inhalation   | Acute local effects        | 101,20 mg/m <sup>3</sup> |
|  | Workers   | Inhalation   | Long-term systemic effects | 67,50 mg/m <sup>3</sup>  |
|  | Workers   | Inhalation   | Long-term local effects    | 67,50 mg/m <sup>3</sup>  |
|  | Workers   | Skin contact | Long-term systemic effects | 83,00 mg/kg bw/day       |
| titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] | Consumers | Ingestion    | Long-term systemic effects | 700,00 mg/kg bw/day      |
|  | Workers   | Inhalation   | Long-term local effects    | 10,00 mg/m <sup>3</sup>  |

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

| Substance name  | Environmental Compartment | Value                         |
|---|---------------------------|-------------------------------|
| 3,6-Bis(4-chlorophenyl)pyrrolo[3,4-c]pyrrole-1,4(2H,5H)-dione | Fresh water sediment      | 377 mg/kg dry weight (d.w.)   |
|   | Fresh water               | 10 mg/l                       |
|   | Soil                      | 1 mg/kg dry weight (d.w.)     |
|   | Intermittent use/release  | 1 mg/l                        |
|   | Sea sediment              | 37,7 mg/kg dry weight (d.w.)  |
|   | Sewage treatment plant    | 1 mg/l                        |
|   | Sea water                 | 1 mg/l                        |
| 2-methylpentane-2,4-diol                                      | Soil                      | 0,11 mg/kg dry weight (d.w.)  |
|   | Intermittent use/release  | 4,29 mg/l                     |
|   | Secondary Poisoning       | 100 mg/kg food                |
|   | Fresh water sediment      | 1,79 mg/kg dry weight (d.w.)  |
|   | Sea water                 | 0,0429 mg/l                   |
|   | Sewage treatment plant    | 20 mg/l                       |
|   | Sea sediment              | 0,179 mg/kg dry weight (d.w.) |
| 2-(2-butoxyethoxy)ethanol                                     | Fresh water               | 0,429 mg/l                    |
|   | Fresh water               | 1,1 mg/l                      |
|   | Fresh water sediment      | 4,4 mg/kg dry weight (d.w.)   |
|   | Intermittent use/release  | 11 mg/l                       |
|   | Sea water                 | 0,11 mg/l                     |
| Sea sediment  | 0,44 mg/kg dry            |                               |



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capacryl PU-Satin Basis R

Version 3.0      Revision Date: 26.01.2023      SDS Number: 6004801      Date of last issue: 17.12.2020  
Date of first issue: 01.12.2019

|   |                          |                              |
|---|--------------------------|------------------------------|
|   |                          | weight (d.w.)                |
|   | Sewage treatment plant   | 200 mg/l                     |
|   | Soil                     | 0,32 mg/kg dry weight (d.w.) |
|   | Secondary Poisoning      | 56 mg/kg food                |
| titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ] | Sewage treatment plant   | 100 mg/l                     |
|   | Fresh water              | 0,184 mg/l                   |
|   | Soil                     | 100 mg/kg dry weight (d.w.)  |
|   | Sea water                | 0,0184 mg/l                  |
|   | Fresh water sediment     | 1000 mg/kg dry weight (d.w.) |
|   | Sea sediment             | 100 mg/kg dry weight (d.w.)  |
|   | Intermittent use/release | 0,193 mg/l                   |

### 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection : DGUV Regulation 112-192 - Use of eye and face protection

Goggles

Hand protection

Material : Nitrile rubber

Glove thickness : 0,2 mm

Protective index : Class 3

Remarks : Before removing gloves clean them with soap and water.  
Wear suitable gloves tested to EN374.  
DGUV Regulation 112-195 - Use of protective gloves

Skin and body protection : Long sleeved clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

Safety shoes

Respiratory protection : No personal respiratory protective equipment normally required.

DGUV Regulation 112-190 - Use of breathing equipment

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capacryl PU-Satin Basis R

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 17.12.2020  |
| 3.0     | 26.01.2023     | 6004801     | Date of first issue: 01.12.2019 |

During spray application: Do not breathe spray dust. Use A2/P2 combination filter for paint spraying.

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

|  |   |                               |
|--|---|-------------------------------|
| Physical state                                   | : | liquid                        |
| Color  | : | No data available             |
| Odor   | : | No data available             |
| Melting point/freezing point                     | : | ca. 0 °C                      |
| Boiling point/boiling range                      | : | ca. 100 °C                    |
| Upper explosion limit / Upper flammability limit | : | not determined                |
| Lower explosion limit / Lower flammability limit | : | not determined                |
| Flash point                                      | : | Not applicable                |
| Autoignition temperature                         | : | not determined                |
| Decomposition temperature                        | : | Not applicable                |
| pH   | : | 8 - 9<br>Concentration: 100 % |
| Viscosity  | : |                               |
| Viscosity, dynamic                               | : | No data available             |
| Solubility(ies)                                  | : |                               |
| Water solubility                                 | : | completely miscible           |
| Partition coefficient: n-octanol/water           | : | not determined                |
| Vapor pressure                                   | : | ca. 23,4 hPa (20 °C)          |
| Relative density                                 | : | not determined                |
| Density  | : | 1,0800 g/cm <sup>3</sup>      |
| Relative vapor density                           | : | not determined                |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capacryl PU-Satin Basis R

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 17.12.2020  |
| 3.0     | 26.01.2023     | 6004801     | Date of first issue: 01.12.2019 |

### 9.2 Other information

Explosives : Not applicable

Oxidizing properties : Not applicable

Flammability (liquids) : The product is not flammable.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

### 10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

### 10.5 Incompatible materials

Materials to avoid : Incompatible with acids and bases.  
Incompatible with oxidizing agents.

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

|| Not classified based on available information.

#### Components:

##### 2-(2-butoxyethoxy)ethanol:

Acute oral toxicity : LD50 (Mouse): 2.410 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 2.764 mg/kg

##### 1,2-benzisothiazol-3(2H)-one:

Acute oral toxicity : LD50 (Rat): 532 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capacryl PU-Satin Basis R

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 17.12.2020  |
| 3.0     | 26.01.2023     | 6004801     | Date of first issue: 01.12.2019 |

Acute inhalation toxicity : LC50 (Rat): 0,4 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

### reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

Acute oral toxicity : LD50 (Rat): 66 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 0,17 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 141 mg/kg  
Method: OECD Test Guideline 402

### Skin corrosion/irritation

|| Not classified based on available information.

### Serious eye damage/eye irritation

|| Not classified based on available information.

### Respiratory or skin sensitization

#### Skin sensitization

|| Not classified based on available information.

#### Respiratory sensitization

|| Not classified based on available information.

### Germ cell mutagenicity

|| Not classified based on available information.

### Carcinogenicity

|| Not classified based on available information.

### Reproductive toxicity

|| Not classified based on available information.

### STOT-single exposure

|| Not classified based on available information.

### STOT-repeated exposure

|| Not classified based on available information.

### Aspiration toxicity

|| Not classified based on available information.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capacryl PU-Satin Basis R

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 17.12.2020  |
| 3.0     | 26.01.2023     | 6004801     | Date of first issue: 01.12.2019 |

### 11.2 Information on other hazards

#### Endocrine disrupting properties

##### Product:

|            |   |   |
|------------|---|---|
| Assessment | : | The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. |
|------------|---|---|

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

##### **1,2-benzisothiazol-3(2H)-one:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2,2 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia): 3,27 mg/l  
aquatic invertebrates : Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : EC50 (Selenastrum capricornutum (green algae)): 0,11 mg/l  
plants : Exposure time: 72 h  
Method: OECD Test Guideline 201

M-Factor (Acute aquatic tox- : 1  
icity)

M-Factor (Chronic aquatic : 1  
toxicity)

##### **reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):**

M-Factor (Acute aquatic tox- : 100  
icity)

M-Factor (Chronic aquatic : 100  
toxicity)

### 12.2 Persistence and degradability

No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capacryl PU-Satin Basis R

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 17.12.2020  |
| 3.0     | 26.01.2023     | 6004801     | Date of first issue: 01.12.2019 |

### 12.3 Bioaccumulative potential

#### Components:

##### **2-(2-butoxyethoxy)ethanol:**

Partition coefficient: n-octanol/water : log Pow: 0,56

##### **reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):**

Partition coefficient: n-octanol/water : log Pow: <= 0,71  
Method: OECD Test Guideline 117

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

#### Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : .

Waste should not be disposed of via wastewater.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capacryl PU-Satin Basis R

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 17.12.2020  |
| 3.0     | 26.01.2023     | 6004801     | Date of first issue: 01.12.2019 |

Contaminated packaging : Only completely emptied containers should be given for recycling.

Waste Code : used product  
080112, waste paint and varnish other than those mentioned  
in 08 01 11\*

### SECTION 14: Transport information

#### 14.1 UN number or ID number

ADN : Not regulated as a dangerous good

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

#### 14.2 UN proper shipping name

ADN : Not regulated as a dangerous good

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

#### 14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

#### 14.4 Packing group

ADN : Not regulated as a dangerous good

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA (Passenger) : Not regulated as a dangerous good

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capacryl PU-Satin Basis R

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 17.12.2020  |
| 3.0     | 26.01.2023     | 6004801     | Date of first issue: 01.12.2019 |

### 14.5 Environmental hazards

Not regulated as a dangerous good

### 14.6 Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Not applicable
- REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59). : This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be generated.
- Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable
- Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable
- REACH - List of substances subject to authorisation (Annex XIV) : None

**Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.** : Not applicable

Water hazard class (Germany) : WGK 1 slightly water endangering  
Classification according to AwSV, Annex 1 (5.2)

Product code for laquers and paints / Giscode : M-LW01 Water-based varnishes



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capacryl PU-Satin Basis R

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 17.12.2020  |
| 3.0     | 26.01.2023     | 6004801     | Date of first issue: 01.12.2019 |

. : BSW30 Coating materials, water-based, containing solvents

Volatile organic compounds : Directive 2004/42/EC  
< 5 %  
< 50 g/l

### Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

### 15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

## SECTION 16: Other information

### Full text of H-Statements

H301 : Toxic if swallowed.  
H302 : Harmful if swallowed.  
H310 : Fatal in contact with skin.  
H314 : Causes severe skin burns and eye damage.  
H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H318 : Causes serious eye damage.  
H319 : Causes serious eye irritation.  
H330 : Fatal if inhaled.  
H351 : Suspected of causing cancer if inhaled.  
H400 : Very toxic to aquatic life.  
H410 : Very toxic to aquatic life with long lasting effects.  
H411 : Toxic to aquatic life with long lasting effects.  
EUH071 : Corrosive to the respiratory tract.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Acute : Short-term (acute) aquatic hazard  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Carc. : Carcinogenicity  
Eye Dam. : Serious eye damage  
Eye Irrit. : Eye irritation  
Skin Corr. : Skin corrosion  
Skin Irrit. : Skin irritation  
Skin Sens. : Skin sensitization  
2006/15/EC : Europe. Indicative occupational exposure limit values  
DE TRGS 527 : Germany. TRGS 527 - Activities with nanomaterials  
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.  
2006/15/EC / TWA : Limit Value - eight hours  
2006/15/EC / STEL : Short term exposure limit  
DE TRGS 527 / BM : Assessment scale

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capacryl PU-Satin Basis R

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 17.12.2020  |
| 3.0     | 26.01.2023     | 6004801     | Date of first issue: 01.12.2019 |

DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

### Sources of key data used to compile the Material Safety Data Sheet:

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs.

Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## Capacryl PU-Satin Basis R

|         |                |             |                                 |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 17.12.2020  |
| 3.0     | 26.01.2023     | 6004801     | Date of first issue: 01.12.2019 |

### REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our up-stream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN