

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



Capalac Holz-Imprägniergrund Farblos

Version	Revision Date:	SDS Number:	Date of last issue: 30.03.2021
1.2	15.05.2024	6005828	Date of first issue: 15.11.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Capalac Holz-Imprägniergrund Farblos

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Wood preservatives

Recommended restrictions : within adequate application - none
on use

1.3 Details of the supplier of the safety data sheet

Company : Caparol Farben Lacke GmbH
Roßdörfer Straße 50
64372 Ober-Ramstadt

Telephone : +496154710
Telefax : +4961547170222

Website :
E-mail address Responsible/issuing person : msds@dr-rmi.com

1.4 Emergency telephone

Emergency telephone 1 : +49613284463 GBK GmbH

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aspiration hazard, Category 1 H304: May be fatal if swallowed and enters airways.

Long-term (chronic) aquatic hazard, Category 3 H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

SAFETY DATA SHEET


according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



Capalac Holz-Imprägniergrund Farblos

Version	Revision Date:	SDS Number:	Date of last issue: 30.03.2021
1.2	15.05.2024	6005828	Date of first issue: 15.11.2019

Hazard pictograms	:	
Signal Word	:	Danger
Hazard Statements	:	H304 May be fatal if swallowed and enters airways. H412 Harmful to aquatic life with long lasting effects.
Supplemental Hazard Statements	:	EUH066 Repeated exposure may cause skin dryness or cracking.
Precautionary Statements	:	P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. Response: P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P331 Do NOT induce vomiting. Storage: P405 Store locked up. Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous ingredients which must be listed on the label:

Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha

Additional Labeling

EUH208 Contains 3-iodo-2-propynyl butylcarbamate. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



Capalac Holz-Imprägniergrund Farblos

Version 1.2 Revision Date: 15.05.2024 SDS Number: 6005828 Date of last issue: 30.03.2021
Date of first issue: 15.11.2019

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha	64742-48-9 265-150-3 649-327-00-6 01-2119457273-39, 01-2119463258-33, 01-2119486659-16	Asp. Tox. 1; H304 EUH066	>= 70 - < 90
3-iodo-2-propynyl butylcarbamate	55406-53-6 259-627-5 616-212-00-7 01-2120762115-60	Acute Tox. 4; H302 Acute Tox. 3; H331 Eye Dam. 1; H318 Skin Sens. 1; H317 STOT RE 1; H372 (larynx) Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1	>= 0,25 - < 1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

- General advice : Never give anything by mouth to an unconscious person.
If you feel unwell, seek medical advice (show the label where possible).
Move out of dangerous area.
First aider needs to protect himself.
- If inhaled : Call a physician.
If breathing is irregular or stopped, administer artificial respiration.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
Move to fresh air.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



Capalac Holz-Imprägniergrund Farblos

Version	Revision Date:	SDS Number:	Date of last issue: 30.03.2021
1.2	15.05.2024	6005828	Date of first issue: 15.11.2019

- In case of skin contact : Do NOT use solvents or thinners.
In case of contact, immediately flush skin with soap and plenty of water.
Take off all contaminated clothing immediately.
- In case of eye contact : If eye irritation persists: Get medical advice/ attention.
IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.
- If swallowed : If accidentally swallowed obtain immediate medical attention.
If swallowed, DO NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : May be fatal if swallowed and enters airways.
Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Risk of serious damage to the lungs (by aspiration).

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
- Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire fighting : Cool closed containers exposed to fire with water spray.
In case of fire hazardous decomposition products may be produced such as:
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

5.3 Advice for firefighters

- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
- Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Standard procedure for chemical fires.
In the event of fire and/or explosion do not breathe fumes.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



Capalac Holz-Imprägniergrund Farblos

Version	Revision Date:	SDS Number:	Date of last issue: 30.03.2021
1.2	15.05.2024	6005828	Date of first issue: 15.11.2019

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Do not get in eyes, on skin, or on clothing.
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
Ensure adequate ventilation.
Remove all sources of ignition.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
Do not flush into surface water or sanitary sewer system.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.
, For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.
Avoid exceeding the given occupational exposure limits (see section 8).
Provide sufficient air exchange and/or exhaust in work rooms.
Keep container closed when not in use.
Do not use for spraying.

In addition, the current technical information for this product and its application on www.caparol.com must be observed.

Advice on protection against fire and explosion : Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hygiene measures : Avoid contact with the skin and the eyes. Wash hands before eating, drinking, or smoking. Do not eat, drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering eating areas.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



Capalac Holz-Imprägniergrund Farblos

Version 1.2 Revision Date: 15.05.2024 SDS Number: 6005828 Date of last issue: 30.03.2021
Date of first issue: 15.11.2019

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Store between 41 and 77 °F in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510) : 10

7.3 Specific end use(s)

Specific use(s) : This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha	64742-48-9	AGW	300 mg/m ³	DE TRGS 900
Peak-limit category: 2;(II)				
Further information: Group exposure limit for hydrocarbon solvent mixtures				
3-iodo-2-propynyl butylcarbamate	55406-53-6	AGW (Vapour and aerosols)	0,005 ppm 0,058 mg/m ³	DE TRGS 900
Peak-limit category: 2;(I)				
Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child, Substance sensitizing through the skin				
		MAK	0,005 ppm 0,058 mg/m ³	DE DFG MAK
Further information: Danger of sensitization of the skin, Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed				

8.2 Exposure controls

Personal protective equipment

Eye/face protection : DGUV Regulation 112-192 - Use of eye and face protection

Goggles

Hand protection

Material : Nitrile rubber
Glove thickness : 0,2 mm
Protective index : Class 3

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



Capalac Holz-Imprägniergrund Farblos

Version	Revision Date:	SDS Number:	Date of last issue: 30.03.2021
1.2	15.05.2024	6005828	Date of first issue: 15.11.2019

- Remarks : Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Before removing gloves clean them with soap and water. Wear suitable gloves tested to EN374.
DGUV Regulation 112-195 - Use of protective gloves
- Skin and body protection : Safety shoes
Remove and wash contaminated clothing before re-use.
Long sleeved clothing
- Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Skin should be washed after contact.
- Remove and wash contaminated clothing before re-use.
- Respiratory protection : Do not use for spraying.
Roller application or brushing: This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.
- During spray application: Do not breathe spray dust. Use A2/P2 combination filter for paint spraying.
- DGUV Regulation 112-190 - Use of breathing equipment

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Physical state : liquid
- Color : colorless
- Odor : No data available
- Odor Threshold : Not relevant
- Melting point/freezing point : not determined
- Boiling point/boiling range : not determined
- Upper explosion limit / Upper : not determined

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



Capalac Holz-Imprägniergrund Farblos

Version	Revision Date:	SDS Number:	Date of last issue: 30.03.2021
1.2	15.05.2024	6005828	Date of first issue: 15.11.2019

flammability limit

Lower explosion limit / Lower
flammability limit : not determined

Flash point : > 61 °C

Autoignition temperature : not determined

Decomposition temperature : Not applicable

pH : 6,95
Concentration: 10 %

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : 1,9 mm²/s (40 °C)

Flow time : < 30 s at 20 °C

Solubility(ies)
Water solubility : partly miscible

Partition coefficient: n-
octanol/water : not determined

Vapor pressure : not determined

Relative density : not determined

Density : 0,83 g/cm³

Relative vapor density : not determined

9.2 Other information

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



Capalac Holz-Imprägniergrund Farblos

Version	Revision Date:	SDS Number:	Date of last issue: 30.03.2021
1.2	15.05.2024	6005828	Date of first issue: 15.11.2019

Explosives : Not applicable

Oxidizing properties : Not applicable

Flammability (liquids) : Sustains combustion

Evaporation rate : Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapors may form explosive mixture with air.
Hazardous decomposition products formed under fire conditions.

10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

10.5 Incompatible materials

Materials to avoid : Incompatible with acids and bases.
Incompatible with oxidizing agents.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



Capalac Holz-Imprägniergrund Farblos

Version	Revision Date:	SDS Number:	Date of last issue: 30.03.2021
1.2	15.05.2024	6005828	Date of first issue: 15.11.2019

Components:

3-iodo-2-propynyl butylcarbamate:

Acute oral toxicity : LD50 (Rat): 500 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0,763 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

Not classified based on available information.

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



Capalac Holz-Imprägniergrund Farblos

Version	Revision Date:	SDS Number:	Date of last issue: 30.03.2021
1.2	15.05.2024	6005828	Date of first issue: 15.11.2019

SECTION 12: Ecological information

12.1 Toxicity

Components:

3-iodo-2-propynyl butylcarbamate:

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 1

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha:

Partition coefficient: n-octanol/water : log Pow: 1,99 - 18,02 (20 °C)
pH: 7

3-iodo-2-propynyl butylcarbamate:

Partition coefficient: n-octanol/water : log Pow: 2,81 (25 °C)

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



Capalac Holz-Imprägniergrund Farblos

Version	Revision Date:	SDS Number:	Date of last issue: 30.03.2021
1.2	15.05.2024	6005828	Date of first issue: 15.11.2019

12.7 Other adverse effects

Product:

Additional ecological information : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : .
Waste should not be disposed of via wastewater.

Contaminated packaging : Only completely emptied containers should be given for recycling.

Waste Code : used product
080111*, waste paint and varnish containing organic solvents or other dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



CAPAROL

Capalac Holz-Imprägniergrund Farblos

Version	Revision Date:	SDS Number:	Date of last issue: 30.03.2021
1.2	15.05.2024	6005828	Date of first issue: 15.11.2019

IATA : Not regulated as a dangerous good

14.4 Packing group

ADN : Not regulated as a dangerous good

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 75, 3

If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59). : None

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : None

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. 34 Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



Capalac Holz-Imprägniergrund Farblos

Version	Revision Date:	SDS Number:	Date of last issue: 30.03.2021
1.2	15.05.2024	6005828	Date of first issue: 15.11.2019

heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Water hazard class (Germany) : WGK 2 obviously hazardous to water

Product code for laquers and paints / Giscode : HSM-LV20 Wood preservatives, preventive, containing solvents, aromatics removed

. : HSL10 solvent-based wood preservatives, aromatics-free

Volatile organic compounds : Volatile organic compounds (VOC) content: 91,5 %, < 750 g/l

Volatile organic compounds : < 92 %
< 750 g/l

15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

15.3 Labeling according to Regulation (EU) 528/2012

EU Registration number : DE-2012-MA-08-00015-ah

Biocidal product type : PT8 - Wood preservatives

Expiry Date : Observe label precautions.

Active substance : 3-iodo-2-propynyl butylcarbamate 7,8 g/l

Use biocides safely. Always read the label and product information before use.

SECTION 16: Other information

Full text of H-Statements

H302 : Harmful if swallowed.

H304 : May be fatal if swallowed and enters airways.

H317 : May cause an allergic skin reaction.

H318 : Causes serious eye damage.

H331 : Toxic if inhaled.

H372 : Causes damage to organs through prolonged or repeated exposure if inhaled.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.

EUH066 : Repeated exposure may cause skin dryness or cracking.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



CAPAROL

Capalac Holz-Imprägniergrund Farblos

Version	Revision Date:	SDS Number:	Date of last issue: 30.03.2021
1.2	15.05.2024	6005828	Date of first issue: 15.11.2019

Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Dam.	:	Serious eye damage
Skin Sens.	:	Skin sensitization
STOT RE	:	Specific target organ toxicity - repeated exposure
DE DFG MAK	:	Germany. MAK BAT Annex IIa
DE TRGS 900	:	Germany. TRGS 900 - Occupational exposure limit values.
DE DFG MAK / MAK	:	MAK value
DE TRGS 900 / AGW	:	Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50% of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC. Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

Sources of key data used to compile the Material Safety Data Sheet : ECHA WebSite
ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation.
2014 ACGIH, Cincinnati OH
NIOSH - Registry of toxic effects of chemical substances
ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities
SAX'S - Dangerous properties of industrial materials
GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)
Toxnet - Toxicology Data Network

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



Capalac Holz-Imprägniergrund Farblos

Version	Revision Date:	SDS Number:	Date of last issue: 30.03.2021
1.2	15.05.2024	6005828	Date of first issue: 15.11.2019

Classification of the mixture:

Asp. Tox. 1	H304
Aquatic Chronic 3	H412

Classification procedure:

Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN