

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Holz-Imprägniergrund Farblos

Version	Revision Date:	Print Date	Date of last issue: 15.11.2019
1.1	30.03.2021	31.03.2021	Date of first issue: 15.11.2019

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Capalac Holz-Imprägniergrund Farblos

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Wood preservatives

Recommended restrictions : within adequate application - none on use

#### 1.3 Details of the supplier of the safety data sheet

Company : Caparol Farben Lacke GmbH  
Roßdörfer Straße 50  
64372 Ober-Ramstadt

Telephone : +496154710  
Telefax : +4961547170222  
E-mail address Responsible/issuing person : msds@dr-rmi.com

#### 1.4 Emergency telephone number

Emergency telephone number 1 : +49613284463 GBK GmbH

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Aspiration hazard, Category 1 H304: May be fatal if swallowed and enters airways.

Long-term (chronic) aquatic hazard, Category 3 H412: Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)


# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Holz-Imprägniergrund Farblos

Version	Revision Date:	Print Date	Date of last issue: 15.11.2019
1.1	30.03.2021	31.03.2021	Date of first issue: 15.11.2019

Hazard pictograms : 

Signal word : Danger

Hazard statements : H304 May be fatal if swallowed and enters airways.  
H412 Harmful to aquatic life with long lasting effects.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements : P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.

**Prevention:**  
P273 Avoid release to the environment.

**Response:**  
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
P331 Do NOT induce vomiting.

**Storage:**  
P405 Store locked up.

### Hazardous components which must be listed on the label:

Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha

### Additional Labelling

EUH208 Contains 3-iodo-2-propynyl butylcarbamate. May produce an allergic reaction.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Holz-Imprägniergrund Farblos

Version 1.1      Revision Date: 30.03.2021      Print Date 31.03.2021      Date of last issue: 15.11.2019  
Date of first issue: 15.11.2019

Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha	64742-48-9 265-150-3 649-327-00-6 01-2119457273-39, 01-2119463258-33, 01-2119486659-16	Asp. Tox. 1; H304	>= 70 - < 90
3-iodo-2-propynyl butylcarbamate	55406-53-6 259-627-5 616-212-00-7 01-2120762115-60	Acute Tox. 4; H302 Acute Tox. 3; H331 Eye Dam. 1; H318 Skin Sens. 1; H317 STOT RE 1; H372 (larynx) Aquatic Acute 1; H400 Aquatic Chronic 1; H410  M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1	>= 0,25 - < 1

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Never give anything by mouth to an unconscious person.  
If you feel unwell, seek medical advice (show the label where possible).  
Move out of dangerous area.  
First aider needs to protect himself.
- If inhaled : Call a physician.  
If breathing is irregular or stopped, administer artificial respiration.  
If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.  
Move to fresh air.
- In case of skin contact : Do NOT use solvents or thinners.  
In case of contact, immediately flush skin with soap and plenty of water.  
Take off all contaminated clothing immediately.
- In case of eye contact : If eye irritation persists: Get medical advice/ attention.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Holz-Imprägniergrund Farblos

Version	Revision Date:	Print Date	Date of last issue: 15.11.2019
1.1	30.03.2021	31.03.2021	Date of first issue: 15.11.2019

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If swallowed : If accidentally swallowed obtain immediate medical attention. If swallowed, DO NOT induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

None known.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Risk of serious damage to the lungs (by aspiration).

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media : None known.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Cool closed containers exposed to fire with water spray. In case of fire hazardous decomposition products may be produced such as:  
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Standard procedure for chemical fires. In the event of fire and/or explosion do not breathe fumes.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Do not get in eyes, on skin, or on clothing.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Holz-Imprägniergrund Farblos

Version	Revision Date:	Print Date	Date of last issue: 15.11.2019
1.1	30.03.2021	31.03.2021	Date of first issue: 15.11.2019

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.  
Ensure adequate ventilation.  
Remove all sources of ignition.

### 6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.  
Do not flush into surface water or sanitary sewer system.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

### 6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.  
,For personal protection see section 8.,For disposal considerations see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Provide sufficient air exchange and/or exhaust in work rooms.  
Keep container closed when not in use.  
Do not use for spraying.

In addition, the current technical information for this product and its application on [www.caparol.com](http://www.caparol.com) must be observed.

Advice on protection against fire and explosion : Vapours are heavier than air and may spread along floors.  
Vapours may form explosive mixtures with air. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hygiene measures : Avoid contact with the skin and the eyes. Wash hands before eating, drinking, or smoking. Do not eat, drink or smoke when using this product.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Store between 5 and 25 °C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Containers which are opened must be

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Holz-Imprägniergrund Farblos

Version 1.1      Revision Date: 30.03.2021      Print Date 31.03.2021      Date of last issue: 15.11.2019  
Date of first issue: 15.11.2019

carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510) : 10, Combustible liquids

### 7.3 Specific end use(s)

Specific use(s) : This information is not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha	64742-48-9	AGW	300 mg/m <sup>3</sup>	DE TRGS 900
Peak-limit: excursion factor (category): 2;(II)				
Further information: See also No. 2.9 of the TRGS 900, Commission for dangerous substances, Group exposure limit for hydrocarbon solvent mixtures				
3-iodo-2-propynyl butylcarbamate	55406-53-6	AGW (Vapour and aerosols)	0,005 ppm 0,058 mg/m <sup>3</sup>	DE TRGS 900
Peak-limit: excursion factor (category): 2;(I)				
Further information: Substance sensitizing through the skin, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child, Sum of vapor and aerosols., Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).				

### 8.2 Exposure controls

#### Personal protective equipment

Eye protection : German trade association rules - BGR 192 Eye protection

Goggles

Hand protection

Material : Nitrile rubber  
Glove thickness : 0,2 mm  
Protective index : Class 3

Remarks : Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Before removing gloves clean them with soap and water. Wear suitable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Holz-Imprägniergrund Farblos

Version	Revision Date:	Print Date	Date of last issue: 15.11.2019
1.1	30.03.2021	31.03.2021	Date of first issue: 15.11.2019

- ble gloves tested to EN374.  
German trade association leaflet: Carry gloves (ZH 1/706)
- Skin and body protection** : Safety shoes  
Remove and wash contaminated clothing before re-use.  
Long sleeved clothing
- Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Skin should be washed after contact.
- Remove and wash contaminated clothing before re-use.
- Respiratory protection** : Do not use for spraying.  
Roller application or brushing: This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.
- German trade association rules - BGR 190 Breathing protection
- During spray application: Do not breathe spray dust. Use A2/P2 combination filter for paint spraying.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Appearance : liquid
- Colour : colourless
- Odour : No data available
- Odour Threshold : Not relevant
- pH : 6,95  
Concentration: 10 %
- Melting point/freezing point : not determined
- Boiling point/boiling range : not determined
- Flash point : > 61 °C
- Evaporation rate : Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Holz-Imprägniergrund Farblos

Version	Revision Date:	Print Date	Date of last issue: 15.11.2019
1.1	30.03.2021	31.03.2021	Date of first issue: 15.11.2019

Upper explosion limit / Upper flammability limit : not determined

Lower explosion limit / Lower flammability limit : not determined

Vapour pressure : not determined

Relative vapour density : not determined

Relative density : not determined

Density : 0,83 g/cm<sup>3</sup>

Solubility(ies)  
Water solubility : insoluble

Partition coefficient: n-octanol/water : not determined

Auto-ignition temperature : not determined

Decomposition temperature : Not applicable

Viscosity  
Viscosity, dynamic : No data available

Viscosity, kinematic : 1,9 mm<sup>2</sup>/s (40 °C)

Flow time : < 30 s at 20 °C

Explosive properties : Not applicable

Oxidizing properties : Not applicable

### 9.2 Other information

Flammability (liquids) : Sustains combustion

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form explosive mixture with air.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Holz-Imprägniergrund Farblos

Version	Revision Date:	Print Date	Date of last issue: 15.11.2019
1.1	30.03.2021	31.03.2021	Date of first issue: 15.11.2019

Hazardous decomposition products formed under fire conditions.

### 10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

### 10.5 Incompatible materials

Materials to avoid : Incompatible with acids and bases.  
Incompatible with oxidizing agents.

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

##### Product:

Acute oral toxicity : Remarks: Based on available data, the classification criteria are not met.

Acute inhalation toxicity : Remarks: Based on available data, the classification criteria are not met.

Acute toxicity estimate: > 5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Calculation method

Acute dermal toxicity : Remarks: Based on available data, the classification criteria are not met.

##### Components:

#### 3-iodo-2-propynyl butylcarbamate:

Acute oral toxicity : LD50 (Rat): 500 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0,763 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Holz-Imprägniergrund Farblos

Version	Revision Date:	Print Date	Date of last issue: 15.11.2019
1.1	30.03.2021	31.03.2021	Date of first issue: 15.11.2019

### Skin corrosion/irritation

**Product:**

Remarks : May cause skin irritation in susceptible persons.

### Serious eye damage/eye irritation

**Product:**

Remarks : According to the classification criteria of the European Union, the product is not considered as being an eye irritant.

### Respiratory or skin sensitisation

**Product:**

Remarks : Repeated contact may cause allergic reactions in very susceptible persons.

## SECTION 12: Ecological information

### 12.1 Toxicity

**Product:**

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

**Components:**

**3-iodo-2-propynyl butylcarbamate:**

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 1

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Holz-Imprägniergrund Farblos

Version	Revision Date:	Print Date	Date of last issue: 15.11.2019
1.1	30.03.2021	31.03.2021	Date of first issue: 15.11.2019

### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Other adverse effects

**Product:**

Additional ecological information : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : .  
Waste should not be disposed of via wastewater.

Contaminated packaging : Only completely emptied containers should be given for recycling.

Waste Code : used product  
080111\*, waste paint and varnish containing organic solvents or other dangerous substances

## SECTION 14: Transport information

### 14.1 UN number

Not regulated as a dangerous good

### 14.2 UN proper shipping name

Not regulated as a dangerous good

### 14.3 Transport hazard class(es)

Not regulated as a dangerous good

### 14.4 Packing group

Not regulated as a dangerous good

### 14.5 Environmental hazards

Not regulated as a dangerous good

### 14.6 Special precautions for user

Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Holz-Imprägniergrund Farblos

Version	Revision Date:	Print Date	Date of last issue: 15.11.2019
1.1	30.03.2021	31.03.2021	Date of first issue: 15.11.2019

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be generated.

REACH - List of substances subject to authorisation (Annex XIV) : None

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.  
34

Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Water contaminating class : 2 significantly water endangering (Germany)

Product code for laquers and paints / Giscode : HSM-LV20 Wood preservatives, preventive, containing solvents, aromatics removed

. : HSL17 Wood preservatives, containing solvents, aromatics-free, sensitising

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Holz-Imprägniergrund Farblos

Version	Revision Date:	Print Date	Date of last issue: 15.11.2019
1.1	30.03.2021	31.03.2021	Date of first issue: 15.11.2019

Volatile organic compounds : < 92 %  
< 750 g/l

### 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

### 15.3 Labeling according to Regulation (EU) 528/2012

EU-Registration number : DE-2012-MA-08-00015-ah

Biocidal product type : 8 - Wood preservatives  
Expiry Date : Observe label precautions.

Active substance : 3-iodo-2-propynyl butylcarbamate 7,8 g/l

Use biocides safely. Always read the label and product information before use.

## SECTION 16: Other information

### Full text of H-Statements

H302 : Harmful if swallowed.  
H304 : May be fatal if swallowed and enters airways.  
H317 : May cause an allergic skin reaction.  
H318 : Causes serious eye damage.  
H331 : Toxic if inhaled.  
H372 : Causes damage to organs through prolonged or repeated exposure.

H400 : Very toxic to aquatic life.  
H410 : Very toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Acute : Short-term (acute) aquatic hazard  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Asp. Tox. : Aspiration hazard  
Eye Dam. : Serious eye damage  
Skin Sens. : Skin sensitisation  
STOT RE : Specific target organ toxicity - repeated exposure  
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.  
DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECS - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concen-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Holz-Imprägniergrund Farblos

Version	Revision Date:	Print Date	Date of last issue: 15.11.2019
1.1	30.03.2021	31.03.2021	Date of first issue: 15.11.2019

tration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### **Other information:**

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

#### **Sources of key data used to compile the Safety Data Sheet:**

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs.

Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

#### **Classification of the mixture:**

Asp. Tox. 1                      H304

Aquatic Chronic 3              H412

#### **Classification procedure:**

Calculation method

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Holz-Imprägniergrund Farblos

Version	Revision Date:	Print Date	Date of last issue: 15.11.2019
1.1	30.03.2021	31.03.2021	Date of first issue: 15.11.2019

---

### REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our up-stream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN