

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Capalac Vario

Version	Revision Date:	Print Date	Date of last issue: -
1.0	10.09.2019	11.09.2019	Date of first issue: 10.09.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Capalac Vario

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Spray paint

Recommended restrictions : within adequate application - none
on use

1.3 Details of the supplier of the safety data sheet

Company : Caparol Farben Lacke GmbH
Roßdörfer Straße 50
64372 Ober-Ramstadt

Telephone : +496154710
Telefax : +4961547170222
E-mail address Responsible/issuing person : msds@dr-rmi.com

1.4 Emergency telephone number

Emergency telephone number 1 : +49613284463 GBK GmbH

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Capalac Vario

Version 1.0 Revision Date: 10.09.2019 Print Date 11.09.2019 Date of last issue: -
Date of first issue: 10.09.2019

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements : P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe vapours/ spray.
P271 Use only outdoors or in a well-ventilated area.

Storage:

P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

acetone
butan-1-ol

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
acetone	67-64-1 200-662-2 606-001-00-8 01-2119471330-49	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066	>= 30 - < 50
xylene	1330-20-7	Flam. Liq. 3; H226	>= 1 - < 10

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Capalac Vario

Version 1.0 Revision Date: 10.09.2019 Print Date 11.09.2019 Date of last issue: -
Date of first issue: 10.09.2019

	215-535-7 601-022-00-9 01-2119488216-32	Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 Asp. Tox. 1; H304 STOT RE 2; H373	
butan-1-ol	71-36-3 200-751-6 603-004-00-6 01-2119484630-38	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H336 STOT SE 3; H335	>= 1 - < 3
Substances with a workplace exposure limit :			
dimethyl ether	115-10-6 204-065-8 603-019-00-8 01-2119472128-37	Flam. Gas 1; H220 Press. Gas C; H280	>= 50 - < 70

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : First aider needs to protect himself.
Move out of dangerous area.
If you feel unwell, seek medical advice (show the label where possible).
Never give anything by mouth to an unconscious person.
- If inhaled : Move to fresh air.
If symptoms persist, call a physician.
- In case of skin contact : Take off all contaminated clothing immediately.
In case of contact, immediately flush skin with soap and plenty of water.
Do NOT use solvents or thinners.
- In case of eye contact : IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/ attention.
- If swallowed : If swallowed, DO NOT induce vomiting.
Clean mouth with water and drink afterwards plenty of water.
Seek medical advice.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Capalac Vario

Version	Revision Date:	Print Date	Date of last issue: -
1.0	10.09.2019	11.09.2019	Date of first issue: 10.09.2019

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : In case of fire hazardous decomposition products may be produced such as:
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).
Cool closed containers exposed to fire with water spray.

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : In the event of fire and/or explosion do not breathe fumes.
Standard procedure for chemical fires.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.
Ensure adequate ventilation.
Do not get in eyes, on skin, or on clothing.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.
Prevent further leakage or spillage if safe to do so.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8., For further information see Section 7 of the safety data sheet.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Capalac Vario

Version	Revision Date:	Print Date	Date of last issue: -
1.0	10.09.2019	11.09.2019	Date of first issue: 10.09.2019

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Provide sufficient air exchange and/or exhaust in work rooms. Avoid exceeding the given occupational exposure limits (see section 8).
For personal protection see section 8.
- Advice on protection against fire and explosion : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands before eating, drinking, or smoking. Avoid contact with the skin and the eyes.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store between 5 and 25 °C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Store in original container. Store in accordance with the particular national regulations.

Store between 5 and 25 °C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Store in accordance with the particular national regulations.

- Storage class (TRGS 510) : 2B, Aerosol cans and lighters

7.3 Specific end use(s)

- Specific use(s) : Please follow the technical information.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
dimethyl ether	115-10-6	TWA	1.000 ppm 1.920 mg/m ³	2000/39/EC
Further information	Indicative			
		AGW	1.000 ppm 1.900 mg/m ³	DE TRGS 900
Peak-limit: excursion factor (category)	8;(II)			
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., European Union (The EU has established a limit value: deviations in value and peak limit are possible)			
acetone	67-64-1	TWA	500 ppm 1.210 mg/m ³	2000/39/EC

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Capalac Vario

Version 1.0 Revision Date: 10.09.2019 Print Date 11.09.2019 Date of last issue: -
Date of first issue: 10.09.2019

Further information	Indicative			
		AGW	500 ppm 1.200 mg/m ³	DE TRGS 900
Peak-limit: excursion factor (category)	2;(I)			
Further information	Commission for dangerous substances, Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission), European Union (The EU has established a limit value: deviations in value and peak limit are possible), When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
xylene	1330-20-7	TWA	50 ppm 221 mg/m ³	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m ³	2000/39/EC
		AGW	100 ppm 440 mg/m ³	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)			
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission), European Union (The EU has established a limit value: deviations in value and peak limit are possible), Skin absorption			
butan-1-ol	71-36-3	AGW	100 ppm 310 mg/m ³	DE TRGS 900
Peak-limit: excursion factor (category)	1;(I)			
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission), When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
acetone	67-64-1	Acetone: 80 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903
xylene	1330-20-7	xylene: 1,5 mg/l (Blood)	Immediately after exposure or after working hours	TRGS 903
		methylhippuric acid (all isomers): 2 g/l (Urine)	Immediately after exposure or after working hours	TRGS 903
butan-1-ol	71-36-3	1-butanol: 2 mg/g Creatinine (Urine)	Before next shift	TRGS 903
		1-butanol: 10 mg/g Creatinine (Urine)	Immediately after exposure or after working hours	TRGS 903

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
dimethyl ether	Consumers	Inhalation	Long-term systemic	471,00 mg/m ³

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Capalac Vario

Version
1.0

Revision Date:
10.09.2019

Print Date
11.09.2019

Date of last issue: -
Date of first issue: 10.09.2019

			effects	
	Workers	Inhalation	Long-term systemic effects	1894,00 mg/m ³
acetone	Consumers	Inhalation	Long-term systemic effects	200,00 mg/m ³
	Consumers	Ingestion	Long-term systemic effects	62,00 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	62,00 mg/kg bw/day
	Workers	Inhalation	Acute local effects	2420,00 mg/m ³
	Workers	Inhalation	Long-term systemic effects	1210,00 mg/m ³
	Workers	Skin contact	Long-term systemic effects	186,00 mg/kg bw/day
xylene	Consumers	Inhalation	Acute local effects	174,00 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	108,00 mg/kg bw/day
	Consumers	Inhalation	Acute systemic effects	174,00 mg/m ³
	Consumers	Ingestion	Long-term systemic effects	1,60 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	14,80 mg/m ³
	Workers	Inhalation	Acute systemic effects	289,00 mg/m ³
	Workers	Inhalation	Acute local effects	289,00 mg/m ³
	Workers	Inhalation	Long-term systemic effects	77,00 mg/m ³
	Workers	Skin contact	Long-term systemic effects	180,00 mg/kg bw/day
butan-1-ol	Consumers	Inhalation	Long-term local effects	55,00 mg/m ³
	Consumers	Ingestion	Long-term systemic effects	3,13 mg/kg bw/day
	Workers	Inhalation	Long-term local effects	310,00 mg/m ³

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
dimethyl ether	Marine sediment	0,069 mg/kg dry weight (d.w.)
	Intermittent use/release	1,549 mg/l
	Marine water	0,016 mg/l
	Fresh water	0,155 mg/l
	Sewage treatment plant	160 mg/l
	Fresh water sediment	0,681 mg/kg dry weight (d.w.)
	Soil	0,045 mg/kg dry weight (d.w.)
acetone	Fresh water sediment	30,4 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 mg/l
	Marine sediment	3,04 mg/kg dry weight (d.w.)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Capalac Vario

Version
1.0

Revision Date:
10.09.2019

Print Date
11.09.2019

Date of last issue: -
Date of first issue: 10.09.2019

	Fresh water	10,6 mg/l
	Marine water	1,06 mg/l
	Intermittent use/release	21 mg/l
	Soil	29,5 mg/kg dry weight (d.w.)
xylene	Fresh water	0,327 mg/l
	Intermittent use/release	0,327 mg/l
	Soil	2,31 mg/kg dry weight (d.w.)
	Fresh water sediment	12,46 mg/kg dry weight (d.w.)
	Sewage treatment plant	6,58 mg/l
	Marine water	0,327 mg/l
	Marine sediment	12,46 mg/kg dry weight (d.w.)
butan-1-ol	Sewage treatment plant	2476 mg/l
	Fresh water	0,082 mg/l
	Intermittent use/release	2,25 mg/l
	Fresh water sediment	0,178 mg/kg dry weight (d.w.)
	Marine water	0,0082 mg/l
	Marine sediment	0,0178 mg/kg dry weight (d.w.)
	Soil	0,015 mg/kg dry weight (d.w.)

8.2 Exposure controls

Personal protective equipment

Eye protection : German trade association rules - BGR 192 Eye protection

Tightly fitting safety goggles

Hand protection

Material : Nitrile rubber
Glove thickness : 0,2 mm
Protective index : Class 3

Remarks : Wear suitable gloves tested to EN374. Before removing gloves clean them with soap and water. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
German trade association leaflet: Carry gloves (ZH 1/706)

Skin and body protection : Long sleeved clothing
Safety shoes

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

During spray application: impervious clothing

Respiratory protection : German trade association rules - BGR 190 Breathing protec-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Capalac Vario

Version 1.0	Revision Date: 10.09.2019	Print Date 11.09.2019	Date of last issue: - Date of first issue: 10.09.2019
----------------	------------------------------	--------------------------	--

tion

During spray application: Do not breathe spray dust. Use A2/P2 combination filter for paint spraying.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	aerosol
Colour	:	No data available
Odour	:	No data available
Odour Threshold	:	Not relevant
pH	:	not determined
Melting point/freezing point	:	not determined
Boiling point/boiling range	:	not determined
Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Sustains combustion
Upper explosion limit / Upper flammability limit	:	26,2 %(V)
Lower explosion limit / Lower flammability limit	:	2,6 %(V)
Vapour pressure	:	4.000 hPa (20 °C)
Relative vapour density	:	not determined
Relative density	:	not determined
Density	:	0,73 g/cm ³ (20 °C)
Solubility(ies) Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	not determined
Auto-ignition temperature	:	240 °C
Decomposition temperature	:	Not applicable
Viscosity Viscosity, dynamic	:	No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Capalac Vario

Version	Revision Date:	Print Date	Date of last issue: -
1.0	10.09.2019	11.09.2019	Date of first issue: 10.09.2019

Explosive properties : Not applicable

Oxidizing properties : Not applicable

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Hazardous decomposition products formed under fire conditions.
Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.
Risk of bursting.

Risk of bursting.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

10.5 Incompatible materials

Materials to avoid : Incompatible with oxidizing agents.
Incompatible with acids and bases.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Remarks: Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Capalac Vario

Version 1.0	Revision Date: 10.09.2019	Print Date 11.09.2019	Date of last issue: - Date of first issue: 10.09.2019
----------------	------------------------------	--------------------------	--

Acute inhalation toxicity : Acute toxicity estimate: > 20000 ppm
Exposure time: 4 h
Test atmosphere: gas
Method: Calculation method

Remarks: Based on available data, the classification criteria are not met.

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Remarks: Based on available data, the classification criteria are not met.

Components:

acetone:

Acute oral toxicity : LD50 Oral (Rat): 5.800 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 20.000 mg/kg

xylene:

Acute inhalation toxicity : LC50 (Rat): 5000 ppm
Exposure time: 4 h
Test atmosphere: gas

butan-1-ol:

Acute oral toxicity : LD50 (Rat): 790 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 3.430 mg/kg

Skin corrosion/irritation

Product:

Remarks : May cause skin irritation in susceptible persons.

Serious eye damage/eye irritation

Product:

Remarks : According to the classification criteria of the European Union, the product is not considered as being an eye irritant.

Respiratory or skin sensitisation

Product:

Remarks : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Capalac Vario

Version	Revision Date:	Print Date	Date of last issue: -
1.0	10.09.2019	11.09.2019	Date of first issue: 10.09.2019

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

acetone:

Partition coefficient: n-octanol/water : log Pow: -0,24 (20 °C)

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : .
Waste should not be disposed of via wastewater.

Contaminated packaging : Only completely emptied containers should be given for recycling.

Waste Code : used product
080111*, waste paint and varnish containing organic solvents or other dangerous substances

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Capalac Vario

Version	Revision Date:	Print Date	Date of last issue: -
1.0	10.09.2019	11.09.2019	Date of first issue: 10.09.2019

SECTION 14: Transport information

14.1 UN number

ADN	:	UN 1950
ADR	:	UN 1950
RID	:	UN 1950
IMDG	:	UN 1950
IATA	:	UN 1950

14.2 UN proper shipping name

ADN	:	AEROSOLS
ADR	:	AEROSOLS
RID	:	AEROSOLS
IMDG	:	AEROSOLS
IATA	:	Aerosols, flammable

14.3 Transport hazard class(es)

ADN	:	2
ADR	:	2
RID	:	2
IMDG	:	2.1
IATA	:	2.1

14.4 Packing group

ADN		
Packing group	:	Not assigned by regulation
Classification Code	:	5F
Labels	:	2.1

ADR		
Packing group	:	Not assigned by regulation
Classification Code	:	5F
Labels	:	2.1
Tunnel restriction code	:	(D)

RID		
Packing group	:	Not assigned by regulation
Classification Code	:	5F
Hazard Identification Number	:	23
Labels	:	2.1

IMDG		
Packing group	:	Not assigned by regulation
Labels	:	2.1
EmS Code	:	F-D, S-U

IATA (Cargo)		
Packing instruction (cargo aircraft)	:	203

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Capalac Vario

Version	Revision Date:	Print Date	Date of last issue: -
1.0	10.09.2019	11.09.2019	Date of first issue: 10.09.2019

Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Division 2.1 - Flammable gases

IATA_P (Passenger)

Packing instruction (passenger aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Division 2.1 - Flammable gases

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be generated.

REACH - List of substances subject to authorisation (Annex XIV) : None

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P3a FLAMMABLE AEROSOLS

Water contaminating class : 1 slightly water endangering

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Capalac Vario

Version	Revision Date:	Print Date	Date of last issue: -
1.0	10.09.2019	11.09.2019	Date of first issue: 10.09.2019

(Germany) Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : < 100 %
< 720 g/l

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

EUH066	: Repeated exposure may cause skin dryness or cracking.
H220	: Extremely flammable gas.
H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H280	: Contains gas under pressure; may explode if heated.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H373	: May cause damage to organs through prolonged or repeated exposure.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Asp. Tox.	: Aspiration hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Gas	: Flammable gases
Flam. Liq.	: Flammable liquids
Press. Gas	: Gases under pressure
Skin Irrit.	: Skin irritation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
DE TRGS 900	: Germany. TRGS 900 - Occupational exposure limit values.
TRGS 903	: TRGS 903 - Biological limit values
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
DE TRGS 900 / AGW	: Time Weighted Average

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Capalac Vario

Version	Revision Date:	Print Date	Date of last issue: -
1.0	10.09.2019	11.09.2019	Date of first issue: 10.09.2019

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Aerosol 1	H222, H229
Eye Irrit. 2	H319
STOT SE 3	H336

Classification procedure:

Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly. This will be put into practice depending on the register-deadline of the substances involved during the transition period from December 1, 2010 till May 31, 2018.

DE / EN