according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Capalac Aqua Metallschutz Basis T

Version Revision Date: SDS Number: Date of last issue: 16.02.2022 2.0 06.09.2023 6007260 Date of first issue: 11.11.2019

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Capalac Aqua Metallschutz Basis T

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Water-borne coatings

stance/Mixture

Recommended restrictions

on use

within adequate application - none

1.3 Details of the supplier of the safety data sheet

Company : Caparol Farben Lacke GmbH

Roßdörfer Straße 50 64372 Ober-Ramstadt

Telephone : +496154710 Telefax : +4961547170222

Website

E-mail address Responsi-

ble/issuing person

msds@dr-rmi.com

1.4 Emergency telephone

Emergency telephone 1 : +49613284463 GBK GmbH

#### **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Skin sensitization, Category 1 H317: May cause an allergic skin reaction.

Long-term (chronic) aquatic hazard, Cat-H411: Toxic to aquatic life with long lasting effects.

egory 2

## 2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Capalac Aqua Metallschutz Basis T

Version Revision Date: SDS Number: Date of last issue: 16.02.2022 2.0 06.09.2023 6007260 Date of first issue: 11.11.2019

Hazard pictograms :





Signal Word : Warning

Hazard Statements : H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements : P101 If medical advice is needed, have product container or

label at hand.

P102 Keep out of reach of children.

**Prevention:** 

P262 Do not get in eyes, on skin, or on clothing.

P273 Avoid release to the environment.P280 Wear protective gloves/ eye protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and

water.

#### Hazardous ingredients which must be listed on the label:

1,2-benzisothiazol-3(2H)-one

2-methylisothiazol-3(2H)-one

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

#### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Chemical nature : Polyacrylate-based lacquer, aqueous

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

**Capalac Aqua Metallschutz Basis T** 

SDS Number: Version Revision Date: Date of last issue: 16.02.2022 2.0 06.09.2023 6007260 Date of first issue: 11.11.2019

Components			
Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
trizinc bis(orthophosphate)	7779-90-0 231-944-3 030-011-00-6 01-2119485044-40	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 2,5 - < 10
2-butoxyethanol	111-76-2 203-905-0 603-014-00-0 01-2119475108-36	Acute Tox. 4; H302 Acute Tox. 3; H331 Skin Irrit. 2; H315 Eye Irrit. 2; H319  Acute toxicity estimate  Acute oral toxicity: 1.200 mg/kg Acute inhalation toxicity (vapor): 3 mg/l	>= 1 - < 10
zinc oxide	1314-13-2 215-222-5 030-013-00-7 01-2119463881-32, 01-2120089607-43, 01-2120767291-53	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 1 - < 2,5
zinc 5-nitroisophthalate	60580-61-2 262-309-9 01-2120768444-47	Aquatic Acute 1; H400 Aquatic Chronic 2; H411	>= 0,25 - < 1
ammonia	1336-21-6 215-647-6 007-001-01-2 01-2119488876-14	Skin Corr. 1B; H314 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 ——————————————————————————————————	>= 0,1 - < 0,25
1,2-benzisothiazol-3(2H)-one	2634-33-5 220-120-9 613-088-00-6 01-2120761540-60	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2;	>= 0,025 - < 0,05

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Capalac Aqua Metallschutz Basis T					
Version	Revision Date:	SDS Number:	Date of last issue: 16.02.2022		
2.0	06.09.2023	6007260	Date of first issue: 11.11.2019		

		H411 Acute Tox. 2; H330  M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1  specific concentration limit Skin Sens. 1; H317 >= 0,05 %	
2-methylisothiazol-3(2H)-one	2682-20-4 220-239-6 613-326-00-9 01-2120764690-50	Acute Tox. 2; H330 Acute Tox. 3; H311 Acute Tox. 3; H301 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071  M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1  specific concentration limit Skin Sens. 1A; H317 >= 0,0015 %	>= 0,0025 - < 0,025
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9 613-167-00-5 01-2120764691-48	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071	>= 0,0002 - < 0,0015

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

rsion )	Revision Date: 06.09.2023	SDS Number: 6007260	Date of last issue: 16.02.2022 Date of first issue: 11.11.2019	
			M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100  specific concentration limit Skin Corr. 1C; H314 >= 0,6 % Skin Irrit. 2; H315 0,06 - < 0,6 % Eye Irrit. 2; H319 0,06 - < 0,6 % Skin Sens. 1A; H317 >= 0,0015 % Eye Dam. 1; H318 >= 0,6 %	
	ances with a workpla			
Talc (I	Mg3H2(SiO3)4)	14807-96-6 238-877-9 01-21201402	>= 1 - <	10

For explanation of abbreviations see section 16.

#### **SECTION 4: First aid measures**

## 4.1 Description of first-aid measures

General advice : Never give anything by mouth to an unconscious person.

If you feel unwell, seek medical advice (show the label where

possible).

Move out of dangerous area. First aider needs to protect himself.

If inhaled : Move to fresh air.

In case of skin contact : Do NOT use solvents or thinners.

In case of contact, immediately flush skin with soap and plenty

of water.

In case of eye contact : If eye irritation persists: Get medical advice/ attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Capalac Aqua Metallschutz Basis T

Version Revision Date: SDS Number: Date of last issue: 16.02.2022 2.0 06.09.2023 6007260 Date of first issue: 11.11.2019

If swallowed : Seek medical advice.

Clean mouth with water and drink afterwards plenty of water.

If swallowed, DO NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Risks : May cause an allergic skin reaction.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

## **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or car-

bon dioxide.

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Do not use a solid water stream as it may scatter and spread

fire.

Unsuitable extinguishing

media

None known.

## 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire

fighting

In case of fire hazardous decomposition products may be

produced such as:

Carbon monoxide, carbon dioxide and unburned hydrocar-

bons (smoke).

#### 5.3 Advice for firefighters

Special protective equipment:

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

Further information : Standard procedure for chemical fires.

The product itself does not burn.

## **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use protective shoes or boots with rough rubber sole.

Material can create slippery conditions. Do not get in eyes, on skin, or on clothing.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Capalac Aqua Metallschutz Basis T

Version Revision Date: SDS Number: Date of last issue: 16.02.2022 2.0 06.09.2023 6007260 Date of first issue: 11.11.2019

### 6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Do not flush into surface water or sanitary sewer system.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

#### 6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.

, For personal protection see section 8., For disposal considerations see section 13.

## **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.

No special technical protective measures required.

In addition, the current technical information for this product and its application on www.caparol.com must be observed.

Hygiene measures : Wash hands before eating, drinking, or smoking. Do not eat,

drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering eating

areas.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Perishable if frozen. To maintain product quality, do not store in heat or direct sunlight. Store at room temperature in the original container. Containers which are opened must be care-

fully resealed and kept upright to prevent leakage.

Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline

materials.

Storage class (TRGS 510) : 12

#### 7.3 Specific end use(s)

Specific use(s) : This information is not available.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

# Capalac Aqua Metallschutz Basis T

Version Revision Date: SDS Number: Date of last issue: 16.02.2022 2.0 06.09.2023 6007260 Date of first issue: 11.11.2019

# **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

## **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis	
Talc	14807-96-6	AGW (Inhalable	10 mg/m3	DE TRGS	
(Mg3H2(SiO3)4)		fraction)		900	
	Peak-limit cat	egory: 2;(II)			
	Further inform	nation: When there is	compliance with the OEL ar	nd biological	
	tolerance valu	ies, there is no risk c	of harming the unborn child		
		AGW (Alveolate	1,25 mg/m3	DE TRGS	
		fraction)		900	
	Peak-limit cat	egory: 2;(II)			
	Further inform	nation: When there is	compliance with the OEL ar	nd biological	
	tolerance valu	ies, there is no risk o	of harming the unborn child	_	
		BM (Alveolar	0,5 mg/m3	DE TRGS	
		dust fraction)	_	527	
2-butoxyethanol	111-76-2	TWA	20 ppm	2000/39/EC	
			98 mg/m3		
	Further inform skin, Indicativ		possibility of significant uptak	e through the	
	,	STEL	50 ppm	2000/39/EC	
			246 mg/m3		
	Further information: Identifies the possibility of significant uptake through the skin, Indicative				
		AGW	10 ppm	DE TRGS	
		49 mg/m3 900			
	Peak-limit category: 2;(I)				
	Further information: Skin absorption, When there is compliance with the OEL				
	and biological tolerance values, there is no risk of harming the unborn child				

## **Biological occupational exposure limits**

Substance name	CAS-No.	Control parameters	Sampling time	Basis
2-butoxyethanol	111-76-2	butoxy acetic acid: 150 mg/g creati- nine (Urine)	In case of long- term exposure: after more than one shift, Immedi- ately after expo- sure or after work- ing hours	TRGS 903

# Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of expo- sure	Potential health effects	Value
trizinc bis(orthophosphate)	Consumers	Ingestion	Long-term systemic effects	0,83 mg/kg bw/day

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

# **Capalac Aqua Metallschutz Basis T**

VersionRevision Date:SDS Number:Date of last issue: 16.02.20222.006.09.20236007260Date of first issue: 11.11.2019

	Consumers	Skin contact	Long-term systemic effects	83,00 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	2,50 mg/m3
	Workers	Inhalation	Long-term systemic effects	5,00 mg/m3
	Workers	Skin contact	Long-term systemic effects	83,00 mg/kg bw/day
2-butoxyethanol	Consumers	Inhalation	Long-term systemic effects	59,00 mg/m3
	Consumers	Ingestion	Acute systemic effects	26,70 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	75,00 mg/kg bw/day
	Consumers	Skin contact	Acute systemic ef- fects	89,00 mg/kg bw/day
	Consumers	Inhalation	Acute local effects	147,00 mg/m3
	Consumers	Ingestion	Long-term systemic effects	6,30 mg/kg bw/day
	Consumers	Inhalation	Acute systemic effects	426,00 mg/m3
	Workers	Inhalation	Acute systemic effects	1091,00 mg/m3
	Workers	Inhalation	Acute local effects	246,00 mg/m3
	Workers	Inhalation	Long-term systemic effects	98,00 mg/m3
	Workers	Skin contact	Acute systemic effects	89,00 mg/kg bw/day
	Workers	Skin contact	Long-term systemic effects	125,00 mg/kg bw/day
isobutyric acid, mo- noester with 2,2,4- trimethylpentane-1,3- diol	Consumers	Inhalation	Long-term systemic effects	14,50 mg/m3
	Consumers	Ingestion	Long-term systemic effects	8,33 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	8,33 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	49,00 mg/m3
	Workers	Skin contact	Long-term systemic effects	13,90 mg/kg bw/day
zinc oxide	Consumers	Skin contact	Long-term systemic effects	83,00 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	2,50 mg/m3
	Consumers	Ingestion	Long-term systemic effects	0,83 mg/kg bw/day

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

# **Capalac Aqua Metallschutz Basis T**

Version Revision Date: SDS Number: Date of last issue: 16.02.2022 2.0 06.09.2023 6007260 Date of first issue: 11.11.2019

Workers	Skin contact	Long-term systemic effects	83,00 mg/kg bw/day
Workers	Inhalation	Long-term local ef- fects	0,50 mg/m3
Workers	Inhalation	Long-term systemic effects	5,00 mg/m3

# Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment Value	
glass, oxide, chemicals	Fresh water sediment	174 mg/kg dry
		weight (d.w.)
	Secondary Poisoning	10,9 mg/kg food
	Sea water	3,4 µg/l
	Sewage treatment plant	100 μg/l
	Sea sediment	164 mg/kg dry
		weight (d.w.)
	Soil	147 mg/kg dry
		weight (d.w.)
	Fresh water	6,5 μg/l
trizinc bis(orthophosphate)	Sea sediment	56,5 mg/kg dry
		weight (d.w.)
	Fresh water	20,6 μg/l
	Soil	35,6 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	100 μg/l
	Fresh water sediment	117,8 mg/kg dry
		weight (d.w.)
	Sea water	6,1 µg/l
2-butoxyethanol	Sea sediment	3,46 mg/kg dry
		weight (d.w.)
	Intermittent use/release	9,1 mg/l
	Secondary Poisoning	0,02 g/kg food
	Sewage treatment plant	463 mg/l
	Sea water	0,88 mg/l
	Fresh water sediment	34,6 mg/kg dry
		weight (d.w.)
	Soil	2,33 mg/kg dry
		weight (d.w.)
	Fresh water	8,8 mg/l
isobutyric acid, monoester with	Fresh water sediment	0,78 mg/kg dry
2,2,4-trimethylpentane-1,3-diol		weight (d.w.)
	Sea water	0,0015 mg/l
	Sea sediment	0,078 mg/kg dry
		weight (d.w.)
	Soil	0,147 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	7,5 mg/l
	Secondary Poisoning	66,7 mg/kg food

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Capalac Aqua Metallschutz Basis T

Version Revision Date: SDS Number: Date of last issue: 16.02.2022 2.0 06.09.2023 6007260 Date of first issue: 11.11.2019

	Intermittent use/release	0,15 mg/l
	Fresh water	0,015 mg/l
zinc oxide	Fresh water sediment	117,8 mg/kg dry weight (d.w.)
	Sea water	6,1 µg/l
	Fresh water	20,6 µg/l
	Sea sediment	56,5 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 μg/l
	Soil	35,6 mg/kg dry weight (d.w.)

#### 8.2 Exposure controls

Personal protective equipment

Eye/face protection : DGUV Regulation 112-192 - Use of eye and face protection

Goggles

Hand protection

Material : Nitrile rubber Glove thickness : 0,2 mm Protective index : Class 3

Remarks : Before removing gloves clean them with soap and water.

Wear suitable gloves tested to EN374.

DGUV Regulation 112-195 - Use of protective gloves

Skin and body protection : Safety shoes

Long sleeved clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

Remove and wash contaminated clothing before re-use.

During spray application: impervious clothing

Respiratory protection : No personal respiratory protective equipment normally re-

quired.

DGUV Regulation 112-190 - Use of breathing equipment

During spray application: Do not breathe spray dust. Use

A2/P2 combination filter for paint spraying.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Capalac Aqua Metallschutz Basis T

Version Revision Date: SDS Number: Date of last issue: 16.02.2022 2.0 06.09.2023 6007260 Date of first issue: 11.11.2019

## **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties

Physical state : liquid

Color : white

Odor : No data available

Melting point/freezing point : ca. 0 °C

Boiling point/boiling range : ca. 100 °C

Upper explosion limit / Upper :

flammability limit

not determined

Lower explosion limit / Lower :

flammability limit

not determined

Flash point : Not applicable

Autoignition temperature : not determined

Decomposition temperature : Not applicable

pH : 8-9

Concentration: 100 %

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 20,5 mm2/s (40 °C)

Flow time : > 60 s at 23 °C

Cross section: 6 mm Method: ISO 2431

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Capalac Aqua Metallschutz Basis T

Version Revision Date: SDS Number: Date of last issue: 16.02.2022 2.0 06.09.2023 6007260 Date of first issue: 11.11.2019

Solubility(ies)

Water solubility : completely miscible

Partition coefficient: n-

octanol/water

: Not applicable

Vapor pressure : ca. 23,4 hPa (20 °C)

Relative density : not determined

Density : 1,2000 g/cm3

Relative vapor density : Not applicable

9.2 Other information

Explosives : Not applicable

Oxidizing properties : Not applicable

Flammability (liquids) : The product is not flammable.

# **SECTION 10: Stability and reactivity**

## 10.1 Reactivity

No decomposition if stored and applied as directed.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.

## 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Capalac Aqua Metallschutz Basis T

Version Revision Date: SDS Number: Date of last issue: 16.02.2022 2.0 06.09.2023 6007260 Date of first issue: 11.11.2019

10.5 Incompatible materials

Materials to avoid : Incompatible with acids and bases.

Incompatible with oxidizing agents.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

**SECTION 11: Toxicological information** 

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Acute toxicity** 

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

**Components:** 

2-butoxyethanol:

Acute oral toxicity : Acute toxicity estimate: 1.200 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l

Test atmosphere: vapor

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

1,2-benzisothiazol-3(2H)-one:

Acute oral toxicity : LD50 (Rat): 532 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0,4 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

2-methylisothiazol-3(2H)-one:

Acute oral toxicity : LD50 (Rat): 120 mg/kg

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Capalac Aqua Metallschutz Basis T

Version Revision Date: SDS Number: Date of last issue: 16.02.2022 2.0 06.09.2023 6007260 Date of first issue: 11.11.2019

Acute inhalation toxicity : LC50 (Rat): 0,145 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one

(3:1):

Acute oral toxicity : LD50 (Rat): 66 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 0,17 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 141 mg/kg

Method: OECD Test Guideline 402

#### Skin corrosion/irritation

Not classified based on available information.

#### Serious eye damage/eye irritation

Not classified based on available information.

#### Respiratory or skin sensitization

## Skin sensitization

May cause an allergic skin reaction.

## Respiratory sensitization

Not classified based on available information.

# Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

#### Reproductive toxicity

Not classified based on available information.

## STOT-single exposure

Not classified based on available information.

#### STOT-repeated exposure

Not classified based on available information.

#### **Aspiration toxicity**

Not classified based on available information.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Capalac Aqua Metallschutz Basis T

Version Revision Date: SDS Number: Date of last issue: 16.02.2022 2.0 06.09.2023 6007260 Date of first issue: 11.11.2019

#### 11.2 Information on other hazards

#### **Endocrine disrupting properties**

## **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

#### **Components:**

1,2-benzisothiazol-3(2H)-one:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2,2 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia): 3,27 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Selenastrum capricornutum (green algae)): 0,11 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

M-Factor (Acute aquatic tox- :

icity)

. !

M-Factor (Chronic aquatic

toxicity)

: 1

2-methylisothiazol-3(2H)-one:

M-Factor (Acute aquatic tox- :

10

icity)

M-Factor (Chronic aquatic

toxicity)

: 1

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

M-Factor (Acute aquatic tox-

icity)

100

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Capalac Aqua Metallschutz Basis T

Version Revision Date: SDS Number: Date of last issue: 16.02.2022 2.0 06.09.2023 6007260 Date of first issue: 11.11.2019

M-Factor (Chronic aquatic

toxicity)

100

#### 12.2 Persistence and degradability

No data available

## 12.3 Bioaccumulative potential

## **Components:**

2-butoxyethanol:

Partition coefficient: n- : log Pow: 0,81 (25 °C)

octanol/water pH: 7

1,2-benzisothiazol-3(2H)-one:

Partition coefficient: n- : log Pow: 0,63 - 0,76

octanol/water pH: 7

2-methylisothiazol-3(2H)-one:

Partition coefficient: n- : log Pow: -0,486 (25 °C)

octanol/water pH: 7

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one

(3:1):

Partition coefficient: n- : log Pow: <= 0,75

octanol/water Method: OECD Test Guideline 117

#### 12.4 Mobility in soil

No data available

# 12.5 Results of PBT and vPvB assessment

#### **Product:**

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

#### 12.6 Endocrine disrupting properties

**Product:** 

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Capalac Aqua Metallschutz Basis T

Version Revision Date: SDS Number: Date of last issue: 16.02.2022 2.0 06.09.2023 6007260 Date of first issue: 11.11.2019

levels of 0.1% or higher.

#### 12.7 Other adverse effects

#### **Product:**

Additional ecological infor-

mation

Toxic to aquatic organisms, may cause long-term adverse

effects in the aquatic environment.

## **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

Product :

Waste should not be disposed of via wastewater.

Contaminated packaging : Only completely emptied containers should be given for recy-

cling.

Waste Code : used product

080112, waste paint and varnish other than those mentioned

in 08 01 11\*

#### **SECTION 14: Transport information**

#### 14.1 UN number or ID number

ADN : UN 3082
ADR : UN 3082
RID : UN 3082
IMDG : UN 3082
IATA : UN 3082

## 14.2 UN proper shipping name

**ADN** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(trizinc bis(orthophosphate), zinc oxide)

**ADR** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(trizinc bis(orthophosphate), zinc oxide)

RID : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(trizinc bis(orthophosphate), zinc oxide)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Capalac Aqua Metallschutz Basis T

Version Revision Date: SDS Number: Date of last issue: 16.02.2022 2.0 06.09.2023 6007260 Date of first issue: 11.11.2019

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(trizinc bis(orthophosphate), zinc oxide)

IATA : Environmentally hazardous substance, liquid, n.o.s.

(trizinc bis(orthophosphate), zinc oxide)

14.3 Transport hazard class(es)

Class Subsidiary risks

 ADN
 : 9

 ADR
 : 9

 RID
 : 9

 IMDG
 : 9

 IATA
 : 9

## 14.4 Packing group

**ADN** 

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9

**ADR** 

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9
Tunnel restriction code : (-)

**RID** 

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9

**IMDG** 

Packing group : III
Labels : 9
EmS Code : F-A, S-F

IATA (Cargo)

Packing instruction (cargo : 964

aircraft)

Packing instruction (LQ) : Y964
Packing group : III

Labels : Miscellaneous

IATA (Passenger)

Packing instruction (passen- : 964

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Capalac Aqua Metallschutz Basis T

Version Revision Date: SDS Number: Date of last issue: 16.02.2022 2.0 06.09.2023 6007260 Date of first issue: 11.11.2019

ger aircraft)

Packing instruction (LQ) : Y964
Packing group : III

Labels : Miscellaneous

#### 14.5 Environmental hazards

**ADN** 

Environmentally hazardous : yes

**ADR** 

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

**IMDG** 

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

#### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)  Conditions of restriction for the following entries should be considered: Number on list 3

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59).

This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be generated.

ated.

Regulation (EC) No 1005/2009 on substances that de- : Not applicable

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Capalac Aqua Metallschutz Basis T

Version Revision Date: SDS Number: Date of last issue: 16.02.2022 2.0 06.09.2023 6007260 Date of first issue: 11.11.2019

plete the ozone layer

Regulation (EU) 2019/1021 on persistent organic pollu- : Not applicable

tants (recast)

REACH - List of substances subject to authorisation : None

(Annex XIV)

Seveso III: Directive 2012/18/EU of the Euro- E2 ENVIRONMENTAL HAZARDS

pean Parliament and of the Council on the control of major-accident hazards involving

dangerous substances.

Water hazard class (Germa- : WGK 2 obviously hazardous to water

ny) Classification according to AwSV, Annex 1 (5.2)

Product code for laquers and : M-LW01 Water-based varnishes

paints / Giscode

. : BSW20 Coating materials, water-based

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 2,19 %

Volatile organic compounds : Directive 2004/42/EC

< 3 % < 30 g/l

#### Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

#### 15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

#### **SECTION 16: Other information**

#### **Full text of H-Statements**

H301 : Toxic if swallowed.
H302 : Harmful if swallowed.
H310 : Fatal in contact with skin.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Capalac	Aqua Metallsc	hu	tz Basis T	
Version	Revision Date:	SE	OS Number:	Date of last issue: 16.02.2022
2.0	06.09.2023	60	07260	Date of first issue: 11.11.2019
H311 H314 H315 H317 H318 H319 H330 H331 H400		: : : : : : : : : : : : : : : : : : : :	Causes skin irritat	rin burns and eye damage. tion. ergic skin reaction. ye damage. ye irritation.
H410		:		atic life with long lasting effects.
H411		:	-	fe with long lasting effects.
EUH07	<b>'</b> 1	:	Corrosive to the re	espiratory tract.

#### Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation
Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitization

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

DE TRGS 527 : Germany. TRGS 527 - Activities with nanomaterials

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

TRGS 903 : TRGS 903 - Biological limit values

2000/39/EC / TWA : Limit Value - eight hours 2000/39/EC / STEL : Short term exposure limit DE TRGS 527 / BM : Assessment scale

DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AlIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELX - Loading rate associated with x% response; EMS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Code for the Construction and Equipment of Ships cancer in the International Maritime Dangerous Goods; IMO - International Convention; IECSC - Inventy and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; no.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR evel; NOELR evel; NOELR evel; NOELR evel; NOELR evel; NOELR evel; NOELR evel;

Further information Other information:

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



DE / EN

Capalac Aqua Metallschutz Basis T

Version Revision Date: SDS Number: Date of last issue: 16.02.2022 2.0 06.09.2023 6007260 Date of first issue: 11.11.2019

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

## Sources of key data used to compile the Material Safety Data Sheet:

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

## Classification of the mixture: Classification procedure:

Skin Sens. 1 H317 Calculation method Aquatic Chronic 2 H411 Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

#### **REACH Information**

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN