

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



Capadur Wetterschutzfarbe NQG Basis 1

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2024
6.3	18.12.2024	6007656	Date of first issue: 01.12.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Capadur Wetterschutzfarbe NQG Basis 1

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Water-borne coatings

Recommended restrictions : within adequate application - none
on use

1.3 Details of the supplier of the safety data sheet

Company : Caparol Farben Lacke GmbH
Roßdörfer Straße 50
64372 Ober-Ramstadt

Telephone : +496154710
Telefax : +4961547170222

Website :
E-mail address Responsible/issuing person : msds@dr-rmi.com

1.4 Emergency telephone

Emergency telephone 1 : +49613284463 GBK GmbH

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Long-term (chronic) aquatic hazard, Category 3 : H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard Statements : H412 Harmful to aquatic life with long lasting effects.


Precautionary Statements : **Prevention:**
P273 Avoid release to the environment.

Disposal:
P501 Dispose of contents/ container to an approved

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



CAPAROL

Capadur Wetterschutzfarbe NQG Basis 1

Version 6.3 Revision Date: 18.12.2024 SDS Number: 6007656 Date of last issue: 06.09.2024
Date of first issue: 01.12.2019

		M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1	
propylidynetrimethanol	77-99-6 201-074-9 01-2119486799-10	Repr. 2; H361fd	$\geq 0,1 - < 1$
1,2-benzisothiazol-3(2H)-one	2634-33-5 220-120-9 613-088-00-6 01-2120761540-60	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 Acute Tox. 2; H330 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1 specific concentration limit Skin Sens. 1; H317 $\geq 0,05 \%$	$\geq 0,0025 - < 0,025$
2,2'-dithiobis[N-methylbenzamide]	2527-58-4 219-768-5	Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1	$\geq 0,0025 - < 0,025$
terbutryn	886-50-0 212-950-5	Acute Tox. 4; H302 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100	$\geq 0,0025 - < 0,025$

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



CAPAROL

Capadur Wetterschutzfarbe NQG Basis 1

Version 6.3 Revision Date: 18.12.2024 SDS Number: 6007656 Date of last issue: 06.09.2024
Date of first issue: 01.12.2019

2-methyl-1,2-benzothiazol-3(2H)-one	2527-66-4 613-336-00-3	Acute Tox. 3; H301 Acute Tox. 4; H312 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 EUH071 M-Factor (Acute aquatic toxicity): 1 specific concentration limit Skin Sens. 1A; H317 >= 0,0015 % Acute toxicity estimate Acute oral toxicity: 175 mg/kg Acute dermal toxicity: 1.100 mg/kg	>= 0,0002 - < 0,0015
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9 613-167-00-5 01-2120764691-48	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100 specific concentration limit Skin Corr. 1C; H314 >= 0,6 % Skin Irrit. 2; H315	<= 0,0002

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



Capadur Wetterschutzfarbe NQG Basis 1

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2024
6.3	18.12.2024	6007656	Date of first issue: 01.12.2019

		0,06 - < 0,6 % Eye Irrit. 2; H319 0,06 - < 0,6 % Skin Sens. 1A; H317 >= 0,0015 % Eye Dam. 1; H318 >= 0,6 %	
Substances with a workplace exposure limit :			
Talc (Mg ₃ H ₂ (SiO ₃) ₄)	14807-96-6 238-877-9 01-2120140278-58		>= 1 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

- General advice : Never give anything by mouth to an unconscious person.
If you feel unwell, seek medical advice (show the label where possible).
Move out of dangerous area.
First aider needs to protect himself.
- If inhaled : Move to fresh air.
- In case of skin contact : Take off all contaminated clothing immediately.
Do NOT use solvents or thinners.
In case of contact, immediately flush skin with soap and plenty of water.
- In case of eye contact : If eye irritation persists: Get medical advice/ attention.
IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.
- If swallowed : Seek medical advice.
Clean mouth with water and drink afterwards plenty of water.
If swallowed, DO NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



Capadur Wetterschutzfarbe NQG Basis 1

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2024
6.3	18.12.2024	6007656	Date of first issue: 01.12.2019

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Do not use a solid water stream as it may scatter and spread fire.

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : In case of fire hazardous decomposition products may be produced such as:
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

5.3 Advice for firefighters

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Use water spray to cool unopened containers.
Standard procedure for chemical fires.
The product itself does not burn.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use protective shoes or boots with rough rubber sole.
Material can create slippery conditions.
Do not get in eyes, on skin, or on clothing.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
Do not flush into surface water or sanitary sewer system.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



Capadur Wetterschutzfarbe NQG Basis 1

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2024
6.3	18.12.2024	6007656	Date of first issue: 01.12.2019

6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.

, For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Use only with adequate ventilation.
For personal protection see section 8.
No special technical protective measures required.

No interior use.

In addition, the current technical information for this product
and its application on www.caparol.com must be observed.

Hygiene measures : Wash hands before eating, drinking, or smoking. Do not eat,
drink or smoke when using this product. Remove contaminat-
ed clothing and protective equipment before entering eating
areas.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage : Perishable if frozen. To maintain product quality, do not store
areas and containers in heat or direct sunlight. Store at room temperature in the
original container. Containers which are opened must be care-
fully resealed and kept upright to prevent leakage.

Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline
materials.

Storage class (TRGS 510) : 12

7.3 Specific end use(s)

Specific use(s) : This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]	13463-67-7	MAK (measured as the alveolate fraction)	0,3 mg/m ³	DE DFG MAK

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



Capadur Wetterschutzfarbe NQG Basis 1

Version 6.3 Revision Date: 18.12.2024 SDS Number: 6007656 Date of last issue: 06.09.2024
Date of first issue: 01.12.2019

		Peak-limit category: 8; II		
	Further information: Substances that cause cancer in humans or animals or that are considered to be carcinogenic for humans and for which a MAK value can be derived., Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			
		AGW (Inhalable fraction)	10 mg/m3 (Titanium dioxide)	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		AGW (Alveolate fraction)	1,25 mg/m3 (Titanium dioxide)	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		BM (Alveolar dust fraction)	0,5 mg/m3	DE TRGS 527
Talc (Mg3H2(SiO3)4)	14807-96-6	AGW (Inhalable fraction)	10 mg/m3	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		AGW (Alveolate fraction)	1,25 mg/m3	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
3-iodo-2-propynyl butylcarbamate	55406-53-6	AGW (Vapour and aerosols)	0,005 ppm 0,058 mg/m3	DE TRGS 900
	Peak-limit category: 2;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child, Substance sensitizing through the skin			
		MAK	0,005 ppm 0,058 mg/m3	DE DFG MAK
	Further information: Danger of sensitization of the skin, Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of exposure	Potential health effects	Value
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	Consumers	Ingestion	Long-term systemic effects	700,00 mg/kg bw/day
	Workers	Inhalation	Long-term local effects	10,00 mg/m3
[(butoxymethylethoxy)methylethoxy]pro	Consumers	Ingestion	Long-term systemic effects	25,00 mg/kg bw/day

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



CAPAROL

Capadur Wetterschutzfarbe NQG Basis 1

Version 6.3 Revision Date: 18.12.2024 SDS Number: 6007656 Date of last issue: 06.09.2024
Date of first issue: 01.12.2019

pan-1-ol	Consumers	Skin contact	Long-term systemic effects	25,00 mg/kg bw/day
	Workers	Skin contact	Long-term systemic effects	50,00 mg/kg bw/day
propylidynetrimethanol	Workers	Inhalation	Long-term systemic effects	3,3 mg/m ³
	Workers	Skin contact	Long-term systemic effects	0,94 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,58 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	0,34 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,34 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10 μ m]	Sewage treatment plant	100 mg/l
	Fresh water	0,184 mg/l
	Soil	100 mg/kg dry weight (d.w.)
	Sea water	0,0184 mg/l
	Fresh water sediment	1000 mg/kg dry weight (d.w.)
	Sea sediment	100 mg/kg dry weight (d.w.)
	Intermittent use/release	0,193 mg/l
[(butoxymethylethoxy)methylethoxy]propan-1-ol	Intermittent use/release	5,64 mg/l
	Fresh water sediment	2,59 mg/kg dry weight (d.w.)
	Fresh water	0,564 mg/l
	Sewage treatment plant	100 mg/l
	Sea water	0,0564 mg/l
	Sea sediment	0,259 ng/kg dry weight (d.w.)
	Soil	0,188 mg/kg dry weight (d.w.)
propylidynetrimethanol	Fresh water	1 mg/l
	Sewage treatment plant	100 mg/l
	Sea sediment	0,351 mg/kg dry weight (d.w.)
	Sea water	0,1 mg/l
	Soil	0,241 mg/kg dry weight (d.w.)
	Fresh water sediment	3,505 mg/kg dry weight (d.w.)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



Capadur Wetterschutzfarbe NQG Basis 1

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2024
6.3	18.12.2024	6007656	Date of first issue: 01.12.2019

	Intermittent use/release	10 mg/l
--	--------------------------	---------

8.2 Exposure controls

Personal protective equipment

Eye/face protection : DGUV Regulation 112-192 - Use of eye and face protection

Goggles

Hand protection

Material : Nitrile rubber
Glove thickness : 0,2 mm
Protective index : Class 3

Remarks : Before removing gloves clean them with soap and water.
Wear suitable gloves tested to EN374.
DGUV Regulation 112-195 - Use of protective gloves

Skin and body protection

: Safety shoes
Long sleeved clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

During spray application: impervious clothing

Respiratory protection

: No personal respiratory protective equipment normally required.

During spray application: Do not breathe spray dust. Use A2/P2 combination filter for paint spraying.

DGUV Regulation 112-190 - Use of breathing equipment

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Color : white

Odor : No data available

Melting point/freezing point : ca. 0 °C

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



Capadur Wetterschutzfarbe NQG Basis 1

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2024
6.3	18.12.2024	6007656	Date of first issue: 01.12.2019

Boiling point/boiling range : ca. 100 °C

Upper explosion limit / Upper flammability limit : not determined

Lower explosion limit / Lower flammability limit : not determined

Flash point : Not applicable

Autoignition temperature : not determined

Decomposition temperature : Not applicable

pH : 8 - 9
Concentration: 100 %

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : not determined

Flow time : not determined

Solubility(ies)
Water solubility : completely miscible

Partition coefficient: n-octanol/water : not determined

Vapor pressure : ca. 23,4 hPa (20 °C)

Density : 1,240 g/cm³ (20 °C)
Method: DIN EN ISO 2811-1

Bulk density : Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



Capadur Wetterschutzfarbe NQG Basis 1

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2024
6.3	18.12.2024	6007656	Date of first issue: 01.12.2019

Relative vapor density : not determined

9.2 Other information

Explosives : Not applicable

Oxidizing properties : Not applicable

Flammability (liquids) : The product is not flammable.

Evaporation rate : Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

10.5 Incompatible materials

Materials to avoid : Incompatible with acids and bases.
Incompatible with oxidizing agents.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



CAPAROL

Capadur Wetterschutzfarbe NQG Basis 1

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2024
6.3	18.12.2024	6007656	Date of first issue: 01.12.2019

Method: Calculation method

Components:

3-iodo-2-propynyl butylcarbamate:

Acute oral toxicity : LD50 (Rat, female): 1.056 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 0,763 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

1,2-benzisothiazol-3(2H)-one:

Acute oral toxicity : LD50 (Rat): 532 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0,4 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

terbutryn:

Acute oral toxicity : LD50 Oral (Rat): > 300 mg/kg

Acute dermal toxicity : LD50 Dermal (Rat): > 2.000 mg/kg

2-methyl-1,2-benzothiazol-3(2H)-one:

Acute oral toxicity : Acute toxicity estimate: 175 mg/kg
Method: Acute toxicity estimate according to Regulation (EC)
No. 1272/2008

Acute dermal toxicity : Acute toxicity estimate: 1.100 mg/kg
Method: Acute toxicity estimate according to Regulation (EC)
No. 1272/2008

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

Acute oral toxicity : LD50 (Rat): 66 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 0,17 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 141 mg/kg
Method: OECD Test Guideline 402

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



CAPAROL

Capadur Wetterschutzfarbe NQG Basis 1

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2024
6.3	18.12.2024	6007656	Date of first issue: 01.12.2019

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Not classified based on available information.

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna Straus (Water flea)): > 10 mg/l
End point: Immobilization
Exposure time: 48 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



CAPAROL

Capadur Wetterschutzfarbe NQG Basis 1

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2024
6.3	18.12.2024	6007656	Date of first issue: 01.12.2019

Test Type: static test
Method: OECD Test Guideline 202
GLP: no

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 10 mg/l
End point: Growth inhibition
Exposure time: 72 h
Test Type: Cell multiplication inhibition test
Method: OECD Test Guideline 201
GLP: no

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Components:

3-iodo-2-propynyl butylcarbamate:

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 1

1,2-benzisothiazol-3(2H)-one:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2,2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia): 3,27 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 0,11 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

2,2'-dithiobis[N-methylbenzamide]:

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



CAPAROL

Capadur Wetterschutzfarbe NQG Basis 1

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2024
6.3	18.12.2024	6007656	Date of first issue: 01.12.2019

terbutryn:

M-Factor (Acute aquatic toxicity) : 100

M-Factor (Chronic aquatic toxicity) : 100

2-methyl-1,2-benzothiazol-3(2H)-one:

M-Factor (Acute aquatic toxicity) : 1

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

M-Factor (Acute aquatic toxicity) : 100

M-Factor (Chronic aquatic toxicity) : 100

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

3-iodo-2-propynyl butylcarbamate:

Partition coefficient: n-octanol/water : log Pow: 2,81 (25 °C)

1,2-benzisothiazol-3(2H)-one:

Partition coefficient: n-octanol/water : log Pow: 0,63 - 0,76
pH: 7

terbutryn:

Partition coefficient: n-octanol/water : log Pow: 3,66

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

Partition coefficient: n-octanol/water : log Pow: <= 0,75
Method: OECD Test Guideline 117

12.4 Mobility in soil

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



CAPAROL

Capadur Wetterschutzfarbe NQG Basis 1

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2024
6.3	18.12.2024	6007656	Date of first issue: 01.12.2019

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of liquid material residues at the collection point for old paints/varnishes, dispose of dried material residues as construction and demolition waste or as municipal waste or household waste.

Waste should not be disposed of via wastewater.

Contaminated packaging : Only completely emptied containers should be given for recycling.

Waste Code : used product
080112, waste paint and varnish other than those mentioned in 08 01 11*

SECTION 14: Transport information

14.1 UN number or ID number

ADN : Not regulated as a dangerous good

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



CAPAROL

Capadur Wetterschutzfarbe NQG Basis 1

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2024
6.3	18.12.2024	6007656	Date of first issue: 01.12.2019

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADN : Not regulated as a dangerous good

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.4 Packing group

ADN : Not regulated as a dangerous good

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, : Conditions of restriction for the following entries should be considered:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



Capadur Wetterschutzfarbe NQG Basis 1

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2024
6.3	18.12.2024	6007656	Date of first issue: 01.12.2019

mixtures and articles (Annex XVII)

Number on list 75, 3

If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59). : None

Regulation (EC) on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : None

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. : Not applicable

Water hazard class (Germany) : WGK 1 slightly water endangering
Classification according to AwSV, Annex 1 (5.2)

. : BSW50 Coating materials, water-based, containing solvents,
film-protected

Labeling according to Regulation (EU) 528/2012 : According to European Regulation 528/2012 this product is defined as a "treated article" (not a biocidal product) and contains the following biocidal substances: 3-iodo-2-propynyl butylcarbamate (CAS-No. 55406-53-6), terbutryn (CAS-No. 886-50-0).

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 0,11 %

Volatile organic compounds : Directive 2004/42/EC
< 1 %
< 10 g/l

15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN

Capadur Wetterschutzfarbe NQG Basis 1



Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2024
6.3	18.12.2024	6007656	Date of first issue: 01.12.2019

SECTION 16: Other information

Full text of H-Statements

H301 : Toxic if swallowed.
H302 : Harmful if swallowed.
H310 : Fatal in contact with skin.
H312 : Harmful in contact with skin.
H314 : Causes severe skin burns and eye damage.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H330 : Fatal if inhaled.
H331 : Toxic if inhaled.
H351 : Suspected of causing cancer if inhaled.
H361fd : Suspected of damaging fertility. Suspected of damaging the unborn child.
H372 : Causes damage to organs through prolonged or repeated exposure if inhaled.
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.
H411 : Toxic to aquatic life with long lasting effects.
EUH071 : Corrosive to the respiratory tract.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard
Carc. : Carcinogenicity
Eye Dam. : Serious eye damage
Repr. : Reproductive toxicity
Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitization
STOT RE : Specific target organ toxicity - repeated exposure
DE DFG MAK : Germany. MAK BAT Annex IIa
DE TRGS 527 : Germany. TRGS 527 - Activities with nanomaterials
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.
DE DFG MAK / MAK : MAK value
DE TRGS 527 / BM : Assessment scale
DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Sub-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN



CAPAROL

Capadur Wetterschutzfarbe NQG Basis 1

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2024
6.3	18.12.2024	6007656	Date of first issue: 01.12.2019

stance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC. Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

Sources of key data used to compile the Material Safety Data Sheet : ECHA WebSite
ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH
NIOSH - Registry of toxic effects of chemical substances
ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities
SAX'S - Dangerous properties of industrial materials
GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)
Toxnet - Toxicology Data Network

Classification of the mixture:

Aquatic Chronic 3 H412

Classification procedure:

Based on product data or assessment

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

DE / EN

Capadur Wetterschutzfarbe NQG Basis 1



Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2024
6.3	18.12.2024	6007656	Date of first issue: 01.12.2019
