

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Dickschichtlack Weiß

Version	Revision Date:	Print Date	Date of last issue: -
1.0	18.10.2019	19.10.2019	Date of first issue: 18.10.2019

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Capalac Dickschichtlack Weiß

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Solvent-borne coatings

Recommended restrictions : within adequate application - none  
on use

#### 1.3 Details of the supplier of the safety data sheet

Company : Caparol Farben Lacke GmbH  
Roßdörfer Straße 50  
64372 Ober-Ramstadt

Telephone : +496154710  
Telefax : +4961547170222  
E-mail address Respon-  
sible/issuing person : msds@dr-rmi.com

#### 1.4 Emergency telephone number

Emergency telephone num-  
ber 1 : +49613284463 GBK GmbH

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

Specific target organ toxicity - single ex-  
posure, Category 3, Central nervous  
system H336: May cause drowsiness or dizziness.

Long-term (chronic) aquatic hazard, Cat-  
egory 3 H412: Harmful to aquatic life with long lasting ef-  
fects.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Capalac Dickschichtlack Weiß

Version 1.0      Revision Date: 18.10.2019      Print Date 19.10.2019      Date of last issue: -  
Date of first issue: 18.10.2019

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements : P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.

### Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 Do not breathe vapours/ spray.  
P271 Use only outdoors or in a well-ventilated area.

### Storage:

P405 Store locked up.

Hazardous components which must be listed on the label:

Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha  
n-butyl acetate

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Alkyd-resin-based lacquer, solvent-containing

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha	64742-48-9 265-150-3 649-327-00-6 01-2119463258-33	Flam. Liq. 3; H226 STOT SE 3; H336 Asp. Tox. 1; H304 EUH066	>= 20 - < 30
aluminium dihydrogen triphosphate	13939-25-8 237-714-9 01-2119970565-28	Eye Irrit. 2; H319	>= 1 - < 10
zinc oxide	1314-13-2	Aquatic Acute 1;	>= 1 - < 2,5

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Capalac Dickschichtlack Weiß

Version  
1.0

Revision Date:  
18.10.2019

Print Date  
19.10.2019

Date of last issue: -  
Date of first issue: 18.10.2019

	215-222-5 030-013-00-7 01-2119463881-32	H400 Aquatic Chronic 1; H410	
2-dimethylaminoethanol	108-01-0 203-542-8 603-047-00-0 01-2119492298-24	Flam. Liq. 3; H226 Acute Tox. 4; H302 Acute Tox. 3; H331 Acute Tox. 4; H312 Skin Corr. 1B; H314 STOT SE 3; H335	>= 0,1 - < 1
zinc carbonate	3486-35-9 222-477-6 01-2120770499-38	Aquatic Acute 1; H400 Aquatic Chronic 2; H411	>= 0,1 - < 0,25
Substances with a workplace exposure limit :			
titanium dioxide	13463-67-7 236-675-5 01-2119489379-17		>= 10 - < 20
(2-methoxymethylethoxy)propanol	34590-94-8 252-104-2 01-2119450011-60		>= 1 - < 10
Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	14807-96-6 238-877-9 01-2120140278-58		>= 1 - < 10
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 EUH066	>= 1 - < 10
Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha	64742-48-9 265-150-3 649-327-00-6 01-2119486659-16	Asp. Tox. 1; H304 EUH066	>= 1 - < 10

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : First aider needs to protect himself.  
Move out of dangerous area.  
If you feel unwell, seek medical advice (show the label where possible).  
Never give anything by mouth to an unconscious person.
- If inhaled : Move to fresh air.  
If symptoms persist, call a physician.
- In case of skin contact : Take off all contaminated clothing immediately.  
In case of contact, immediately flush skin with soap and plenty of water.  
Do NOT use solvents or thinners.
- In case of eye contact : IF IN EYES: Rinse cautiously with water for several minutes.  
Remove contact lenses, if present and easy to do. Continue rinsing.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Capalac Dickschichtlack Weiß

Version	Revision Date:	Print Date	Date of last issue: -
1.0	18.10.2019	19.10.2019	Date of first issue: 18.10.2019

If eye irritation persists: Get medical advice/ attention.

If swallowed : If swallowed, DO NOT induce vomiting.  
Clean mouth with water and drink afterwards plenty of water.  
Seek medical advice.

### 4.2 Most important symptoms and effects, both acute and delayed

None known.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media : None known.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : In case of fire hazardous decomposition products may be produced such as:  
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).  
Cool closed containers exposed to fire with water spray.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : In the event of fire and/or explosion do not breathe fumes.  
Standard procedure for chemical fires.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.  
Ensure adequate ventilation.  
Do not get in eyes, on skin, or on clothing.

### 6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.  
Prevent further leakage or spillage if safe to do so.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Capalac Dickschichtlack Weiß

Version	Revision Date:	Print Date	Date of last issue: -
1.0	18.10.2019	19.10.2019	Date of first issue: 18.10.2019

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8., For further information see Section 7 of the safety data sheet.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Provide sufficient air exchange and/or exhaust in work rooms. Avoid exceeding the given occupational exposure limits (see section 8).  
For personal protection see section 8.  
Non-sparking tools should be used.

Advice on protection against fire and explosion : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands before eating, drinking, or smoking. Avoid contact with the skin and the eyes.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store between 5 and 25 °C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Store in original container.

Storage class (TRGS 510) : 3, Flammable liquids

### 7.3 Specific end use(s)

Specific use(s) : Please follow the technical information.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha	64742-48-9	AGW	300 mg/m <sup>3</sup>	DE TRGS 900

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Capalac Dickschichtlack Weiß

Version 1.0      Revision Date: 18.10.2019      Print Date 19.10.2019      Date of last issue: -  
Date of first issue: 18.10.2019

Peak-limit: excursion factor (category)	2;(II)			
Further information	Group exposure limit for hydrocarbon solvent mixtures, Commission for dangerous substances, See also No. 2.9 of the TRGS 900			
titanium dioxide	13463-67-7	AGW (Inhalable fraction)	10 mg/m <sup>3</sup> (Titanium dioxide)	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)			
Further information	General dust value. For this substance no specific occupational exposure limit value is established, since the AGS does not yet have information regarding unspecific action on the respiratory organs in excess of the normal values., Commission for dangerous substances, Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
		AGW (Alveolate fraction)	1,25 mg/m <sup>3</sup> (Titanium dioxide)	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)			
(2-methoxymethylethoxy)propanol	34590-94-8	TWA	50 ppm 308 mg/m <sup>3</sup>	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		AGW (Vapour and aerosols)	50 ppm 310 mg/m <sup>3</sup>	DE TRGS 900
Peak-limit: excursion factor (category)	1;(I)			
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., European Union (The EU has established a limit value: deviations in value and peak limit are possible), Sum of vapor and aerosols.			
Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	14807-96-6	AGW (Inhalable fraction)	10 mg/m <sup>3</sup>	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)			
Further information	General dust value. For this substance no specific occupational exposure limit value is established, since the AGS does not yet have information regarding unspecific action on the respiratory organs in excess of the normal values., Commission for dangerous substances, Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
		AGW (Alveolate fraction)	1,25 mg/m <sup>3</sup>	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)			
n-butyl acetate	123-86-4	AGW	62 ppm 300 mg/m <sup>3</sup>	DE TRGS 900
Peak-limit: excursion factor (category)	2;(I)			
Further information	Commission for dangerous substances, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn			

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Capalac Dickschichtlack Weiß

Version  
1.0

Revision Date:  
18.10.2019

Print Date  
19.10.2019

Date of last issue: -  
Date of first issue: 18.10.2019

	child			
Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha	64742-48-9	AGW	300 mg/m <sup>3</sup>	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)			
Further information	Group exposure limit for hydrocarbon solvent mixtures, Commission for dangerous substances, See also No. 2.9 of the TRGS 900			

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
titanium dioxide	Consumers	Ingestion	Long-term systemic effects	700,00 mg/kg bw/day
	Workers	Inhalation	Long-term local effects	10,00 mg/m <sup>3</sup>
(2-methoxymethylethoxy)propanol	Consumers	Ingestion	Long-term systemic effects	0,33 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	475,00 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	202,00 mg/m <sup>3</sup>
	Consumers	Ingestion	Long-term systemic effects	36,00 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	121,00 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	37,20 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	308,00 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	404,00 mg/m <sup>3</sup>
n-butyl acetate	Workers	Skin contact	Long-term systemic effects	283,00 mg/kg bw/day
	Workers	Skin contact	Long-term systemic effects	950,00 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	12,00 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	3,40 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	3,40 mg/kg bw/day
	Consumers	Inhalation	Acute systemic effects	859,70 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	102,34 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	102,34 mg/m <sup>3</sup>
Consumers	Inhalation	Acute local effects	859,70 mg/m <sup>3</sup>	
Workers	Inhalation	Acute systemic effects	960,00 mg/m <sup>3</sup>	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Capalac Dickschichtlack Weiß

Version  
1.0

Revision Date:  
18.10.2019

Print Date  
19.10.2019

Date of last issue: -  
Date of first issue: 18.10.2019

	Workers	Inhalation	Acute systemic effects	960,00 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	960,00 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	960,00 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	48,00 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	480,00 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	480,00 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	480,00 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	480,00 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	7,00 mg/kg bw/day
	Consumers	Inhalation	Acute systemic effects	859,70 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	859,70 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	102,34 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	102,34 mg/m <sup>3</sup>
zinc oxide	Consumers	Skin contact	Long-term systemic effects	83,00 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	2,50 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	2,50 mg/m <sup>3</sup>
	Consumers	Ingestion	Long-term systemic effects	0,83 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,83 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	83,00 mg/kg bw/day
2-dimethylaminoethanol	Workers	Inhalation	Acute systemic effects	22,00 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	22,00 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	7,40 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	7,40 mg/m <sup>3</sup>
	Workers	Skin contact	Acute systemic effects	5,00 mg/kg bw/day
	Workers	Skin contact	Acute local effects	80,00 µg/cm <sup>2</sup>
	Workers	Skin contact	Long-term systemic effects	1,04 mg/kg bw/day

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
titanium dioxide	Sewage treatment plant	100 mg/l
	Fresh water	0,184 mg/l
	Soil	100 mg/kg dry weight (d.w.)
	Marine water	0,0184 mg/l



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Capalac Dickschichtlack Weiß

Version  
1.0

Revision Date:  
18.10.2019

Print Date  
19.10.2019

Date of last issue: -  
Date of first issue: 18.10.2019

	Fresh water sediment	1000 mg/kg dry weight (d.w.)
	Marine sediment	100 mg/kg dry weight (d.w.)
	Intermittent use/release	0,193 mg/l
(2-methoxymethylethoxy)propanol	Soil	2,2 mg/kg dry weight (d.w.)
	Intermittent use/release	192 mg/l
	Fresh water	19,2 mg/l
	Sewage treatment plant	4168 mg/l
	Marine water	1,92 mg/l
	Intermittent use/release	190 mg/l
	Fresh water sediment	70,2 mg/kg dry weight (d.w.)
	Marine water	1,9 mg/l
	Soil	2,74 mg/kg dry weight (d.w.)
	Marine sediment	7,02 mg/kg dry weight (d.w.)
	Fresh water	19 mg/l
n-butyl acetate	Fresh water sediment	0,981 mg/kg dry weight (d.w.)
	Soil	0,0903 mg/kg dry weight (d.w.)
	Marine sediment	0,0981 mg/kg dry weight (d.w.)
	Intermittent use/release	0,36 mg/l
	Sewage treatment plant	35,6 mg/l
	Marine water	0,018 mg/l
	Fresh water	0,18 mg/l
zinc oxide	Fresh water sediment	117,8 mg/kg dry weight (d.w.)
	Marine water	6,1 µg/l
	Fresh water	20,6 µg/l
	Marine sediment	56,5 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 µg/l
	Soil	35,6 mg/kg dry weight (d.w.)
2-dimethylaminoethanol	Sewage treatment plant	10 mg/l
	Marine water	0,00661 mg/l
	Fresh water sediment	0,0529 mg/kg dry weight (d.w.)
	Intermittent use/release	0,0661 mg/l
	Soil	0,0177 mg/kg dry weight (d.w.)
	Fresh water	0,0661 mg/l

### 8.2 Exposure controls

#### Personal protective equipment

Eye protection : German trade association rules - BGR 192 Eye protection

Goggles

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Capalac Dickschichtlack Weiß

Version	Revision Date:	Print Date	Date of last issue: -
1.0	18.10.2019	19.10.2019	Date of first issue: 18.10.2019

### Hand protection

Material : Nitrile rubber  
Glove thickness : 0,2 mm  
Protective index : Class 3

### Remarks

: Wear suitable gloves tested to EN374. Before removing gloves clean them with soap and water. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.  
German trade association leaflet: Carry gloves (ZH 1/706)

### Skin and body protection

: Long sleeved clothing  
Safety shoes

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

During spray application: impervious clothing

### Respiratory protection

: No personal respiratory protective equipment normally required.

German trade association rules - BGR 190 Breathing protection

During spray application: Do not breathe spray dust. Use A2/P2 combination filter for paint spraying.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance : liquid  
Colour : white  
Odour : No data available  
Odour Threshold : Not relevant  
pH : not determined  
Melting point/freezing point : not determined  
Boiling point/boiling range : not determined  
Flash point : 41,5 °C  
Method: ISO 1523  
Evaporation rate : Not applicable  
Upper explosion limit / Upper : not determined

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Capalac Dickschichtlack Weiß

Version 1.0	Revision Date: 18.10.2019	Print Date 19.10.2019	Date of last issue: - Date of first issue: 18.10.2019
----------------	------------------------------	--------------------------	--

flammability limit

Lower explosion limit / Lower  
flammability limit : not determined

Vapour pressure : not determined

Relative vapour density : not determined

Relative density : not determined

Density : 1,2900 g/cm<sup>3</sup>

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-  
octanol/water : not determined

Auto-ignition temperature : not determined

Decomposition temperature : Not applicable

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 21 mm<sup>2</sup>/s (40 °C)  
Method: ISO 3104/3105

Flow time : > 60 s  
Cross section: 6 mm  
Method: DIN 53211

Explosive properties : Not applicable

Oxidizing properties : Not applicable

### 9.2 Other information

Flammability (liquids) : Sustains combustion

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Hazardous decomposition products formed under fire conditions.  
Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Capalac Dickschichtlack Weiß

Version	Revision Date:	Print Date	Date of last issue: -
1.0	18.10.2019	19.10.2019	Date of first issue: 18.10.2019

Conditions to avoid : Protect from frost, heat and sunlight.

### 10.5 Incompatible materials

Materials to avoid : Incompatible with oxidizing agents.  
Incompatible with acids and bases.

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

##### Product:

Acute oral toxicity : Remarks: Based on available data, the classification criteria are not met.

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method  
  
Remarks: Based on available data, the classification criteria are not met.

Acute dermal toxicity : Remarks: Based on available data, the classification criteria are not met.

##### Components:

#### **2-dimethylaminoethanol:**

Acute oral toxicity : LD50 (Rat): 1.183 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 6,1 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): 1.219 mg/kg  
Method: OECD Test Guideline 402

#### **n-butyl acetate:**

Acute oral toxicity : LD50 Oral (Rat): 14.000 mg/kg

#### **Skin corrosion/irritation**

##### Product:

Remarks : May cause skin irritation in susceptible persons.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Capalac Dickschichtlack Weiß

Version	Revision Date:	Print Date	Date of last issue: -
1.0	18.10.2019	19.10.2019	Date of first issue: 18.10.2019

### Components:

#### **2-dimethylaminoethanol:**

Species	:	Rabbit
Assessment	:	Corrosive
Method	:	OECD Test Guideline 404
Result	:	Corrosive

### **Serious eye damage/eye irritation**

#### Product:

Remarks : According to the classification criteria of the European Union, the product is not considered as being an eye irritant.

### Components:

#### **aluminium dihydrogen triphosphate:**

Species	:	Rabbit
Method	:	OECD Test Guideline 405
Result	:	Irritating to eyes.

#### **2-dimethylaminoethanol:**

Species	:	Rabbit
Assessment	:	Risk of serious damage to eyes.
Method	:	OECD Test Guideline 405
Result	:	Irreversible effects on the eye

### **Respiratory or skin sensitisation**

#### Product:

Remarks : No data available

### Components:

#### **2-dimethylaminoethanol:**

Test Type	:	Buehler Test
Exposure routes	:	Dermal
Species	:	Guinea pig
Assessment	:	Does not cause skin sensitisation.
Method	:	OECD Test Guideline 406
Result	:	Does not cause skin sensitisation.

### **STOT - single exposure**

#### Components:

#### **2-dimethylaminoethanol:**

Exposure routes	:	Inhalation
Target Organs	:	Upper respiratory tract
Assessment	:	May cause respiratory irritation.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Capalac Dickschichtlack Weiß

Version	Revision Date:	Print Date	Date of last issue: -
1.0	18.10.2019	19.10.2019	Date of first issue: 18.10.2019

### SECTION 12: Ecological information

#### 12.1 Toxicity

**Product:**

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

#### 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

**Components:**

**(2-methoxymethylethoxy)propanol:**

Partition coefficient: n-octanol/water : Pow: 1,01 (25 °C)

**n-butyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 2,3 (25 °C)  
Method: OECD Test Guideline 117

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

#### 12.6 Other adverse effects

**Product:**

Additional ecological information : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Product : .

Waste should not be disposed of via wastewater.

Contaminated packaging : Only completely emptied containers should be given for recycling.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Capalac Dickschichtlack Weiß

Version	Revision Date:	Print Date	Date of last issue: -
1.0	18.10.2019	19.10.2019	Date of first issue: 18.10.2019

Waste Code : used product  
080112, waste paint and varnish other than those mentioned  
in 08 01 11\*

### SECTION 14: Transport information

#### 14.1 UN number

**ADN** : UN 1263  
**ADR** : UN 1263  
**RID** : UN 1263  
**IMDG** : UN 1263  
**IATA** : UN 1263

#### 14.2 UN proper shipping name

**ADN** : PAINT  
**ADR** : PAINT  
**RID** : PAINT  
**IMDG** : PAINT  
**IATA** : Paint

#### 14.3 Transport hazard class(es)

**ADN** : 3  
**ADR** : 3  
**RID** : 3  
**IMDG** : 3  
**IATA** : 3

#### 14.4 Packing group

**ADN**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

**ADR**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3  
Tunnel restriction code : (D/E)

**RID**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Capalac Dickschichtlack Weiß

Version	Revision Date:	Print Date	Date of last issue: -
1.0	18.10.2019	19.10.2019	Date of first issue: 18.10.2019

### IMDG

Packing group : III  
Labels : 3  
EmS Code : F-E, S-E

### IATA (Cargo)

Packing instruction (cargo aircraft) : 366  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Class 3 - Flammable liquids

### IATA\_P (Passenger)

Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Class 3 - Flammable liquids

### 14.5 Environmental hazards

#### ADN

Environmentally hazardous : no

#### ADR

Environmentally hazardous : no

#### RID

Environmentally hazardous : no

#### IMDG

Marine pollutant : no

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be generated.

REACH - List of substances subject to authorisation (Annex XIV) : None

REACH - Restrictions on the manufacture, placing on : Conditions of restriction for the fol-



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Capalac Dickschichtlack Weiß

Version 1.0	Revision Date: 18.10.2019	Print Date 19.10.2019	Date of last issue: - Date of first issue: 18.10.2019
----------------	------------------------------	--------------------------	--

the market and use of certain dangerous substances, preparations and articles (Annex XVII)

lowing entries should be considered:  
Number on list 3

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c FLAMMABLE LIQUIDS

34

Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams), (d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Water contaminating class (Germany) : 1 slightly water endangering  
Classification according to AwSV, Annex 1 (5.2)

Product code for laquers and paints / Giscode : M-LL01 Alkyd resin varnishes, aromatics removed

. : BSL20 Coating materials, solvent-based, aromatic-free, classified

Volatile organic compounds : Directive 2004/42/EC  
< 31 %  
< 400 g/l

### Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

## 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

## SECTION 16: Other information

### Full text of H-Statements

EUH066	: Repeated exposure may cause skin dryness or cracking.
H226	: Flammable liquid and vapour.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H314	: Causes severe skin burns and eye damage.
H319	: Causes serious eye irritation.
H331	: Toxic if inhaled.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Capalac Dickschichtlack Weiß

Version	Revision Date:	Print Date	Date of last issue: -
1.0	18.10.2019	19.10.2019	Date of first issue: 18.10.2019

H335 : May cause respiratory irritation.  
H336 : May cause drowsiness or dizziness.  
H400 : Very toxic to aquatic life.  
H410 : Very toxic to aquatic life with long lasting effects.  
H411 : Toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Acute : Short-term (acute) aquatic hazard  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Asp. Tox. : Aspiration hazard  
Eye Irrit. : Eye irritation  
Flam. Liq. : Flammable liquids  
Skin Corr. : Skin corrosion  
STOT SE : Specific target organ toxicity - single exposure  
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values  
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.  
2000/39/EC / TWA : Limit Value - eight hours  
DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

#### Sources of key data used to compile the Safety Data Sheet:

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs.

Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Capalac Dickschichtlack Weiß

Version	Revision Date:	Print Date	Date of last issue: -
1.0	18.10.2019	19.10.2019	Date of first issue: 18.10.2019

---

Toxnet - Toxicology Data Network

### Classification of the mixture:

Flam. Liq. 3	H226
STOT SE 3	H336
Aquatic Chronic 3	H412

### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

### REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly. This will be put into practice depending on the register-deadline of the substances involved during the transition period from December 1, 2010 till May 31, 2018.

DE / EN