

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Disbocolor 781 sm. RAL 9006

Version	Revision Date:	Print Date	Date of last issue: 10.03.2020
1.1	01.09.2022	02.09.2022	Date of first issue: 10.03.2020

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Capalac Disbocolor 781 sm. RAL 9006

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Spray paint

Recommended restrictions : within adequate application - none on use

#### 1.3 Details of the supplier of the safety data sheet

Company : Caparol Farben Lacke GmbH  
Roßdörfer Straße 50  
64372 Ober-Ramstadt

Telephone : +496154710  
Telefax : +4961547170222  
E-mail address Responsible/issuing person : msds@dr-rmi.com

#### 1.4 Emergency telephone

Emergency telephone 1 : +49613284463 GBK GmbH

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.

#### 2.2 Label elements

##### Labeling (REGULATION (EC) No 1272/2008)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Disbocolor 781 sm. RAL 9006

Version	Revision Date:	Print Date	Date of last issue: 10.03.2020
1.1	01.09.2022	02.09.2022	Date of first issue: 10.03.2020

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary Statements : P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.

### Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P260 Do not breathe vapours/ spray.  
P271 Use only outdoors or in a well-ventilated area.

### Storage:

P405 Store locked up.  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

### Hazardous ingredients which must be listed on the label:

acetone  
n-butyl acetate

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Disbocolor 781 sm. RAL 9006

Version	Revision Date:	Print Date	Date of last issue: 10.03.2020
1.1	01.09.2022	02.09.2022	Date of first issue: 10.03.2020

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
acetone	67-64-1 200-662-2 606-001-00-8 01-2119471330-49	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066	>= 20 - < 30
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	>= 1 - < 10
xylene	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 Asp. Tox. 1; H304 STOT RE 2; H373	>= 1 - < 10
ethanol	64-17-5 200-578-6 603-002-00-5 01-2119457610-43	Eye Irrit. 2; H319 Flam. Liq. 2; H225	>= 1 - < 10
Substances with a workplace exposure limit :			
dimethyl ether	115-10-6 204-065-8 603-019-00-8 01-2119472128-37	Flam. Gas 1A; H220 Press. Gas Compr. Gas; H280	>= 20 - < 30
propane	74-98-6 200-827-9 601-003-00-5 01-2119486944-21	Flam. Gas 1A; H220 Press. Gas Compr. Gas; H280	>= 10 - < 20
butane	106-97-8 203-448-7 601-004-00-0 01-2119474691-32	Flam. Gas 1A; H220 Press. Gas Compr. Gas; H280	>= 1 - < 10
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 607-195-00-7 01-2119475791-29	Flam. Liq. 3; H226	>= 1 - < 10

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Disbocolor 781 sm. RAL 9006

Version	Revision Date:	Print Date	Date of last issue: 10.03.2020
1.1	01.09.2022	02.09.2022	Date of first issue: 10.03.2020

isobutane	75-28-5 200-857-2 601-004-00-0 01-2119485395-27	Flam. Gas 1A; H220 Press. Gas Compr. Gas; H280	>= 1 - < 10
aluminium powder (stabilised)	7429-90-5 231-072-3 013-002-00-1 01-2119529243-45	Flam. Sol. 1; H228 Water-react 2; H261	>= 1 - < 10

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first-aid measures

- General advice : Never give anything by mouth to an unconscious person.  
If you feel unwell, seek medical advice (show the label where possible).  
Move out of dangerous area.  
First aider needs to protect himself.
- If inhaled : If symptoms persist, call a physician.  
Move to fresh air.
- In case of skin contact : Do NOT use solvents or thinners.  
In case of contact, immediately flush skin with soap and plenty of water.  
Take off all contaminated clothing immediately.
- In case of eye contact : If eye irritation persists: Get medical advice/ attention.  
IF IN EYES: Rinse cautiously with water for several minutes.  
Remove contact lenses, if present and easy to do. Continue rinsing.
- If swallowed : Seek medical advice.  
Clean mouth with water and drink afterwards plenty of water.  
If swallowed, DO NOT induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Repeated exposure may cause skin dryness or cracking.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No information available.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Disbocolor 781 sm. RAL 9006

Version	Revision Date:	Print Date	Date of last issue: 10.03.2020
1.1	01.09.2022	02.09.2022	Date of first issue: 10.03.2020

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media : None known.

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Cool closed containers exposed to fire with water spray.  
In case of fire hazardous decomposition products may be produced such as:  
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

#### 5.3 Advice for firefighters

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
Standard procedure for chemical fires.  
In the event of fire and/or explosion do not breathe fumes.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Do not get in eyes, on skin, or on clothing.  
Ensure adequate ventilation.  
Remove all sources of ignition.

#### 6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.  
Do not flush into surface water or sanitary sewer system.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Disbocolor 781 sm. RAL 9006

Version	Revision Date:	Print Date	Date of last issue: 10.03.2020
1.1	01.09.2022	02.09.2022	Date of first issue: 10.03.2020

### 6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.

, For personal protection see section 8., For disposal considerations see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Provide sufficient air exchange and/or exhaust in work rooms.

In addition, the current technical information for this product and its application on [www.caparol.com](http://www.caparol.com) must be observed.

Advice on protection against fire and explosion : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hygiene measures : Avoid contact with the skin and the eyes. Wash hands before eating, drinking, or smoking. Do not eat, drink or smoke when using this product.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in accordance with the particular national regulations.  
Store in original container. Store between 41 and 77 °F in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510) : 2B, Aerosol cans and lighters

### 7.3 Specific end use(s)

Specific use(s) : This information is not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
acetone	67-64-1	TWA	500 ppm 1.210 mg/m <sup>3</sup>	2000/39/EC
Further information: Indicative				

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Disbocolor 781 sm. RAL 9006

Version 1.1      Revision Date: 01.09.2022      Print Date 02.09.2022      Date of last issue: 10.03.2020  
Date of first issue: 10.03.2020

		AGW	500 ppm 1.200 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 2;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
dimethyl ether	115-10-6	TWA	1.000 ppm 1.920 mg/m <sup>3</sup>	2000/39/EC
	Further information: Indicative			
		AGW	1.000 ppm 1.900 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 8;(II)			
	Further information: European Union (The EU has established a limit value: deviations in value and peak limit are possible), Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
propane	74-98-6	AGW	1.000 ppm 1.800 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 4;(II)			
	Further information: Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
butane	106-97-8	AGW	1.000 ppm 2.400 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 4;(II)			
	Further information: Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
n-butyl acetate	123-86-4	AGW	62 ppm 300 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 2;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child, Commission for dangerous substances			
2-methoxy-1-methylethyl acetate	108-65-6	STEL	100 ppm 550 mg/m <sup>3</sup>	2000/39/EC
	Further information: Indicative, Identifies the possibility of significant uptake through the skin			
		TWA	50 ppm 275 mg/m <sup>3</sup>	2000/39/EC
	Further information: Indicative, Identifies the possibility of significant uptake through the skin			
		AGW	50 ppm 270 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 1;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child, European Union (The EU has established a limit value: deviations in value and peak limit are possible), Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Disbocolor 781 sm. RAL 9006

Version 1.1      Revision Date: 01.09.2022      Print Date: 02.09.2022      Date of last issue: 10.03.2020  
Date of first issue: 10.03.2020

isobutane	75-28-5	AGW	1.000 ppm 2.400 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 4;(II)			
	Further information: Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
aluminium powder (stabilised)	7429-90-5	AGW (Inhalable fraction)	10 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 2;(II)			
		AGW (Alveolate fraction)	1,25 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 2;(II)			
xylene	1330-20-7	TWA	50 ppm 221 mg/m <sup>3</sup>	2000/39/EC
	Further information: Indicative, Identifies the possibility of significant uptake through the skin			
		STEL	100 ppm 442 mg/m <sup>3</sup>	2000/39/EC
	Further information: Indicative, Identifies the possibility of significant uptake through the skin			
		AGW	100 ppm 440 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: Skin absorption, European Union (The EU has established a limit value: deviations in value and peak limit are possible), Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
ethanol	64-17-5	AGW	200 ppm 380 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 4;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child, Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
acetone	67-64-1	Acetone: 80 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903
aluminium powder (stabilised)	7429-90-5	Aluminum: 50 µg/g creatinine (Urine)	In case of long-term exposure: after more than one shift	TRGS 903
xylene	1330-20-7	xylene: 1,5 mg/l (Blood)	Immediately after exposure or after working hours	TRGS 903
		methylhippuric acid (all isomers): 2 g/l (Urine)	Immediately after exposure or after working hours	TRGS 903



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Disbocolor 781 sm. RAL 9006

Version  
1.1

Revision Date:  
01.09.2022

Print Date  
02.09.2022

Date of last issue: 10.03.2020  
Date of first issue: 10.03.2020

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of exposure	Potential health effects	Value
acetone	Consumers	Inhalation	Long-term systemic effects	200,00 mg/m <sup>3</sup>
	Consumers	Ingestion	Long-term systemic effects	62,00 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	62,00 mg/kg bw/day
	Workers	Inhalation	Acute local effects	2420,00 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	1210,00 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	186,00 mg/kg bw/day
dimethyl ether	Consumers	Inhalation	Long-term systemic effects	471,00 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	1894,00 mg/m <sup>3</sup>
n-butyl acetate	Workers	Inhalation	Long-term systemic effects	48,00 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	600,00 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	300 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	600 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	7,00 mg/kg bw/day
	Workers	Skin contact	Acute systemic effects	11 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	12,00 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	35,7 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	300 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	3,40 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	6 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	2 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	2 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	275,00 mg/m <sup>3</sup>
2-methoxy-1-methylethyl acetate	Workers	Inhalation	Acute local effects	550,00 mg/m <sup>3</sup>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Disbocolor 781 sm. RAL 9006

Version 1.1      Revision Date: 01.09.2022      Print Date 02.09.2022      Date of last issue: 10.03.2020  
Date of first issue: 10.03.2020

	Workers	Skin contact	Long-term systemic effects	796,00 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	33,00 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	33,00 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	320,00 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	36,00 mg/kg bw/day
aluminium powder (stabilised)	Consumers	Ingestion	Long-term systemic effects	7,90 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	3,95 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	3,72 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	3,72 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	3,72 mg/m <sup>3</sup>
xylene	Consumers	Inhalation	Acute local effects	174,00 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	108,00 mg/kg bw/day
	Consumers	Inhalation	Acute systemic effects	174,00 mg/m <sup>3</sup>
	Consumers	Ingestion	Long-term systemic effects	1,60 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	14,80 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	289,00 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	289,00 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	77,00 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	180,00 mg/kg bw/day
ethanol	Consumers	Inhalation	Acute local effects	950,00 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	1900,00 mg/m <sup>3</sup>

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
acetone	Fresh water sediment	30,4 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 mg/l
	Sea sediment	3,04 mg/kg dry weight (d.w.)
	Fresh water	10,6 mg/l
	Sea water	1,06 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Disbocolor 781 sm. RAL 9006

Version 1.1      Revision Date: 01.09.2022      Print Date: 02.09.2022      Date of last issue: 10.03.2020  
Date of first issue: 10.03.2020

	Intermittent use/release	21 mg/l
	Soil	29,5 mg/kg dry weight (d.w.)
dimethyl ether	Sea sediment	0,069 mg/kg dry weight (d.w.)
	Intermittent use/release	1,549 mg/l
	Sea water	0,016 mg/l
	Fresh water	0,155 mg/l
	Sewage treatment plant	160 mg/l
	Fresh water sediment	0,681 mg/kg dry weight (d.w.)
	Soil	0,045 mg/kg dry weight (d.w.)
n-butyl acetate	Fresh water sediment	0,981 mg/kg dry weight (d.w.)
	Soil	0,0903 mg/kg dry weight (d.w.)
	Sea sediment	0,0981 mg/kg dry weight (d.w.)
	Intermittent use/release	0,36 mg/l
	Sewage treatment plant	35,6 mg/l
	Sea water	0,018 mg/l
	Fresh water	0,18 mg/l
2-methoxy-1-methylethyl acetate	Fresh water	0,635 mg/l
	Intermittent use/release	6,35 mg/l
	Sea sediment	0,329 mg/kg dry weight (d.w.)
	Fresh water sediment	3,29 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 mg/l
	Sea water	0,0635 mg/l
	Soil	0,29 mg/kg dry weight (d.w.)
aluminium powder (stabilised)	Sewage treatment plant	20 mg/l
	Fresh water	74,9 µg/l
xylene	Fresh water	0,327 mg/l
	Intermittent use/release	0,327 mg/l
	Soil	2,31 mg/kg dry weight (d.w.)
	Fresh water sediment	12,46 mg/kg dry weight (d.w.)
	Sewage treatment plant	6,58 mg/l
	Sea water	0,327 mg/l
	Sea sediment	12,46 mg/kg dry weight (d.w.)
ethanol	Sea sediment	2,9 mg/kg dry weight (d.w.)
	Sewage treatment plant	580 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Disbocolor 781 sm. RAL 9006

Version 1.1      Revision Date: 01.09.2022      Print Date 02.09.2022      Date of last issue: 10.03.2020  
Date of first issue: 10.03.2020

	Fresh water sediment	3,6 mg/kg dry weight (d.w.)
	Sea water	0,79 mg/l
	Soil	0,63 mg/kg dry weight (d.w.)
	Intermittent use/release	2,75 mg/l
	Fresh water	0,96 mg/l
	Secondary Poisoning	0,72 g/kg food

### 8.2 Exposure controls

#### Personal protective equipment

Eye protection : German trade association rules - BGR 192 Eye protection  
Tightly fitting safety goggles

#### Hand protection

Material : Nitrile rubber  
Glove thickness : 0,2 mm  
Protective index : Class 3

Remarks : Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Before removing gloves clean them with soap and water. Wear suitable gloves tested to EN374.  
German trade association leaflet: Carry gloves (ZH 1/706)

#### Skin and body protection

: Safety shoes  
Long sleeved clothing  
  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.  
  
Skin should be washed after contact.  
  
During spray application: impervious clothing

#### Respiratory protection

: German trade association rules - BGR 190 Breathing protection  
  
During spray application: Do not breathe spray dust. Use A2/P2 combination filter for paint spraying.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state : aerosol

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Disbocolor 781 sm. RAL 9006

Version	Revision Date:	Print Date	Date of last issue: 10.03.2020
1.1	01.09.2022	02.09.2022	Date of first issue: 10.03.2020

Color	:	No data available
Odor	:	No data available
Odor Threshold	:	Not relevant
Melting point/freezing point	:	not determined
Boiling point/boiling range	:	not determined
Flammability	:	Sustains combustion
Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower flammability limit	:	not determined
Flash point	:	Not applicable
Autoignition temperature	:	not determined
Decomposition temperature	:	Not applicable
pH	:	6,95 Concentration: 10 %
Viscosity	:	
Viscosity, dynamic	:	No data available
Solubility(ies)	:	
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	not determined
Vapor pressure	:	not determined
Relative density	:	not determined
Density	:	0,74 g/cm <sup>3</sup>
Relative vapor density	:	not determined

### 9.2 Other information

Explosives	:	Not applicable
------------	---	----------------

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Disbocolor 781 sm. RAL 9006

Version	Revision Date:	Print Date	Date of last issue: 10.03.2020
1.1	01.09.2022	02.09.2022	Date of first issue: 10.03.2020

Oxidizing properties : Not applicable

Evaporation rate : Not applicable

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

No decomposition if stored and applied as directed.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Vapors may form explosive mixture with air.  
Hazardous decomposition products formed under fire conditions.

#### 10.4 Conditions to avoid

Conditions to avoid : Risk of bursting.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.  
Protect from frost, heat and sunlight.

Risk of bursting.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

#### 10.5 Incompatible materials

Materials to avoid : Incompatible with acids and bases.  
Incompatible with oxidizing agents.

#### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

Not classified based on available information.

##### Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20000 ppm  
Exposure time: 4 h  
Test atmosphere: gas

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Disbocolor 781 sm. RAL 9006

Version	Revision Date:	Print Date	Date of last issue: 10.03.2020
1.1	01.09.2022	02.09.2022	Date of first issue: 10.03.2020

Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

### Components:

#### **acetone:**

Acute oral toxicity : LD50 Oral (Rat): 5.800 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 20.000 mg/kg

#### **n-butyl acetate:**

Acute oral toxicity : LD50 Oral (Rat): 14.000 mg/kg

#### **xylene:**

Acute inhalation toxicity : LC50 (Rat): 5000 ppm  
Exposure time: 4 h  
Test atmosphere: gas

#### **Skin corrosion/irritation**

Repeated exposure may cause skin dryness or cracking.

#### **Serious eye damage/eye irritation**

Causes serious eye irritation.

#### **Respiratory or skin sensitization**

##### **Skin sensitization**

Not classified based on available information.

##### **Respiratory sensitization**

Not classified based on available information.

##### **Germ cell mutagenicity**

Not classified based on available information.

##### **Carcinogenicity**

Not classified based on available information.

##### **Reproductive toxicity**

Not classified based on available information.

##### **STOT-single exposure**

May cause drowsiness or dizziness.

##### **STOT-repeated exposure**

Not classified based on available information.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Disbocolor 781 sm. RAL 9006

Version	Revision Date:	Print Date	Date of last issue: 10.03.2020
1.1	01.09.2022	02.09.2022	Date of first issue: 10.03.2020

### Aspiration toxicity

Not classified based on available information.

### 11.2 Information on other hazards

#### Endocrine disrupting properties

##### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

#### Components:

##### **acetone:**

Partition coefficient: n-octanol/water : log Pow: -0,24 (20 °C)

##### **n-butyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 2,3 (25 °C)  
Method: OECD Test Guideline 117

##### **2-methoxy-1-methylethyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 1,2 (20 °C)  
Method: OECD Test Guideline 117

### 12.4 Mobility in soil

No data available



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Disbocolor 781 sm. RAL 9006

Version	Revision Date:	Print Date	Date of last issue: 10.03.2020
1.1	01.09.2022	02.09.2022	Date of first issue: 10.03.2020

### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : .  
Waste should not be disposed of via wastewater.

Contaminated packaging : Only completely emptied containers should be given for recycling.

Waste Code : used product  
080111\*, waste paint and varnish containing organic solvents or other dangerous substances

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADN : UN 1950  
ADR : UN 1950  
RID : UN 1950

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Disbocolor 781 sm. RAL 9006

Version	Revision Date:	Print Date	Date of last issue: 10.03.2020
1.1	01.09.2022	02.09.2022	Date of first issue: 10.03.2020

**IMDG** : UN 1950

**IATA** : UN 1950

### 14.2 UN proper shipping name

**ADN** : AEROSOLS

**ADR** : AEROSOLS

**RID** : AEROSOLS

**IMDG** : AEROSOLS

**IATA** : Aerosols, flammable

### 14.3 Transport hazard class(es)

**ADN** : 2

**ADR** : 2

**RID** : 2

**IMDG** : 2.1

**IATA** : 2.1

### 14.4 Packing group

#### **ADN**

Packing group : Not assigned by regulation

Classification Code : 5F

Labels : 2.1

#### **ADR**

Packing group : Not assigned by regulation

Classification Code : 5F

Labels : 2.1

Tunnel restriction code : (D)

#### **RID**

Packing group : Not assigned by regulation

Classification Code : 5F

Hazard Identification Number : 23

Labels : 2.1

#### **IMDG**

Packing group : Not assigned by regulation

Labels : 2.1

EmS Code : F-D, S-U

#### **IATA (Cargo)**

Packing instruction (cargo aircraft) : 203

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Disbocolor 781 sm. RAL 9006

Version	Revision Date:	Print Date	Date of last issue: 10.03.2020
1.1	01.09.2022	02.09.2022	Date of first issue: 10.03.2020

### IATA (Passenger)

Packing instruction (passenger aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

### 14.5 Environmental hazards

#### ADN

Environmentally hazardous : no

#### ADR

Environmentally hazardous : no

#### RID

Environmentally hazardous : no

#### IMDG

Marine pollutant : no

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59). : This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be generated.

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Disbocolor 781 sm. RAL 9006

Version	Revision Date:	Print Date	Date of last issue: 10.03.2020
1.1	01.09.2022	02.09.2022	Date of first issue: 10.03.2020

REACH - List of substances subject to authorisation : None  
(Annex XIV)

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. Please see [https://ec.europa.eu/home-affairs/sites/homeaffairs/files/what-we-do/policies/crisis-and-terrorism/explosives/explosives-precursors/docs/list\\_of\\_competent\\_authorities\\_and\\_national\\_contact\\_points\\_en.pdf](https://ec.europa.eu/home-affairs/sites/homeaffairs/files/what-we-do/policies/crisis-and-terrorism/explosives/explosives-precursors/docs/list_of_competent_authorities_and_national_contact_points_en.pdf)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P3a FLAMMABLE AEROSOLS

18 Liquefied extremely flammable gases (including LPG) and natural gas

Water hazard class (Germany) : 2 significantly water endangering  
Volatile organic compounds : < 93 %  
< 690 g/l

### Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

## 15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

## SECTION 16: Other information

### Full text of H-Statements

H220 : Extremely flammable gas.  
H225 : Highly flammable liquid and vapor.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Disbocolor 781 sm. RAL 9006

Version	Revision Date:	Print Date	Date of last issue: 10.03.2020
1.1	01.09.2022	02.09.2022	Date of first issue: 10.03.2020

H226 : Flammable liquid and vapor.  
H228 : Flammable solid.  
H261 : In contact with water releases flammable gas.  
H280 : Contains gas under pressure; may explode if heated.  
H304 : May be fatal if swallowed and enters airways.  
H312 : Harmful in contact with skin.  
H315 : Causes skin irritation.  
H319 : Causes serious eye irritation.  
H332 : Harmful if inhaled.  
H335 : May cause respiratory irritation.  
H336 : May cause drowsiness or dizziness.  
H373 : May cause damage to organs through prolonged or repeated exposure.  
EUH066 : Repeated exposure may cause skin dryness or cracking.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Asp. Tox. : Aspiration hazard  
Eye Irrit. : Eye irritation  
Flam. Gas : Flammable gases  
Flam. Liq. : Flammable liquids  
Flam. Sol. : Flammable solids  
Press. Gas : Gases under pressure  
Skin Irrit. : Skin irritation  
STOT RE : Specific target organ toxicity - repeated exposure  
STOT SE : Specific target organ toxicity - single exposure  
Water-react : Substances and mixtures which in contact with water emit flammable gases  
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values  
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.  
TRGS 903 : TRGS 903 - Biological limit values  
2000/39/EC / TWA : Limit Value - eight hours  
2000/39/EC / STEL : Short term exposure limit  
DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Disbocolor 781 sm. RAL 9006

Version	Revision Date:	Print Date	Date of last issue: 10.03.2020
1.1	01.09.2022	02.09.2022	Date of first issue: 10.03.2020

### Further information

#### **Other information:**

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

#### **Sources of key data used to compile the Material Safety Data Sheet:**

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

#### **Classification of the mixture:**

Aerosol 1	H222, H229
Eye Irrit. 2	H319
STOT SE 3	H336

#### **Classification procedure:**

Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

### REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Capalac Disbocolor 781 sm. RAL 9006

Version	Revision Date:	Print Date	Date of last issue: 10.03.2020
1.1	01.09.2022	02.09.2022	Date of first issue: 10.03.2020

---

DE / EN