

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboTHAN 449 RAL7035

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2021
4.0	16.02.2023	6010632	Date of first issue: 10.12.2019

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : DisboTHAN 449 RAL7035

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Polyurethane-resin-based coating material, solvent-containing

Recommended restrictions on use : within adequate application - none

#### 1.3 Details of the supplier of the safety data sheet

Company : Disbon GmbH  
Roßdörfer Straße 50  
64372 Ober-Ramstadt

Telephone : +496154710  
Telefax : +4961547170222

E-mail address Responsible/issuing person : msds@dr-rmi.com

#### 1.4 Emergency telephone

Emergency telephone 1 : +49613284463 GBK GmbH

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapor.
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboTHAN 449 RAL7035

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2021
4.0	16.02.2023	6010632	Date of first issue: 10.12.2019

### 2.2 Label elements

#### Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H226 Flammable liquid and vapor.  
H317 May cause an allergic skin reaction.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 Do not breathe vapours/ spray.  
P262 Do not get in eyes, on skin, or on clothing.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

#### **Response:**

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

#### **Hazardous ingredients which must be listed on the label:**

Carbonic acid, dimethyl ester, polymer with 1,6-hexanediol, 5-isocyanato-1-(isocyanatomethyl)-1,3,3-trimethylcyclohexane and 2-oxepanone  
2-methoxy-1-methylethyl acetate  
1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate  
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

#### **Additional Labeling**

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

"As from 24 August 2023 adequate training is required before industrial or professional use."

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboTHAN 449 RAL7035

Version 4.0      Revision Date: 16.02.2023      SDS Number: 6010632      Date of last issue: 06.09.2021  
Date of first issue: 10.12.2019

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Carbonic acid, dimethyl ester, polymer with 1,6-hexanediol, 5-isocyanato-1-(isocyanatomethyl)-1,3,3-trimethylcyclohexane and 2-oxepanone	426822-87-9	Skin Sens. 1; H317	>= 30 - < 50
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 607-195-00-7 01-2119475791-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 10 - < 20
1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate	140921-24-0 411-700-4 616-079-00-5 01-2119890830-32, 01-0000015906-63	Skin Sens. 1; H317	>= 10 - < 20
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified	64742-95-6 265-199-0 649-356-00-4 01-2119455851-35, 01-2119486773-24	Flam. Liq. 3; H226 STOT SE 3; H336 STOT SE 3; H335 Asp. Tox. 1; H304 Aquatic Chronic 2; H411 Acute Tox. 4; H332 EUH066	>= 2,5 - < 10
xylene	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315	>= 1 - < 10
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤	13463-67-7 236-675-5 022-006-00-2	Carc. 2; H351	>= 1 - < 10

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboTHAN 449 RAL7035

Version 4.0      Revision Date: 16.02.2023      SDS Number: 6010632      Date of last issue: 06.09.2021  
Date of first issue: 10.12.2019

10 µm]	01-2119489379-17		
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9 223-861-6 615-008-00-5 01-2119490408-31	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 Aquatic Chronic 2; H411 Acute Tox. 3; H331  specific concentration limit Resp. Sens. 1; H334 >= 0,5 % Skin Sens. 1; H317 >= 0,5 %	>= 0,25 - < 0,5

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first-aid measures

- General advice : Show this material safety data sheet to the doctor in attendance.  
When symptoms persist or in all cases of doubt seek medical advice.  
Move out of dangerous area.  
First aider needs to protect himself.  
Never give anything by mouth to an unconscious person.
- If inhaled : Call a physician.  
If breathing is irregular or stopped, administer artificial respiration.  
If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.  
Move to fresh air.
- In case of skin contact : Do NOT use solvents or thinners.  
In case of contact, immediately flush skin with soap and plenty of water.  
Take off all contaminated clothing immediately.
- In case of eye contact : If eye irritation persists: Get medical advice/ attention.  
IF IN EYES: Rinse cautiously with water for several minutes.  
Remove contact lenses, if present and easy to do. Continue

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboTHAN 449 RAL7035

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2021
4.0	16.02.2023	6010632	Date of first issue: 10.12.2019

rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.  
If accidentally swallowed obtain immediate medical attention.  
If swallowed, DO NOT induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

Risks : May cause an allergic skin reaction.  
May cause drowsiness or dizziness.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Foam  
Carbon dioxide (CO<sub>2</sub>)

Unsuitable extinguishing media : Water

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Cool closed containers exposed to fire with water spray.  
In case of fire hazardous decomposition products may be produced such as:  
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

### 5.3 Advice for firefighters

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
Standard procedure for chemical fires.  
In the event of fire and/or explosion do not breathe fumes.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboTHAN 449 RAL7035

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2021
4.0	16.02.2023	6010632	Date of first issue: 10.12.2019

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Do not get in eyes, on skin, or on clothing.  
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.  
Evacuate personnel to safe areas.  
Ensure adequate ventilation.  
Remove all sources of ignition.

#### 6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.  
Do not flush into surface water or sanitary sewer system.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

#### 6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.

, For personal protection see section 8., For disposal considerations see section 13.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Provide sufficient air exchange and/or exhaust in work rooms.  
Contains isocyanates. Please, attend to producer's advice.  
Liquid product may irritate and sensitize skin and respiratory tract and may cause allergic reaction. Do not inhale vapours.  
Take care for sufficient fresh air supply during and after use.  
Product must not be sprayed. Allergics or persons tending to respiratory tract diseases must not be involved in operations with this product.

In addition, the current technical information for this product and its application on [www.caparol.com](http://www.caparol.com) must be observed.

Advice on protection against fire and explosion : Vapors may form explosive mixtures with air. Vapors are heavier than air and may spread along floors. Keep away from

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboTHAN 449 RAL7035

Version 4.0      Revision Date: 16.02.2023      SDS Number: 6010632      Date of last issue: 06.09.2021  
Date of first issue: 10.12.2019

heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hygiene measures : Keep working clothes separately. Remove and wash contaminated clothing before re-use. Avoid contact with the skin and the eyes. Wash hands before eating, drinking, or smoking. Do not eat, drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering eating areas.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Store between 41 and 77 °F in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510) : 3

### 7.3 Specific end use(s)

Specific use(s) : This information is not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2-methoxy-1-methylethyl acetate	108-65-6	STEL	100 ppm 550 mg/m <sup>3</sup>	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
		TWA	50 ppm 275 mg/m <sup>3</sup>	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
		AGW	50 ppm 270 mg/m <sup>3</sup>	DE TRGS 900
		Peak-limit category: 1;(I)		
		Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child		
xylene	1330-20-7	TWA	50 ppm 221 mg/m <sup>3</sup>	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboTHAN 449 RAL7035

Version 4.0      Revision Date: 16.02.2023      SDS Number: 6010632      Date of last issue: 06.09.2021  
Date of first issue: 10.12.2019

		STEL	100 ppm 442 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		AGW	50 ppm 220 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: Skin absorption			
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	AGW (Inhalable fraction)	10 mg/m <sup>3</sup> (Titanium dioxide)	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		AGW (Alveolate fraction)	1,25 mg/m <sup>3</sup> (Titanium dioxide)	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		BM (Alveolar dust fraction)	0,5 mg/m <sup>3</sup>	DE TRGS 527
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9	AGW	0,005 ppm 0,046 mg/m <sup>3</sup>	TRGS 430
	Peak-limit category: 1;=2=(I)			
	Further information: In well-founded cases also a momentary value can be established, that never can be exceeded. This substance will be indicated by = = in combination with an exceeding value., airway sensitizing substance			
		AGW (Vapour and aerosols)	0,005 ppm 0,046 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 1;=2=(I)			
	Further information: In well-found cases also a momentary value can be established, that never can be exceeded. This substance will be indicated by = = in combination with an exceeding value., Substance sensitizing through the respiratory system			

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
xylene	1330-20-7	methylhippuric acid (all isomers): 2.000 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboTHAN 449 RAL7035

Version 4.0      Revision Date: 16.02.2023      SDS Number: 6010632      Date of last issue: 06.09.2021  
Date of first issue: 10.12.2019

Substance name	End Use	Routes of exposure	Potential health effects	Value
2-methoxy-1-methylethyl acetate	Workers	Inhalation	Long-term systemic effects	275,00 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	550,00 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	796,00 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	33,00 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	33,00 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	320,00 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	36,00 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,83 mg/kg bw/day
1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate	Consumers	Skin contact	Long-term systemic effects	8,30 mg/kg bw/day
	Consumers	Inhalation	Acute local effects	174,00 mg/m <sup>3</sup>
xylene	Consumers	Skin contact	Long-term systemic effects	108,00 mg/kg bw/day
	Consumers	Inhalation	Acute systemic effects	174,00 mg/m <sup>3</sup>
	Consumers	Ingestion	Long-term systemic effects	1,60 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	14,80 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	289,00 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	289,00 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	77,00 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	180,00 mg/kg bw/day
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	Consumers	Ingestion	Long-term systemic effects	700,00 mg/kg bw/day
	Workers	Inhalation	Long-term local effects	10,00 mg/m <sup>3</sup>
3-isocyanatomethyl-3,5,5-	Workers	Inhalation	Acute local effects	0,05 mg/m <sup>3</sup>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboTHAN 449 RAL7035

Version 4.0      Revision Date: 16.02.2023      SDS Number: 6010632      Date of last issue: 06.09.2021  
Date of first issue: 10.12.2019

trimethylcyclohexyl isocyanate				
	Workers	Inhalation	Long-term local effects	0,05 mg/m3

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2-methoxy-1-methylethyl acetate	Fresh water	0,635 mg/l
	Intermittent use/release	6,35 mg/l
	Sea sediment	0,329 mg/kg dry weight (d.w.)
	Fresh water sediment	3,29 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 mg/l
	Sea water	0,0635 mg/l
1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate	Soil	0,29 mg/kg dry weight (d.w.)
	Sea water	0,0029 mg/l
	Fresh water sediment	111,2 mg/kg dry weight (d.w.)
	Sewage treatment plant	35 mg/l
	Intermittent use/release	0,29 mg/l
	Soil	22,2 mg/kg dry weight (d.w.)
xylene	Sea sediment	11,1 mg/kg dry weight (d.w.)
	Fresh water	0,029 mg/l
	Fresh water	0,327 mg/l
	Intermittent use/release	0,327 mg/l
	Soil	2,31 mg/kg dry weight (d.w.)
	Fresh water sediment	12,46 mg/kg dry weight (d.w.)
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq$ 10 $\mu$ m]	Sewage treatment plant	6,58 mg/l
	Sea water	0,327 mg/l
	Sea sediment	12,46 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 mg/l
	Fresh water	0,184 mg/l
	Soil	100 mg/kg dry weight (d.w.)
	Sea water	0,0184 mg/l
	Fresh water sediment	1000 mg/kg dry weight (d.w.)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboTHAN 449 RAL7035

Version 4.0      Revision Date: 16.02.2023      SDS Number: 6010632      Date of last issue: 06.09.2021  
Date of first issue: 10.12.2019

	Sea sediment	100 mg/kg dry weight (d.w.)
	Intermittent use/release	0,193 mg/l
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	Sea water	0,006 mg/l
	Fresh water	0,06 mg/l
	Sewage treatment plant	10,6 mg/l
	Fresh water sediment	218,92 mg/kg dry weight (d.w.)
	Intermittent use/release	0,04 mg/l
	Soil	44,01 mg/kg dry weight (d.w.)
	Sea sediment	21,89 mg/kg dry weight (d.w.)

### 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection : DGUV Regulation 112-192 - Use of eye and face protection

Goggles

Hand protection

Material : butyl-rubber  
Glove thickness : 0,3 mm  
Protective index : Class 3  
Wearing time : 30 min

Remarks : Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Before removing gloves clean them with soap and water. Wear suitable gloves tested to EN374.  
DGUV Regulation 112-195 - Use of protective gloves

Skin and body protection : Safety shoes  
Long sleeved clothing  
Remove and wash contaminated clothing before re-use.  
Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, disposable suits) to avoid exposed skin surfaces.

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

Respiratory protection : When exceeding the WEL substance Limit a respiratory filter Type A is necessary. Class 1 or 2 has to be chosen depending on the workplace concentration.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboTHAN 449 RAL7035

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2021
4.0	16.02.2023	6010632	Date of first issue: 10.12.2019

Do not use for spraying.

DGUV Regulation 112-190 - Use of breathing equipment

During spray application: Do not breathe spray dust. Use A2/P2 combination filter for paint spraying.

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Color	:	No data available
Odor	:	No data available
Odor Threshold	:	Not relevant
Melting point/freezing point	:	not determined
Boiling point/boiling range	:	not determined
Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower flammability limit	:	not determined
Flash point	:	> 37 °C
Autoignition temperature	:	not determined
Decomposition temperature	:	Not applicable
pH	:	6,95 Concentration: 10 %
Viscosity	:	
Viscosity, dynamic	:	No data available
Flow time	:	> 60 s at 23 °C Cross section: 6 mm Method: ISO 2431
Solubility(ies)	:	
Water solubility	:	partly miscible

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboTHAN 449 RAL7035

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2021
4.0	16.02.2023	6010632	Date of first issue: 10.12.2019

Partition coefficient: n-octanol/water	:	not determined
Vapor pressure	:	not determined
Relative density	:	not determined
Density	:	1,04 g/cm <sup>3</sup> (20 °C)
Relative vapor density	:	Heavier than air.

### 9.2 Other information

Explosives	:	Not applicable
Oxidizing properties	:	Not applicable
Flammability (liquids)	:	Sustains combustion
Evaporation rate	:	Not applicable

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions	:	Amines and alcohols cause exothermic reactions. Mixture reacts slowly with water resulting in evolution of CO <sub>2</sub> .
---------------------	---	---

### 10.4 Conditions to avoid

Conditions to avoid	:	Exposure to water vapor. Protect from frost, heat and sunlight.
---------------------	---	--

### 10.5 Incompatible materials

Materials to avoid	:	Amines Incompatible with oxidizing agents. Incompatible with acids and bases.
--------------------	---	---

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboTHAN 449 RAL7035

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2021
4.0	16.02.2023	6010632	Date of first issue: 10.12.2019

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

|| Not classified based on available information.

##### Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

##### Skin corrosion/irritation

|| Not classified based on available information.

##### Serious eye damage/eye irritation

|| Not classified based on available information.

##### Respiratory or skin sensitization

##### Skin sensitization

|| May cause an allergic skin reaction.

##### Respiratory sensitization

|| Not classified based on available information.

##### Germ cell mutagenicity

|| Not classified based on available information.

##### Carcinogenicity

|| Not classified based on available information.

##### Reproductive toxicity

|| Not classified based on available information.

##### STOT-single exposure

|| May cause drowsiness or dizziness.

##### STOT-repeated exposure

|| Not classified based on available information.

##### Aspiration toxicity

|| Not classified based on available information.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboTHAN 449 RAL7035

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2021
4.0	16.02.2023	6010632	Date of first issue: 10.12.2019

### 11.2 Information on other hazards

#### Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 12: Ecological information

### 12.1 Toxicity

No data available

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

**Components:**

**2-methoxy-1-methylethyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 1,2 (20 °C)  
Method: OECD Test Guideline 117

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboTHAN 449 RAL7035

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2021
4.0	16.02.2023	6010632	Date of first issue: 10.12.2019

### 12.7 Other adverse effects

**Product:**

Additional ecological information : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Uncured product residues and unpurified packaging should be disposed of as hazardous waste.  
Waste should not be disposed of via wastewater.

Material residues: Allow the basic substance to harden with hardener and dispose of as paint waste.

Contaminated packaging : Only completely emptied containers should be given for recycling.

Waste Code : used product  
080111\*, waste paint and varnish containing organic solvents or other dangerous substances

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADN : UN 1866

ADR : UN 1866

RID : UN 1866

IMDG : UN 1866

IATA : UN 1866

### 14.2 UN proper shipping name

ADN : RESIN SOLUTION

ADR : RESIN SOLUTION

RID : RESIN SOLUTION

IMDG : RESIN SOLUTION  
(2-methoxy-1-methylethyl acetate, Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified)

IATA : Resin solution  
(2-methoxy-1-methylethyl acetate, Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified)



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboTHAN 449 RAL7035

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2021
4.0	16.02.2023	6010632	Date of first issue: 10.12.2019

### 14.3 Transport hazard class(es)

	Class	Subsidiary risks
<b>ADN</b>	: 3	
<b>ADR</b>	: 3	
<b>RID</b>	: 3	
<b>IMDG</b>	: 3	
<b>IATA</b>	: 3	

### 14.4 Packing group

<b>ADN</b>	
Packing group	: III
Classification Code	: F1
Hazard Identification Number	: 30
Labels	: 3
<b>ADR</b>	
Packing group	: III
Classification Code	: F1
Hazard Identification Number	: 30
Labels	: 3
Tunnel restriction code	: (D/E)
<b>RID</b>	
Packing group	: III
Classification Code	: F1
Hazard Identification Number	: 30
Labels	: 3
<b>IMDG</b>	
Packing group	: III
Labels	: 3
EmS Code	: F-E, <u>S-E</u>
<b>IATA (Cargo)</b>	
Packing instruction (cargo aircraft)	: 366
Packing instruction (LQ)	: Y344
Packing group	: III
Labels	: Flammable Liquids
<b>IATA (Passenger)</b>	
Packing instruction (passenger aircraft)	: 355
Packing instruction (LQ)	: Y344
Packing group	: III
Labels	: Flammable Liquids

### 14.5 Environmental hazards

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboTHAN 449 RAL7035

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2021
4.0	16.02.2023	6010632	Date of first issue: 10.12.2019

### ADN

Environmentally hazardous : no

### ADR

Environmentally hazardous : no

### RID

Environmentally hazardous : no

### IMDG

Marine pollutant : no

### 14.6 Special precautions for user

Remarks : ADR: Packages smaller than or equal to 450 liters, not goods/merchandise of Class 3  
IMDG: Packages smaller than or equal to 450 liters, not goods/merchandise of Class 3

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 3

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate  
(Number on list 74)

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59). : This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be generated.

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants : Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboTHAN 449 RAL7035

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2021
4.0	16.02.2023	6010632	Date of first issue: 10.12.2019

tants (recast)

REACH - List of substances subject to authorisation (Annex XIV) : None

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

34 Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Water hazard class (Germany) : WGK 2 obviously hazardous to water  
Classification according VwVwS, Annex 4.

Product code for laquers and paints / Giscode : PU50 PU systems, containing solvents, harmful, sensitising

. : PU50 PU systems, containing solvents, harmful, sensitising

Volatile organic compounds : < 30 %  
< 310 g/l

Directive 2004/42/EC  
< 44 %  
< 460 g/l

### Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

### 15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboTHAN 449 RAL7035

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2021
4.0	16.02.2023	6010632	Date of first issue: 10.12.2019

### SECTION 16: Other information

#### Full text of H-Statements

H226	: Flammable liquid and vapor.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H331	: Toxic if inhaled.
H332	: Harmful if inhaled.
H334	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H351	: Suspected of causing cancer if inhaled.
H411	: Toxic to aquatic life with long lasting effects.
EUH066	: Repeated exposure may cause skin dryness or cracking.

#### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Carc.	: Carcinogenicity
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Resp. Sens.	: Respiratory sensitization
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitization
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
DE TRGS 527	: Germany. TRGS 527 - Activities with nanomaterials
DE TRGS 900	: Germany. TRGS 900 - Occupational exposure limit values.
TRGS 430	: Germany. TRGS 430 - Isocyanates
TRGS 903	: TRGS 903 - Biological limit values
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
DE TRGS 527 / BM	: Assessment scale
DE TRGS 900 / AGW	: Time Weighted Average
TRGS 430 / AGW	: Occupational Exposure Limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safe-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboTHAN 449 RAL7035

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2021
4.0	16.02.2023	6010632	Date of first issue: 10.12.2019

ty and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

### Sources of key data used to compile the Material Safety Data Sheet:

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

#### Classification of the mixture:

Flam. Liq. 3	H226
Skin Sens. 1	H317
STOT SE 3	H336
Aquatic Chronic 3	H412

#### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

## DisboTHAN 449 RAL7035

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2021
4.0	16.02.2023	6010632	Date of first issue: 10.12.2019

---

### REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN