according to Regulation (EC) No. 1907/2006



DE / EN

DisboXID 462 Comp. B

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 2.1 06.02.2023 6008180 Date of first issue: 10.12.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : DisboXID 462 Comp. B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Epoxide-resin-based coating material, totally solid

stance/Mixture

Recommended restrictions

on use

within adequate application - none

1.3 Details of the supplier of the safety data sheet

Company : Disbon GmbH

Roßdörfer Straße 50 64372 Ober-Ramstadt

Telephone : +496154710 Telefax : +4961547170222

E-mail address Responsi-

ble/issuing person

: msds@dr-rmi.com

1.4 Emergency telephone

Emergency telephone 1 : +49613284463 GBK GmbH

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4 H302: Harmful if swallowed.

Acute toxicity, Category 4 H332: Harmful if inhaled.

Skin corrosion, Sub-category 1B H314: Causes severe skin burns and eye damage.

Serious eye damage, Category 1 H318: Causes serious eye damage.

Skin sensitization, Category 1 H317: May cause an allergic skin reaction.

Long-term (chronic) aquatic hazard, Cat-

egory 3

H412: Harmful to aquatic life with long lasting ef-

fects.

according to Regulation (EC) No. 1907/2006



DE / EN

DisboXID 462 Comp. B

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 2.1 06.02.2023 6008180 Date of first issue: 10.12.2019

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms





Signal Word : Danger

Hazard Statements : H302 + H332 Harmful if swallowed or if inhaled.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Supplemental Hazard

Statements

EUH071

Corrosive to the respiratory tract.

Precautionary Statements : Prevention:

P260 Do not breathe vapours/ spray.

P262 Do not get in eyes, on skin, or on clothing.

P280 Wear protective gloves/ protective clothing/ eye protec-

tion/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immedi-

ately all contaminated clothing. Rinse skin with water.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a

POISON CENTER/ doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if pre-

sent and easy to do. Continue rinsing. Immediately call a

POISON CENTER/ doctor.

Hazardous ingredients which must be listed on the label:

benzyl alcohol

m-phenylenebis(methylamine)

3-aminomethyl-3,5,5-trimethylcyclohexylamine

3,6,9-triazaundecamethylenediamine

Fatty acids C18 unsat, reaction products with triethylenetetramine

3-aminopropyldimethylamine

3,6-diazaoctanethylenediamin

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006



DE / EN

DisboXID 462 Comp. B

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 2.1 06.02.2023 6008180 Date of first issue: 10.12.2019

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Epoxide-resin-based coating material, totally solid

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
benzyl alcohol	100-51-6 202-859-9 603-057-00-5 01-2119492630-38	Acute Tox. 4; H302 Acute Tox. 4; H332	>= 30 - < 50
3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2 220-666-8 612-067-00-9 01-2119514687-32	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Chronic 3; H412 specific concentration limit Skin Sens. 1A; H317 >= 0,001 % Acute toxicity estimate Acute oral toxicity: 1.030 mg/kg	>= 10 - < 20
m-phenylenebis(methylamine)	1477-55-0 216-032-5 01-2119480150-50	Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Corr. 1B; H314 Skin Sens. 1; H317 Aquatic Chronic 3;	>= 10 - < 20

according to Regulation (EC) No. 1907/2006



DE / EN

DisboXID 462 Comp. B

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 2.1 06.02.2023 6008180 Date of first issue: 10.12.2019

		H412 EUH071	
3,6,9- triazaundecamethylenediamine	112-57-2 203-986-2 612-060-00-0	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1B; H314 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 5 - < 10
2,4,6- tris(dimethylaminomethyl)phenol	90-72-2 202-013-9 603-069-00-0 01-2119560597-27	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2; H319	>= 1 - < 10
Fatty acids C18 unsat, reaction products with triethylenetetramine	1226892-44-9 01-2119490750-36	Skin Corr. 1C; H314 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1	>= 1 - < 2,5
3-aminopropyldimethylamine	109-55-7 203-680-9 612-061-00-6 01-2119486842-27	Flam. Liq. 3; H226 Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1B; H314 Skin Sens. 1; H317	>=1-<3
3,6-diazaoctanethylenediamin	112-24-3 203-950-6 612-059-00-5	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1B; H314 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 1 - < 2,5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice : Never give anything by mouth to an unconscious person.

If you feel unwell, seek medical advice (show the label where

possible).

Move out of dangerous area. First aider needs to protect himself.

according to Regulation (EC) No. 1907/2006



DE / EN

DisboXID 462 Comp. B

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 06.02.2023 6008180 Date of first issue: 10.12.2019 2.1

If inhaled Move to fresh air.

In case of skin contact Do NOT use solvents or thinners.

In case of contact, immediately flush skin with soap and plenty

of water.

Take off all contaminated clothing immediately.

IF IN EYES: Rinse cautiously with water for several minutes. In case of eye contact

> Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ phy-

sician.

If swallowed Call a physician.

Clean mouth with water and drink afterwards plenty of water.

If swallowed, DO NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Risks Harmful if swallowed or if inhaled.

> May cause an allergic skin reaction. Causes serious eye damage. Corrosive to the respiratory tract.

Causes severe burns.

4.3 Indication of any immediate medical attention and special treatment needed

No information available. **Treatment**

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Foam

Carbon dioxide (CO2)

Unsuitable extinguishing

media

None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire

fighting

Cool closed containers exposed to fire with water spray. Hazardous decomposition products formed under fire condi-

tions.

5.3 Advice for firefighters

for fire-fighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

according to Regulation (EC) No. 1907/2006



DE / EN

DisboXID 462 Comp. B

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 2.1 06.02.2023 6008180 Date of first issue: 10.12.2019

Further information : Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Standard procedure for chemical fires.

In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Do not get in eyes, on skin, or on clothing.

When workers are facing concentrations above the exposure

limit they must use appropriate certified respirators.

Ensure adequate ventilation. Remove all sources of ignition.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Do not flush into surface water or sanitary sewer system.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.

, For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.

Avoid exceeding the given occupational exposure limits (see

section 8).

Provide sufficient air exchange and/or exhaust in work rooms.

In addition, the current technical information for this product and its application on www.caparol.com must be observed.

Advice on protection against

fire and explosion

The product is flammable but not readily ignited.

Hygiene measures : Avoid contact with the skin and the eyes. Wash hands before

according to Regulation (EC) No. 1907/2006



DE / EN

DisboXID 462 Comp. B

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 2.1 06.02.2023 6008180 Date of first issue: 10.12.2019

eating, drinking, or smoking. Do not eat, drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering eating areas.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Store in original container. Store between 41 and 77 °F in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510) : 8A

7.3 Specific end use(s)

Specific use(s) : This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
benzyl alcohol	100-51-6	AGW (Vapour and aerosols)	5 ppm 22 mg/m3	DE TRGS 900
	Peak-limit category: 2;(I)			
	Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of expo-	Potential health ef- fects	Value
benzyl alcohol	Consumers	Skin contact	Acute systemic effects	20,00 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	4,00 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	5,40 mg/m3
	Consumers	Skin contact	Long-term systemic effects	4,00 mg/kg bw/day
	Consumers	Ingestion	Acute systemic ef- fects	20,00 mg/kg bw/day
	Consumers	Inhalation	Acute systemic effects	27,00 mg/m3
	Workers	Inhalation	Acute systemic ef- fects	110,00 mg/m3
	Workers	Inhalation	Long-term systemic	22,00 mg/m3

according to Regulation (EC) No. 1907/2006



DE / EN

DisboXID 462 Comp. B

VersionRevision Date:SDS Number:Date of last issue: 11.01.20232.106.02.20236008180Date of first issue: 10.12.2019

			effects	
	Workers	Skin contact	Acute systemic ef-	40,00 mg/kg
			fects	bw/day
	Workers	Skin contact	Long-term systemic	8,00 mg/kg
			effects	bw/day
m- phe- nylenebis(methylamin e)	Workers	Inhalation	Long-term systemic effects	1,20 mg/m3
	Workers	Inhalation	Long-term local ef- fects	0,20 mg/m3
	Workers	Skin contact	Long-term systemic effects	0,33 mg/kg bw/day
3-aminomethyl-3,5,5- trimethylcyclohexyla- mine	Consumers	Ingestion	Long-term systemic effects	0,53 mg/kg bw/day
	Workers	Inhalation	Acute local effects	0,07 mg/m3
	Workers	Inhalation	Long-term local ef- fects	0,07 mg/m3
Fatty acids C18 unsat, reaction products with triethylenetetramine	Consumers	Inhalation	Long-term systemic effects	0,87 mg/m3
	Consumers	Ingestion	Long-term systemic effects	0,25 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	0,25 mg/kg bw/day
	Workers	Skin contact	Long-term systemic effects	0,42 mg/kg bw/day
3- aminopropyldimethyl- amine	Workers	Inhalation	Acute systemic effects	9,80 mg/m3
	Workers	Inhalation	Long-term systemic effects	4,90 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

	` ,	•
Substance name	Environmental Compartment	Value
benzyl alcohol	Sewage treatment plant	39 mg/l
	Fresh water	1 mg/l
	Sea sediment	0,527 mg/kg dry weight (d.w.)
	Sea water	0,1 mg/l
	Fresh water sediment	5,27 mg/kg dry weight (d.w.)
	Soil	0,456 mg/kg dry weight (d.w.)
	Intermittent use/release	2,3 mg/l
m-phenylenebis(methylamine)	Soil	0,045 mg/kg dry weight (d.w.)

according to Regulation (EC) No. 1907/2006



DE / EN

DisboXID 462 Comp. B

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 2.1 06.02.2023 6008180 Date of first issue: 10.12.2019

	Sewage treatment plant	10 mg/l
	Sea sediment	0,043 mg/kg dry
		weight (d.w.)
	Fresh water sediment	0,43 mg/kg dry
		weight (d.w.)
	Fresh water	0,094 mg/l
	Intermittent use/release	0,152 mg/l
	Sea water	0,0094 mg/l
3-aminomethyl-3,5,5-	Sea sediment	0,578 mg/kg dry
trimethylcyclohexylamine		weight (d.w.)
	Fresh water sediment	5,784 mg/kg dry
		weight (d.w.)
	Fresh water	0,06 mg/l
	Sewage treatment plant	3,18 mg/l
	Sea water	0,006 mg/l
	Soil	1,121 mg/kg dry
		weight (d.w.)
	Intermittent use/release	0,23 mg/l
2,4,6-	Intermittent use/release	0,84 mg/l
tris(dimethylaminomethyl)phenol		, 3
	Sea water	0,0084 mg/l
	Fresh water	0,084 mg/l
	Sewage treatment plant	0,2 mg/l
Fatty acids C18 unsat, reaction	Sea sediment	9,94 mg/kg dry
products with triethylenetetra-		weight (d.w.)
mine		
	Intermittent use/release	2,94 µg/l
	Sewage treatment plant	5,57 mg/l
	Sea water	2,54 µg/l
	Fresh water sediment	99,4 mg/kg dry
		weight (d.w.)
	Soil	9,44 mg/kg dry
		weight (d.w.)
	Fresh water	25,4 μg/l
	Secondary Poisoning	2 mg/kg food
3-aminopropyldimethylamine	Fresh water	0,034 mg/l
	Sea sediment	0,0221 mg/kg dry
		weight (d.w.)
	Sea water	0,0034 mg/l
	Sewage treatment plant	69,5 mg/l
	Intermittent use/release	0,34 mg/l
	Fresh water sediment	0,221 mg/kg dry
		weight (d.w.)
	Soil	0,0242 mg/kg dry
		weight (d.w.)

8.2 Exposure controls

Personal protective equipment

according to Regulation (EC) No. 1907/2006



DE / EN

DisboXID 462 Comp. B

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 2.1 06.02.2023 6008180 Date of first issue: 10.12.2019

Eye/face protection : DGUV Regulation 112-192 - Use of eye and face protection

Tightly fitting safety goggles

Hand protection

Material : Nitrile rubber Glove thickness : 0,2 mm Protective index : Class 3

Remarks : Gloves should be discarded and replaced if there is any indi-

cation of degradation or chemical breakthrough. Before removing gloves clean them with soap and water. Wear suita-

ble gloves tested to EN374.

DGUV Regulation 112-195 - Use of protective gloves

Skin and body protection : Safety shoes

Use appropriate degowning techniques to remove potentially

contaminated clothing.

Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, dis-

posable suits) to avoid exposed skin surfaces.

Long sleeved clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

Respiratory protection : Roller application or brushing: This product should not be

used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to

standard EN 14387) is used.

DGUV Regulation 112-190 - Use of breathing equipment

During spray application: Do not breathe spray dust. Use

A2/P2 combination filter for paint spraying.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Color : No data available

Odor : No data available

according to Regulation (EC) No. 1907/2006



DE / EN

DisboXID 462 Comp. B

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 2.1 06.02.2023 6008180 Date of first issue: 10.12.2019

Melting point/freezing point : not determined

Boiling point/boiling range : not determined

Upper explosion limit / Upper

flammability limit

not determined

Lower explosion limit / Lower

flammability limit

not determined

Flash point : > 100 °C

Autoignition temperature : not determined

Decomposition temperature : Not applicable

pH : substance/mixture is non-soluble (in water)

Viscosity

Viscosity, dynamic : No data available

Solubility(ies)

Water solubility : partly miscible

Partition coefficient: n-

octanol/water

not determined

Vapor pressure : not determined

Density : 1,03 g/cm3 (20 °C)

Relative vapor density : not determined

9.2 Other information

Oxidizing properties : Not applicable

Flammability (liquids) : The product is not flammable.

Evaporation rate : Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

according to Regulation (EC) No. 1907/2006



DE / EN

DisboXID 462 Comp. B

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 2.1 06.02.2023 6008180 Date of first issue: 10.12.2019

10.3 Possibility of hazardous reactions

Hazardous reactions : Hazardous decomposition products formed under fire condi-

tions

10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

10.5 Incompatible materials

Materials to avoid : Incompatible with acids.

Incompatible with oxidizing agents.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if swallowed or if inhaled.

Product:

Acute oral toxicity : Acute toxicity estimate: 1.020 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 4,65 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg

Method: Calculation method

Components:

benzyl alcohol:

Acute oral toxicity : LD50 Oral (Rat, male and female): 1.230 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): > 4,178 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Acute oral toxicity : Acute toxicity estimate: 1.030 mg/kg

according to Regulation (EC) No. 1907/2006



DE / EN

DisboXID 462 Comp. B

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 2.1 06.02.2023 6008180 Date of first issue: 10.12.2019

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

Acute dermal toxicity : LD50 (Rabbit): 1.840 mg/kg

m-phenylenebis(methylamine):

Acute oral toxicity : LD50 (Rat): 930 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 3.100 mg/kg

2,4,6-tris(dimethylaminomethyl)phenol:

Acute oral toxicity : LD50 (Rat): 1.200 mg/kg

3-aminopropyldimethylamine:

Acute dermal toxicity : LD50 (Rat): 1.100 mg/kg

3,6-diazaoctanethylenediamin:

Acute dermal toxicity : LD50 (Rabbit): 1.465 mg/kg

Skin corrosion/irritation

Causes severe burns.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Corrosive to the respiratory tract.

STOT-repeated exposure

Not classified based on available information.

according to Regulation (EC) No. 1907/2006



DE / EN

DisboXID 462 Comp. B

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 2.1 06.02.2023 6008180 Date of first issue: 10.12.2019

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Fatty acids C18 unsat, reaction products with triethylenetetramine:

M-Factor (Acute aquatic tox- : 10

icity)

M-Factor (Chronic aquatic :

toxicity)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to

according to Regulation (EC) No. 1907/2006



DE / EN

DisboXID 462 Comp. B

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 2.1 06.02.2023 6008180 Date of first issue: 10.12.2019

REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

Harmful to aquatic organisms, may cause long-term adverse

effects in the aquatic environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Uncured product residues and unpurified packaging should be

disposed of as hazardous waste.

Material residues: Allow the basic substance to harden with

hardener and dispose of as paint waste.

Waste should not be disposed of via wastewater.

Contaminated packaging : Only completely emptied containers should be given for recy-

cling.

Waste Code : used product

080111*, waste paint and varnish containing organic solvents

or other dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 2735
ADR : UN 2735
RID : UN 2735
IMDG : UN 2735
IATA : UN 2735

14.2 UN proper shipping name

ADN : AMINES, LIQUID, CORROSIVE, N.O.S.

(m-phenylenebis(methylamine), 3-aminomethyl-3,5,5-

trimethylcyclohexylamine)

ADR : AMINES, LIQUID, CORROSIVE, N.O.S.

(m-phenylenebis(methylamine), 3-aminomethyl-3,5,5-

trimethylcyclohexylamine)

according to Regulation (EC) No. 1907/2006



DE / EN

DisboXID 462 Comp. B

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 2.1 06.02.2023 6008180 Date of first issue: 10.12.2019

RID : AMINES, LIQUID, CORROSIVE, N.O.S.

(m-phenylenebis(methylamine), 3-aminomethyl-3,5,5-

trimethylcyclohexylamine)

IMDG : AMINES, LIQUID, CORROSIVE, N.O.S.

(m-phenylenebis(methylamine), 3-aminomethyl-3,5,5-

trimethylcyclohexylamine)

IATA : Amines, liquid, corrosive, n.o.s.

(m-phenylenebis(methylamine), 3-aminomethyl-3,5,5-

trimethylcyclohexylamine)

14.3 Transport hazard class(es)

Class Subsidiary risks

ADN : 8
ADR : 8
RID : 8
IMDG : 8
IATA : 8

14.4 Packing group

ADN

Packing group : II
Classification Code : C7
Hazard Identification Number : 80
Labels : 8

ADR

Packing group : II
Classification Code : C7
Hazard Identification Number : 80
Labels : 8
Tunnel restriction code : (E)

RID

Packing group : II
Classification Code : C7
Hazard Identification Number : 80
Labels : 8

IMDG

Packing group : II Labels : 8

EmS Code : F-A, S-B

IATA (Cargo)

Packing instruction (cargo

aircraft)

Packing instruction (LQ) : Y840

16/20

855

according to Regulation (EC) No. 1907/2006



DE / EN

DisboXID 462 Comp. B

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 2.1 06.02.2023 6008180 Date of first issue: 10.12.2019

Packing group : II

Labels : Corrosive

IATA (Passenger)

Packing instruction (passen: 851

ger aircraft)

Packing instruction (LQ) : Y840
Packing group : II

Labels : Corrosive

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) Conditions of restriction for the following entries should be considered: Number on list 3

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59).

This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be generated.

· - ·

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

according to Regulation (EC) No. 1907/2006



DE / EN

DisboXID 462 Comp. B

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 2.1 06.02.2023 6008180 Date of first issue: 10.12.2019

Regulation (EU) 2019/1021 on persistent organic pollu- : Not applicable

tants (recast)

REACH - List of substances subject to authorisation : None

(Annex XIV)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving

dangerous substances.

Water hazard class (Germa- : WGK 2 obviously hazardous to water

(4) Classification according to AwSV, Annex 1

Product code for laquers and

paints / Giscode

: RE1 Epoxy resin products, solvent-free, sensitising

Not applicable

: RE30 Epoxy resin products, sensitising, totally solid

Volatile organic compounds : Directive 2004/42/EC

< 49 % < 510 g/l

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapor. H302 : Harmful if swallowed. H312 : Harmful in contact with skin.

H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.

H332 : Harmful if inhaled. H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.H411 : Toxic to aquatic life with long lasting effects.

according to Regulation (EC) No. 1907/2006



DE / EN

DisboXID 462 Comp. B

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 2.1 06.02.2023 6008180 Date of first issue: 10.12.2019

H412 : Harmful to aquatic life with long lasting effects.

EUH071 : Corrosive to the respiratory tract.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitization

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; Ems - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Corial Variation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose; Doserved (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation

Further information

Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

Sources of key data used to compile the Material Safety Data Sheet:

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

according to Regulation (EC) No. 1907/2006



DE / EN

DisboXID 462 Comp. B

Version Revision Date: SDS Number: Date of last issue: 11.01.2023 2.1 06.02.2023 6008180 Date of first issue: 10.12.2019

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

Classification of the mixture: Classification procedure:

Acute Tox. 4	H302	Calculation method
Acute Tox. 4	H332	Calculation method
Skin Corr. 1B	H314	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN