

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

Capalac Aqua Metallschutz Basis EG

Version	Revision Date:	SDS Number:	Date of last issue: 28.01.2021
2.0	09.02.2023	6023708	Date of first issue: 28.01.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Capalac Aqua Metallschutz Basis EG

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Water-borne coatings

Recommended restrictions on use : within adequate application - none

1.3 Details of the supplier of the safety data sheet

Company : Caparol Farben Lacke GmbH
Roßdörfer Straße 50
64372 Ober-Ramstadt

Telephone : +496154710
Telefax : +4961547170222

E-mail address Responsible/issuing person : msds@dr-rmi.com

1.4 Emergency telephone

Emergency telephone 1 : +49613284463 GBK GmbH

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin sensitization, Category 1 H317: May cause an allergic skin reaction.

Long-term (chronic) aquatic hazard, Category 2 H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

Capalac Aqua Metallschutz Basis EG

Version	Revision Date:	SDS Number:	Date of last issue: 28.01.2021
2.0	09.02.2023	6023708	Date of first issue: 28.01.2021

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements : P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.

Prevention:

P262 Do not get in eyes, on skin, or on clothing.
P273 Avoid release to the environment.
P280 Wear protective gloves/ eye protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

Hazardous ingredients which must be listed on the label:

1,2-benzisothiazol-3(2H)-one
2-methylisothiazol-3(2H)-one
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one
(3:1)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

Capalac Aqua Metallschutz Basis EG

Version 2.0 Revision Date: 09.02.2023 SDS Number: 6023708 Date of last issue: 28.01.2021
Date of first issue: 28.01.2021

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
trizinc bis(orthophosphate)	7779-90-0 231-944-3 030-011-00-6 01-2119485044-40	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	$\geq 2,5 - < 10$
2-butoxyethanol	111-76-2 203-905-0 603-014-00-0 01-2119475108-36	Acute Tox. 4; H302 Acute Tox. 3; H331 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute toxicity estimate Acute oral toxicity: 1.200 mg/kg Acute inhalation toxicity (vapor): 3 mg/l	$\geq 1 - < 10$
zinc oxide	1314-13-2 215-222-5 030-013-00-7 01-2119463881-32, 01-2120089607-43, 01-2120767291-53	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	$\geq 1 - < 2,5$
zinc 5-nitroisophthalate	60580-61-2 262-309-9 01-2120768444-47	Aquatic Acute 1; H400 Aquatic Chronic 2; H411	$\geq 0,25 - < 1$
ammonia	1336-21-6 215-647-6 007-001-01-2 01-2119488876-14	Skin Corr. 1B; H314 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 specific concentration limit STOT SE 3; H335 $\geq 5 \%$	$\geq 0,1 - < 0,25$
1,2-benzisothiazol-3(2H)-one	2634-33-5 220-120-9 613-088-00-6 01-2120761540-60	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 Acute Tox. 2; H330	$\geq 0,025 - < 0,05$

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

Capalac Aqua Metallschutz Basis EG

Version 2.0 Revision Date: 09.02.2023 SDS Number: 6023708 Date of last issue: 28.01.2021
Date of first issue: 28.01.2021

		M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1 specific concentration limit Skin Sens. 1; H317 >= 0,05 %	
2-methylisothiazol-3(2H)-one	2682-20-4 220-239-6 613-326-00-9 01-2120764690-50	Acute Tox. 2; H330 Acute Tox. 3; H311 Acute Tox. 3; H301 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1 specific concentration limit Skin Sens. 1A; H317 >= 0,0015 %	>= 0,0025 - < 0,025
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9 613-167-00-5 01-2120764691-48	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 M-Factor (Acute	>= 0,0002 - < 0,0015

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

Capalac Aqua Metallschutz Basis EG

Version 2.0 Revision Date: 09.02.2023 SDS Number: 6023708 Date of last issue: 28.01.2021
Date of first issue: 28.01.2021

		aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100	
		specific concentration limit Skin Corr. 1C; H314 >= 0,6 % Skin Irrit. 2; H315 0,06 - < 0,6 % Eye Irrit. 2; H319 0,06 - < 0,6 % Skin Sens. 1A; H317 >= 0,0015 % Eye Dam. 1; H318 >= 0,6 %	
Substances with a workplace exposure limit :			
Talc (Mg ₃ H ₂ (SiO ₃) ₄)	14807-96-6 238-877-9 01-2120140278-58		>= 1 - < 10
aluminium powder (stabilised)	7429-90-5 231-072-3 013-002-00-1 01-2119529243-45	Flam. Sol. 1; H228	>= 1 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

- General advice : Never give anything by mouth to an unconscious person.
If you feel unwell, seek medical advice (show the label where possible).
Move out of dangerous area.
First aider needs to protect himself.
- If inhaled : Move to fresh air.
- In case of skin contact : Do NOT use solvents or thinners.
In case of contact, immediately flush skin with soap and plenty of water.
- In case of eye contact : If eye irritation persists: Get medical advice/ attention.
IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

Capalac Aqua Metallschutz Basis EG

Version	Revision Date:	SDS Number:	Date of last issue: 28.01.2021
2.0	09.02.2023	6023708	Date of first issue: 28.01.2021

If swallowed : Seek medical advice.
Clean mouth with water and drink afterwards plenty of water.
If swallowed, DO NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Risks : May cause an allergic skin reaction.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Do not use a solid water stream as it may scatter and spread fire.

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : In case of fire hazardous decomposition products may be produced such as:
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

5.3 Advice for firefighters

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Standard procedure for chemical fires.
The product itself does not burn.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use protective shoes or boots with rough rubber sole.
Material can create slippery conditions.
Do not get in eyes, on skin, or on clothing.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

Capalac Aqua Metallschutz Basis EG

Version	Revision Date:	SDS Number:	Date of last issue: 28.01.2021
2.0	09.02.2023	6023708	Date of first issue: 28.01.2021

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
Do not flush into surface water or sanitary sewer system.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.
, For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.
No special technical protective measures required.

In addition, the current technical information for this product and its application on www.caparol.com must be observed.

Hygiene measures : Wash hands before eating, drinking, or smoking. Do not eat, drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering eating areas.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Perishable if frozen. To maintain product quality, do not store in heat or direct sunlight. Store at room temperature in the original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline materials.

Storage class (TRGS 510) : 12

7.3 Specific end use(s)

Specific use(s) : This information is not available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

Capalac Aqua Metallschutz Basis EG

Version 2.0 Revision Date: 09.02.2023 SDS Number: 6023708 Date of last issue: 28.01.2021
Date of first issue: 28.01.2021

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Talc (Mg ₃ H ₂ (SiO ₃) ₄)	14807-96-6	AGW (Inhalable fraction)	10 mg/m ³	DE TRGS 900
		Peak-limit category: 2;(II)		
		Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child		
		AGW (Alveolate fraction)	1,25 mg/m ³	DE TRGS 900
		Peak-limit category: 2;(II)		
		Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child		
		BM (Alveolar dust fraction)	0,5 mg/m ³	DE TRGS 527
2-butoxyethanol	111-76-2	TWA	20 ppm 98 mg/m ³	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
		STEL	50 ppm 246 mg/m ³	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
		AGW	10 ppm 49 mg/m ³	DE TRGS 900
		Peak-limit category: 2;(I)		
		Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child		
aluminium powder (stabilised)	7429-90-5	AGW (Inhalable fraction)	10 mg/m ³	DE TRGS 900
		Peak-limit category: 2;(II)		
		Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child		
		AGW (Alveolate fraction)	1,25 mg/m ³	DE TRGS 900
		Peak-limit category: 2;(II)		
		Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child		
		BM (Alveolar dust fraction)	0,5 mg/m ³	DE TRGS 527

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
2-butoxyethanol	111-76-2	butoxy acetic acid:	In case of long-	TRGS 903

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

Capalac Aqua Metallschutz Basis EG

Version 2.0 Revision Date: 09.02.2023 SDS Number: 6023708 Date of last issue: 28.01.2021
Date of first issue: 28.01.2021

		150 mg/g Creatinine (Urine)	term exposure: after more than one shift, Immediately after exposure or after working hours	
aluminium powder (stabilised)	7429-90-5	Aluminum: 50 µg/g creatinine (Urine)	In case of long-term exposure: after more than one shift	TRGS 903

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of exposure	Potential health effects	Value
trizinc bis(orthophosphate)	Consumers	Ingestion	Long-term systemic effects	0,83 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	83,00 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	2,50 mg/m3
	Workers	Inhalation	Long-term systemic effects	5,00 mg/m3
	Workers	Skin contact	Long-term systemic effects	83,00 mg/kg bw/day
2-butoxyethanol	Consumers	Inhalation	Long-term systemic effects	59,00 mg/m3
	Consumers	Ingestion	Acute systemic effects	26,70 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	75,00 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	89,00 mg/kg bw/day
	Consumers	Inhalation	Acute local effects	147,00 mg/m3
	Consumers	Ingestion	Long-term systemic effects	6,30 mg/kg bw/day
	Consumers	Inhalation	Acute systemic effects	426,00 mg/m3
	Workers	Inhalation	Acute systemic effects	1091,00 mg/m3
	Workers	Inhalation	Acute local effects	246,00 mg/m3
	Workers	Inhalation	Long-term systemic effects	98,00 mg/m3
	Workers	Skin contact	Acute systemic effects	89,00 mg/kg bw/day
	Workers	Skin contact	Long-term systemic effects	125,00 mg/kg bw/day
aluminium powder (stabilised)	Consumers	Ingestion	Long-term systemic effects	7,90 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic	3,95 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

Capalac Aqua Metallschutz Basis EG

Version 2.0 Revision Date: 09.02.2023 SDS Number: 6023708 Date of last issue: 28.01.2021
Date of first issue: 28.01.2021

			effects	bw/day
	Workers	Inhalation	Long-term systemic effects	3,72 mg/m ³
	Workers	Inhalation	Long-term local effects	3,72 mg/m ³
	Workers	Inhalation	Long-term local effects	3,72 mg/m ³
isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol	Consumers	Inhalation	Long-term systemic effects	14,50 mg/m ³
	Consumers	Ingestion	Long-term systemic effects	8,33 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	8,33 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	49,00 mg/m ³
	Workers	Skin contact	Long-term systemic effects	13,90 mg/kg bw/day
zinc oxide	Consumers	Skin contact	Long-term systemic effects	83,00 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	2,50 mg/m ³
	Consumers	Ingestion	Long-term systemic effects	0,83 mg/kg bw/day
	Workers	Skin contact	Long-term systemic effects	83,00 mg/kg bw/day
	Workers	Inhalation	Long-term local effects	0,50 mg/m ³
	Workers	Inhalation	Long-term systemic effects	5,00 mg/m ³

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
glass, oxide, chemicals	Fresh water sediment	174 mg/kg dry weight (d.w.)
	Secondary Poisoning	10,9 mg/kg food
	Sea water	3,4 µg/l
	Sewage treatment plant	100 µg/l
	Sea sediment	164 mg/kg dry weight (d.w.)
	Soil	147 mg/kg dry weight (d.w.)
trizinc bis(orthophosphate)	Fresh water	6,5 µg/l
	Sea sediment	56,5 mg/kg dry weight (d.w.)
	Fresh water	20,6 µg/l
	Soil	35,6 mg/kg dry weight (d.w.)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

Capalac Aqua Metallschutz Basis EG

Version 2.0 Revision Date: 09.02.2023 SDS Number: 6023708 Date of last issue: 28.01.2021
Date of first issue: 28.01.2021

	Sewage treatment plant	100 µg/l
	Fresh water sediment	117,8 mg/kg dry weight (d.w.)
	Sea water	6,1 µg/l
2-butoxyethanol	Sea sediment	3,46 mg/kg dry weight (d.w.)
	Intermittent use/release	9,1 mg/l
	Secondary Poisoning	0,02 g/kg food
	Sewage treatment plant	463 mg/l
	Sea water	0,88 mg/l
	Fresh water sediment	34,6 mg/kg dry weight (d.w.)
	Soil	2,33 mg/kg dry weight (d.w.)
	Fresh water	8,8 mg/l
aluminium powder (stabilised)	Sewage treatment plant	20 mg/l
	Fresh water	74,9 µg/l
isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol	Fresh water sediment	0,78 mg/kg dry weight (d.w.)
	Sea water	0,0015 mg/l
	Sea sediment	0,078 mg/kg dry weight (d.w.)
	Soil	0,147 mg/kg dry weight (d.w.)
	Sewage treatment plant	7,5 mg/l
	Secondary Poisoning	66,7 mg/kg food
	Intermittent use/release	0,15 mg/l
	Fresh water	0,015 mg/l
zinc oxide	Fresh water sediment	117,8 mg/kg dry weight (d.w.)
	Sea water	6,1 µg/l
	Fresh water	20,6 µg/l
	Sea sediment	56,5 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 µg/l
	Soil	35,6 mg/kg dry weight (d.w.)

8.2 Exposure controls

Personal protective equipment

Eye/face protection : DGUV Regulation 112-192 - Use of eye and face protection

Goggles

Hand protection

Material : Nitrile rubber
Glove thickness : 0,2 mm
Protective index : Class 3

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

Capalac Aqua Metallschutz Basis EG

Version	Revision Date:	SDS Number:	Date of last issue: 28.01.2021
2.0	09.02.2023	6023708	Date of first issue: 28.01.2021

- Remarks : Before removing gloves clean them with soap and water.
Wear suitable gloves tested to EN374.
DGUV Regulation 112-195 - Use of protective gloves
- Skin and body protection : Safety shoes
Long sleeved clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

Remove and wash contaminated clothing before re-use.
During spray application: impervious clothing
- Respiratory protection : No personal respiratory protective equipment normally required.

DGUV Regulation 112-190 - Use of breathing equipment

During spray application: Do not breathe spray dust. Use A2/P2 combination filter for paint spraying.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Physical state : liquid
- Color : No data available
- Odor : No data available
- Melting point/freezing point : ca. 0 °C
- Boiling point/boiling range : ca. 100 °C
- Upper explosion limit / Upper flammability limit : not determined
- Lower explosion limit / Lower flammability limit : not determined
- Flash point : Not applicable
- Autoignition temperature : not determined

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

Capalac Aqua Metallschutz Basis EG

Version	Revision Date:	SDS Number:	Date of last issue: 28.01.2021
2.0	09.02.2023	6023708	Date of first issue: 28.01.2021

Decomposition temperature : Not applicable

pH : 8 - 9
Concentration: 100 %

Viscosity
Viscosity, dynamic : No data available

Solubility(ies)
Water solubility : completely miscible

Partition coefficient: n-
octanol/water : Not applicable

Vapor pressure : ca. 23,4 hPa (20 °C)

Relative density : not determined

Density : 1,1600 g/cm³

Relative vapor density : Not applicable

9.2 Other information

Explosives : Not applicable

Oxidizing properties : Not applicable

Flammability (liquids) : The product is not flammable.

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

10.5 Incompatible materials

Materials to avoid : Incompatible with acids and bases.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

Capalac Aqua Metallschutz Basis EG

Version	Revision Date:	SDS Number:	Date of last issue: 28.01.2021
2.0	09.02.2023	6023708	Date of first issue: 28.01.2021

Incompatible with oxidizing agents.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

|| Not classified based on available information.

Product:

Acute oral toxicity	:	Acute toxicity estimate: > 2.000 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: > 20 mg/l Exposure time: 4 h Test atmosphere: vapor Method: Calculation method

Components:

2-butoxyethanol:

Acute oral toxicity	:	Acute toxicity estimate: 1.200 mg/kg Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008
Acute inhalation toxicity	:	Acute toxicity estimate: 3 mg/l Test atmosphere: vapor Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008

1,2-benzisothiazol-3(2H)-one:

Acute oral toxicity	:	LD50 (Rat): 532 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 0,4 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	:	LD50 (Rat): > 2.000 mg/kg

2-methylisothiazol-3(2H)-one:

Acute oral toxicity	:	LD50 (Rat): 120 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 0,145 mg/l Exposure time: 4 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

Capalac Aqua Metallschutz Basis EG

Version	Revision Date:	SDS Number:	Date of last issue: 28.01.2021
2.0	09.02.2023	6023708	Date of first issue: 28.01.2021

Test atmosphere: dust/mist

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

Acute oral toxicity : LD50 (Rat): 66 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 0,17 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 141 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation

|| Not classified based on available information.

Serious eye damage/eye irritation

|| Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

|| May cause an allergic skin reaction.

Respiratory sensitization

|| Not classified based on available information.

Germ cell mutagenicity

|| Not classified based on available information.

Carcinogenicity

|| Not classified based on available information.

Reproductive toxicity

|| Not classified based on available information.

STOT-single exposure

|| Not classified based on available information.

STOT-repeated exposure

|| Not classified based on available information.

Aspiration toxicity

|| Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

Capalac Aqua Metallschutz Basis EG

Version	Revision Date:	SDS Number:	Date of last issue: 28.01.2021
2.0	09.02.2023	6023708	Date of first issue: 28.01.2021

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

1,2-benzisothiazol-3(2H)-one:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2,2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia): 3,27 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 0,11 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

2-methylisothiazol-3(2H)-one:

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 1

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

M-Factor (Acute aquatic toxicity) : 100

M-Factor (Chronic aquatic toxicity) : 100

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

Capalac Aqua Metallschutz Basis EG

Version	Revision Date:	SDS Number:	Date of last issue: 28.01.2021
2.0	09.02.2023	6023708	Date of first issue: 28.01.2021

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

2-butoxyethanol:

Partition coefficient: n-octanol/water : log Pow: 0,81 (25 °C)
pH: 7

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

Partition coefficient: n-octanol/water : log Pow: <= 0,71
Method: OECD Test Guideline 117

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : .

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

Capalac Aqua Metallschutz Basis EG

Version	Revision Date:	SDS Number:	Date of last issue: 28.01.2021
2.0	09.02.2023	6023708	Date of first issue: 28.01.2021

Waste should not be disposed of via wastewater.

Contaminated packaging : Only completely emptied containers should be given for recycling.

Waste Code : used product
080112, waste paint and varnish other than those mentioned
in 08 01 11*

SECTION 14: Transport information

14.1 UN number or ID number

ADN	: UN 3082
ADR	: UN 3082
RID	: UN 3082
IMDG	: UN 3082
IATA	: UN 3082

14.2 UN proper shipping name

ADN	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (trizinc bis(orthophosphate), zinc oxide)
ADR	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (trizinc bis(orthophosphate), zinc oxide)
RID	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (trizinc bis(orthophosphate), zinc oxide)
IMDG	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (trizinc bis(orthophosphate), zinc oxide)
IATA	: Environmentally hazardous substance, liquid, n.o.s. (trizinc bis(orthophosphate), zinc oxide)

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 9	
ADR	: 9	
RID	: 9	
IMDG	: 9	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

Capalac Aqua Metallschutz Basis EG

Version	Revision Date:	SDS Number:	Date of last issue: 28.01.2021
2.0	09.02.2023	6023708	Date of first issue: 28.01.2021

IATA : 9

14.4 Packing group

ADN

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9

ADR

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9
Tunnel restriction code : (-)

RID

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9

IMDG

Packing group : III
Labels : 9
EmS Code : F-A, S-F

IATA (Cargo)

Packing instruction (cargo aircraft) : 964
Packing instruction (LQ) : Y964
Packing group : III
Labels : Miscellaneous

IATA (Passenger)

Packing instruction (passenger aircraft) : 964
Packing instruction (LQ) : Y964
Packing group : III
Labels : Miscellaneous

14.5 Environmental hazards

ADN

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

Capalac Aqua Metallschutz Basis EG

Version	Revision Date:	SDS Number:	Date of last issue: 28.01.2021
2.0	09.02.2023	6023708	Date of first issue: 28.01.2021

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59). : This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be generated.

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : None

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. E2 ENVIRONMENTAL HAZARDS

Water hazard class (Germany) : WGK 2 obviously hazardous to water
Classification according to AwSV, Annex 1 (5.2)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

Capalac Aqua Metallschutz Basis EG

Version	Revision Date:	SDS Number:	Date of last issue: 28.01.2021
2.0	09.02.2023	6023708	Date of first issue: 28.01.2021

. : BSW20 Coating materials, water-based

Volatile organic compounds : Directive 2004/42/EC
< 3 %
< 30 g/l

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

SECTION 16: Other information

Full text of H-Statements

H228	: Flammable solid.
H301	: Toxic if swallowed.
H302	: Harmful if swallowed.
H310	: Fatal in contact with skin.
H311	: Toxic in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H330	: Fatal if inhaled.
H331	: Toxic if inhaled.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.
EUH071	: Corrosive to the respiratory tract.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Sol.	: Flammable solids
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitization
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

Capalac Aqua Metallschutz Basis EG

Version	Revision Date:	SDS Number:	Date of last issue: 28.01.2021
2.0	09.02.2023	6023708	Date of first issue: 28.01.2021

list of indicative occupational exposure limit values

DE TRGS 527	:	Germany. TRGS 527 - Activities with nanomaterials
DE TRGS 900	:	Germany. TRGS 900 - Occupational exposure limit values.
TRGS 903	:	TRGS 903 - Biological limit values
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
DE TRGS 527 / BM	:	Assessment scale
DE TRGS 900 / AGW	:	Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

Sources of key data used to compile the Material Safety Data Sheet:

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs.

Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

Classification of the mixture:

Skin Sens. 1 H317

Classification procedure:

Calculation method

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DE / EN

Capalac Aqua Metallschutz Basis EG

Version	Revision Date:	SDS Number:	Date of last issue: 28.01.2021
2.0	09.02.2023	6023708	Date of first issue: 28.01.2021

Aquatic Chronic 2

H411

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN