

Version	Revision Date:	Print Date	Date of last issue: -
1.0	08.09.2022	07.07.2023	Date of first issue: 08.09.2022

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier Trade name	:	DisboXID 467 Comp. A Basis Weiß
Relevant identified uses of th	ne s	ubstance or mixture and uses advised against
Use of the Sub- stance/Mixture	:	Epoxide-resin-based coating material, totally solid
Recommended restrictions on use	:	within adequate application - none
Details of the supplier of the sa	afety	data sheet
Company	-	Disbon GmbH Roßdörfer Straße 50 64372 Ober-Ramstadt
Telephone	:	+496154710
Telefax		+4961547170222
E-mail address Responsible/issuing person	:	msds@dr-rmi.com
Emergency telephone		
Emergency telephone 1	:	+49613284463 GBK GmbH
	Relevant identified uses of the Sub- stance/Mixture Recommended restrictions on use Details of the supplier of the sa Company Telephone Telefax E-mail address Responsi- ble/issuing person Emergency telephone	Trade name       :         Relevant identified uses of the s         Use of the Sub-       :         stance/Mixture         Recommended restrictions       :         on use         Details of the supplier of the safety         Company       :         Telephone       :         Telefax       :         E-mail address Responsi-       :         ble/issuing person       :

## **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)				
Skin irritation, Category 2	H315: Causes skin irritation.			
Eye irritation, Category 2	H319: Causes serious eye irritation.			
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.			
Long-term (chronic) aquatic hazard, Cat- egory 3	H412: Harmful to aquatic life with long lasting effects.			

## 2.2 Label elements

## Labeling (REGULATION (EC) No 1272/2008)



Version 1.0	Revision Date: 08.09.2022	-	Print Date 7.07.202	-	Date of last issue: - Date of first issue: 08.09.2022
Hazar	d pictograms	:			
Signa	l Word	:	Warnir	ng	
Hazar	d Statements	:	H315 H317 H319 H412	May causes s	skin irritation. se an allergic skin reaction. serious eye irritation. to aquatic life with long lasting effects.
Preca	utionary Statements	:	<b>Prevei</b> P262 P264 P273 P280	Do not ge Wash ha Avoid rel	et in eyes, on skin, or on clothing. nds thoroughly after handling. ease to the environment. otective gloves/ eye protection.
			attentio	⊦ P313 li on. ⊦ P313 li	f skin irritation occurs: Get medical advice/ f eye irritation persists: Get medical advice/

## Hazardous ingredients which must be listed on the label:

bis-[4-(2,3-epoxipropoxi)phenyl]propane bisphenol-F epoxy resin MW <700 1,6-Hexanediol, reaction products with epichlorohydrin oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

#### **Additional Labeling**

EUH211

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

## 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Components

Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)
---------------	-------------------	----------------	--------------------------



08.09.2022 07.0	07.2023 Date	of first issue: 08.09.2022	
	Index-No. Registration number		
bis-[4-(2,3- epoxipropoxi)phenyl]propane	1675-54-3 216-823-5 603-073-00-2 01-2119456619-26	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 10 - <
		specific concentration limit Eye Irrit. 2; H319 >= 5 % Skin Irrit. 2; H315 >= 5 %	
titanium dioxide; [in powder form containing 1 % or more of parti- cles with aerodynamic diameter ≤ 10 µm]	13463-67-7 236-675-5 022-006-00-2 01-2119489379-17	Carc. 2; H351	>= 10 - <
bisphenol-F epoxy resin MW <700	9003-36-5 500-006-8 01-2119454392-40	Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 2,5 - <
1,6-Hexanediol, reaction products with epichlorohydrin	933999-84-9 01-2119463471-41	Skin Irrit. 2; H315 Skin Sens. 1; H317 Eye Irrit. 2; H319 Aquatic Chronic 3; H412	>= 2,5 - <
oxirane, mono[(C12-14- alkyloxy)methyl] derivs.	68609-97-2 271-846-8 603-103-00-4 01-2119485289-22	Skin Irrit. 2; H315 Skin Sens. 1; H317	>= 1 - <
Substances with a workplace expo			
silicon carbide	409-21-2 206-991-8 01-2119402892-42		>= 30 - <
Quartz (SiO2)	14808-60-7 238-878-4 01-2120770509-45		>= 10 - <
barium sulfate	7727-43-7 231-784-4		>= 1 - <

For explanation of abbreviations see section 16.



Version	Revision Date:	Print Date	Date of last issue: -
1.0	08.09.2022	07.07.2023	Date of first issue: 08.09.2022

## **SECTION 4: First aid measures**

4.1 Description of first-aid measures			
General advice :	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Move out of dangerous area. First aider needs to protect himself.		
If inhaled :	Move to fresh air.		
In case of skin contact :	Do NOT use solvents or thinners. In case of contact, immediately flush skin with soap and plenty of water. Take off all contaminated clothing immediately.		
In case of eye contact :	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ phy- sician.		
If swallowed :	Call a physician. Clean mouth with water and drink afterwards plenty of water. If swallowed, DO NOT induce vomiting.		

## 4.2 Most important symptoms and effects, both acute and delayed

None known.

## **4.3 Indication of any immediate medical attention and special treatment needed** Treatment : No information available.

## **SECTION 5: Firefighting measures**

#### 

## 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting	:	Cool closed containers exposed to fire with water spray. Hazardous decomposition products formed under fire condi-
		tions.



Version	Revision Date:	Print Date	Date of last issue: -
1.0	08.09.2022	07.07.2023	Date of first issue: 08.09.2022

5.3 Advice for firefighters		
Special protective equipment for fire-fighters	:	In the event of fire, wear self-contained breathing apparatus.
Further information	:	Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Standard procedure for chemical fires. In the event of fire and/or explosion do not breathe fumes.

## **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Do not get in eyes, on skin, or on clothing. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure adequate ventilation. Remove all sources of ignition.
6.2 Environmental precautions		
Environmental precautions	:	Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities. Do not flush into surface water or sanitary sewer system.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

#### 6.4 Reference to other sections

For further information see Section 7 of the safety data sheet. , For personal protection see section 8., For disposal considerations see section 13.

## **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

 Advice on safe handling
 : For personal protection see section 8.

 Avoid exceeding the given occupational exposure limits (see section 8).

 Provide sufficient air exchange and/or exhaust in work rooms.

 In addition, the current technical information for this product

and its application on www.caparol.com must be observed.



Version 1.0	Revision Date: 08.09.2022	Print Date 07.07.202			
	e on protection against nd explosion	: The p	oduct is flammable but not readily ignited.		
Hygiene measures		eating	contact with the skin and the eyes. Wash hands before , drinking, or smoking. Do not eat, drink or smoke when this product.		
7.2 Conditions for safe storage, including any incompatibilities					
Requirements for storage areas and containers			n original container. Store between 41 and 77 °F in a ell ventilated place away from sources of heat, ignition		

areas and containers		dry, well ventilated place away from sources of heat, ignitio and direct sunlight. Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Storage class (TRGS 510)	:	10, Combustible liquids

## 7.3 Specific end use(s)

Specific use(s)	: This information is not available.
-----------------	--------------------------------------

## **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

## Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parameters	Basis		
Componento	0/10/110.	of exposure)	Control parameters	Dasis		
silicon carbide 409-21-2		AGW (Inhalable	10 mg/m3	DE TRGS		
	100 21 2	fraction)	i o mg/mo	900		
	Peak-limit cat	/		500		
	1 Call Infile Oat	AGW (Alveolate	1,25 mg/m3	DE TRGS		
		fraction)	1,20 mg/mo	900		
	Peak-limit cat	/		500		
Quartz (SiO2)	14808-60-7	TWA (Respirable	0,1 mg/m3	2004/37/EC		
Qualtz (5102)	14000-00-7	dust)	0,11119/1113	2004/37/20		
	Further inform	. /				
	Further information: Carcinogens or mutagens					
titanium dioxide; [in	13463-67-7	AGW (Inhalable	10 mg/m3	DE TRGS		
powder form con-		fraction)	(Titanium dioxide)	900		
taining 1 % or						
more of particles						
with aerodynamic						
diameter ≤ 10 µm]						
	Peak-limit cat	egory: 2;(II)				
		AGW (Alveolate	1,25 mg/m3	DE TRGS		
		fraction)	(Titanium dioxide)	900		
	Peak-limit category: 2;(II)					



rsion )	sion Revision Date: Print Date 08.09.2022 07.07.2023						
			fraction)			900	
	F	Peak-limit cate	/				
	F V C C F	Further information: Senate commission for the review of com work place dangerous for the health (MAK-commission)., Cor dangerous substances, General dust value. For this substance occupational exposure limit value is established, since the AC have information regarding unspecific action on the respirator cess of the normal values.					
			AGW (Alveol fraction)	ate	1,25 mg/m3	DE TRGS 900	
	F	Peak-limit category: 2;(II)					
	v c c t	Further information: Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., Commission for dangerous substances, General dust value. For this substance no specific occupational exposure limit value is established, since the AGS does not yo have information regarding unspecific action on the respiratory organs in excess of the normal values.					
Derive	ed No Effect Lev	vel (DNEL) a	ccording to R	egulati	on (EC) No. 1907/2006:		
Substa	ance name	End Use	Routes sure	of expo	<ul> <li>Potential health ef- fects</li> </ul>	Value	
silicon	carbide	Consumers	Skin co	ntact	Acute systemic ef- fects	200,00 mg/k bw/day	
		Consumers	s Ingestio	n	Acute systemic ef-	13,00 mg/kg	

	Consumers	Ingestion	Acute systemic ef- fects	13,00 mg/kg bw/day
	Consumers	Inhalation	Acute systemic ef- fects	23,00 mg/m3
	Workers	Inhalation	Acute systemic ef- fects	94,00 mg/m3
titanium dioxide; [in powder form contain- ing 1 % or more of particles with aerody- namic diameter ≤ 10 µm]	Consumers	Ingestion	Long-term systemic effects	700,00 mg/kg bw/day
	Workers	Inhalation	Long-term local ef- fects	10,00 mg/m3
bisphenol-F epoxy resin MW <700	Consumers	Skin contact	Long-term systemic effects	62,50 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	6,25 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	8,70 mg/m3
	Workers	Skin contact	Acute local effects	8,30 µg/cm2
	Workers	Skin contact	Long-term systemic effects	104,15 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	29,39 mg/m3
1,6-Hexanediol, reac-	Consumers	Skin contact	Acute systemic ef-	1,70 mg/kg



Version 1.0	Revision Date: 08.09.2022	Print Date 07.07.202		f last issue: - f first issue: 08.09.2022	
	products with Iorohydrin			fects	bw/day
	,	Consumers	Skin contact	Long-term systemic effects	1,70 mg/kg bw/day
		Consumers	Skin contact	Long-term local ef- fects	13,60 µg/cm2
		Consumers	Inhalation	Long-term local ef- fects	0,27 mg/m3
		Consumers	Inhalation	Acute systemic ef- fects	2,90 mg/m3
		Consumers	Ingestion	Acute systemic ef- fects	0,83 mg/kg bw/day
		Consumers	Ingestion	Long-term systemic effects	0,83 mg/kg bw/day
		Consumers	Inhalation	Long-term systemic effects	2,90 mg/m3
		Consumers	Skin contact	Acute local effects	13,60 µg/cm2
bariu	m sulfate	Consumers	Inhalation	Long-term systemic effects	10,00 mg/m3
		Consumers	Ingestion	Long-term systemic effects	13000,00 mg/kg bw/day
		Workers	Inhalation	Long-term systemic effects	10,00 mg/m3
		Workers	Inhalation	Long-term local ef- fects	10,00 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
titanium dioxide; [in powder form containing 1 % or more of parti- cles with aerodynamic diameter ≤ 10 µm]	Sewage treatment plant	100 mg/l
	Fresh water	0,184 mg/l
	Soil	100 mg/kg dry weight (d.w.)
	Sea water	0,0184 mg/l
	Fresh water sediment	1000 mg/kg dry weight (d.w.)
	Sea sediment	100 mg/kg dry weight (d.w.)
	Intermittent use/release	0,193 mg/l
bisphenol-F epoxy resin MW <700	Fresh water	0,003 mg/l
	Fresh water sediment	0,294 mg/kg dry weight (d.w.)
	Intermittent use/release	0,0254 mg/l
	Sea sediment	0,0294 mg/kg dry weight (d.w.)
	Sea water	0,0003 mg/l



ersion 0	Revision Date: 08.09.2022	Print Date 07.07.2023	Date of last issue: - Date of first issue: 08.09.2022	
1		Sewage tre	tment plant 10 r	ng/l
		Soil	0,23	37 mg/kg dry ght (d.w.)
	exanediol, reaction p vith epichlorohydrin	rod- Sea water		)115 mg/l
		Fresh wate	0,01	l15 mg/l
		Soil		23 mg/kg dry
				ght (d.w.)
		Sewage tre	tment plant 1 m	g/l
		Intermittent	use/release 0,11	l5 mg/l
		Sea sedime		283 mg/kg di ght (d.w.)
		Fresh wate		33 mg/kg dry ght (d.w.)
bariur	n sulfate	Fresh wate		µg/l
		Fresh wate	sediment 600	,4 mg/kg dry ght (d.w.)
		Soil	207	,7 mg/kg dry ght (d.w.)
		Sewage tre	tment plant 62,2	2 mg/l

#### 8.2 Exposure controls

Personal protective equipment						
Eye protection	:	German trade association rules - BGR 192 Eye protection				
		Tightly fitting safety goggles				
Glove thickness	:	Nitrile rubber 0,2 mm Class 3				
Remarks	:	Gloves should be discarded and replaced if there is any indi- cation of degradation or chemical breakthrough. Before re- moving gloves clean them with soap and water. Wear suita- ble gloves tested to EN374. German trade association leaflet: Carry gloves (ZH 1/706)				
Skin and body protection	:	Safety shoes Use appropriate degowning techniques to remove potentially contaminated clothing. Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, dis- posable suits) to avoid exposed skin surfaces. Long sleeved clothing				
		Choose body protection according to the amount and con- centration of the dangerous substance at the work place.				



Version 1.0	Revision Date: 08.09.2022	Print Date 07.07.2023	Date of last issue: - Date of first issue: 08.09.2022
		Skin should	be washed after contact.
Resp	iratory protection	used under o mask with ar	ation or brushing: This product should not be conditions of poor ventilation unless a protective a appropriate gas filter (i.e. type A1 according to 14387) is used.
		German trad	e association rules - BGR 190 Breathing protec-
			application: Do not breathe spray dust. Use ination filter for paint spraying.

## **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Color	:	No data available
Odor	:	No data available
Melting point/freezing point	:	not determined
Boiling point/boiling range	:	not determined
Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower flammability limit	:	not determined
Flash point	:	> 100 °C
Autoignition temperature	:	not determined
Decomposition temperature	:	Not applicable
рН	:	substance/mixture is non-soluble (in water)
Viscosity Viscosity, dynamic	:	No data available
Solubility(ies) Water solubility	:	insoluble



Versi 1.0		Revision Date: 08.09.2022		nt Date 07.2023	Date of last issue: - Date of first issue: 08.09.2022
Partition coefficient: n- octanol/water		:	not determined		
,	Vapor pr	essure	:	not determined	
I	Density		:	1,9400 g/cm3	
ļ	Relative vapor density		:	not determined	
<b>9.2 Other information</b> Oxidizing properties			:	Not applicable	
I	Flammat	oility (liquids)	:	The product is no	ot flammable.
I	Evaporat	tion rate	:	Not applicable	

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No decomposition if stored and applied as directed.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions	Hazardous decomposition products formed under fire condi- tions.					
10.4 Conditions to avoid						
Conditions to avoid	Protect from frost, heat and sunlight.					
10.5 Incompatible materials	10.5 Incompatible materials					
Materials to avoid	Incompatible with acids. Incompatible with oxidizing agents.					
10.6 Hazardous decomposition products						

No decomposition if stored and applied as directed.

## **SECTION 11: Toxicological information**

## 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

## Acute toxicity

#### Product:

Acute oral toxicity

: Remarks: Based on available data, the classification criteria



DisboXID 467 Comp. A Basis Weiß					
Version 1.0	Revision Date: 08.09.2022		int Date 2.07.2023	Date of last issue: - Date of first issue: 08.09.2022	
			are not met.		
Acute	inhalation toxicity	:	Remarks: Based on available data, the classification criteria are not met.		
Acute	dermal toxicity	:	Remarks: Based on available data, the classification criteria are not met.		
Skin	corrosion/irritation				
<u>Product:</u> Remarks			May cause skin irritation and/or dermatitis.		
Serio	us eye damage/eye ir	rritati	ion		
<u>Product:</u> Remarks		:	Vapors may cause irritation to the eyes, respiratory system and the skin.		
Resp	iratory or skin sensit	izatio	on		
<u>Produ</u> Rema		:	Causes sens	itization.	
11.2 Infor	mation on other haza	rds			
Furth	er information				
<u>Produ</u> Rema		:	molecular we	product only contains epoxy resins with high ight, follow good industrial hygiene practice and led skin contact.	
SECTION	12: Ecological info	orma	ition		

## 12.1 Toxicity

Product:		
Toxicity to fish	:	Remarks: No data available
Toxicity to daphnia and other aquatic invertebrates	:	Remarks: No data available

## Components:

#### barium sulfate:



Versio 1.0	'n	Revision Date: 08.09.2022		nt Date .07.2023	Date of last issue: - Date of first issue: 08.09.2022
Т	oxicity	r to fish	:	Remarks	No toxicity at the limit of solubility.
		to daphnia and other invertebrates	:	Remarks	No toxicity at the limit of solubility.
	oxicity lants	to algae/aquatic	:	Remarks	No toxicity at the limit of solubility.
	oxicity ity)	to fish (Chronic tox-	:	Remarks	No toxicity at the limit of solubility.
a		invertebrates (Chron-	:	Remarks	No toxicity at the limit of solubility.
		tence and degradabili a available	ity		
12.3 B	Bioacc	umulative potential			
<u>c</u>	ompo	onents:			
1,	,6-Hex	canediol, reaction pro	du	cts with e	bichlorohydrin:
	artition ctanol	n coefficient: n- /water	:	log Pow:	ca. 0,822 (20 °C)
0	xirane	e, mono[(C12-14-alky	loxy	/)methyl]	derivs.:
P		n coefficient: n-	:	log Pow:	
		<b>y in soil</b> a available			
12.5 R	esult	s of PBT and vPvB as	ses	ssment	
<u>P</u>	roduc	<u>:t:</u>			
A	SSESS	ment	:	to be eith	tance/mixture contains no components considered er persistent, bioaccumulative and toxic (PBT), or istent and very bioaccumulative (vPvB) at levels of igher.
		rine disrupting prope a available	rtie	S	
12.7 0	)ther a	adverse effects			
	roduc				
A	dditior	nal ecological infor-	:	Harmful t	o aquatic organisms, may cause long-term adverse



#### DisboXID 467 Comp. A Basis Weiß Version Revision Date: Date of last issue: -Print Date 1.0 08.09.2022 07.07.2023 Date of first issue: 08.09.2022 mation effects in the aquatic environment. **SECTION 13: Disposal considerations** 13.1 Waste treatment methods Uncured product residues and unpurified packaging should be Product : disposed of as hazardous waste. Material residues: Allow the basic substance to harden with hardener and dispose of as paint waste. Waste should not be disposed of via wastewater. Contaminated packaging Only completely emptied containers should be given for recy-5 cling. Waste Code used product 5 080111\*, waste paint and varnish containing organic solvents or other dangerous substances

## **SECTION 14: Transport information**

#### 14.1 UN number or ID number

Not regulated as a dangerous good

#### 14.2 UN proper shipping name

Not regulated as a dangerous good

## 14.3 Transport hazard class(es)

Not regulated as a dangerous good

## 14.4 Packing group

Not regulated as a dangerous good

## 14.5 Environmental hazards

Not regulated as a dangerous good

## 14.6 Special precautions for user

Remarks

: Not classified as dangerous in the meaning of transport regulations.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture



Vers 1.0	sion	Revision Date: 08.09.2022	Print Date 07.07.2023		last issue: - first issue: 08.09.2022
	the mai	I - Restrictions on the n ket and use of certain o tions and articles (Ann	dangerous substances		Conditions of restriction for the fol- lowing entries should be considered: Number on list 3
		I - Candidate List of Su n for Authorization (Arti		:	This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be gener- ated.
	REACH (Annex	I - List of substances so XIV)	ubject to authorisation	:	None
	pean Pa control	III: Directive 2012/18/E arliament and of the Co of major-accident haza ous substances.	ouncil on the	Not	applicable
	Water h ny)	nazard class (Germa-			endangering AwSV, Annex 1 (5.2)
		t code for laquers and Giscode	: RE1 Epoxy resin p	products,	, solvent-free, sensitising
			: RE30 Epoxy resin	products	s, sensitising, totally solid
	Volatile	organic compounds	: Directive 2004/42/ < 0.1 % < 1 g/l	ÆC	

## Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

## **15.2 Chemical Safety Assessment**

A Chemical Safety Assessment is not required for this mixture.

## **SECTION 16: Other information**

#### Full text of H-Statements

H315 :	Causes skin irritation.
H317 :	May cause an allergic skin reaction.
H319 :	Causes serious eye irritation.
H351 :	Suspected of causing cancer if inhaled.



Version 1.0	Revision Date: 08.09.2022		int Date .07.2023	Date of last issue: - Date of first issue: 08.09.2022		
H411 H412		:	Toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects.			
Full te	xt of other abbreviat	ions				
Carc. Eye Irri Skin Irr Skin Se	Aquatic Chronic Carc. Eye Irrit. Skin Irrit. Skin Sens. 2004/37/EC		Long-term (chronic) aquatic hazard Carcinogenicity Eye irritation Skin irritation Skin sensitization Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutage at work			
DE TRGS 900 : 2004/37/EC / TWA : DE TRGS 900 / AGW :		:	Germany. TRGS 900 - Occupational exposure limit values. Long term exposure limit Time Weighted Average			

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; Ec-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EMS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; IECSC - Inventory of Existing Chemicals Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Level; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - R

#### Further information

#### Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

#### Sources of key data used to compile the Material Safety Data Sheet:

#### ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials



Version	Revision Date:	Print Date	Date of last issue: -
1.0	08.09.2022	07.07.2023	Date of first issue: 08.09.2022

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

Classification of t	he mixture:	Classification procedure:
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

## **REACH Information**

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN