

Capadecor®

VarioFinish Matt/Silk-Matt

Protective top sealant within the surface coating system for VarioChips.



Product Description

Field of Application

Suitable as protective finishing coat (transparent sealant) for VarioChips.

Material Properties

- Emission-minimised, solvent-free, unplasticized and AgBB tested.
- Lightfast/fadeless at its best.
- Thixotropic.
- Wet scrub resistance Class 2 (Gloss level: Matt) according to DIN EN 13 300.
- Wet scrub resistance Class 1 (Gloss level: Silk-matt) according to DIN EN 13 300.
- Resistant to aqueous disinfectants (Gloss level: Silk-matt).

Material Base / Vehicle

Synthetic resin dispersion/emulsion according to German standard DIN 55945.

Packaging/Package Size

10 l plastic bucket, oval-shaped

Colours

Transparent

Gloss Level

Matt/Silk-matt (Mid sheen)

Storage

Keep in a cool, but frost-free place.

Suitability according to
Technical Information No. 606
Definition of Application Areas

Interior 1	Interior 2	Interior 3	Exterior 1	Exterior 2
+	+	○	-	-
(-) inapplicable / (○) of limited suitability / (+) suitable				

Application

Suitable Substrates

The substrate must be sound/stable, dry, clean and free from all substances that may prevent good adhesion. In Germany: Follow VOB, part C, DIN 18363, section 3.

Method of Application

Paint roller or brush application.

Surface Coating System

Apply VarioFinish liberally and evenly onto the fully dry surface using short pile lambskin paint roller to obtain a sufficient coating thickness. Spread the product onto the surface in one direction. Avoid lapping by wet-on-wet roller application. The matt visual effect supports the natural appearance of VarioChips (highly recommended for rooms with critical lighting conditions).

Advice:

Some designs/types contain mica chips (flakes) and should be coated with VarioFinish Silk-Matt (see the table in Technical Information No. 810 - VarioChips).



TECHNICAL INFORMATION NO. 907

Consumption	Approx. 130 ml/m ² per coat. Determine the exact amount of material required by coating a test area on site.
Application Conditions	Lower Temperature Limit for Application and Drying: +5 °C for product, substrate and ambient air.
Drying/Drying Time	At +20 °C and 65 % relative humidity surface-dry after approx. 4 hours. Lower temperatures and higher humidity extend the drying time.
Tool Cleaning	Immediately after use with water.

Advice

Please Note (Status as at Date of Publication)

Keep out of reach from children. Ensure good ventilation during use and drying. Do not eat, drink or smoke while using the product. In case of contact with eyes or skin, immediately and thoroughly rinse with water. Do not allow product to enter drains, waterways or soil. Clean utensils immediately after use with soap and water. Use P2 dust filter for grinding. Do not breathe spray dust. Use A2/P2 combination filter for paint spraying.
Further information: See Material Safety Data Sheet (MSDS).

Contains: 1,2-benzisothiazol-3(2H)-one, 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.

In Germany: Advice for allergy sufferers with isothiazolinone allergy: Hotline 0180/5308928 (0.14 €/minute from German landline, MTS max. 0.42 €/minute).

Disposal

Materials and all related packaging must be disposed of in a safe way in accordance with the full requirements of the local authorities. Particular attention should be made to removing wastage from site in compliance with standard construction site procedures.
In Germany: Only completely empty containers should be handed in for recycling. Dispose containers with residues of liquid product via waste collection point accepting old paints and enamels. Dispose dried/hardened product residues as construction site/demolition/municipal or domestic waste.

EU limit value for the VOC content

of this product (category A/a): max. 30 g/l (2010). This product contains max. 1 g/l VOC.

Product Code Paints and Enamels

M-KH01 (Germany)

Substances of Content - Declaration

Polyacrylate resin, silicon dioxide (SiO₂), water, waxes, additives, preservative (Methyl-/Benzisothiazolinone).

Customer Service Centre

Tel.: +49 6154 71-71710
Fax: +49 6154 71-71711
e-mail: kundenservicecenter@caparol.de

International Distribution: Please see www.caparol.com

Technical Information No. 907 · Issue: July 2016

All suggestions and application instructions herein are based on our latest technical experience. Due to the wide variety of individual project conditions, we cannot be held responsible for their content. These instructions do not release the purchaser/apPLICATOR from his responsibility to determine the suitability of the product in consideration of the project characteristics. These instructions are to be considered void when a new edition is released. Our general conditions of sale and delivery in their latest edition apply. This document is a translation of our German Technical Information No.907 · Capadecor®
VarioFinish Matt/Silk-Matt · Issued: October 2020