

Dupa-Haftgrund

High-quality, adhesion-promoting, solidifying priming colour, for exterior use.



Product Description

Field of Application	White-pigmented, adhesion-promoting and solidifying priming paint. Particularly suitable for exterior substrates with chalking but adherent existing coatings as well as for stripped surfaces, that are going to be coated with Duparol as finishing coat. Other finishing coats are possible, but must be checked for compatibility on site. Not suitable for polystyrene boards or ETIC/EWI systems with polystyrene insulation material.										
Material Properties	<ul style="list-style-type: none"> ■ Solvent-based. ■ Adhesion-promoting. ■ Solidifies chalking but adherent existing coatings. 										
Material Base / Vehicle	Polymer resin										
Packaging/Package Size	10 l										
Colours	White Colour shades of Dupa-Haftgrund are factory-made.										
Gloss Level	Matt										
Supplementary Product	<ul style="list-style-type: none"> ■ Duparol ■ Duparol-W 										
Suitability according to Technical Information No. 606 Definition of Application Areas	<table border="1" style="width: 100%; text-align: center;"> <thead> <tr> <th>Interior 1</th> <th>Interior 2</th> <th>Interior 3</th> <th>Exterior 1</th> <th>Exterior 2</th> </tr> </thead> <tbody> <tr> <td>-</td> <td>-</td> <td>-</td> <td>+</td> <td>+</td> </tr> </tbody> </table> <p>(-) inapplicable / (○) of limited suitability / (+) applicable</p>	Interior 1	Interior 2	Interior 3	Exterior 1	Exterior 2	-	-	-	+	+
Interior 1	Interior 2	Interior 3	Exterior 1	Exterior 2							
-	-	-	+	+							

Application

Suitable Substrates	The substrate must be stable, dry/cured, clean, and free from all substances that may prevent good adhesion. In Germany: Follow VOB, part C, DIN 18363, section 3.
Substrate Preparation	Please see Technical Information No. 650 "Substrates and their preparation" for further information.
Method of Application	Apply with solvent-resistant coating tools.
Thinning	Product is only to be diluted with Dupa-grund.
Surface Coating System	Dilute Dupa-Haftgrund up to a max. of 20 % with Dupa-grund for use on highly absorbent substrates. On compact, non-absorbing substrates dilute up to a max. of 10 % with Dupa-grund.



Consumption	Approx. 180 - 220 ml/m ² on an even surface, according to substrate condition. On rough-textured substrates correspondingly more.
Application Conditions	Lower Temperature Limit for Application and Drying: The product is applicable even in frosty conditions, provided that the substrate is dry and ice-free.
Drying/Drying Time	At +20 °C and 65 % relative humidity coatable after approx. 12 hours. Lower temperature and higher humidity extend the drying time.
Tools	Only use solvent-resistant paint brushes or rollers, to achieve good priming results.
Tool Cleaning	Clean tools with nitro-cellulose combination thinner.
Note	Do not mix with other products. Dupa-Haftgrund is incompatible with other materials, as well as with Duparol and Duparol-W.

Advice

Special Risks (Hazard Note) / Safety Advice (Status as at Date of Publication)	Highly flammable liquid and vapour. Causes serious eye damage. May cause drowsiness or dizziness. Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Take precautionary measures against static discharge. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Do not get in eyes, on skin, or on clothing. Use only outdoors or in a well-ventilated area. Avoid release to the environment. IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell. Do NOT induce vomiting. IF ON SKIN: Gently wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/ attention. Store in a well-ventilated place. Keep cool.
Disposal	Materials and all related packaging must be disposed of in a safe way in accordance with the full requirements of the local authorities. In Germany: Dispose containers with residues of liquid product via waste collection point accepting old paints and enamels. Dispose dried/hardened product residues as construction site/demolition/municipal or domestic waste.
EU limit value for the VOC content	of this product (category A/h): max. 750 g/l (2010). This product contains max. 750 g/l VOC.
Product Code Paints and Enamels	M-GP05
Further Details	See Material Safety Data Sheet (MSDS)
Technical Assistance	As it is impossible to list herein the wide variety of substrates and their specific problems, please request our technical assistance in case of queries. We will describe appropriate working methods, if a substrate not specified above is to be coated.
Customer Service Centre	Tel.: (+49) 0 61 54 / 71 17 10 Fax: (+49) 0 61 54 / 71 17 11 e-mail: kundenservicecenter@caparol.de International Distribution: Please see www.caparol.com

Technical Information No. 735 · Issue: July 2014

All suggestions and application instructions herein are based on our latest technical experience. Due to the wide variety of individual project conditions, we cannot be held responsible for their content. These instructions do not release the purchaser/ applicator from his responsibility to determine the suitability of the product in consideration of the project characteristics. These instructions are to be considered void when a new edition is released. Our general conditions of sale and delivery in their latest edition apply. This document is a translation of our German Technical Information No. 735 · Dupa-Haftgrund · Issued: February 2014