

Capadecor®

ArteDolce

Fine grained, emulsion based wall glaze (scumble) to create sturdy, matt interior surfaces.



Product Description

Field of Application

Tintable, matt emulsion wall glaze (scumble) with content of fine coloured particles to obtain a decorative effect on internal walls.

Material Properties

- Easy to apply.
- Discreet design.
- Resistant / low writing effect.
- Efficient and safe application method.
- Resistant to water-based (aqueous) disinfectants.

Packaging/Package Size

- 2.5 litres

Colours

White

Tinting:

ArteDolce can be tinted via ColorExpress in colour shades of Caparol 3D System and CaparolColor. **Stir up tinted product very thoroughly before applying. Use a low-speed paddle mixer or stir by hand.**

When applying on seamless surfaces, all tinted product must be thoroughly mixed before use to avoid colour differences.

When colour shades as red and orange are applied, the content of organic pigments may lead to colour deviation in the area of intensive daylight illumination.

Gloss Level

Dull matt (Dead-matt as per DIN EN 13300)

Storage

Keep in a cool, but frost-free place.

Technical Data

- Wet abrasion: Wet scrub resistance Class 2 as per DIN EN 13300 , corresponds to "scrub resistant" as per German standard DIN 53778

Supplementary Product

- DecoGrund (primer)
- EffektGrund
- AkkordSpachtel fein (fine type filler)

Suitability according to Technical Information No. 606 Definition of Application Areas

Interior 1	Interior 2	Interior 3	Exterior 1	Exterior 2
+	+	○	-	-
(-) inapplicable / (○) of limited suitability / (+) suitable				



Application

Suitable Substrates	<p>Interior surfaces: Mineral plasters in mortar groups PII (lime-cement mortars), PIII (cement mortars), PIV (gypsum mortar and ready-mixed gypsum plaster), plasterboards, gypsum wallboards and concrete.</p> <p>The substrate must be dry, clean, sound/stable, planar (trowelled up smoothly), without any colour contrast, and free from all substances that may prevent good adhesion. In Germany: Follow VOB, part C, DIN 18363, section 3.</p> <p>Follow Technical Information No. 650 for substrate preparation.</p>
Substrate Preparation	<p>Coarse (roughly textured) substrates, walls made of plasterboards and all walls and ceilings subjected to adverse lighting conditions (sided/grazing light) should previously be primed with Caparol-Haftgrund.</p> <p>Use filler Caparol-Akkordspachtel fein (fine) on the full surface (1 or 2 coats) to match the quality of approx. surface level Q4.</p> <p>Intermediate sanding after drying of filler coat (up to P200-240 grit).</p> <p>Then prime with CapaSol in order to equalize the absorption capacity and for embedding dust particles.</p> <p>Substrates of approximately quality level Q4 can directly be coated with the surface coating system.</p>
Method of Application	<p>Priming Coat: Roller-apply one priming coat of Capadecor DecoGrund, tinted to match the finishing coat in shade, diluted 10 % with tap (potable) water, then spread with a scumble brush. For intensive colors Capadecor EffektGrund can be used as a base coat alternatively.</p> <p>Intermediate Coat: Apply undiluted ArteDolce (in desired shade) crosswise with a short pile roller (10 - 12 mm piles) and then spread slightly to equalize/level visible roller marks.</p> <p>Finishing Coat: Apply undiluted ArteDolce (in desired shade) crosswise with a short pile roller (10 - 12 mm piles) and then spread slightly to equalize/level visible roller marks.</p>
Thinning	Apply ArteDolce in undiluted form.
Consumption	Approx. 100 - 120 ml/m ² per coat. Determine the exact amount of material required by coating a test area on site.
Application Conditions	Low Temperature Limit for Application and Drying: +5 °C for product, ambient air and substrate.
Drying/Drying Time	At + 20 °C and 65 % relative humidity surface-dry after 30 - 60 minutes. Completely cured and ready for stress after 1 - 2 days. Lower temperatures and higher relative humidity extend the drying time.
Tools	Recommendation: Use short pile roller (10 - 12 mm piles) for application and level roller marks with a soft brush.
Tool Cleaning	Immediately after use with soapy water.
Note	Advice for Cleaning and Care/Maintenance: Always check for cleanability, previously by trials (test area), working with due care. Note: Changes in surface appearance (shiny spots), caused by cleaning, are not removable.

Advice

German Certificates	<p>Prüfung auf Desinfektionsmittelbeständigkeit / Testing for resistance to disinfectants: - Desinfektionsmittelbeständig gegen wässrige Desinfektionsmittel (Resistance to water-based/aqueous disinfectants)</p>
Please Note (Status as at Date of Publication)	<p>Keep out of reach of children. Ensure good ventilation during use and drying. Do not eat, drink or smoke while using the product. In case of contact with eyes or skin, immediately and thoroughly rinse with water. Do not allow product to enter drains, waterways or soil. Clean utensils immediately after use with soap and water. Do not breathe spray dust. Use A2/P2 combination filter for paint spraying. Further information: See Material Safety Data Sheet (MSDS).</p> <p>Contains: 1,2-benzisothiazol-3(2H)-one, 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction. In Germany: Advice for allergy sufferers with isothiazolinone allergy: Hotline 0180/5308928 (0.14 €/minute from German landline, MTS max. 0.42 €/minute).</p>
Disposal	<p>Materials and all related packaging must be disposed of in a safe way in accordance with the full requirements of the local authorities. Particular attention should be made to removing wastage from site in compliance with standard construction site procedures.</p> <p>In Germany: Only completely empty buckets/containers should be handed in for recycling. Dispose containers with residues of liquid product via waste collection point accepting old paints and enamels. Dispose dried/hardened product residues as construction site/demolition/municipal or domestic waste.</p>

TECHNICAL INFORMATION NO. 912

EU limit value for the VOC content

Product Code Paints and Enamels

Substances of Content - Declaration

Customer Service Centre

of this product (category A/l): max. 200 g/l (2010). This product contains max. 50 g/l VOC.

M-DF01 (Germany)

Polyacrylate/Polyvinyl acetate resin, mineral fillers, water, additives, preservative (Methyl-, Benzisothiazolinone).

Tel.: +49 6154 71-71710

Fax: +49 6154 71-71711

e-mail: kundenservicecenter@caparol.de

International Distribution: Please see www.caparol.com

Technical Information No. 912 · Issue: July 2016

All suggestions and application instructions herein are based on our latest technical experience. Due to the wide variety of individual project conditions, we cannot be held responsible for their content. These instructions do not release the purchaser/ applicator from his responsibility to determine the suitability of the product in consideration of the project characteristics. These instructions are to be considered void when a new edition is released. Our general conditions of sale and delivery in their latest edition apply. This document is a translation of our German Technical Information No.912 · Capadecor®
ArteDolce · Issued: January 2017