Capadur UniversalLasur Farblos



Version	Revision Date:	SDS Number:	Date of last issue: 23.01.2024
4.1	26.02.2024	6007566	Date of first issue: 26.07.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier Trade name	:	Capadur UniversalLasur Farblos
1.2 Relevant identified uses of th	ne s	ubstance or mixture and uses advised against
Use of the Sub- stance/Mixture	:	Solvent-borne coatings
Recommended restrictions on use	:	within adequate application - none
1.3 Details of the supplier of the	saf	ety data sheet
Company	:	Caparol Farben Lacke GmbH Roßdörfer Straße 50 64372 Ober-Ramstadt
Telephone Telefax		+496154710 +4961547170222
Website E-mail address Responsi- ble/issuing person	:	msds@dr-rmi.com
1.4 Emergency telephone		

Emergency telephone 1

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin sensitization, Category 1

H317: May cause an allergic skin reaction.

Long-term (chronic) aquatic hazard, Category 3

H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



: +49613284463 GBK GmbH

Capadur UniversalLasur Farblos



Vers 4.1	sion	Revision Date: 26.02.2024	-	DS Number: 007566	Date of last issue: 23.01.2024 Date of first issue: 26.07.2019
	Signal	Word	:	Warning	
	Hazard	Statements	:	H317 H412	May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects.
	Supple Statem	mental Hazard ents	:	EUH066	Repeated exposure may cause skin dryness or cracking.
	Precau	tionary Statements	:	P101 P102	If medical advice is needed, have product con- tainer or label at hand. Keep out of reach of children.
				Prevention	:
				P261 P273 P280	Avoid breathing mist or vapors. Avoid release to the environment. Wear protective gloves.
				Disposal:	
				P501	Dispose of contents/ container to an approved waste disposal plant.

Hazardous ingredients which must be listed on the label:

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6pentamethyl-4-piperidyl sebacate 4,5-dichloro-2-octyl-2H-isothiazol-3-one octhilinone (ISO) maleic anhydride

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

.

Chemical nature	:	Alkyd-resin-based wood varnish, protection	solvent-containing , with film
		protoction	

Chemical name	CAS-No.	Classification	Concentration

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

DE / EN

Capadur UniversalLasur Farblos



rsion			of last issue: 23.01.2024 of first issue: 26.07.2019	
		EC-No. Index-No. Registration number		(% w/w)
ed hea	na (petroleum), hydrotreat- wy; Low boiling point ydro- eated naphtha	64742-48-9 265-150-3 649-327-00-6 01-2119457273-39, 01-2119463258-33, 01-2119486659-16	Asp. Tox. 1; H304 EUH066	>= 30 - < 50
	opyl-2,2- yltrimethylene diisobutyrate	6846-50-0 229-934-9 01-2119451093-47	Repr. 2; H361d Aquatic Chronic 3; H412	>= 1 - < 2,5
pentan and me	on mass of bis(1,2,2,6,6- nethyl-4-piperidyl) sebacate ethyl 1,2,2,6,6-pentamethyl ridyl sebacate	1065336-91-5 915-687-0	Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Repr. 2; H361f	>= 0,25 - <
4,5-dic 3-one	hloro-2-octyl-2H-isothiazol-	64359-81-5 264-843-8 613-335-00-8	Acute Tox. 4; H302 Acute Tox. 2; H330 Skin Corr. 1; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 	>= 0,0025 - 0,025
			aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100	
			specific concentration limit Skin Irrit. 2; H315 0,025 - < 5 % Eye Irrit. 2; H319 0,025 - < 3 % Skin Sens. 1A; H317 >= 0,0015 %	
			Acute toxicity esti- mate Acute oral toxicity: 567 mg/kg Acute inhalation tox-	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

DE / EN

Capadur UniversalLasur Farblos



rsion	Revision Date: 26.02.2024	SDS Number: 6007566	Date of last issue: 23.01.2024 Date of first issue: 26.07.2019	
			icity (dust/mist): 0,16 mg/l	
octhili	inone (ISO)	26530-20-1 247-761-7 613-112-00-5 01-212076892	Acute Tox. 3; H301 >= 0,00. Acute Tox. 2; H330 0,02 Acute Tox. 3; H311 0,02	
			M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100	
			specific concentration limit Skin Sens. 1A; H317 >= 0,0015 %	
			Acute toxicity esti- mate	
			Acute oral toxicity: 125 mg/kg Acute inhalation tox- icity (dust/mist): 0,27 mg/l Acute dermal toxicity: 311 mg/kg	
malei	c anhydride	108-31-6 203-571-6 607-096-00-9 01-211947242 01-212075969	Acute Tox. 4; H302 < 0,0 Skin Corr. 1B; H314 Eye Dam. 1; H318 8-31, Resp. Sens. 1; H334	001
			specific concentration limit Skin Sens. 1A; H317 >= 0,001 %	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

DE / EN





Version 4.1	Revision Date: 26.02.2024	SDS Number: 6007566	Date of last issue: 23.01.2024 Date of first issue: 26.07.2019	_
Subs	tances with a workpla	ce exposure limit :	I	
Silica	gel, pptd., crystfree	112926-00-8 231-545-4 01-21193794 01-21201053	.99-16,)

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

4.1 Description of mist-ald measure				
General advice :	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Move out of dangerous area. First aider needs to protect himself.			
If inhaled :	Call a physician. If breathing is irregular or stopped, administer artificial respira- tion. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician. Move to fresh air.			
In case of skin contact :	Do NOT use solvents or thinners. In case of contact, immediately flush skin with soap and plenty of water. Take off all contaminated clothing immediately.			
In case of eye contact :	If eye irritation persists: Get medical advice/ attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.			
If swallowed :	Seek medical advice. Clean mouth with water and drink afterwards plenty of water. If swallowed, DO NOT induce vomiting.			
4.2 Most important symptoms and effects, both acute and delayed				
Risks :	May cause an allergic skin reaction. Repeated exposure may cause skin dryness or cracking.			
4.3 Indication of any immediate medical attention and special treatment needed				
Treatment :	No information available.			

Capadur UniversalLasur Farblos



Version	Revision Date:	SDS Number:	Date of last issue: 23.01.2024
4.1	26.02.2024	6007566	Date of first issue: 26.07.2019

SECTION 5: Firefighting measures

E 1 Extinguishing modia		
5.1 Extinguishing media Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment. Use water spray, alcohol-resistant foam, dry chemical or car- bon dioxide. Do not use a solid water stream as it may scatter and spread fire.
Unsuitable extinguishing media	:	None known.
5.2 Special hazards arising from	the	e substance or mixture
Specific hazards during fire fighting	:	Cool closed containers exposed to fire with water spray. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocar- bons (smoke).
5.3 Advice for firefighters		
Special protective equipment for fire-fighters	:	In the event of fire, wear self-contained breathing apparatus.
Further information	:	Standard procedure for chemical fires. In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Do not get in eyes, on skin, or on clothing. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure adequate ventilation. Remove all sources of ignition.
6.2 Environmental precautions		
Environmental precautions	:	Prevent further leakage or spillage if safe to do so.

ivironmental precautions		Prevent further leakage or spillage if safe to do so.
		If the product contaminates rivers and lakes or drains inform
		respective authorities.
		Do not flush into surface water or sanitary sewer system.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Keep in suitable, closed containers for disposal.
		Soak up with inert absorbent material (e.g. sand, silica gel,
		acid binder, universal binder, sawdust).

Capadur UniversalLasur Farblos



Version	Revision Date:	SDS Number:
4.1	26.02.2024	6007566

Date of last issue: 23.01.2024 Date of first issue: 26.07.2019

6.4 Reference to other sections

For further information see Section 7 of the safety data sheet. , For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling :	Non-sparking tools should be used. For personal protection see section 8. Avoid exceeding the given occupational exposure limits (see section 8). Provide sufficient air exchange and/or exhaust in work rooms.
	In addition, the current technical information for this product and its application on www.caparol.com must be observed.
Advice on protection against : fire and explosion	Vapors may form explosive mixtures with air. Vapors are heavier than air and may spread along floors. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Hygiene measures :	Avoid contact with the skin and the eyes. Wash hands before eating, drinking, or smoking. Do not eat, drink or smoke when using this product. Remove contaminated clothing and protec- tive equipment before entering eating areas.
7.2 Conditions for safe storage, incl	luding any incompatibilities
Requirements for storage : areas and containers	Store in original container. Store between 41 and 77 °F in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Storage class (TRGS 510) :	10
7.3 Specific end use(s)	

Specific use(s) : This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Naphtha (petrole- um), hydrotreated	64742-48-9	AGW	300 mg/m3	DE TRGS 900

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

DE / EN

Capadur UniversalLasur Farblos



Version 4.1	Revision Da 26.02.2024	te: SDS 6007		ate of last issue: 23.01.2024 ate of first issue: 26.07.2019	
point	r; Low boiling ydrogen d naphtha				
		Peak-limit cat			
		Further inform	ation: Group expos	ure limit for hydrocarbon solv	ent mixtures
	gel, pptd.,	112926-00-	AGW (Inhalable	4 mg/m3	DE TRGS
cryst	free	8	fraction)	(Silica)	900
				is compliance with the OEL a	nd biological
		tolerance valu		of harming the unborn child	
octhili	none (ISO)	26530-20-1	AGW (Inhalable fraction)	0,05 mg/m3	DE TRGS 900
		Peak-limit cat	egory: 2;(I)		
		Further information: Skin absorption, When there is compliance with the and biological tolerance values, there is no risk of harming the unborn ch			
malei	c anhydride	108-31-6	AGW (Vapour	0,02 ppm	DE TRGS
			and aerosols)	0,081 mg/m3	900
		Peak-limit cat	egory: 1; =2.5=(I)		
		Further information: In well-found cases also a momentary value can be es- tablished, that never can be exceeded. This substance will be indicated by = = in combination with an exceeding value., When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child, Substance sensitizing through the skin and respiratory system			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of expo- sure	Potential health ef- fects	Value
1-isopropyl-2,2- dimethyltrimethylene diisobutyrate	Consumers	Ingestion	Long-term systemic effects	18,80 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	18,80 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	32,60 mg/m3
	Workers	Inhalation	Long-term systemic effects	110,00 mg/m3
	Workers	Skin contact	Long-term systemic effects	31,20 mg/kg bw/day
propane-1,2-diol	Consumers	Inhalation	Long-term systemic effects	50,00 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	10,00 mg/m3
	Workers	Inhalation	Long-term systemic effects	168,00 mg/m3
	Workers	Inhalation	Long-term systemic effects	168,00 mg/m3
	Workers	Inhalation	Long-term local ef- fects	10,00 mg/m3
	Workers	Inhalation	Long-term local ef- fects	10,00 mg/m3
	Consumers	Inhalation	Long-term systemic effects	50,00 mg/m3

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

DE / EN

Capadur UniversalLasur Farblos



ersion Revision Da 1 26.02.2024		SDS Nu 6007566		Date of last issue: 23.01.2024 Date of first issue: 26.07.2019	
		Consumers	Inhalation	Long-term local ef- fects	10,00 mg/m3
Reaction mass of bis(1,2,2,6,6- pentamethyl-4- piperidyl) sebacate and methyl 1,2,2,6,6- pentamethyl-4- piperidyl sebacate		Consumers	Inhalation	Acute local effects	0,58 mg/m3
		Consumers	Ingestion	Long-term systemic effects	1,25 mg/kg bw/day
		Consumers	Inhalation	Long-term systemic effects	0,58 mg/m3
		Consumers	Inhalation	Acute systemic ef- fects	0,58 mg/m3
		Consumers	Skin contact	Long-term systemic effects	1,25 mg/kg bw/day
		Consumers	Skin contact	Acute systemic ef- fects	1,25 mg/kg bw/day
		Consumers	Ingestion	Acute systemic ef- fects	1,25 mg/kg bw/day
		Workers	Inhalation	Acute systemic ef- fects	2,35 mg/m3
		Workers	Inhalation	Acute local effects	2,35 mg/m3
		Workers	Inhalation	Long-term systemic effects	2,35 mg/m3
		Workers	Skin contact	Acute systemic ef- fects	2,50 mg/kg bw/day
		Workers	Skin contact	Long-term systemic effects	2,50 mg/kg bw/day
malei	c anhydride	Consumers	Inhalation	Long-term systemic effects	0,05 mg/m3
		Consumers	Ingestion	Long-term systemic effects	0,06 mg/kg bw/day
		Consumers	Ingestion	Acute systemic ef- fects	0,10 mg/kg bw/day
		Consumers	Skin contact	Acute systemic ef- fects	0,10 mg/kg bw/day
		Consumers	Inhalation	Long-term local ef- fects	0,08 mg/m3
		Consumers	Skin contact	Long-term systemic effects	0,10 mg/kg bw/day
		Workers	Inhalation	Acute systemic ef- fects	0,80 mg/m3
		Workers	Inhalation	Acute systemic ef- fects	0,95 mg/m3
		Workers	Inhalation	Acute local effects	0,80 mg/m3
		Workers	Inhalation	Long-term systemic effects	0,40 mg/m3
		Workers	Inhalation	Long-term systemic effects	0,19 mg/m3

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

DE / EN

Capadur UniversalLasur Farblos



Version 4.1	Revision Date: 26.02.2024	SDS Num 6007566	SDS Number:Date of last issue: 23.01.20246007566Date of first issue: 26.07.2019		
		Workers	Inhalation	Long-term local ef- fects	0,40 mg/m3
		Workers	Inhalation	Long-term local ef- fects	0,32 mg/m3
		Workers	Skin conta	ct Acute systemic ef- fects	0,20 mg/kg bw/day
		Workers	Skin conta	ct Long-term systemic effects	0,20 mg/kg bw/day
		Consumers	Inhalation	Acute systemic ef- fects	

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
1-isopropyl-2,2- dimethyltrimethylene diisobutyr- ate	Sea water	0,0014 mg/l
	Sewage treatment plant	3 mg/l
	Sea sediment	0,529 mg/kg dry weight (d.w.)
	Secondary Poisoning	83,3 mg/kg food
	Fresh water	0,014 mg/l
	Soil	1,05 mg/kg dry weight (d.w.)
	Fresh water sediment	5,29 mg/kg dry weight (d.w.)
propane-1,2-diol	Sea sediment	57,2 mg/kg dry weight (d.w.)
	Soil	50 mg/kg dry weight (d.w.)
	Sea water	26 mg/l
	Fresh water sediment	572 mg/kg dry weight (d.w.)
	Fresh water	260 mg/l
	Intermittent use/release	183 mg/l
	Sewage treatment plant	20000 mg/l
Reaction mass of bis(1,2,2,6,6- pentamethyl-4-piperidyl) seba- cate and methyl 1,2,2,6,6- pentamethyl-4-piperidyl sebacate	Sea water	0,00022 mg/l
	Soil	0,21 mg/kg dry weight (d.w.)
	Fresh water	0,0022 mg/l
	Sewage treatment plant	1 mg/l
	Fresh water sediment	1,05 mg/kg dry weight (d.w.)
	Intermittent use/release	0,009 mg/l
	Sea sediment	0,11 mg/kg dry weight (d.w.)
maleic anhydride	Fresh water	0,075 mg/l
<u> </u>	Fresh water sediment	0,334 mg/kg dry weight (d.w.)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

DE / EN

Capadur UniversalLasur Farblos



Version 4.1	Revision Date: 26.02.2024	SDS Number: 6007566	Date of last issue: Date of first issue:	
		Soil		0,0415 mg/kg dry weight (d.w.)
		Sea water		0,01 mg/l
		Intermittent u	ise/release	0,4281 mg/l
		Sewage trea	tment plant	44,6 mg/l
		Soil		0,01 mg/kg dry weight (d.w.)
		Sea water		0,0075 mg/l
		Secondary P	oisoning	6,67 mg/kg food
		Fresh water		0,1 mg/l
		Sewage trea	tment plant	4,46 mg/l
		Sea sedimer	ht	0,006 mg/kg dry weight (d.w.)
		Fresh water	sediment	0,06 mg/kg dry weight (d.w.)
		Intermittent u	ise/release	0,75 mg/l
		Sea sedimer	nt	0,0334 mg/kg dry weight (d.w.)

8.2 Exposure controls

Personal protective equipment

Eye/face protection : DGUV Regulation 112-192 - Use of eye and face protection Goggles

Glove thickness :	Nitrile rubber 0,2 mm Class 3
Remarks :	Gloves should be discarded and replaced if there is any indi- cation of degradation or chemical breakthrough. Before re- moving gloves clean them with soap and water. Wear suita- ble gloves tested to EN374. DGUV Regulation 112-195 - Use of protective gloves
Skin and body protection :	Safety shoes Long sleeved clothing
	Choose body protection according to the amount and con- centration of the dangerous substance at the work place.
	Skin should be washed after contact.
	Remove and wash contaminated clothing before re-use. During spray application: impervious clothing
Respiratory protection :	Roller application or brushing: This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to

Capadur UniversalLasur Farblos



Version 4.1	Revision Date: 26.02.2024	SDS Number: 6007566	Date of last issue: 23.01.2024 Date of first issue: 26.07.2019		
		standard EN 1	4387) is used.		
	DGUV Regulation 112-190 - Use of breathing equipment				
		During spray application: Do not breathe spray dust. Use A2/P2 combination filter for paint spraying.			

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

 Physical state		liquid
Color	:	colorless
Odor	:	characteristic
Odor Threshold	:	Not relevant
Melting point/freezing point	:	not determined
Boiling point/boiling range	:	not determined
Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower flammability limit	:	not determined
Flash point	:	> 60 °C Method: ISO 1523
Autoignition temperature	:	not determined
Decomposition temperature	:	Not applicable
рН	:	substance/mixture is non-soluble (in water)
Viscosity Viscosity, dynamic	:	> 100 mPa.s (40 °C) Method: ISO 3219
		12 / 22

Capadur UniversalLasur Farblos



Versic 4.1	on Revisio 26.02.2	on Date: 2024		S Number: 07566	Date of last issue: 23.01.2024 Date of first issue: 26.07.2019
	Viscosity, ki	nematic	:	>= 21 mm2/s (40) °C)
F	low time		:	Not applicable	
S	olubility(ies) Water solub	ility	:	partly miscible	
	Partition coeffic ctanol/water	ient: n-	:	not determined	
V	apor pressure/		:	not determined	
F	Relative density	/	:	not determined	
C	Density		:	0,93 g/cm3 (20 ° Method: DIN EN	C) ISO 2811-1
E	Bulk density		:	Not applicable	
F	elative vapor	density	:	Heavier than air.	
9.2 Of	her informati	on			
	xplosives	•	:	Not applicable	
C)xidizing prope	erties	:	Not applicable	
F	lammability (li	quids)	:	Sustains combus	stion
E	evaporation rat	e	:	Not applicable	

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

Capadur UniversalLasur Farblos



Version	Revision Date:	SDS Number:	Date of last issue: 23.01.2024
4.1	26.02.2024	6007566	Date of first issue: 26.07.2019

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions					
Hazardous reactions :	Vapors may form explosive mixture with air. Hazardous decomposition products formed under fire condi- tions.				
10.4 Conditions to avoid					
Conditions to avoid :	Protect from frost, heat and sunlight.				
10.5 Incompatible materials					
Materials to avoid :	Incompatible with acids and bases. Incompatible with oxidizing agents.				

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

4,5-dichloro-2-octyl-2H-isothiazol-3-one:

Acute oral toxicity :	Acute toxicity estimate: 567 mg/kg Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008
Acute inhalation toxicity :	Acute toxicity estimate: 0,16 mg/l Test atmosphere: dust/mist Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008
octhilinone (ISO):	
Acute oral toxicity :	Acute toxicity estimate: 125 mg/kg Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008
Acute inhalation toxicity :	Acute toxicity estimate: 0,27 mg/l Test atmosphere: dust/mist Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008
Acute dermal toxicity :	Acute toxicity estimate: 311 mg/kg Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008

Capadur UniversalLasur Farblos



Version	Revision Date:	SDS Number:	Date of last issue: 23.01.2024
4.1	26.02.2024	6007566	Date of first issue: 26.07.2019

maleic anhydride:

Acute oral toxicity	:	LD50 (Rat, male and female): 1.090 mg/kg Method: OECD Test Guideline 401
Silica gel, pptd., crystfree Acute oral toxicity		LD50 Oral (Rat): > 10.000 mg/kg
Acute dermal toxicity	:	LD50 (Rat): > 5.000 mg/kg

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Components:

maleic anhydride:

Species	:	Rabbit
Assessment	:	Causes burns.

Serious eye damage/eye irritation

Not classified based on available information.

Components:

maleic anhydride:

Species	:	Rabbit
Assessment	:	Causes burns.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Components:

maleic anhydride:

Species: RatResult: Causes sensitization.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

Capadur UniversalLasur Farblos

Version **Revision Date:** SDS Number: 4.1 26.02.2024 6007566

Date of last issue: 23.01.2024 Date of first issue: 26.07.2019

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

5

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

4,5-dichloro-2-octyl-2H-isothiazol-3-one:

M-Factor (Acute aquatic tox- icity)	:	100
M-Factor (Chronic aquatic toxicity)	:	100

octhilinone (ISO):

M-Factor (Acute aquatic tox- : 100 icity)

M-Factor (Chronic aquatic : 100 toxicity)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha:

Partition coefficient: n-	:	log Pow: 1,99 - 18,02 (20 °C)
octanol/water		pH: 7



Capadur UniversalLasur Farblos



opyl-2,2-dimethyltr coefficient: n- water n mass of bis(1,2,2 ethyl-4-piperidyl so coefficient: n- water one (ISO): coefficient: n- water	: 2,6,6-r ebaca	log Pow: 4,49	(25 °C)
water n mass of bis(1,2,2 ethyl-4-piperidyl so coefficient: n- water one (ISO): coefficient: n-	2,6,6-p ebaca	bentamethyl-4- te: log Pow: 2,37	piperidyl) sebacate and methyl 1,2,2,6,6-
ethyl-4-piperidyl so coefficient: n- water one (ISO): coefficient: n-	ebaca	te: log Pow: 2,37	
coefficient: n- water one (ISO): coefficient: n-		log Pow: 2,37	- 2,77 (25 °C)
coefficient: n-			
	:	log Pow: 2,61 pH: 7	(25 °C)
anhydride:			
coefficient: n-	:	log Pow: -2,61 pH: 4 - 9	(19,8 °C)
v in soil			
available			
of PBT and vPvB	asses	sment	
<u>:</u>			
nent	:	to be either pervery persisten	e/mixture contains no components considered rsistent, bioaccumulative and toxic (PBT), or t and very bioaccumulative (vPvB) at levels of r.
ine disrupting prop	oertie	5	
:			
	:	ered to have e REACH Article (EU) 2017/210	e/mixture does not contain components considendocrine disrupting properties according to 57(f) or Commission Delegated regulation 0 or Commission Regulation (EU) 2018/605 a or higher.
dverse effects			
<u>:</u>			
al ecological infor-	:		atic organisms, may cause long-term adverse equatic environment.
	t: nent ine disrupting prop t: nent dverse effects t: al ecological infor-	water / in soil available of PBT and vPvB asses t: nent : dverse effects t: al ecological infor- :	water pH: 4 - 9 y in soil available of PBT and vPvB assessment t: nent : This substance to be either pe very persistent 0.1% or higher ine disrupting properties t: nent : The substance ered to have e REACH Article (EU) 2017/210 levels of 0.1% dverse effects t: al ecological infor- : Harmful to aqu

Capadur UniversalLasur Farblos



Version 4.1	Revision Date: 26.02.2024	SDS Number: 6007566	Date of last issue: 23.01.2024 Date of first issue: 26.07.2019
Produ	ct	: .	
		Waste should i	not be disposed of via wastewater.
Conta	minated packaging	: Only complete cling.	ly emptied containers should be given for recy-
Waste	e Code	: used product 080112, waste in 08 01 11*	paint and varnish other than those mentioned

SECTION 14: Transport information

14.1 UN number or ID number

	ADN	:	Not regulated as a dangerous good
	ADR	:	Not regulated as a dangerous good
	RID	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	ΙΑΤΑ	:	Not regulated as a dangerous good
14.	2 UN proper shipping name		
	ADN	:	Not regulated as a dangerous good
	ADR	:	Not regulated as a dangerous good
	RID	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	ΙΑΤΑ	:	Not regulated as a dangerous good
14.:	3 Transport hazard class(es)		
	ADN	:	Not regulated as a dangerous good
	ADR	:	Not regulated as a dangerous good
	RID	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	ΙΑΤΑ	:	Not regulated as a dangerous good
14.	4 Packing group		
	ADN	:	Not regulated as a dangerous good
	ADR	:	Not regulated as a dangerous good
	RID	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	IATA (Cargo)	:	Not regulated as a dangerous good

Capadur UniversalLasur Farblos



Version	Revision Date:	SDS Number:
4.1	26.02.2024	6007566

Date of last issue: 23.01.2024 Date of first issue: 26.07.2019

IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 75, 3
		If you intend to use this product as tattoo ink, please contact your ven- dor.
REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59).	:	This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be gener- ated.
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
Regulation (EU) 2019/1021 on persistent organic pollutants (recast)	:	Not applicable
REACH - List of substances subject to authorisation (Annex XIV)	:	None
Seveso III: Directive 2012/18/EU of the Euro- pean Parliament and of the Council on the control of major-accident hazards involving dangerous substances.	and (inc (inc hea stre alte pur ties	troleum products: (a) gasolines d naphthas, (b) kerosenes cluding jet fuels), (c) gas oils cluding diesel fuels, home ating oils and gas oil blending eams),(d) heavy fuel oils (e) ernative fuels serving the same poses and with similar proper- s as regards flammability and vironmental hazards as the

Capadur UniversalLasur Farblos



Version 4.1	Revision Date: 26.02.2024	SDS Number: 6007566	Date of last issue: 23.01.2024 Date of first issue: 26.07.2019
			products referred to in points (a) to (d)
Wate ny)	r hazard class (Germa-	Classification	ously hazardous to water according to AwSV, Annex 1 (5.2) ng materials, strongly solvent-based, aromatic-
		free, classifie	
Volat	ile organic compounds	emissions (in	0/75/EU of 24 November 2010 on industrial tegrated pollution prevention and control) nic compounds (VOC) content: 38,11 %
Volat	ile organic compounds	: Directive 200 < 39 % < 360 g/l	94/42/EC

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

SECTION 16: Other information

Full text of H-Statements

H302 :	Toxic if swallowed. Harmful if swallowed.
H304 :	May be fatal if swallowed and enters airways.
H311 :	Toxic in contact with skin.
H314 :	Causes severe skin burns and eye damage.
H317 :	May cause an allergic skin reaction.
H318 :	Causes serious eye damage.
H330 :	Fatal if inhaled.
H334 :	May cause allergy or asthma symptoms or breathing difficul- ties if inhaled.
H361d :	Suspected of damaging the unborn child.
H361f :	Suspected of damaging fertility.
H372 :	Causes damage to organs through prolonged or repeated exposure.
H400 :	Very toxic to aquatic life.
H410 :	Very toxic to aquatic life with long lasting effects.
H412 :	Harmful to aquatic life with long lasting effects.
EUH066 :	Repeated exposure may cause skin dryness or cracking.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

DE / EN

Capadur UniversalLasur Farblos



VersionRevision Date:SDS Number:Date of last issue: 23.01.20244.126.02.20246007566Date of first issue: 26.07.2019	
---	--

EUH071

: Corrosive to the respiratory tract.

Full text of other	abbreviations
--------------------	---------------

Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Dam.	:	Serious eye damage
Repr.	:	Reproductive toxicity
Resp. Sens.	:	Respiratory sensitization
Skin Corr.	:	Skin corrosion
Skin Sens.	:	Skin sensitization
STOT RE	:	Specific target organ toxicity - repeated exposure
DE TRGS 900	:	Germany. TRGS 900 - Occupational exposure limit values.
DE TRGS 900 / AGW	:	Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AlIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELX - Loading rate associated with x% response; EMS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ETCX - Concentration associated with x% growth rate response; (ENS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Convention for the Prevention of So% of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Observable Effect Loading Rate; NZIGC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration,

Further information

Other information	:	No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC. Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.
Sources of key data used to compile the Material Safety Data Sheet	:	ECHA WebSite ACGIH (American Conference of Government Industrial Hy- gienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH NIOSH - Registry of toxic effects of chemical substances ECDIN - Environmental Chemicals Data and Information Net- work - Joint Research Centre, Commission of the European Communities SAX'S - Dangerous properties of industrial materials GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the Ger- man Social Accident Insurance)

Capadur UniversalLasur Farblos



Version	Revision Date:	SDS Number:	Date of last issue: 23.01.2024
4.1	26.02.2024	6007566	Date of first issue: 26.07.2019

Toxnet - Toxicology Data Network

Classification of the	mixture:	Classification procedure:
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN